Order No (v4)	2127_GT102017		
PL order No.	QS0003 QS0004		first version:25-10-2017, 10:12
Client			this version:13-11-2017, 9:30
Delivery address to client	Orab (Podenzano)		
VIN	ZB3M31245CC066704 - ZB3M31245CC066705		
Production slot (week)	1		
Units	2		
Brand	Viberti		
Category	Container goose neck		
Typ	NS3P40-IT GooseNeck		

axle producer	SAF Disc	Break pad wear sensors	brake pad wear sensors K178000 (3424203300 HALDEX +WABCO wire 449 816 030 0)
Calliper	Haldex	full mudguards	YES
options	Configuration 1, axles with Tire Pilot	ferry rings	YES
KTL	YES	1st axle lifted (steering from the cabin)	YES
Nominal5 wheel	1150	Hubodometer	YES
(real 5 wheel)	1170	Lights	Europoint II
wheel size	385/65/R22,5	tire from Poland	YES
wheels*	6x BRIDGESTONE R168, 7x steel rims	rims from Poland	YES
steering axle	NO	Electric socket	2x 7pin + 1x 15 pin
axle type	BI9-22S IU30/2505 33 2040-1300 (Integral, Haldex brake callipers/zaciskie hamulcowe), with Tire Pilot	Frame	KTL + 7021- gray
Chassis PDM drawing	P005-W994650	Rear bumper profile, light fixing profile	Standard RAL 9003
QAD NR	K234724	Wheel hub	Original
landing legs/shaft length/foot/position/ground dis.	L500S750/1450/S/-/230	Side protection color	Standard (aluminum)
accessory 1	toolbox Jbz700 (W191948) + wheel basket (W017307 for ET120)	information abour standard configuration	brake system is Wabco, aluminium air tanks (160 litre total), Speed limits 70 and 80 on the rear (K033319)
accessory 2	ADR: extinguisher, extinguisher toolbox on landing leg(W983059), ADR plate, grounding strap (m07050305), assembly one wedge on mail beam (W100067) becouse of extinguisher box		
Non standard description	SAF TIRE PILOT-included		

For logistics/Indeksy magazynowe

axle type	BI9-22S IU30/2505 33 2040-1300 (Integral, Haldex brake callipers/zaciskie hamulcowe), with Tire Pilot	2x M01010001010501, M01010001010502
Break pad wear sensors	brake pad wear sensors K178000 (3424203300 HALDEX +WABCO wire 449 816 030 0)	K178000