Order No (v4) PL order No.	RS0113 first version:22-11-2017, 16:4			
Client	stock first version:22-11-2017, 16:4 stock			
Delivery address to client	Tocco CONFIGURATOR:G251145KRB-			
VIN	ZB3M300010Y066805			
	5 5			
Production slot (week)				
Units				
Brand	Viberti			
Category	Coil (107mm neck)			
Тур	NS3KRBM3-IT			
axle producer	SAF Disc	accesory, side protection		side protection when adopted for long paletbox (O204-K032615)
Calliper	Knorr	Break pad wear sensors		Knorr break pad wear sensors K025586 (Knorr sensors+WABCO wire 449 816 030 0)
options	Knorr calliper, curtainsider with dropsides, long paletbox, 2 pockets in front, 2 in rear,6 pairs of pockets in side profiles for 80x80 pillars	rear buffer		roll stop- W184261
upper structure type	Curtainsider with dropsides	mudguards		full mudguards with rainflaps only on rea axle (W973391)
hinges for dropsides	YES	ferry rings		YES
pocket for hestal pillars	YES	lashing rings for fixing goods inside semi.		YES
long palletbox	YES	1st axle lifted (steering from the cabin)		YES (axle lift K234900 according to drawing M059-W223488)
pockets for 80x80 pillars	2 pockets in front, 2 in rear,6 pairs of pockets in side profiles for 80x80 pillars	1st and 3rd axle lifted (steering from the cabin)		NO
KTL	YES	Hubodometer		NO
Nominal5 wheel	1150	Antispray on all mudguards		NO
(real 5 wheel)	1145	Lights		Aspock Europoint III (with bulbs)
wheel size	385/65/R22,5	tire from	ı Poland	NO
wheels*	6x CONTINENTAL HT3, 6x steel rims	rims from	n Poland	NO
steering axle	YES	Electric socket		2x 7pin + 1x 15 pin
axle type	BILL9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr brake callipers/zaciski hamulcowe)	Frame		KTL + 7021- gray
Chassis PDM drawing	P090-K032520	Rear bumper profile, light fixing profile		Standard RAL 9003
QAD NR	K234257	Wheel hub		Original
steering axle crossbeam	2 291 0449 00	Side protection color		Standard (aluminum)
dropside	K031360- H800-L3185-bolted with eyelets fixed to 2nd plank from bottom	Front pillar		Standard RAL9006
front wall	Viberti front wall	Rear pillar		Standard RAL9006
upper structure	M3 (aluminium rear pillars and doors, all elements from PL)	Front wall color		Standard RAL9006
roof type	lift to load	Rear door		Original
double plywood on front wall	NO	Hestal		Original
internal heights	2700	tarpaulin No.		none
upper structure planks	3 rows of alu planks 100mm	tarpaulin color		default
planks holder	W125086 - left	tarpaulin with graphic		NO
landing legs/shaft length/foot/position/ground dis.	L500S750/1450/S/up/215	back doors with graphic		NO
accesory, boxes and wheel holders, 1	toolbox Jbz700 (W191948) + wheel basket (W015165 for ET-120 or W185514 for ET-0)	information abour standard configuration		brake system is Wabco, steel air tanks (120 litre total, 2x K234810)
accesory, boxes and wheel holders, 2	ADR: extinguisher, extinguisher toolbox on landing leg(W983059), ADR plate, grounding strap (m07050305), assembly one wedge on mail beam (W100067) becouse of extinguisher box			
Non standard description	planks holder supplied by Wielton not mounted			
For logistics/Indeksy magazy				
axle type	BILL9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr brake callipers/zaciski hamulcowe)		2xM010100010113, M01010101015	
steering axle crossbeam	2 291 0449 00		M0101100299	
roof type	lift to load		oil pomp with tubes and fitting kit for chassis only M09090103_01, M09090104	

KONFIGURATOR: G251145KRB-IT

first version:22-11-2017, 16:40 this version:13-12-2017, 11:21

CONFIGURATOR:G251145KRB-IT