Order No (v9) PL order No.	2169_FP102017 WS0157 first version: 30.10.2017 14:10		
Client	Romana Diesel first version:30-10-2017, 14:10 this version:8-11-2017, 13:40		
	nomana Diesei		in production since:30-11-2017, 14:5
Delivery address to client VIN	ZB3M300010Y066714		
Production slot (week)	1		
Units			
Brand			
	Viberti NS2K/KP/KO M2 IT (107mm pock)		
Category	NS3K/KB/KO M2-IT (107mm neck)		
Тур	NS3KBM3-IT		
axle producer	SAF Disc	accesory, other, 1	none
Calliper	Knorr	accesory, side protection	side protection standard(2x w030388+ 4x M142301)
options	Knorr callipers, Curtainsider with dropsides, adopted for rear lift	accessory 1	ADR:extinguisher; extinguisher toolbox on landing leg (W983059); ADR plate; grounding strap (m07050305); assembly wedges on mai beam (2x W100067) becouse of extinguisher box
upper structure type	Curtainsider with dropsides	Break pad wear sensors	Knorr break pad wear sensors K025586 (Knorr sensors+WABCO wire 449 816 030 0)
hinges for dropsides	YES	rear buffer	roll stop- W184261
pocket for hestal pillars	YES	ferry rings	YES
long palletbox	NO	lashing rings for fixing goods inside semi.	YES
pockets for 80x80 pillars	none	1st axle lifted (steering from the cabin)	YES
KTL	YES	Lights	Aspock Europoint III (with bulbs)
Nominal5 wheel	1150	tire from Poland	NO
(real 5 wheel)	1145	rims from Poland	NO
wheel size	385/65/R22,5	Electric socket	2x 7pin + 1x 15 pin
wheels*	6x tire, 6x rims	Frame	KTL + 7021- gray
wileels.	ox tire, ox tiris		KIL + 7021- gray
steering axle	NO	Rear bumper profile, light fixing profile	Standard RAL 9003
axle type	BI9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr brake callipers/zaciski hamulcowe)	Wheel hub	Original
Chassis PDM drawing	O294-K032760	Side protection color	Standard (aluminum)
QAD NR	K234321	Front pillar	Standard RAL9006
dropside	K031360- H800-L3185-bolted with eyelets fixed to 2nd plank from bottom	Rear pillar	Standard RAL9006
front wall	Viberti front wall	Rear door	Original
upper structure	M3 (aluminium rear pillars and doors, all elements from PL)	Hestal	Original
roof type	lift to load	tarpaulin No.	none
internal heights	2700	tarpaulin color	default
upper structure planks	3 rows of alu planks 100mm	tarpaulin with graphic	NO
planks holder	W125086 - left	back doors with graphic	NO
landing legs/shaft length/foot/position/ground dis.	L500S750/1450/S/up/324	information abour standard configuration	brake system is Wabco, steel air tanks (120 litre total, 2x K034285)
accesory, boxes and wheel holders, 1	toolbox Jbz700 (W191948)		
accesory, boxes and wheel	double wheel basket (W755340)		
Non standard description	M3 version , aluminum doors from pl knorr caliper , EP3 steel airtanks 2x60 all included		
	Upper stru	cture:	
	-	054-K234250	
	NR QAD K2		
	NR QAD of front wall KC		
	NR QAD of rear KO	34399	
	NR QAD roof K2	234020	
	NR QAD planks pockets K2	234264	
For logistics/Indeksy magazy	Nr QAD Hestal pillar KO	031759	
		. 1	
axle type	BI9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr b	rake M010100010112, 2x	M010100010113

lift to load

oil pomp with tubes and fitting kit for chassis only M09090103\_01, M09090104 first version: 30-10-2017, 14:

first version:30-10-2017, 14:10 this version:8-11-2017, 13:49 in production since:30-11-2017, 14:56