

Order No (v2)	2173_FP102017		
PL order No.	first version:12-12-2017, 13:04 this version:13-12-2017, 12:46		
Client	Mossucca		
Delivery address to client	Tocco		
VIN	from ZB3M300010Y066818 to ZB3M300010Y066827		
Production slot (week)	7		
Units	10		
Brand	Viberti		
Category	NS3K/KB/KO MM2-IT-01 (80 mm neck)		
Typ	NS3KMM2-IT		

axle producer	SAF Disc	Break pad wear sensors	brake pad wear sensors K178000 (3424203300 HALDEX +WABCO wire 449 816 030 0)
Calliper	Haldex	rear buffer	roll stop- W184261
options	curtainsider	full mudguards	YES
upper structure type	curtainsider	ferry rings	YES
hinges for dropsides	NO	lashing rings for fixing goods inside semi.	NO
pocket for hestall pillars	YES	1st axle lifted (steering from the cabin)	NO
long palletbox	NO	1st and 3rd axle lifted (steering from the cabin)	NO
pockets for 80x80 pillars	none	Antispray on all mudguards	YES
KTL	YES	Lights	other
Nominal5 wheel (real 5 wheel)	1050	tire from Poland	NO
wheel size	1045	rims from Poland	NO
wheels*	385/55/R22,5	Electric socket	2x 7pin + 1x 15 pin
	7x MICHELIN Multit T, 7x rims	Frame	KTL + 7021- gray
steering axle	NO	Rear bumper profile, light fixing profile	Standard RAL 9003
axle type	BI9-22S IU28/2005 33 2040-1300 (Integral, Haldex brake callipers/zaciskie hamulcowe)	Wheel hub	Original
Chassis PDM drawing	P184-K030120	Side protection color	Standard (aluminum)
QAD NR	K030867	Front pillar	Standard RAL9006
front wall	Aluminium front wall	Rear pillar	Standard RAL9006
upper structure	M3 (aluminium rear pillars and doors, all elements from PL)	Front wall color	Standard RAL9006
roof type	multi-point	Rear door	Original
double plywood on front wall	NO	Hestall	Original
internal heights	2850	tarpaulin No.	none
upper structure planks	5 rows of alu planks 100mm (1 on floor + 4 per section)	tarpaulin color	default
planks holder	none	tarpaulin with graphic	NO
landing legs/shaft length/foot/position/ground dis.	L500S750/1450/S/up/198	back doors with graphic	NO
accessory 1	2x spare wheel winch (W195853 for ET 120) + toolbox Jbz700 (W191948)	information about standard configuration	brake system is Wabco, aluminium air tanks (160 litre total), side profile with safety lock
accessory 2	Pallet stoppers (8x W185358)		
Non standard description	upperstructure wielton (front wall in alluminum, front and rear pillar in alluminum, system to lift each pillars) tarapulin XL steel protection for the floor (anti slipery plate on the rear)		

For logistics/Indeksy magazynowe

Category	NS3K/KB/KO MM2-IT-01 (80 mm neck)	plywood for floor M120301_02
axle type	BI9-22S IU28/2005 33 2040-1300 (Integral, Haldex brake callipers/zaciskie hamulcowe)	M010100010104, 2x M010100010105
roof type	multi-point	oil pump with tubes and fitting kit for chassis only M09090103_01, M09090104
Break pad wear sensors	brake pad wear sensors K178000 (3424203300 HALDEX +WABCO wire 449 816 030 0)	K178000

KONFIGURATOR: G061050PODWO-IT/M2