IF2130 – Organisasi dan Arsitektur Komputer

sumber: Greg Kesden, CMU 15-213, 2012

Representasi Informasi

Achmad Imam Kistijantoro (imam@informatika.org)
Anggrahita Bayu Sasmita
Rahmat Mulyawan
Infall Syafalni

Representasi Biner



source: Slide CMU 15-213

Encoding Byte Values

- Byte = 8 bit
- 00000000_2 hingga 11111111_2
- Desimal 0 – 255
- Hexadesimal 00 – FF
  - 0xdeadbeef
  - 0xc0ffeeee

Organisasi Memori Berorientasi Byte



- Program mengakses lokasi berbasis virtual memori
- terdiri atas array byte yang sangat besar
- diimplementasikan sebagai hierarki dari beberapa jenis memori
- sistem menyediakan private address space ke proses
  - program dijalankan dan tidak saling mengganggu program lain
- Compiler + Runtime system mengontrol alokasi
  - dimana berbagai objek program harus disimpan
  - semua alokasi berada pada virtual address space yang tunggal

Machine Words

- **Mesin memiliki "Word Size"**
  - Ukuran nominal data bernilai integer
    - Termasuk addresses
  - Umumnya, mesin sekarang menggunakan 32 bits (4 bytes) words
    - Batas alamat 4GB
    - Terlalu kecil untuk aplikasi yang memerlukan memori intensif
  - High-end systems menggunakan 64 bits (8 bytes) words
    - Potential address space ≈ 1.8 X 1019 bytes
    - x86-64 machines support 48-bit addresses: 256 Terabytes
  - Machines support multiple data formats
    - Fractions or multiples of word size
    - Always integral number of bytes

Word Oriented Memory Organization

- **Addresses Specify Byte Locations**
  - Address of first byte in word
  - Addresses of successive words differ by 4 (32-bit) or 8 (64-bit)



Representasi Data

C Data Type	Typical 32-bit	Intel IA32	x86-64
char	1	1	1
short	2	2	2
int	4	4	4
long	4	4	8
long long	8	8	8
float	4	4	4
double	8	8	8
long double	8	10/12	10/16
pointer	4	4	8

Byte Ordering

- **How should bytes within a multi-byte word be ordered in memory?**
- **Conventions**
  - Big Endian: Sun, PPC Mac, Internet
    - Least significant byte has highest address
  - Little Endian: x86
    - Least significant byte has lowest address



Melihat representasi data

- Code untuk mencetak representasi data

```
typedef unsigned char *pointer;

void show_bytes(pointer start, int len){
  int i;
  for (i = 0; i < len; i++)
    printf(”%p\t0x%.2x\n",start+i, start[i]);
  printf("\n");
}
```

Printf directives:
%p: Print pointer
%x: Print Hexadecimal

```
int a = 15213;
printf("int a = 15213;\n");
show_bytes((pointer) &a, sizeof(int));
```

integer = 4 byte

Result (Linux):

least significant digit

```
int a = 15213;
0x11ffffcb8 0x6d
0x11ffffcb9 0x3b
0x11ffffcba 0x00
0x11ffffcbb 0x00
```

address

merepresentasikan heksa

lowest significant digit

little endian

least significant di lowest address

heksadesimal
0123456789
a = 10
b = 11
c = 12
d = 13
e =14
f = 15

1 byte = 2 heksa = 1 alamat

Representing Integers

Decimal:	15213			
Binary:	0011	1011	0110	1101
Hex:	3	B	6	D

negatif
1111
-8 + 4 + 2 + 1 = -1

int A = 15213;

address low

address high



int B = -15213;



komplemen 1100 0100 1001
1
1100 0100 1001 0011

long int C = 15213;



representasi 4 bit,
kalau paling kirinya 1 berarti negatif

Two's complement representation

biner dikomplemen (0 diganti 1 dan sebaliknya) lalu ditambah 1

Representing Pointers

```
int B = -15213;
int *P = &B;
```

Sun	IA32	x86-64
EF	D4	0C
FF	F8	89
FB	FF	EC
2C	BF	FF
		FF
		7F
		00
		00

Different compilers & machines assign different locations to objects

Representing Strings

nilai 1 udh pasti disimpan di
alamat paling rendah
nilai 8 di alamat kedua dst

```
char S[6] = "18243";
```

- Strings in C
  - Represented by array of characters
  - Each character encoded in ASCII format
    - Standard 7-bit encoding of character set
    - Character "0" has code 0x30
      - Digit *i* has code 0x30+*i*
  - String should be null-terminated
    - Final character = 0
- Compatibility
  - Byte ordering not an issue



gaada little endian sm big endian krn string disimpan per character

Boolean Algebra

- Developed by George Boole in 19th Century
  - Algebraic representation of logic
    - Encode "True" as 1 and "False" as 0

And

- **A&B = 1 when both A=1 and B=1**

&	0	1
0	0	0
1	0	1

Or

- **A|B = 1 when either A=1 or B=1**

|	0	1
0	0	1
1	1	1

Not

- **~A = 1 when A=0**

~	
0	1
1	0

Exclusive-Or (Xor)

- **A^B = 1 when either A=1 or B=1, but not both**

^	0	1
0	0	1
1	1	0

General Boolean Algebras

- Operate on Bit Vectors
  - Operations applied bitwise

```
  01101001     01101001     01101001
& 01010101   | 01010101   ^ 01010101   ~ 01010101
  01000001     01111101     00111100     10101010
```

- All of the Properties of Boolean Algebra Apply

Example: Representing & Manipulating Sets

- Representation
  - Width w bit vector represents subsets of {0, …, w–1}
  - $a_j = 1$ if $j \in A$

    - 01101001 { 0, 3, 5, 6 }
    - *76543210*

    - 01010101 { 0, 2, 4, 6 }
    - *76543210*
- Operations

&	Intersection	01000001	{ 0, 6 }
|	Union	01111101	{ 0, 2, 3, 4, 5, 6 }
^	Symmetric difference	00111100	{ 2, 3, 4, 5 }
~	Complement	10101010	{ 1, 3, 5, 7 }

Bit-Level Operations in C

- Operations &, |, ~, ^ Available in C
  - Apply to any "integral" data type
    - long, int, short, char, unsigned
  - View arguments as bit vectors
  - Arguments applied bit-wise
- Examples (Char data type)
  - ~0x41 = 0xBE
    - $\sim 01000001_2 = 10111110_2$
  - ~0x00 = 0xFF
    - $\sim 00000000_2 = 11111111_2$
  - 0x69 & 0x55 = 0x41
    - $01101001_2 \,\&\, 01010101_2 = 01000001_2$
  - 0x69 | 0x55 = 0x7D
    - $01101001_2 \mid 01010101_2 = 01111101_2$

Contrast: Logic Operations in C

- Contrast to Logical Operators
  - &&, ||, !
    - View 0 as "False"
    - Anything nonzero as "True"
    - Always return 0 or 1
    - Early termination

0 = false
selain 0 = true

- Examples (char data type)
  - !0x41 = 0x00
  - !0x00 = 0x01
  - !!0x41 = 0x01
  - 0x69 && 0x55 = 0x01
  - 0x69 || 0x55 = 0x01
  - p && *p (avoids null pointer access)

true and false = false
true or false = true

Contrast: Logic Operations in C

- Contrast to Logical Operators
  - &&, ||, !
    - View 0 as “Fa
    - Anything nonz ”
    - Alway
    - Early
- Example
  - !0x41 =
  - !0x00 =
  - !!0x41 =
  - 0x69 &&
  - 0x69 || 0x55 = 0x01
  - p && *p (avoids null pointer access)

Watch out for && vs. & (and || vs. |)…
one of the more common oopsies in C programming

Shift Operations

x86 = little endian

- Left Shift: x << y
  - Shift bit-vector x left y positions
    - Throw away extra bits on left
  - Fill with 0's on right
- Right Shift: x >> y
  - Shift bit-vector x right y positions
    - Throw away extra bits on right
  - Logical shift
    - Fill with 0's on left
  - Arithmetic shift
    - Replicate most significant bit on left
- Undefined Behavior
  - Shift amount < 0 or ≥ word size

sama

Argument x	01100010
<< 3	00010000
Log. >> 2	00011000
Arith. >> 2	00011000

unsigned (+)

signed (-)

Argument x	10100010
<< 3	00010000
Log. >> 2	00101000
Arith. >> 2	11101000

karena +, jadi kirinya diisi 00

karena -, jadi kirinya diisi 11

geser kanan:
semua yang kosong kalau ARITH diisi 1
semua yang kosong kalau LOGIC diisi 0

Encoding Integers

Unsigned

$$B2U(X) = \sum_{i=0}^{w-1} x_i \cdot 2^i$$

Two's Complement

$$B2T(X) = -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$

Sign Bit

```
short int x =  15213;
short int y = -15213;
```

- C `short` 2 bytes long

	Decimal	Hex	Binary
x	15213	**3B 6D**	**00111011 01101101**
y	-15213	**C4 93**	**11000100 10010011**

- Sign Bit
  - For 2's complement, most significant bit indicates sign
    - 0 for nonnegative
    - 1 for negative

Two-complement Encoding Example (Cont.)

```
x =      15213: 00111011 01101101
y =     -15213: 11000100 10010011
```

signed

Weight	15213		-15213	
1	1	1	1	1
2	0	0	1	2
4	1	4	0	0
8	1	8	0	0
16	0	0	1	16
32	1	32	0	0
64	1	64	0	0
128	0	0	1	128
256	1	256	0	0
512	1	512	0	0
1024	0	0	1	1024
2048	1	2048	0	0
4096	1	4096	0	0
8192	1	8192	0	0
16384	0	0	1	16384
-32768	0	0	1	-32768
Sum		**15213**		**-15213**

Numeric Ranges

- Unsigned Values
  - *UMin* = 0

    000…0
  - *UMax* = $2^w - 1$

    111…1

- Two's Complement Values
  - *TMin* = -2^{w-1}

    100…0
  - *TMax* = $2^{w-1} - 1$

    011…1
- Other Values
  - Minus 1

    111…1 = -1

Values for $W = 16$

	Decimal	Hex	Binary
UMax	**65535**	**FF FF**	11111111 11111111
TMax	**32767**	**7F FF**	01111111 11111111
TMin	**-32768**	80 00	10000000 00000000
-1	**-1**	**FF FF**	11111111 11111111
0	**0**	00 00	00000000 00000000

Values for Different Word Sizes

	W			
	8	**16**	**32**	**64**
UMax	255	65,535	4,294,967,295	18,446,744,073,709,551,615
TMax	127	32,767	2,147,483,647	9,223,372,036,854,775,807
TMin	-128	-32,768	-2,147,483,648	-9,223,372,036,854,775,808

- Observations
  - $|TMin| = TMax + 1$
    - Asymmetric range
  - $UMax = 2 * TMax + 1$

- **C Programming**
  - #include <limits.h>
  - Declares constants, e.g.,
    - ULONG_MAX
    - LONG_MAX
    - LONG_MIN
  - Values platform specific

Unsigned & Signed Numeric Values

X	B2U(X) biner to unsigned	B2T(X) biner to two's complement int
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	8	–8
1001	9	–7
1010	10	–6
1011	11	–5
1100	12	–4
1101	13	–3
1110	14	–2
1111	15	–1

- **Equivalence**
  - Same encodings for nonnegative values
- **Uniqueness**
  - Every bit pattern represents unique integer value
  - Each representable integer has unique bit encoding
- **$\Rightarrow$ Can Invert Mappings**
  - $U2B(x) = B2U^{-1}(x)$
    - Bit pattern for unsigned integer
  - $T2B(x) = B2T^{-1}(x)$
    - Bit pattern for two's comp integer

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - **Conversion, casting**
  - Expanding, truncating
  - Addition, negation, multiplication, shifting
  - Summary
- Representations in memory, pointers, strings

Mapping Between Signed & Unsigned



- Mappings between unsigned and two's complement numbers: keep bit representations and reinterpret

Mapping Signed ↔ Unsigned

Bits	Signed	Unsigned
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	-8	8
1001	-7	9
1010	-6	10
1011	-5	11
1100	-4	12
1101	-3	13
1110	-2	14
1111	-1	15

→ T2U →

← U2T ←

Mapping Signed ↔ Unsigned

Bits	Signed	Unsigned
0000	0	0
0001	1	1
0010	2	2
0011	3	3
0100	4	4
0101	5	5
0110	6	6
0111	7	7
1000	-8	8
1001	-7	9
1010	-6	10
1011	-5	11
1100	-4	12
1101	-3	13
1110	-2	14
1111	-1	15

=

+/- 16

Relation between Signed & Unsigned



Maintain Same Bit Pattern



Large negative weight
becomes
Large positive weight

Conversion Visualized

- 2's Comp. → Unsigned
  - Ordering Inversion
  - Negative → Big Positive



Signed vs. Unsigned in C

e.g.
x = 15
y = x + 20

20 defaultnya signed, kalau mau jadi unsigned harus dikasih u setelahnya

- Constants
  - By default are considered to be signed integers
  - Unsigned if have "U" as suffix

```
0U, 4294967259U
```

- Casting
  - Explicit casting between signed & unsigned same as U2T and T2U

```
int tx, ty;
unsigned ux, uy;
tx = (int) ux;
uy = (unsigned) ty;
```

  - Implicit casting also occurs via assignments and procedure calls

```
tx = ux;
uy = ty;
```

Casting Surprises

- Expression Evaluation
  - If there is a mix of unsigned and signed in single expression, ***signed values implicitly cast to unsigned***
  - Including comparison operations <, >, ==, <=, >=
  - Examples for *W* = 32: **TMIN = -2,147,483,648 , TMAX = 2,147,483,647**

kalau salah 1 unsigned, jadiin 22 nya unsigned

Constant$_1$	Constant$_2$	Relation	Evaluation
0	0U	==	unsigned
-1	0	<	signed
-1	0U	>	unsigned
2147483647	-2147483647-1	>	signed
2147483647U	-2147483647-1	<	unsigned
-1	-2	>	signed
(unsigned)-1	-2	>	unsigned
2147483647	2147483648U	<	unsigned
2147483647	(int) 2147483648U	>	signed

yg di unsigned ini doang

jadi signed karena ada int

Summary
Casting Signed ↔ Unsigned: Basic Rules

- Bit pattern is maintained
- But reinterpreted
- Can have unexpected effects: adding or subtracting 2^w

- Expression containing signed and unsigned int
  - `int` **is cast to** `unsigned`**!!**

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - **Expanding, truncating**
  - Addition, negation, multiplication, shifting
  - Summary
- Representations in memory, pointers, strings

Sign Extension

- Task:
  - Given w-bit signed integer x
  - Convert it to $w+k$-bit integer with same value
- Rule:
  - Make k copies of sign bit:
  - $X' = \underbrace{x_{w-1}, \ldots, x_{w-1}}_{k \text{ copies of MSB}}, x_{w-1}, x_{w-2}, \ldots, x_0$



Sign Extension Example

```
short int x =  15213;
int      ix = (int) x;
short int y = -15213;
int      iy = (int) y;
```

	Decimal	Hex	Binary
x	15213	3B 6D	00111011 01101101
ix	15213	00 00 3B 6D	00000000 00000000 00111011 01101101
y	-15213	C4 93	11000100 10010011
iy	-15213	FF FF C4 93	11111111 11111111 11000100 10010011

- Converting from smaller to larger integer data type
- C automatically performs sign extension

Summary:
Expanding, Truncating: Basic Rules

- Expanding (e.g., short int to int)
  - Unsigned: zeros added
  - Signed: sign extension
  - Both yield expected result

- Truncating (e.g., unsigned to unsigned short)
  - Unsigned/signed: bits are truncated
  - Result reinterpreted
  - Unsigned: mod operation
  - Signed: similar to mod
  - For small numbers yields expected behaviour

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - **Addition, negation, multiplication, shifting**
- Representations in memory, pointers, strings
- Summary

Unsigned Addition

Operands: *w* bits

True Sum: *w*+1 bits

Discard Carry: *w* bits



- Standard Addition Function
  - Ignores carry output
- Implements Modular Arithmetic

$s \quad = \quad \mathrm{UAdd}_w(u, v) \quad = \quad u + v \mod 2^w$

Visualizing (Mathematical) Integer Addition

- Integer Addition
  - 4-bit integers *u*, *v*
  - Compute true sum $\text{Add}_4(u, v)$
  - Values increase linearly with *u* and *v*
  - Forms planar surface

$\text{Add}_4(u, v)$



Visualizing Unsigned Addition

- Wraps Around
  - If true sum ≥ 2^w
  - At most once





Two’s Complement Addition

Operands: *w* bits

True Sum: *w*+1 bits

Discard Carry: *w* bits



- TAdd and UAdd have Identical Bit-Level Behavior
  - Signed vs. unsigned addition in C:

```
int s, t, u, v;
s = (int) ((unsigned) u + (unsigned) v);
t = u + v
```

  - Will give `s == t`

TAdd Overflow

- **Functionality**
  - True sum requires w+1 bits
  - Drop off MSB
  - Treat remaining bits as 2's comp. integer



Visualizing 2's Complement Addition

- Values
  - 4-bit two's comp.
  - Range from -8 to +7
- Wraps Around
  - If sum $\geq 2^{w-1}$
    - Becomes negative
    - At most once
  - If sum $< -2^{w-1}$
    - Becomes positive
    - At most once



Multiplication

- Goal: Computing Product of w-bit numbers x, y
  - Either signed or unsigned
- But, exact results can be bigger than w bits
  - Unsigned: up to $2w$ bits
    - Result range: $0 \leq x * y \leq (2^w - 1)^2 = 2^{2w} - 2^{w+1} + 1$
  - Two's complement min (negative): Up to $2w$-1 bits
    - Result range: $x * y \geq (-2^{w-1})*(2^{w-1}-1) = -2^{2w-2} + 2^{w-1}$
  - Two's complement max (positive): Up to $2w$ bits, but only for $(TMin_w)^2$
    - Result range: $x * y \leq (-2^{w-1})^2 = 2^{2w-2}$
- So, maintaining exact results…
  - would need to keep expanding word size with each product computed
  - is done in software, if needed
    - e.g., by "arbitrary precision" arithmetic packages

Unsigned Multiplication in C

Operands: *w* bits

True Product: 2**w* bits

Discard *w* bits: *w* bits



- Standard Multiplication Function
  - Ignores high order *w* bits
- Implements Modular Arithmetic

  $\mathrm{UMult}_w(u, v) = u \cdot v \bmod 2^w$

Signed Multiplication in C

Operands: *w* bits

True Product: 2**w* bits

Discard *w* bits: *w* bits



- Standard Multiplication Function
  - Ignores high order *w* bits
  - Some of which are different for signed vs. unsigned multiplication
  - Lower bits are the same

Power-of-2 Multiply with Shift

- Operation
  - `u << k` gives `u * 2`^{k}
  - Both signed and unsigned

Operands: w bits

True Product: $w+k$ bits

Discard k bits: w bits



- Examples
  - `u << 3          ==   u * 8`
  - `u << 5 - u << 3    ==     u * 24`
  - Most machines shift and add faster than multiply
    - Compiler generates this code automatically

Unsigned Power-of-2 Divide with Shift

- Quotient of Unsigned by Power of 2
  - `u >> k` gives $\lfloor u / 2^k \rfloor$
  - Uses logical shift



	Division	Computed	Hex	Binary
`x`	15213	15213	`3B 6D`	`00111011 01101101`
`x >> 1`	7606.5	7606	`1D B6`	`00011101 10110110`
`x >> 4`	950.8125	950	`03 B6`	`00000011 10110110`
`x >> 8`	59.4257813	59	`00 3B`	`00000000 00111011`

Signed Power-of-2 Divide with Shift

- Quotient of Signed by Power of 2
  - `x >> k` gives $\lfloor$ `x / 2`^{k} $\rfloor$
  - Uses arithmetic shift
  - Rounds wrong direction when `u < 0`



	Division	Computed	Hex	Binary
`y`	-15213	-15213	C4 93	11000100 10010011
`y >> 1`	-7606.5	-7607	E2 49	11100010 01001001
`y >> 4`	-950.8125	-951	FC 49	11111100 01001001
`y >> 8`	-59.4257813	-60	FF C4	11111111 11000100

Correct Power-of-2 Divide

- Quotient of Negative Number by Power of 2
  - Want $\lceil$ **`x / 2`**$^k \rceil$ (Round Toward 0)
  - Compute as $\lfloor$ **`(x+2`**^{k}**`-1) / 2`**$^k \rfloor$
    - In C: **`(x + (1<<k)-1) >> k`**
    - Biases dividend toward 0

Case 1: No rounding



Biasing has no effect

Correct Power-of-2 Divide (Cont.)

Case 2: Rounding



Biasing adds 1 to final result

Today: Bits, Bytes, and Integers

- Representing information as bits
- Bit-level manipulations
- Integers
  - Representation: unsigned and signed
  - Conversion, casting
  - Expanding, truncating
  - Addition, negation, multiplication, shifting
  - **Summary**
- Representations in memory, pointers, strings

Arithmetic: Basic Rules

- Addition:
  - Unsigned/signed: Normal addition followed by truncate, same operation on bit level
  - Unsigned: addition mod 2^w
    - Mathematical addition + possible subtraction of 2^w
  - Signed: modified addition mod 2^w (result in proper range)
    - Mathematical addition + possible addition or subtraction of 2^w

- Multiplication:
  - Unsigned/signed: Normal multiplication followed by truncate, same operation on bit level
  - Unsigned: multiplication mod 2^w
  - Signed: modified multiplication mod 2^w (result in proper range)

Why Should I Use Unsigned?

- *Don't* Use Just Because Number Nonnegative
  - Easy to make mistakes

```
unsigned i;
for (i = cnt-2; i >= 0; i--)
  a[i] += a[i+1];
```

  - Can be very subtle

```
#define DELTA sizeof(int)
int i;
for (i = CNT; i-DELTA >= 0; i-= DELTA)
  . . .
```

- *Do* Use When Performing Modular Arithmetic
  - Multiprecision arithmetic
- *Do* Use When Using Bits to Represent Sets
  - Logical right shift, no sign extension