




# IF2240 – Basis Data SQL (Part 4)

# Summer


---

Silberschatz, Korth, Sudarshan: "Database System Concepts", 7<sup>th</sup> Edition

- Chapter 3 : Introduction to SQL
- Chapter 4 : Intermediate SQL



### Schema Diagram



# Views

---

In some cases, it is not desirable for all users to see the entire logical model (that is, all the actual relations stored in the database.)

Consider a person who needs to know an instructors name and department, but not the salary. This person should see a relation described, in SQL, by

```
select ID, name, dept_name  
from instructor
```

A **view** provides a mechanism to hide certain data from the view of certain users.

Any relation that is not of the conceptual model but is made visible to a user as a “virtual relation” is called a **view**.

# View Definition

---

A view is defined using the **create view** statement which has the form

```
create view v as < query expression >
```

where <query expression> is any legal SQL expression. The view name is represented by **v**.

Once a view is defined, the view name can be used to refer to the virtual relation that the view generates.

View definition is not the same as creating a new relation by evaluating the query expression

- Rather, a view definition causes the saving of an expression; the expression is substituted into queries using the view.

# View Definition and Use

---

A view of instructors without their salary

```
create view faculty as  
    select ID, name, dept_name  
    from instructor
```

Find all instructors in the Biology department

```
select name  
from faculty  
where dept_name = 'Biology'
```

Create a view of department salary totals

```
create view departments_total_salary(dept_name, total_salary) as  
    select dept_name, sum (salary)  
    from instructor  
    group by dept_name;
```

# Views Defined Using Other Views

---

One view may be used in the expression defining another view

A view relation  $v_1$  is said to *depend directly* on a view relation  $v_2$  if  $v_2$  is used in the expression defining  $v_1$

A view relation  $v_1$  is said to *depend on* view relation  $v_2$  if either  $v_1$  depends directly to  $v_2$  or there is a path of dependencies from  $v_1$  to  $v_2$

A view relation  $v$  is said to be *recursive* if it depends on itself.

# Views Defined Using Other Views

---

```
create view physics_fall_2017 as
  select course.course_id, sec_id, building, room_number
  from course, section
  where course.course_id = section.course_id
        and course.dept_name = 'Physics'
        and section.semester = 'Fall'
        and section.year = '2017';
```

```
create view physics_fall_2017_watson as
  select course_id, room_number
  from physics_fall_2017
  where building= 'Watson';
```



# Materialized Views

---

Certain database systems allow view relations to be physically stored.

- Physical copy created when the view is defined.
- Such views are called **Materialized view**:

If relations used in the query are updated, the materialized view result becomes out of date

- Need to **maintain** the view, by updating the view whenever the underlying relations are updated.

# Modification of the Database

---

Deletion of tuples from a given relation.

Insertion of new tuples into a given relation

Updating of values in some tuples in a given relation

# Deletion

---

Delete all instructors

```
delete from instructor
```

Delete all instructors from the Finance department

```
delete from instructor  
where dept_name = 'Finance';
```

*Delete all tuples in the instructor relation for those instructors associated with a department located in the Watson building.*

```
delete from instructor  
where dept name in (select dept name  
                    from department  
                    where building = 'Watson');
```

## Deletion (Cont.)

---

Delete all instructors whose salary is less than the average salary of instructors

```
delete from instructor
where salary < (select avg (salary)
                  from instructor);
```

- Problem: as we delete tuples from *instructor*, the average salary changes
- Solution used in SQL:
  1. First, compute **avg** (*salary*) and find all tuples to delete
  2. Next, delete all tuples found above (without recomputing **avg** or retesting the tuples)

# Insertion

---

Add a new tuple to *course*

```
insert into course
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

or equivalently

```
insert into course (course_id, title, dept_name, credits)
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

Add a new tuple to *student* with *tot\_creds* set to null

```
insert into student
  values ('3003', 'Green', 'Finance', null);
```

## Insertion (Cont.)

---

Make each student in the Music department who has earned more than 144 credit hours an instructor in the Music department with a salary of \$18,000.

```
insert into instructor
  select ID, name, dept_name, 18000
  from student
  where dept_name = 'Music' and total_cred > 144;
```

The **select from where** statement is evaluated fully before any of its results are inserted into the relation.

Otherwise queries like

```
insert into table1 select * from table1
```

would cause problem

# Updates

---

Give a 5% salary raise to all instructors

```
update instructor  
set salary = salary * 1.05
```

Give a 5% salary raise to those instructors who earn less than 70000

```
update instructor  
set salary = salary * 1.05  
where salary < 70000;
```

Give a 5% salary raise to instructors whose salary is less than average

```
update instructor  
set salary = salary * 1.05  
where salary < (select avg (salary)  
                from instructor);
```

# Updates (Cont.)

---

Increase salaries of instructors whose salary is over \$100,000 by 3%, and all others by a 5%

- Write two **update** statements:

```
update instructor
  set salary = salary * 1.03
  where salary > 100000;
update instructor
  set salary = salary * 1.05
  where salary <= 100000;
```

- The order is important
- Can be done better using the **case** statement (next slide)



# Case Statement for Conditional Updates

---

Same query as before but with case statement

```
update instructor
set salary = case
    when salary <= 100000 then salary * 1.05
    else salary * 1.03
end
```

# Updates with Scalar Subqueries

---

Recompute and update *tot\_creds* value for all students

```
update student S
set tot_cred = (select sum(credits)
                from takes, course
                where takes.course_id = course.course_id and
                      S.ID= takes.ID and
                      takes.grade <> 'F' and
                      takes.grade is not null);
```

Sets *tot\_creds* to null for students who have not taken any course

Instead of `sum(credits)`, use:

```
case
  when sum(credits) is not null then sum(credits)
  else 0
end
```

# Update of a View

---

Add a new tuple to *faculty* view which we defined earlier

```
insert into faculty  
  
values ('30765', 'Green', 'Music');
```

This insertion must be represented by the insertion into the *instructor* relation

- Must have a value for salary.

Two approaches

- Reject the insert
- Insert the tuple

```
('30765', 'Green', 'Music', null)
```

into the *instructor* relation

# Some Updates Cannot be Translated Uniquely

---

```
create view instructor_info as
  select ID, name, building
  from instructor, department
  where instructor.dept_name = department.dept_name;
```

```
insert into instructor_info
  values ('69987', 'White', 'Taylor');
```

Issues

- Which department, if multiple departments in Taylor?
- What if no department is in Taylor?

# And Some Not at All

---

```
create view history_instructors as  
  select *  
  from instructor  
  where dept_name= 'History';
```

What happens if we insert

```
('25566', 'Brown', 'Biology', 100000)
```

into *history\_instructors*?

# View Updates in SQL

---

Most SQL implementations allow updates only on simple views

- The **from** clause has only one database relation.
- The **select** clause contains only attribute names of the relation, and does not have any expressions, aggregates, or **distinct** specification.
- Any attribute not listed in the **select** clause can be set to null
- The query does not have a **group** by or **having** clause.

# Data Definition Language

---

The SQL data-definition language (DDL) allows the specification of information about relations, including:

1. The schema for each relation.
2. The type of values associated with each attribute.
3. The Integrity constraints
4. The set of indices to be maintained for each relation.
5. Security and authorization information for each relation.
6. The physical storage structure of each relation on disk.

# Domain Types in SQL (1)

---

**char(*n*)**. Fixed length character string, with user-specified length *n*.

**varchar(*n*)**. Variable length character strings, with user-specified maximum length *n*.

**int**. Integer (a finite subset of the integers that is machine-dependent).

**smallint**. Small integer (a machine-dependent subset of the integer domain type).

**numeric(*p*,*d*)**. Fixed point number, with user-specified precision of *p* digits, with *d* digits to the right of decimal point. (ex., **numeric(3,1)**, allows 44.5 to be stored exactly, but not 444.5 or 0.32)

**real, double precision**. Floating point and double-precision floating point numbers, with machine-dependent precision.

**float(*n*)**. Floating point number, with user-specified precision of at least *n* digits.



# Domain Types in SQL (2)

---

**date** Dates, containing a (4 digit) year, month and date

- Example: **date** '2005-7-27'

**time** Time of day, in hours, minutes and seconds.

- Example: **time** '09:00:30'      **time** '09:00:30.75'

**timestamp** date plus time of day

- Example: **timestamp** '2005-7-27 09:00:30.75'

**interval** period of time

- Example: **interval** '1' day
- Subtracting a date/time/timestamp value from another gives an interval value
- Interval values can be added to date/time/timestamp values

# Create Table Construct

---

An SQL relation is defined using the **create table** command:

```
create table r
```

```
(A1 D1, A2 D2, ..., An Dn,  
  (integrity-constraint1),  
  ...,  
  (integrity-constraintk))
```

- *r* is the name of the relation
- each *A<sub>i</sub>* is an attribute name in the schema of relation *r*
- *D<sub>i</sub>* is the data type of values in the domain of attribute *A<sub>i</sub>*

Example:

```
create table instructor (  
    ID          char(5),  
    name        varchar(20),  
    dept_name   varchar(20),  
    salary      numeric(8,2))
```

# Integrity Constraints in Create Table

---

Types of integrity constraints

- **primary key** ( $A_1, \dots, A_n$ )
- **foreign key** ( $A_m, \dots, A_n$ ) references  $r$
- **not null**

SQL prevents any update to the database that violates an integrity constraint.

Example:

```
create table instructor (  
    ID          char(5),  
    name        varchar(20) not null,  
    dept_name   varchar(20),  
    salary      numeric(8,2),  
    primary key (ID),  
    foreign key (dept_name) references department);
```

## And a Few More Relation Definitions

---

```
create table student (  
    ID          varchar(5),  
    name        varchar(20) not null,  
    dept_name    varchar(20),  
    tot_cred     numeric(3,0),  
    primary key (ID),  
    foreign key (dept_name) references department);
```

```
create table takes (  
    ID          varchar(5),  
    course_id    varchar(8),  
    sec_id       varchar(8),  
    semester     varchar(6),  
    year         numeric(4,0),  
    grade        varchar(2),  
    primary key (ID, course_id, sec_id, semester, year) ,  
    foreign key (ID) references student,  
    foreign key (course_id, sec_id, semester, year) references section);
```

## And more still

---

```
create table course (  
    course_id      varchar(8),  
    title           varchar(50),  
    dept_name      varchar(20),  
    credits         numeric(2,0),  
    primary key (course_id),  
    foreign key (dept_name) references department);
```

# Updates to tables

---

## Drop Table

- `drop table  $r$`

## Alter

- `alter table  $r$  add  $A$   $D$` 
  - where  $A$  is the name of the attribute to be added to relation  $r$  and  $D$  is the domain of  $A$ .
  - All exiting tuples in the relation are assigned *null* as the value for the new attribute.
- `alter table  $r$  drop  $A$` 
  - where  $A$  is the name of an attribute of relation  $r$
  - Dropping of attributes not supported by many databases.

# View Updates in SQL

---

Most SQL implementations allow updates only on simple views

- The **from** clause has only one database relation.
- The **select** clause contains only attribute names of the relation, and does not have any expressions, aggregates, or **distinct** specification.
- Any attribute not listed in the **select** clause can be set to null
- The query does not have a **group by** or **having** clause.