Processes

Achmad Imam Kistijantoro (imam@staff.stei.itb.ac.id)
Judhi Santoso (judhi@staff.stei.itb.ac.id)
Robithoh Annur (robithoh@stafff.stei.itb.ac.id)

Chapter 3: Processes

- Process Concept
- Process Scheduling
- Operations on Processes
- Cooperating Processes
- Interprocess Communication
- Communication in Client-Server Systems

Process Concept

- An operating system executes a variety of programs:
  - Batch system – jobs
  - Time-shared systems – user programs or tasks
- Textbook uses the terms *job* and *process* almost interchangeably
- Process – a program in execution; process execution must progress in sequential fashion
- A process includes:
  - program counter
  - stack
  - data section

Process in Memory



Process State

- As a process executes, it changes *state*
  - **new**: The process is being created
  - **running**: Instructions are being executed
  - **waiting**: The process is waiting for some event to occur
  - **ready**: The process is waiting to be assigned to a process
  - **terminated**: The process has finished execution

Diagram of Process State



Process Control Block (PCB)

Information associated with each process

- Process state
- Program counter
- CPU registers
- CPU scheduling information
- Memory-management information
- Accounting information
- I/O status information

Process Control Block (PCB)



CPU Switch From Process to Process



Process Representation in Linux

- Represented by the C structure `task_struct`

```
pid t_pid; /* process identifier */
long state; /* state of the process */
unsigned int time_slice /* scheduling information */
struct task_struct *parent; /* this process's parent */
struct list_head children; /* this process's children */
struct files_struct *files; /* list of open files */
struct mm_struct *mm; /* address space of this process */
```



https://git.kernel.org/pub/scm/linux/kernel/git/torvalds/linux.git/tree/include/linux/sched.h?h=v5.11-rc5#n649

Process Scheduling Queues

- **Job queue** – set of all processes in the system
- **Ready queue** – set of all processes residing in main memory, ready and waiting to execute
- **Device queues** – set of processes waiting for an I/O device
- Processes migrate among the various queues

Ready Queue And Various I/O Device Queues



Representation of Process Scheduling



Schedulers

- **Long-term scheduler** (or job scheduler) – selects which processes should be brought into the ready queue
- **Short-term scheduler** (or CPU scheduler) – selects which process should be executed next and allocates CPU

Addition of Medium Term Scheduling



Schedulers (Cont.)

- Short-term scheduler is invoked very frequently (milliseconds) $\Rightarrow$ (must be fast)
- Long-term scheduler is invoked very infrequently (seconds, minutes) $\Rightarrow$ (may be slow)
- The long-term scheduler controls the *degree of multiprogramming*
- Processes can be described as either:
  - **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts
  - **CPU-bound process** – spends more time doing computations; few very long CPU bursts

Multitasking in Mobile Systems

- Some systems / early systems allow only one process to run, others suspended
- Due to screen real estate, user interface limits iOS provides for a
  - Single **foreground** process- controlled via user interface
  - Multiple **background** processes– in memory, running, but not on the display, and with limits
  - Limits include single, short task, receiving notification of events, specific long-running tasks like audio playback
- Android runs foreground and background, with fewer limits
  - Background process uses a **service** to perform tasks
  - Service can keep running even if background process is suspended
  - Service has no user interface, small memory use

Context Switch

- When CPU switches to another process, the system must save the state of the old process and load the saved state for the new process
- Context-switch time is overhead; the system does no useful work while switching
- Time dependent on hardware support

Process Creation

- Parent process create children processes, which, in turn create other processes, forming a tree of processes
- Resource sharing
  - Parent and children share all resources
  - Children share subset of parent’s resources
  - Parent and child share no resources
- Execution
  - Parent and children execute concurrently
  - Parent waits until children terminate

Process Creation (Cont.)

- Address space
  - Child duplicate of parent
  - Child has a program loaded into it
- UNIX examples
  - **fork** system call creates new process
  - **exec** system call used after a **fork** to replace the process' memory space with a new program

Process Creation



C Program Forking Separate Process

```
int main()
{
Pid_t  pid;
    /* fork another process */
    pid = fork();
    if (pid < 0) { /* error occurred */
            fprintf(stderr, "Fork Failed");
            exit(-1);
    }
    else if (pid == 0) { /* child process */
            execlp("/bin/ls", "ls", NULL);
    }
    else { /* parent process */
            /* parent will wait for the child to complete */
            wait (NULL);
            printf ("Child Complete");
            exit(0);
    }
}
```

A tree of processes on a typical Solaris



Process Termination

- Process executes last statement and asks the operating system to delete it (**exit**)
  - Output data from child to parent (via **wait**)
  - Process' resources are deallocated by operating system
- Parent may terminate execution of children processes (**abort**)
  - Child has exceeded allocated resources
  - Task assigned to child is no longer required
  - If parent is exiting
    - Some operating system do not allow child to continue if its parent terminates
      - All children terminated - *cascading termination*

Cooperating Processes

- **Independent** process cannot affect or be affected by the execution of another process
- **Cooperating** process can affect or be affected by the execution of another process
- Advantages of process cooperation
  - Information sharing
  - Computation speed-up
  - Modularity
  - Convenience

Producer-Consumer Problem

- Paradigm for cooperating processes, *producer* process produces information that is consumed by a *consumer* process
  - *unbounded-buffer* places no practical limit on the size of the buffer
  - *bounded-buffer* assumes that there is a fixed buffer size

Bounded-Buffer – Shared-Memory Solution

- Shared data

```
#define BUFFER_SIZE 10
Typedef struct {
    . . .
} item;

item buffer[BUFFER_SIZE];
int in = 0;
int out = 0;
```

- Solution is correct, but can only use BUFFER_SIZE-1 elements

Bounded-Buffer – Insert() Method

```
while (true) {
   /* Produce an item */
    while (((in = (in + 1) % BUFFER SIZE)  == out)
     ;   /* do nothing -- no free buffers */
    buffer[in] = item;
    in = (in + 1) % BUFFER SIZE;
 {
```

Bounded Buffer – Remove() Method

```
while (true) {
        while (in == out)
                ; // do nothing -- nothing to
consume

      // remove an item from the buffer
      item = buffer[out];
      out = (out + 1) % BUFFER SIZE;
return item;
  }
```

Interprocess Communication (IPC)

- Mechanism for processes to communicate and to synchronize their actions
- Message system – processes communicate with each other without resorting to shared variables
- IPC facility provides two operations:
  - **send**(*message*) – message size fixed or variable
  - **receive**(*message*)
- If *P* and *Q* wish to communicate, they need to:
  - establish a *communication link* between them
  - exchange messages via send/receive
- Implementation of communication link
  - physical (e.g., shared memory, hardware bus)
  - logical (e.g., logical properties)

Implementation Questions

- How are links established?
- Can a link be associated with more than two processes?
- How many links can there be between every pair of communicating processes?
- What is the capacity of a link?
- Is the size of a message that the link can accommodate fixed or variable?
- Is a link unidirectional or bi-directional?

Communications Models



Direct Communication

- Processes must name each other explicitly:
  - **send** (*P, message*) – send a message to process P
  - **receive**(*Q, message*) – receive a message from process Q
- Properties of communication link
  - Links are established automatically
  - A link is associated with exactly one pair of communicating processes
  - Between each pair there exists exactly one link
  - The link may be unidirectional, but is usually bi-directional

Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Each mailbox has a unique id
  - Processes can communicate only if they share a mailbox
- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional

Indirect Communication

- Operations
  - create a new mailbox
  - send and receive messages through mailbox
  - destroy a mailbox
- Primitives are defined as:

  send(*A, message*) – send a message to mailbox A

  receive(*A, message*) – receive a message from mailbox A

Indirect Communication

- Mailbox sharing
  - P_1, P_2, and P_3 share mailbox A
  - P_1, sends; P_2 and P_3 receive
  - Who gets the message?
- Solutions
  - Allow a link to be associated with at most two processes
  - Allow only one process at a time to execute a receive operation
  - Allow the system to select arbitrarily the receiver. Sender is notified who the receiver was.

Synchronization

- Message passing may be either blocking or non-blocking
- **Blocking** is considered **synchronous**
  - **Blocking send** has the sender block until the message is received
  - **Blocking receive** has the receiver block until a message is available
- **Non-blocking** is considered **asynchronous**
  - **Non-blocking** send has the sender send the message and continue
  - **Non-blocking** receive has the receiver receive a valid message or null

Buffering

- Queue of messages attached to the link; implemented in one of three ways
  1. Zero capacity – 0 messages
     Sender must wait for receiver (rendezvous)
  2. Bounded capacity – finite length of *n* messages
     Sender must wait if link full
  3. Unbounded capacity – infinite length
     Sender never waits

Client-Server Communication

- Sockets
- Remote Procedure Calls
- Remote Method Invocation (Java)

Sockets

- A socket is defined as an *endpoint for communication*
- Concatenation of IP address and port
- The socket **161.25.19.8:1625** refers to port **1625** on host **161.25.19.8**
- Communication consists between a pair of sockets

Socket Communication



Remote Procedure Calls

- Remote procedure call (RPC) abstracts procedure calls between processes on networked systems.
- **Stubs** – client-side proxy for the actual procedure on the server.
- The client-side stub locates the server and *marshalls* the parameters.
- The server-side stub receives this message, unpacks the marshalled parameters, and performs the procedure on the server.

Execution of RPC



Remote Method Invocation

- Remote Method Invocation (RMI) is a Java mechanism similar to RPCs.
- RMI allows a Java program on one machine to invoke a method on a remote object.



Marshalling Parameters



Contoh IPC: shared memory di Linux

- Kernel mengelola struktur untuk segmen shared memory
-

```
struct shmid_ds {
  struct ipc_perm  shm_perm;    /* see Section 15.6.2 */
  size_t           shm_segsz;   /* size of segment in bytes */
  pid_t            shm_lpid;    /* pid of last shmop() */
  pid_t            shm_cpid;    /* pid of creator */
  shmatt_t         shm_nattch;  /* number of current attaches */
  time_t           shm_atime;   /* last-attach time */
  time_t           shm_dtime;   /* last-detach time */
  time_t           shm_ctime;   /* last-change time */
  .
  .
  .
};
```

Contoh IPC: shared memory di Linux

- shmget: untuk mendapatkan shared memory id
- Key dapat menggunakan IPC_PRIVATE, atau nilai yang disepakati oleh kedua proses, atau menggunakan ftok(path, id) untuk membangkitkan key dari path dan id yang disepakati

```
#include <sys/shm.h>

int shmget(key_t key, size_t size, int flag);
```

Returns: shared memory ID if OK, 1 on error

Contoh IPC: shared memory di Linux

- shmctl: menyediakan berbagai control untuk shared memory
- cmd:
  - IPC_STAT: membaca shmid_ds
  - IPC_SET: menset nilai shm_perm.uid, shm_perm.gid dan shm_perm.mode
  - IPC_RMID: menghapus shared memory segment
  - SHM_LOCK dan SHM_UNLOCK

```
#include <sys/shm.h>

int shmctl(int shmid, int cmd, struct shmid_ds *buf);

                                    Returns: 0 if OK, 1 on error
```

Contoh IPC: shared memory di Linux

- shmat: attach shared memory ke process address space
- Shmdt: detach shared memory

```
#include <sys/shm.h>

void *shmat(int shmid, const void *addr, int flag);
```

Returns: pointer to shared memory segment if OK, 1 on error

```
#include <sys/shm.h>

int shmdt(void *addr);
```

Returns: 0 if OK, 1 on error

```c
#include "apue.h"
#include <sys/shm.h>

#define ARRAY_SIZE  40000
#define MALLOC_SIZE 100000
#define SHM_SIZE    100000
#define SHM_MODE    0600    /* user read/write */

char    array[ARRAY_SIZE];  /* uninitialized data = bss */

int
main(void)
{
    int     shmid;
    char    *ptr, *shmptr;

    printf("array[] from %lx to %lx\n", (unsigned long)&array[0],
      (unsigned long)&array[ARRAY_SIZE]);
    printf("stack around %lx\n", (unsigned long)&shmid);

    if ((ptr = malloc(MALLOC_SIZE)) == NULL)
        err_sys("malloc error");
    printf("malloced from %lx to %lx\n", (unsigned long)ptr,
      (unsigned long)ptr+MALLOC_SIZE);

    if ((shmid = shmget(IPC_PRIVATE, SHM_SIZE, SHM_MODE)) < 0)
        err_sys("shmget error");
    if ((shmptr = shmat(shmid, 0, 0)) == (void *)-1)
        err_sys("shmat error");
    printf("shared memory attached from %lx to %lx\n",
      (unsigned long)shmptr, (unsigned long)shmptr+SHM_SIZE);

    if (shmctl(shmid, IPC_RMID, 0) < 0)
        err_sys("shmctl error");

    exit(0);
}
```

IPC POSIX Producer

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <sys/shm.h>
#include <sys/stat.h>

int main()
{
/* the size (in bytes) of shared memory object */
const int SIZE = 4096;
/* name of the shared memory object */
const char *name = "OS";
/* strings written to shared memory */
const char *message_0 = "Hello";
const char *message_1 = "World!";

/* shared memory file descriptor */
int shm_fd;
/* pointer to shared memory obect */
void *ptr;

    /* create the shared memory object */
    shm_fd = shm_open(name, O_CREAT | O_RDWR, 0666);

    /* configure the size of the shared memory object */
    ftruncate(shm_fd, SIZE);

    /* memory map the shared memory object */
    ptr = mmap(0, SIZE, PROT_WRITE, MAP_SHARED, shm_fd, 0);

    /* write to the shared memory object */
    sprintf(ptr,"%s",message_0);
    ptr += strlen(message_0);
    sprintf(ptr,"%s",message_1);
    ptr += strlen(message_1);

    return 0;
}
```

IPC POSIX Consumer

```
#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <sys/shm.h>
#include <sys/stat.h>

int main()
{
/* the size (in bytes) of shared memory object */
const int SIZE = 4096;
/* name of the shared memory object */
const char *name = "OS";
/* shared memory file descriptor */
int shm_fd;
/* pointer to shared memory obect */
void *ptr;

   /* open the shared memory object */
   shm_fd = shm_open(name, O_RDONLY, 0666);

   /* memory map the shared memory object */
   ptr = mmap(0, SIZE, PROT_READ, MAP_SHARED, shm_fd, 0);

   /* read from the shared memory object */
   printf("%s",(char *)ptr);

   /* remove the shared memory object */
   shm_unlink(name);

   return 0;
}
```

Contoh IPC: message queue

- Struktur di kernel

```
struct msqid_ds {
  struct ipc_perm  msg_perm;     /* see Section 15.6.2 */
  msgqnum_t        msg_qnum;     /* # of messages on queue */
  msglen_t         msg_qbytes;   /* max # of bytes on queue */
  pid_t            msg_lspid;    /* pid of last msgsnd() */
  pid_t            msg_lrpid;    /* pid of last msgrcv() */
  time_t           msg_stime;    /* last-msgsnd() time */
  time_t           msg_rtime;    /* last-msgrcv() time */
  time_t           msg_ctime;    /* last-change time */
  .
  .
  .
};
```

- Msgget: membangkitkan id dari key

```
#include <sys/msg.h>

int msgget(key_t key, int flag);
```

Returns: message queue ID if OK, 1 on error

- Mengirim dan menerima data ke/dari message queue

[View full width]

```
#include <sys/msg.h>

int msgsnd(int msqid, const void *ptr, size_t
➥ nbytes, int flag);
```

Returns: 0 if OK, 1 on error

[View full width]

```
#include <sys/msg.h>

ssize_t msgrcv(int msqid, void *ptr, size_t nbytes
➥ , long type, int flag);
```

Returns: size of data portion of message if OK, 1 on error