

## Section 1 Chemical Product and Company Identification

**Product Identifier** MiraBrass<sup>®</sup>, AquaMulsion Negative Resist Coated

Product Number IF-BRS8223

General Use Foil stamping or embossing

**Company** UEI Systems®, a UEI Group Company

Address 9090 Nieman Road

Overland Park, KS 66214 USA

**Phone** +1 800 221 9059 or +1 913 541 0503

Emergency Contact Number CHEMTEL – Available 24 hours/day, 7 days/week

Domestic North America: +1 800 255 3924

International: +1 813 248 0585

# **Section 2**

## **Hazards Identification**

#### **GHS Classification**

Hazard Class	Hazard Category	Route of Exposure		
Sensitization, Skin	1	-		
Serious Eye Damage/Eye Irritation	2A	-		
Carcinogenicity	2B	-		
Toxic to Reproduction	1A	-		
Specific Target Organ Toxicity, Repeated Exposure	1	Nervous System		

### **GHS Labeling**

**Contains** Copper (7440-50-8), Zinc (7440-66-6), Lead (7439-92-1)





#### Danger

**Hazard Statement** May cause an allergic skin reaction.

Causes serious eye irritation.
Suspected of causing cancer.

Causes damage to nervous system through prolonged or repeated exposure.

May damage fertility or the unborn child.

**Precautionary Statements** Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Wear eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.



9090 Nieman • Overland Park, KS 66	6214 • (913) 541-0503 • Toll Fre	e: 800-221-9059 • sal	es@ueisystems.co	m • ueisystems.com	
Section 2	Hazards Identification, continued				
Response					
Storage	Store locked up.				
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations				
Section 3	Hazardous Ingredients / I	dentity Informat	ion		
	Hazardous Components	CAS No.	%		
Metal	Copper Zinc Tin Lead Acrylates	7440-50-8 7440-66-6 7440-31-5 7439-92-1	55–65 30–45 <1 <4 <1		
Section 4	First Aid Measures				
Inhalation	Remove to fresh air. If not breath If breathing is difficult, give oxyg		oiration.		
Ingestion	Wash out mouth with water. Do <b>not</b> induce vomiting if conscious. Call a physician.				
Eye Contact	Immediately flush eyes with large amounts of water for at least 15 minutes.				
Skin Contact	•	mmediately flush skin with large amounts of water for at least 15 minutes while remoontaminated clothing and shoes. Wash hands before eating and smoking.			
Section 5	Firefighting Measures				
Flammable/Combustible Properties	This product does not present fi Dust and fines may be readily ig		ls as shipped.		
Fire/Explosion	<ul> <li>May be a potential hazard under the following conditions:</li> <li>Heavily concentrated dust clouds are dispersed in the air.</li> <li>Dust or fines dispersed in the air can be explosive if subjected to a strong ignition source.</li> <li>Molten metal in contact with water/moisture. Moisture entrapped by molten metal can be explosive.</li> </ul>				
<b>Extinguishing Media</b>					
Unsuitable Extinguishing Media	Do Not Use:  • Halogenated agents on dust or fines.  • Water around molten metal.  These agents will react with the burning material.				
Firefighting Equipment/Instructions	Fire fighters should wear NIOSH apparatus and full protective clo			ned breathing	



ection 6	Accidental Release Measures					
Personal Precautions	Wear gloves and approved respiratory protection if possibility of dust, mist and fume exposure exists.					
<b>Environmental Precautions</b>	Brass-containing waste is normally collected for recycling. Should waste disposal be deeme necessary, follow Federal, State, or Local regulations.					
Methods for Cleaning Up	Do not use compressed air for cleaning.					
Section 7	<b>Handling and Stora</b>	ge				
	Do not breathe dust or so the eyes and skin. Wash h					
Section 8	Component Exposure Limits					
	Hazardous Components	CAS No.	OSHA (P	EL/TWA)	ACGIH TLV	
Metal	Copper	7440-50-8	1 mg/m 0.1 mg/n	n³, Fume	1 mg/m³, Dust 0.2 mg/m³, Fume	
	Zinc Tin	7440-66-6	15 m	-	10 mg/m <sup>3</sup>	
	Lead	7440-31-5 7439-92-1	2 mg/m³ .05 mg/m³		2 mg/m³ .05 mg/m³	
Commonant Francisco Limite				J	3	
COMPONENT EXPOSITE LIMITS						
Component Exposure Limits ppropriate Engineering Controls	When handling molten br gloves and respirator if ne Do not eat, drink or smoke	eded, must be use	d. Avoid inge	stion and inha	alation of dust and fur	
ppropriate Engineering Controls	gloves and respirator if ne	eded, must be used e during use and w	d. Avoid inge ash hands be	stion and inha fore eating, d	alation of dust and fur rinking or smoking.	
ppropriate Engineering Controls	gloves and respirator if ne Do not eat, drink or smoke	eded, must be used e during use and w ved dust respirator	d. Avoid inge ash hands be to avoid exce	stion and inha fore eating, d	alation of dust and fur rinking or smoking.	
ppropriate Engineering Controls Personal Respiratory Protection	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv	eded, must be used e during use and w ved dust respirator ainst melt splashir	d. Avoid inge ash hands be to avoid exc ng.	stion and inha fore eating, d essive inhalat	alation of dust and fur rinking or smoking. ion of dust, fume or r	
ppropriate Engineering Controls  Personal Respiratory Protection  Personal Hand Protection	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag	eded, must be used e during use and w red dust respirator ainst melt splashir e shield in exposur	d. Avoid inge ash hands be to avoid exc ng. e to dust, fu	stion and inha fore eating, d essive inhalat me or mist ar	alation of dust and fur rinking or smoking. ion of dust, fume or n	
ppropriate Engineering Controls  Personal Respiratory Protection  Personal Hand Protection  Eye Protection  Skin Protection	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again	eded, must be used e during use and w yed dust respirator ainst melt splashir e shield in exposur ast melt splashing.	d. Avoid inge ash hands be to avoid exc ng. e to dust, fu Wear trouse	stion and inha fore eating, d essive inhalat me or mist ar	alation of dust and fur rinking or smoking. ion of dust, fume or n	
ppropriate Engineering Controls  Personal Respiratory Protection  Personal Hand Protection  Eye Protection  Skin Protection	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.	eded, must be used a during use and waved dust respirator ainst melt splashing shield in exposurant melt splashing.	d. Avoid inge ash hands be to avoid exc ng. e to dust, fu Wear trouse	stion and inha fore eating, d essive inhalat me or mist ar	alation of dust and fur rinking or smoking. ion of dust, fume or n	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurnst melt splashing.  I cal Properties Odor	d. Avoid inge ash hands be to avoid exc ng. e to dust, fu Wear trouse	stion and inha fore eating, d essive inhalat me or mist ar er legs outside No data	alation of dust and fur rinking or smoking. ion of dust, fume or n	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Section 9 Appearance/Odor	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Street Protective Clothing again	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurest melt splashing.  I cal Properties Odor Bo	d. Avoid inge ash hands be to avoid exce ng. e to dust, fur Wear trouse Threshold	stion and inha fore eating, d essive inhalat me or mist ar er legs outside No data	alation of dust and fur rinking or smoking. ion of dust, fume or r nd when handling ma e boots to avoid melt	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Appearance/Odor pH Melting Point Specific Gravity	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Yellow/No odor No data >1,630° (885°C) No data	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurest melt splashing.  I cal Properties Odor Bo	d. Avoid inge ash hands be to avoid exco ng. e to dust, fur Wear trouse Threshold iling Point	stion and inha fore eating, d essive inhalat me or mist ar r legs outside No data No data Insoluble in 0.307lb/in <sup>3</sup> (	alation of dust and fur rinking or smoking. ion of dust, fume or r nd when handling ma e boots to avoid melt water	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Appearance/Odor pH Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemi Yellow/No odor No data >1,630° (885°C) No data No data	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurest melt splashing.  I cal Properties  Odor  Both  Solut  Evapor	d. Avoid inge ash hands be to avoid excends.  e to dust, fur Wear trouse  Threshold iling Point bility (H <sub>2</sub> O)  Density ration Rate	stion and inha fore eating, d essive inhalat me or mist ar r legs outside No data No data Insoluble in 0.307lb/in³ (	alation of dust and fur rinking or smoking. ion of dust, fume or r nd when handling ma e boots to avoid melt water	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient Molecular Weight	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approv Use protective gloves ag Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemic Yellow/No odor No data >1,630° (885°C) No data No data	eded, must be used a during use and waved dust respirator ainst melt splashing shield in exposur ast melt splashing.  Cal Properties  Odor  Both Solut  Evapor Decomposition Te	d. Avoid inge ash hands be to avoid excend.  Threshold illing Point billity (H <sub>2</sub> O) Density ration Rate imperature	stion and inhal fore eating, d essive inhalat me or mist ar er legs outside No data No data Insoluble in 0.307lb/in³ ( No data No data	alation of dust and fur rinking or smoking. ion of dust, fume or r ad when handling ma e boots to avoid meli water	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Section 9  Appearance/Odor pH Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient Molecular Weight Auto Ignition	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approvuse protective gloves aguse safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Yellow/No odor No data >1,630° (885°C) No data No data No data No data	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurest melt splashing.  Cal Properties Odor Bo Solul  Evapor Decomposition Tel	d. Avoid inge ash hands be to avoid excend.  e to dust, fur Wear trouse  Threshold illing Point pility (H <sub>2</sub> O)  Density ration Rate imperature bility Limit	stion and inhal fore eating, d essive inhalat me or mist ar r legs outside No data No data Insoluble in 0.307lb/in³ ( No data No data No data	alation of dust and fur rinking or smoking. ion of dust, fume or r nd when handling ma e boots to avoid melt water	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Section 9  Appearance/Odor pH Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient Molecular Weight Auto Ignition Flash Point	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approvuments of the protective gloves ago Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Yellow/No odor No data >1,630° (885°C) No data	eded, must be used a during use and water dust respirator ainst melt splashing shield in exposurest melt splashing.  Cal Properties  Odor  Both Solul  Evapor Decomposition Tell Lower Flammal	d. Avoid inge ash hands be to avoid exceed g. The to dust, further wear troused. Threshold iling Point polity (H <sub>2</sub> O)  Density the polity cation Rate polity Limit bility Limit bility Limit	stion and inhal fore eating, d essive inhalat me or mist and relegs outside No data No data No data No data No data No data No data	alation of dust and fur rinking or smoking. ion of dust, fume or r ad when handling ma e boots to avoid meli water	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Section 9  Appearance/Odor pH Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient Molecular Weight Auto Ignition Flash Point Vapor Density	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approvuse protective gloves aguse safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Yellow/No odor No data >1,630° (885°C) No data	eded, must be used a during use and waved dust respirator ainst melt splashing shield in exposur ast melt splashing.  Cal Properties  Odor  Bo  Solul  Evapor Decomposition Tel  Lower Flammal  Upper Flammal	d. Avoid inge ash hands be to avoid exceed g. The to dust, further the control of	stion and inhal fore eating, dessive inhalated me or mist are regs outsided No data No data Insoluble in 0.307lb/in³ ( No data No data No data No data No data	alation of dust and fur rinking or smoking. ion of dust, fume or r ad when handling ma e boots to avoid meli	
Personal Respiratory Protection Personal Hand Protection Eye Protection Skin Protection Skin Protection  Section 9  Appearance/Odor pH Melting Point Specific Gravity Octanol/H <sub>2</sub> O Coefficient Molecular Weight Auto Ignition Flash Point	gloves and respirator if ne Do not eat, drink or smoke Use NIOSH/MSHA approvuments of the protective gloves ago Use safety glasses or face Protective clothing again entrance in the boots.  Physical and Chemical Yellow/No odor No data >1,630° (885°C) No data	eded, must be used a during use and waved dust respirator ainst melt splashing shield in exposur ast melt splashing.  Cal Properties  Odor  Bo  Solul  Evapor Decomposition Tel  Lower Flammal  Upper Flammal	d. Avoid inge ash hands be to avoid exceed g. The to dust, further wear troused. Threshold iling Point polity (H <sub>2</sub> O)  Density the polity cation Rate polity Limit bility Limit bility Limit	stion and inhal fore eating, d essive inhalat me or mist and relegs outside No data No data No data No data No data No data No data	alation of dust and fur rinking or smoking. ion of dust, fume or r nd when handling ma e boots to avoid melt water	



Section 10	Chemical Stability and Reactivity
Stability	Stable under normal handling conditions.
Incompatibility	None known
Hazardous Decomposition/ By-Products	Thermal decomposition products of the cured coating may yield small quantities of fine particulates and gases from the fluoropolymer that can include hydrogen fluoride.
Hazardous Polymerization	Will not occur
Section 11	Toxicological Information
Likely routes of exposure	Brass compounds may be toxic by inhalation, ingestion, injection, and skin or eye exposure.
Acute Effects Inhalation	Exposure to fumes or dust may cause irritation of the nose and upper respiratory tract, as well as sneezing and coughing. Perforation of the nasal septum can also occur. "Metal fume fever", with respiratory and flu-like symptoms such as chills and muscle aches, may result from exposure to fumes or fine dust. The incidence of copper-induced metal fume fever is low due to the high temperatures required to volatilize copper.
Eye Contact	Exposure of the eyes to copper fumes or dust can cause irritation, conjunctivitis, palpebral edema, ulceration and corneal turbidity. Eye irritation, uveitis, abscess and loss of the eye may also occur from the mechanical action of lodged copper particles. Penetration of the eye by fine fragments can result in severe ocular damage. Corneal discoloration (Kayser-Fleischer ring) is a hallmark of Wilson disease.
Skin Contact	Skin exposure may cause irritation, itching, eczema, allergic contact dermatitis, hypersensitivity, and a greenish discoloration of the hair, teeth and skin.
Ingestion	Acute ingestion of copper salts can cause irritation, severe nausea and vomiting, salivation, abdominal pain, epigastric burning, hemolysis, gastrointestinal bleeding with hemorrhagic gastritis, hematemesis and melena, anemia, hypotension, jaundice, seizures, coma, shock and death. Hepatic and renal failure may develop several days after acute ingestion. Methemoglobinemia may rarely occur. Copper may produce a metallic or sweet taste.
Sensitization	Skin exposure may cause irritation, itching, eczema, allergic contact dermatitis, hypersensitivity, and a greenish discoloration of the hair, teeth and skin.
Carcinogenicity Lead Classification	B2; probable human carcinogen.
Target Organ Effects Lead (7439-92-1)	Impairment of psychological and neurobehavioral functions has been found after long-term lead exposure of workers.
Reproductive Toxicity	The reproductive effects of lead in the male are limited to sperm morphology and count. In the female, some adverse pregnancy outcomes have been attributed to lead.
	Pregnancy and lactation further increase mobilization of lead from the maternal skeleton with proportionate increase in blood lead in the prenatal period.
Teratogenicity	Lead has been shown to be associated with impaired neurobehavioral functioning in children. Impairment of psychological and neurobehavioral functions has been found after long-term lead exposure of workers. Electrophysiological parameters have been shown to be useful indicators of subclinical lead effects in the CNS. Peripheral neuropathy has long been known to be caused by long-term high-level lead exposure at the workplace. Slowing of nerve conduction velocity has been found at lower levels.



### Section 12

### **Ecological Information**

**Ecotoxicity** 

No data is available on this product. Individual constituents are as following:

Component	Species	Exposure Time	LC50/EC50/IC50
Copper (7440-50-8)	Selenastrum capricornatum (green alga)	14 days	EC50 85 ug/l
	Oncorhynchus kisutch (coho salmon)	96 hrs	LC50 286 ug/l
Zinc (7440-66-6)	Daphnia magna (water flea)	48 hrs	LC50 0.068 mg/l
Lead (7439-92-1)	Chlamydomonas reinhardtii (green algae)	3 min	EC50 0.0000022 M
	Daphnia magna (water flea)	48 hrs	LC50 4400 ug/l

Persistence/Degradability

No evidence was found to indicate that there is any biotransformation process for

copper compounds.

**Bioaccumulative Potential** 

Copper is accumulated by all plants and animals.

**Mobility in Soil** 

Copper is relatively mobile in soils.

Zinc is strongly adsorbed to soils at pH 5 or greater and is expected to have low mobility in most soils. Lead in the soil has a limited mobility except when soluble organic complexes or when the soil lead exchange capacity approaches saturation.

## Section 13

### **Disposal Considerations**

**Disposal Instructions** 

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. This product may be a candidate for metal reclamation.

## **Section 14**

## **Transportation Information**

The material is not regulated under DOT provisions.

#### **Section 15**

### **Regulatory Information**

	SARA <sup>1</sup>	SARA <sup>1</sup> EHS	RCRA <sup>2</sup>	CERCLA <sup>3</sup>	CERCLA <sup>3</sup> RQ	TSCA⁴
Copper	Listed	Not listed	Not listed	Listed per CWA Section 307(a)	5000 lb (2268 kg)	Listed
Zinc	Listed	Not listed	Not listed	Listed per CWA Section 307(a)	1000 lb (453.5 kg)	Listed
Lead	Listed	Not listed	Listed	Listed per CWA Section 307(a)	10 lb (4.535 kg)	Listed

#### Component Analysis - State

Component	CA	MA	MN	NJ	PA	RI
Copper (7440-50-8)	N	Υ	Υ	Υ	Υ	Υ
Zinc (7440-66-6)	N	Υ	N	Υ	Υ	Υ
Lead (7439-92-1)	Υ	Υ	Υ	Υ	Υ	Υ

#### California Prop 65

**Warning**: This product contains a chemical known to the State of California to cause cancer. **Warning**: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Safety
Data
Sheet



9090 Nieman • Overland Park, KS 66214 • (913) 541-0503 • Toll Free: 800-221-9059 • sales@ueisystems.com • ueisystems.com

#### **Section 16**

### **Other Information**

UEI Systems® provides the information contained herein in good faith. It is believed to be correct. However it is not all-inclusive and should be used only as a guide. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. UEI Systems shall not be held liable for any damage resulting from handling or from contact with this product. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources.

Abbreviations PEL Permissible Exposure Limit

**TLV** Threshold Limit Value

**End Notes** 

1. SARA - Signed into law in 1986, the Superfund Amendments and Reauthorization Act (SARA) is an extension of CERCLA, and is intended to encourage and support local and state emergency planning efforts. SARA provides citizens and local governments with information about potential chemical hazards, and calls for facilities that store hazardous materials to provide officials and citizens with data on the type and amount on hand at specific locations. This field states whether a material is listed or not listed in section 372.65 of SARA. EHS - This states if a material is listed or not listed in Appendix B to part 355, the SARA Extremely Hazardous Substances (EHS) section. RQ is the reportable quantity. TPQ is the Threshold Planning Quantity.

2. RCRA - The Resource Conservation and Recovery Act enacted in 1976 and subsequently amended, controls solid-waste disposal and encourages recycling. This states whether a material is listed or not listed under this regulation. If listed the Hazardous Waste Number and waste characterization assigned by RCRA is also provided. 3. CERCLA - Enacted in 1980 and amended thereafter, the Comprehensive Environmental Response, Compensation, and Liability Act provides for identification and cleanup of hazardous materials released on land, into the air, waterways, and groundwater. It covers areas affected by newly released materials and older leaking or abandoned dump sites. This states whether a material is listed or not listed in CERCLA Table 302.4. If listed the section(s) that it is listed under and the Reportable Quantity (RQ) are also provided. 4. TSCA - The Toxic Substances Control Act controls the exposure to and use of raw industrial chemicals not subject to other laws. This states whether the chemical is listed or not listed under this regulation.

**Revision** 21 April 2020

Supersedes 26 March 2014

Evidence http://toxnet.nlm.nih.gov/cgi-bin/sis/search/f?./temp/~uCl2Um:4 http://toxnet.nlm.nih.gov/cgi-bin/sis/search/f?./temp/~njkGDl:1

http://toxnet.nlm.nih.gov/cgi-bin/sis/search/f?./temp/~uCl2Um:3