

Retrieval-Conditional Parsing Score (RCPS): Choosing Document Parsers by Retrieval, Not by Appearance

Anonymous ACL submission

Abstract

Document parsers for retrieval-augmented generation (RAG) are commonly selected by intrinsic quality metrics—text fidelity, boundary clarity—although a production pipeline ultimately depends on whether the parsed content can be *retrieved*. Building a RAG system over Korean government documents, we find the assumption fails operationally: across the full candidate pool, parser selection alone moves retrieval Hit@1 by 35.1 absolute percentage points (a $2.8\times$ relative increase), and the parsers with the cleanest chunk boundaries rank near the bottom under retrieval. We introduce the Retrieval-Conditional Parsing Score (RCPS), a training-free selection protocol that ranks the parsers and chunkers a team should deploy using a held-out Q-A probe, averaging over multiple retrievers, with format-normalised answer matching; and a retriever-free coverage diagnostic that attributes missing answers to parser omission versus chunk-boundary splitting before any retriever is run. On our production pipeline 20.2% of gold answers are missing from the parser output itself—unrecoverable by any chunker—while at most 2.3% are lost at chunk boundaries; parser choice spans an RCPS range of 0.44 on the full evaluation set, against 0.06 for chunker choice. Controlled cross-domain perturbations (OHR-Bench) confirm this: semantic noise collapses retrieval while boundary metrics barely move. Finally, we bound parser-side training: retrieval-aware preference optimisation lifts OHR-Bench Hit@5 by +0.85 pp, but a simpler fidelity-distillation control achieves +1.22 pp with substantially overlapping confidence intervals—*selection, not training*, is the lever. We release KoGovDocRAG, a Korean document-RAG benchmark, with a reference implementation of RCPS.

1 Introduction

Retrieval-augmented generation (RAG) is increasingly deployed over real-world document collections—government records, enterprise reports, technical manuals—that exist only as scanned or born-digital PDFs. Every such pipeline begins with a document parser that converts each page to text, which is then chunked, embedded, and retrieved. Because the parser sits at the head of the pipeline its errors cascade downstream; the practical question is how to choose it. Faced with many candidates, practitioners rank them by intrinsic parsing-quality metrics that reward clean-looking output—low text-edit distance, high boundary clarity (Zhao et al., 2025a)—on the assumption that cleaner output retrieves better.

We hit this problem building a production RAG system over Korean government documents, and found the assumption fails operationally. A team ranking by intrinsic metrics would deploy MinerU (Niu et al., 2025), whose boundary-clarity score (0.72) is matched only by Marker; yet its retrieval Hit@1 is 0.20, against the 0.50–0.55 of three lower-scoring vision-language parsers—35.1 absolute Hit@1 percentage points ($2.8\times$ relative) from parser selection alone. On our parser set, Boundary Clarity ranks the candidates in nearly the opposite order from retrieval (Pearson $r = -0.81$, $n = 5$; sensitive in sign to the corpus), but the robust signal is its insensitivity: on a cross-domain English check (OHR-Bench, Zhang et al., 2025a), injecting semantic noise collapses retrieval while Boundary Clarity barely moves, so the intrinsic metric cannot perceive the content corruption retrieval depends on. Selection by appearance optimises a quantity structurally blind to retrievability—




Figure 1: **Overview.** (C1) Selecting a document parser by appearance (Boundary Clarity) rather than retrieval is a trap: MinerU has the highest Boundary Clarity yet the lowest Hit@1, and parser choice alone moves Hit@1 by 35.1 points (2.8×; scalar correlations illustrative, §4.2). (C2) A retriever-free coverage diagnostic localises the gap to the parser—20.2% of answers are missing from the parser output itself, unrecoverable by any chunker. (C3) RCPS selects parsers and chunkers by retrieval over a held-out Q–A probe and three retrievers, with no training. (C4) Parser-side training is a bounded lever: the fidelity-distillation control and the retrieval-reward variant have substantially overlapping CIs—no evidence the retrieval reward helps.

at least for the scanned, layout-heavy documents we study.

The question this paper answers is operational: *given candidate parsers and chunkers, how should a production team pick what to deploy—and is parser training worth the cost?* Our central contribution is the RCPS protocol, a training-free procedure that selects the parser and chunker by what retrieval does with their output (C3). We support it with an empirical characterisation of the parsing–retrieval disconnect that motivates retrieval-grounded selection (C1), a coverage diagnostic that localises failures to the parser or chunker layer (C2), and a secondary investigation showing that parser-side training provides only bounded gains beyond selection (C4).

Figure 1 previews all four.

We release **KoGovDoc-RAG**, a Korean document-RAG benchmark of 663 question–answer pairs over 294 pages, with a reference implementation of RCPS and the RADP checkpoints.

2 Related Work

Diagnosing the parsing–retrieval gap. OHR-Bench (Zhang et al., 2025a) measures the cascading impact of OCR noise on RAG; EnterpriseDocBench (Singh and Raj, 2026) reports a weak parsing-quality–retrieval correlation; concurrent analyses agree (Sun

et al., 2026; Song, 2026). Parsing benchmarks still rank parsers by intrinsic fidelity (Ouyang et al., 2025)—the signal C1 shows is misleading—and vision-based retrieval (Faysse et al., 2025) sidesteps text parsing, orthogonal to the text pipelines we target. None provides a reusable selection protocol or fault localisation—which our RCPS (C3) and coverage diagnostic (C2) supply.

Training-time methods, by pipeline layer. Retrieval-oriented training exists at every layer except the parser: chunking (Günther et al., 2024; Duarte et al., 2024; Zhao et al., 2024, 2025a; Singh et al., 2025), contrastive embedding (Conti et al., 2025; Zhao et al., 2025b), and retriever- or reader-side tuning (Nguyen et al., 2024; Chia et al., 2025; Yan et al., 2025). Parsers are themselves trained—with RL on edit-distance and layout rewards (Wang et al., 2025) or query-driven for efficient RAG (Wang et al., 2026)—but not on a retrieval signal; we test that signal and find no evidence that it improves over a matched fidelity-based control (C4). Our primary contributions (C1–C3) sit upstream of any training.

3 Two Tools: Selection and Diagnosis

3.1 RCPS: Retrieval-Conditional Parsing Score

RCPS ranks parsers by what downstream retrieval does with their output, not by how clean it looks. It is not a new similarity function but an evaluation protocol wrapping ordinary retrieval MRR in three choices, each removing a failure mode our experiments exhibit: (i) it is *extrinsic*, scoring a held-out Q–A probe on the parsed corpus, because intrinsic text metrics reward formatting that retrieval does not depend on (§4.2); (ii) it is *retriever-agnostic*, averaging over several embedders, because a single embedder can silently flip the top-ranked parser (Table 2); and (iii) it uses *format-normalised exact-span relevance*, counting a chunk relevant iff it contains the answer span under shared whitespace/markdown normalisation (0.02–0.03 score shifts, no re-ordering). Throughout, the *RCPS score* is the aggregate value of Equation 1; the *RCPS protocol* is the complete procedure—probe, retriever averaging, format-normalised relevance. The contribution is the protocol, not the scoring function (§4.3).

Given a parser P , a Q–A set $D = \{(q_i, a_i, \text{page}_i)\}$, a set of retrievers R , and cut-offs K , RCPS averages MRR across the cross-product:

$$\text{RCPS}(P) = \frac{1}{|R||K|} \sum_{r \in R} \sum_{k \in K} \text{MRR}@k(r, P, D). \quad (1)$$

We use $R = \{\text{BGE-M3 (Chen et al., 2024), multilingual-e5-large (Wang et al., 2024), Qwen3-Embedding-8B (Zhang et al., 2025b)}\}$ and $K = \{1, 5, 10\}$; cutoff-averaging avoids tying selection to one retrieval depth, and both the parser and chunker rankings of §4.3 are unchanged when RCPS is computed with MRR@10 alone. A chunk is relevant iff its source page matches the answer’s and the gold span is a substring under whitespace- and markdown-insensitive normalisation. Figure 2 sketches the protocol; the implementation is released.

Running the protocol. A team (1) holds out a probe of a few hundred Q–A whose answers occur verbatim in the corpus (ours are




Figure 2: RCPS as a protocol, not a new scoring function (C3): ordinary retrieval MRR wrapped in a held-out Q–A probe, retriever-averaging, and format-normalised relevance. Run with no training, it ranks the parser and chunker a team would deploy.

LLM-generated and judge-filtered, §4.1); (2) parses the evaluation pages once per candidate; (3) chunks, embeds with the $|R|$ retrievers, and computes Equation 1; (4) deploys the arg-max. RCPS is an offline procedure—for m parsers, c chunkers, and r retrievers, m parse runs and mcr indexing-and-retrieval evaluations—with no model training and no manual chunk-level relevance annotation (relevance derives automatically from the gold span and source page). Holding the parse fixed instead ranks chunkers with the same probe. RCPS returns a ranking under a fixed probe, not an absolute score.

3.2 Coverage Diagnostic — Locating the Gap (Parser vs Chunker)

RCPS scores the parser, chunker, and retriever jointly, so a low score does not localise the fault. We separate the parser from the chunker with a retriever-free diagnostic: holding the parser output fixed and varying the chunker, we classify each gold answer as *covered* (inside a single chunk, retrievable); *split* (present in the page text but cut across chunks—a chunker-side failure, recoverable with overlap); or *absent* (not found in the parser output under the same normalisation—a parser-side coverage failure: no chunker can recover content the parsed text lacks). Coverage is the ceiling on retrieval (split and absent score zero); the split/absent breakdown decides whether a parser-side fix can help (§4.2). Relevance




Figure 3: The coverage diagnostic (C2): with the parser fixed (Prod) and the chunker varied, each gold answer is *covered*, *split* (a chunker-side failure, recoverable with overlap), or *absent* (a parser-side coverage failure, unrecoverable by chunking). Absence is determined on the full parser output before chunking, so its rate ($\approx 20.2\%$) is chunker-invariant by construction; the chunker sweep measures what chunking can affect—the split rate, at most 2.3% (§4.2).

reuses RCPS’s format-normalised matching.

4 Experiments

4.1 Setup

We construct **KoGovDoc-RAG**: 663 Q–A pairs over 294 pages of Korean government documents, generated with the OpenAI gpt-5.4-2026-03-05 model and verified by an LLM-as-judge against the teacher-distilled reference markdown (Qwen3-VL-30B pseudo-labels; 100 eval Q–A sampled, 94/100 accept). For RADP-aux’s full-scale training we additionally generate 6,164 Q–A on the 2,667-page Prod training set. Cross-domain replication uses OHR-Bench (Zhang et al., 2025a) (seven domains, 2,264 verbatim-answerable Q–A; its Law + Manual subset of 1,043 Q–A is used only for the data-mix-sensitivity comparison in §4.2) across the three released parser outputs (gt, MinerU, Qwen2.5-VL) plus twelve controlled noise perturbations.

Throughout, **Prod** denotes our production parser, a Qwen3-VL-2B model (Qwen Team, Alibaba, 2025) fine-tuned for Korean document parsing; all training deltas are measured against it. RADP-aux uses a 73-page held-out fold (202 Q–A); RADP-DPO, SimPO, and the §4.4 analysis use the combined 242-page fold (train $\cup$ eval, 663 Q–A), with preference pairs built only from the 169-page train fold. The same 663 Q–A occupy 242 of the 294 KoGov pages; the coverage diagnostic (§4.2) runs over Prod’s full 294-page output, the extra 52 Q–A-free pages acting as distractors. Parses for the

12-variant comparison (§4.4) use deterministic decoding (temperature 0, max 1536 tokens). We fine-tune with LoRA (Hu et al., 2022) ($r = 8$, $\alpha = 32$), sweeping $\lambda \in \{0, 0.1, 0.3, 0.5\}$ for RADP-aux ($\lambda = 0$ drops the contrastive term; the sweep is read within the aux family, Table 6). RCPS uses the three retrievers and cutoffs of §3.1; we report paired percentile-bootstrap 95% CIs (1,000 resamples), preserving Q–A pairing across systems.

4.2 The Parsing–Retrieval Disconnect and Coverage Diagnostic (C1–C2)

Korean government documents (Figure 4; full grid in Table 1, §4.3). Across the five parsers evaluated on the complete KoGov set, RCPS spans 0.14–0.58—vision-language parsers on top, OCR systems trailing; Marker (output available for a 38-page subset only) scores 0.073 there and is excluded from full-set rank comparisons. The large full-pool spread is driven mainly by the OCR-style parsers, not the near-tied vision-language tier; the operational failure is that intrinsic metrics cannot flag these weak candidates. The Qwen3-VL-30B teacher and the deployable 2B Prod form a near-tied top tier (RCPS 0.584 and 0.583); Figure 4b contrasts Prod against the appearance-ranked MinerU. The intrinsic Boundary Clarity metric (Zhao et al., 2025a) anti-correlates with RCPS at Pearson $r = -0.81$ ($n = 5$, excluding PaddleOCR, whose BC is undefined): the two cleanest-boundary parsers (MinerU, Marker; $BC \approx 0.72$) land near the bottom, while the lower-BC vision-language parsers retrieve best (leave-one-out robustness in Limitations). MoC’s Chunk Stickiness is similarly disconnected ($r = +0.26$); neither intrinsic axis predicts RCPS.

Cross-domain insensitivity test. Across all seven OHR-Bench domains (2,264 Q–A) we evaluate 15 parser-output variants—three released outputs plus twelve controlled noise perturbations (Appendix E). Within each semantic-noise family, Boundary Clarity stays flat while RCPS collapses—it is insensitive to semantic corruption that materially degrades retrieval. For the MinerU family BC holds at 0.71–0.74 from clean to severe while RCPS falls -51% , with GOT and Qwen2.5-VL show-




Figure 4: The parsing–retrieval disconnect (Korean government documents). (a) Boundary Clarity (MoC) anti-correlates with RCPS (Pearson $r = -0.81$, $n = 5$; PaddleOCR excluded, BC undefined): cleanest-boundary MinerU and Marker rank near the bottom, lower-BC vision–language parsers best. (b) Selecting by RCPS (Prod) over appearance (MinerU) improves Hit@1 by 35.1 points (2.8 $\times$; absolute Hit@1 values on the bars). Marker: 38-page subset; direction holds without it ($r = -0.74$, $n = 4$).

ing the same direction (Table 8)—the intrinsic metric sees formatting, not content.

The aggregate cross-variant correlation is sensitive to the document mix: Pearson $BC \leftrightarrow RCPS$ across all 15 variants is -0.35 on Law + Manual alone but $+0.25$ on the full seven-domain corpus; we therefore report the per-family insensitivity pattern, which reproduces in every domain, as the robust finding and treat the cross-variant scalar as illustrative only.

Locating the gap: parser or chunker? (Figure 3; per-chunker table in Appendix D). The disconnect shows that intrinsic metrics mislead, but not which pipeline layer is at fault. Applying the §3.2 classification with no retriever to Prod’s output (294 pages, 663 Q–A), 20.2% of gold answers are absent and at most 2.3% split. Absence is determined on the full parser output before chunking, so its rate is chunker-invariant by construction; the diagnostic quantifies this parser-side ceiling: one answer in five is unrecoverable by any chunking strategy, against at most 2.3% lost at chunk boundaries—a parser problem, motivating the training in §4.4.

4.3 RCPS Selects Both Parsers and Chunkers (C3)

Selecting parsers. The parser grid of §4.2 (Table 1, Figure 4) is itself an RCPS ranking: it tells a team that Prod (RCPS 0.583, Hit@1 0.55) beats MinerU (0.21, 0.20) by 2.8 $\times$ —the decision intrinsic metrics invert. Within the

Parser	BC	CS	RCPS	Hit@1
Qwen3-VL-30B (teacher)	0.623	3.38	0.584	0.545
Prod (ours, 2B)	0.610	3.07	0.583	0.549
Qwen3-VL-2B (base)	0.520	3.74	0.532	0.500
MinerU	0.716	2.81	0.212	0.197
PaddleOCR	—	3.46	0.140	0.125
Marker (38p)	0.717	3.41	0.073	0.068

Table 1: The KoGov parser grid (RCPS averaged over three retrievers; Marker: 38-page subset only, excluded from full-set rank comparisons). Simultaneously the C1 evidence—BC anti-correlates with RCPS, $r = -0.81$ ($n = 5$; PaddleOCR excluded, BC undefined); CS similarly uninformative ($r = +0.26$; scale differs from Table 6)—and the C3 deliverable: the deployment ranking a team reads off.

near-tied top tier (30B vs Prod), retrieval does not separate them; deployment cost (latency, compute) decides.

Selecting chunkers. On a fixed Prod output, the same probe separates four chunking strategies cleanly—markdown-header (md-h3, RCPS 0.593) > parser-native (0.583) > LumberChunker (Duarte et al., 2024) (0.557) > fixed-size (0.535)—whereas intrinsic boundary metrics rank them inconsistently, or rank fixed-size highest because its boundaries are clean by construction. The chunker spread (0.06) compares with 0.44 across the full parser pool but only 0.052 among the three vision–language parsers: parser screening matters most when the pool spans different parsing paradigms, and once the parser tier is fixed, chunker choice can be comparably consequen-

Protocol configuration	Top pair	τ vs RCPS
naive MRR (1 embedder)	Prod $\succ$ 30B	0.80
+ retriever-averaging	30B $\succ$ Prod	1.00
+ format-normalised	Prod $\succ$ 30B	0.80
full RCPS	30B $\succ$ Prod	—

Table 2: RCPS protocol ablation on the five full-set KoGov parsers (Marker excluded, cf. Table 1): only the inverted top pair is shown; the lower ranks (Qwen3-VL-2B $\succ$ MinerU $\succ$ PaddleOCR) are identical throughout. Retriever-averaging alone flips the top pair. Kendall τ : over the five-parser ranking; “30B” = Qwen3-VL-30B teacher.

tial ($\leq 2.3\%$ chunker-recoverable, §4.2). One probe set ranks both knobs for the pool at hand.

RCPS is not single-embedder MRR (Table 2). The contribution of RCPS is not a new retrieval metric but an operational evaluation package—downstream scoring, retriever averaging, and format-normalised relevance under a shared probe (§3.1). The single-embedder ablation is a secondary illustration of retriever sensitivity: the overall rankings remain similar (Kendall $\tau = 0.80$), but BGE-M3 alone reverses the near-tied top pair (0.583 vs 0.584), showing that a production embedder alone can determine the choice within a near-tied top tier; format normalisation shifts scores without reordering (§3.1). This sensitivity is limited to that near-tied pair—the chunker ordering is unchanged under BGE-M3 alone—so retriever averaging is an operational edge case rather than a broad ranking reversal.

4.4 Parser-Side Training Is a Bounded, Reward-Agnostic Lever (C4)

Given the parser-side ceiling of §4.2, does parser training add anything beyond selection? We evaluate two retrieval-aware parser interventions (Retrieval-Aware Document Parsing, RADP)—a hidden-state auxiliary loss (RADP-aux) and discrete-output DPO on a page-local RCPS reward (RADP-DPO) (Rafailov et al., 2023)—against RADP-Distill, a matched control selecting candidates by edit distance to the reference markdown with no retrieval reward, plus reference-free SimPO (Meng et al., 2024) as an additional control. Among the retrieval-aware variants, only

Variant	Selection signal	Δ Hit@5 [95% CI]
RADP-Distill	ref. edit dist.	+1.22 [+0.35, +2.15]
RADP-DPO-R2	page-local RCPS	+0.85 [+0.35, +1.43]
RADP-DPO-R3	+ hard negatives	+1.03 [+0.24, +1.84]

Table 3: C4 at the confirmatory endpoint: OHR-Bench Δ Hit@5 vs Prod, pp (2,264 Q–A, seven domains, three-retriever macro, paired bootstrap). Fidelity control and retrieval-reward variants have substantially overlapping intervals—no evidence the reward improves over the control. RADP-aux is sub-threshold, SimPO negative (Appendix B).

RADP-DPO yields a statistically significant positive gain on the confirmatory OHR-Bench Hit@5 evaluation—the auxiliary loss is sub-threshold and SimPO negative—at +0.85 pp [+0.35, +1.43] (KoGov $\approx +2$ pp, exploratory; R2 is primary for its clearest cross-domain fidelity, R3 reported for completeness). RADP-Distill achieves +1.22 pp [+0.35, +2.15] (Table 3); the intervals overlap substantially, so **we find no evidence the retrieval reward improves over a fidelity-based control**—the lever is text fidelity, not chunking. Recipe, per-variant results, and mechanism statistics: Appendices A–C.

5 Discussion and Conclusion

Selection, not training, is the headline. The largest effect is not a training method: selecting the parser by retrieval rather than intrinsic metrics moves Hit@1 by 35.1 points ($2.8\times$, §4.2). Training is a bounded, secondary lever (≈ 1 pp Hit@5) with no evidence the retrieval reward beats fidelity distillation (§4.4).

Why the diagnosis and the training lever agree. “Clean” splits into two axes: Boundary Clarity measures formatting, TextNED content. MinerU is formatting-clean but loses content (C1); training raises fidelity, not chunk structure—cross-domain too, OHR-Bench R2 and KoGov RADP-Distill both pair lower TextNED with higher retrieval (Table 6).

Playbook and conclusion. For practitioners: (1) select parsers with RCPS (a few hundred Q–A, no training); (2) run the coverage diagnostic—fix the chunker if *split*, the parser if *absent*; (3) if you train, distil toward clean reference text—retrieval-aware methods must beat that control.

Limitations

Single primary language and statistical power. The C1 diagnostic is strongest in Korean ($n = 5$, $r = -0.81$). On English OHR-Bench the aggregate cross-variant scalar is sign-sensitive to document mix ($r = -0.35$ on Law + Manual, $+0.25$ on the full seven-domain corpus), so directional consistency holds only for the per-family insensitivity pattern (§4.2), which replicates in every domain—not for the scalar correlation. The English evidence is also built on three real parser outputs plus twelve controlled perturbations rather than fifteen independent parsers. The negative KoGov association is not driven by a single parser—leave-one-parser-out correlations range from $r = -0.74$ to -0.97 , including $r = -0.76$ when MinerU is removed—but with only four or five observations these values remain descriptive rather than inferential.

Q–A generation and construct validity. The KoGov reference markdown is itself pseudo-ground-truth distilled from a Qwen3-VL-30B teacher (with manual de-noising of contaminated samples), and the Q–A were LLM-generated and checked by an LLM-as-judge against that reference (94/100 accept on a 100-Q–A stratified sample); neither the reference parses nor the queries were fully human-verified. Synthetic queries and pseudo-reference bound what RCPS can claim absolutely, but the exposure is narrow: our comparative findings—the $2.8\times$ parser-choice swing and every parser/chunker ranking—hold the Q–A set fixed across systems and so are internally valid regardless of how queries were generated, and the confirmatory cross-domain test (§4.4) uses OHR-Bench’s own externally curated Q–A. We release the frozen KoGov eval set for audit. RCPS also uses format-normalised exact-span relevance by design and is therefore biased toward content fidelity and verbatim-answerable queries; it does not evaluate semantic equivalence when the gold answer is paraphrased or implicit.

KoGov is exploratory; OHR-Bench is confirmatory. The headline KoGov cell (R2 $+1.96$ pp, Table 5) has a paired 95% interval of $[-1.06, +5.03]$ —two-sided non-significant and selected from a multi-cell scan—so we claim

no two-sided significance on KoGov. The confirmatory evidence is the held-out OHR-Bench replication (R2 $+0.85$ pp $[+0.35, +1.43]$, $n = 2,264$). A larger KoGov fold ($\geq 1,500$ Q–A) would be needed for a powered two-sided result.

Candidate pool and untested paradigms. Preference pairs are sampled from Prod itself; an alternative pool (e.g. chosen/rejected pairs from other parsers) might shift the mechanism away from reference-fidelity, which we did not test. We also test only the hidden-state auxiliary loss, discrete-output DPO with a reference policy, and reference-free SimPO; token-level RL, multi-task interleaving, curriculum schedules, and chunk-granularity oracle distillation are untested. Finally, RADP-DPO is a parser-layer intervention; chunker-, embedder-, and reranker-side training on RCPS-graded chunks are complementary directions left to future work.

References

- Jianlv Chen and 1 others. 2024. M3-embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. Released as BGE-M3; arXiv:2402.03216.
- Yew Ken Chia and 1 others. 2025. M-longdoc: A benchmark for multimodal super-long document understanding and a retrieval-aware tuning framework. In *Proceedings of EMNLP*. ArXiv:2411.06176.
- Max Conti and 1 others. 2025. Context is gold to find the gold passage: Evaluating and training contextual document embeddings. In *SenT*; arXiv:2505.24782.
- André V. Duarte and 1 others. 2024. Lumberchunker: Long-form narrative document segmentation. In *Findings of EMNLP*. ArXiv:2406.17526.
- Manuel Faysse and 1 others. 2025. Colpali: Efficient document retrieval with vision language models. In *International Conference on Learning Representations (ICLR)*. ArXiv:2407.01449.
- Michael Günther and 1 others. 2024. Late chunking: Contextual chunk embeddings using long-context embedding models. Jina AI; arXiv:2409.04701.
- Edward J. Hu and 1 others. 2022. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*. ArXiv:2106.09685.

Yu Meng, Mengzhou Xia, and Danqi Chen. 2024. Simpo: Simple preference optimization with a reference-free reward. In *Advances in Neural Information Processing Systems (NeurIPS)*. ArXiv:2405.14734.

Thang Nguyen and 1 others. 2024. Reward-rag: Enhancing rag with reward driven supervision. ArXiv:2410.03780.

Junbo Niu and 1 others. 2025. Mineru2.5: A decoupled vision-language model for efficient high-resolution document parsing. ArXiv:2509.22186.

Linke Ouyang and 1 others. 2025. Omnidocbench: Benchmarking diverse pdf document parsing with comprehensive annotations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. ArXiv:2412.07626.

Qwen Team, Alibaba. 2025. Qwen3-vl technical report. ArXiv:2511.21631.

Rafael Rafailov and 1 others. 2023. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems (NeurIPS)*. ArXiv:2305.18290.

Ishneet Sukhvinder Singh and 1 others. 2025. Chunkrag: Novel llm-chunk filtering method for rag systems. In *Proceedings of NAACL Student Research Workshop*. ArXiv:2410.19572.

Saurabh K. Singh and Sachin Raj. 2026. Benchmarking complex multimodal document processing pipelines: A unified evaluation framework for enterprise ai. ArXiv:2604.26382.

Minchae Song. 2026. Defining the problem: The impact of ocr quality on retrieval-augmented generation performance and strategies for improvement. *Information Processing & Management*, 63(1). Doi:10.1016/j.ipm.2025.104368.

Lin Sun and 1 others. 2026. When good ocr is not enough: Benchmarking ocr robustness for retrieval-augmented generation. ArXiv:2605.00911.

Baode Wang and 1 others. 2025. Infinity parser: Layout aware reinforcement learning for scanned document parsing. ArXiv:2506.03197.

Liang Wang and 1 others. 2024. Multilingual e5 text embeddings: A technical report. Microsoft; arXiv:2402.05672.

Zhengren Wang and 1 others. 2026. Agenticocr: Parsing only what you need for efficient retrieval-augmented generation. ArXiv:2602.24134.

Shi-Qi Yan and 1 others. 2025. Rpo: Retrieval preference optimization for robust retrieval-augmented generation. ArXiv:2501.13726.

Junyuan Zhang and 1 others. 2025a. Ocr hinders rag: Evaluating the cascading impact of ocr on retrieval-augmented generation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*. ArXiv:2412.02592.

Yanzhao Zhang and 1 others. 2025b. Qwen3 embedding: Advancing text embedding and reranking through foundation models. ArXiv:2506.05176.

Jihao Zhao and 1 others. 2024. Meta-chunking: Learning text segmentation and semantic completion via logical perception. ArXiv:2410.12788.

Jihao Zhao and 1 others. 2025a. Moc: Mixtures of text chunking learners for retrieval-augmented generation system. ArXiv:2503.09600.

Yao Zhao, Yantian Ding, Zhiyue Zhang, Dapeng Yao, and Yanxun Xu. 2025b. Lmar: Language model augmented retriever for domain-specific knowledge indexing. ArXiv:2508.05672.

A RADP-DPO Milestone Construction

This appendix details RADP-DPO, the discrete-output retrieval-aware intervention of §4.4: it samples multiple parses from the production parser Prod (Qwen3-VL-2B fine-tuned for Korean document parsing), ranks them by page-local RCPS score (Equation 1 restricted to the page’s questions), and converts candidate pairs with a sufficient reward gap into DPO preferences. Pages come from the 169-page KoGov train fold.

For each train page we sample K alternative parses from the production parser, chunk and score each by a page-local RCPS (the page’s questions against the parse’s own chunks plus distractors), and form preference pairs (chosen = higher-RCPS parse, gap ≥ 5 pp). The reward is sharpened across three milestones: **R1** ($K = 2$ parses, uniform distractors, $\beta = 0.1$) $\rightarrow$ **R2** (a warm-started iterative round, $\beta = 0.05$) $\rightarrow$ **R3** ($K = 14$ parses with a full-corpus hard-negative pool—the other-page chunks closest to the page’s queries—widening the candidate-score gap from about 0.05 to 0.56). We train with a LoRA-toggle reference ($\pi_\theta = \text{LoRA on}$, $\pi_{\text{ref}} = \text{LoRA off}$):

$$\mathcal{L}_{\text{DPO}} = -\log \sigma(\beta [\Delta_\theta - \Delta_{\text{ref}}]), \quad (2)$$

where $\Delta_{\bullet} = \log \pi_{\bullet}(c) - \log \pi_{\bullet}(r)$ for the chosen (c) and rejected (r) parse. The reference-free SimPO control ($\beta = 2.0$, $\gamma = 1.0$) removes the reference policy entirely.

B KoGov DPO Progression, RADP-aux Sweep, SimPO, and Robustness

This appendix reports the complete parser-training results underlying §4.4: the RADP-DPO milestone progression (R1–R3, constructed in Appendix A), the RADP-aux sweep, the SimPO control, and the cross-domain OHR-Bench evaluation. A go/no-go gate of ≥ 5 pp RCPS gain (with a 95% CI lower bound > 0) was fixed on the 169-page pilot before these runs; both RADP-aux (+1.8 pp) and RADP-DPO (a +4 pp ceiling with the CI crossing zero) fell short of it. We therefore characterise parser-side training as a *bounded* lever from a pre-set criterion, not from a target re-framed after the fact; the small but significant OHR-Bench gain (§4.4) is reported separately as the powered confirmatory endpoint. All systems are LoRA fine-tunes of the same production parser Prod (Qwen3-VL-2B); KoGov results use the 242-page / 663-Q–A fold against the same Prod baseline, with Hit@ k macro-averaged over the three retrievers BGE-M3, multilingual-e5-large, and Qwen3-Embedding-8B; Table 4 and the robustness paragraph concern OHR-Bench (2,264 English Q–A, seven domains).

On the KoGov fold (10,000-resample paired bootstrap), the three RADP-DPO milestones improve Hit@5 on parser-native chunking over Prod along the reward-sharpening axis (+1.96 to +2.11 pp, all $P[\Delta > 0] \approx 0.90$; per-milestone point estimates and CIs in Table 5). At $n = 663$ every two-sided interval spans zero, so these are exploratory: the Hit@5 / parser-native cell was selected from a multi-cell scan over (chunker $\times$ retriever $\times k$) with no family-wise correction. The reward-agnostic RADP-Distill control reaches +2.61 pp on this fold (exploratory, like the milestones; it uses a fixed chunking scheme and so is not a row in the parser-native Table 5); its powered confirmation is the held-out OHR-Bench replication (+1.22 pp Hit@5, Table 4).

RADP-aux is sub-threshold. The auxiliary loss peaks at $\lambda = 0.1$ (+1–2 pp RCPS) then declines monotonically as the contrastive objective competes with $\mathcal{L}_{\text{parse}}$ over the same LoRA parameters; every Δ -versus-control interval includes zero and the one-sided $P[\Delta > 0]$ never approaches 0.90. The hidden-state route does not reach the deployed markdown—only the discrete output does.

SimPO is negative. The reference-free length-normalised variant gives uniformly negative deltas (−0.7 to −1.7 pp Hit@5), indicating the DPO reference policy is load-bearing: without it the parser drifts from the production distribution before any preference signal can compound.

Robustness. The headline RADP-Distill OHR-Bench gain survives two checks. Because it ranks candidates by edit-distance and uses no retriever, it cannot overfit any embedder; its Hit@5 gain is near-uniform across the three (BGE-M3 +1.06, ml-e5-large +1.10, Qwen3-Emb +1.50 pp). And it concentrates on text-evidence (factoid) queries (+1.19 pp) while near-neutral on table-evidence ones (+0.32 pp), consistent with the text-fidelity mechanism.

C Chunk-Level Mechanism Statistics

This appendix examines whether the retrieval gains of §4.4 arise from changes in chunk structure (boundaries, cohesion) or from improvements in parsed-text fidelity. We measure four chunk-level statistics on the 242-page KoGov fold for every trained system and Prod, the shared baseline, in Table 6: MoC Boundary Clarity (BC, adjacent-chunk discontinuity), MoC Chunk Stickiness (CS, within-chunk cohesion), normalised edit distance to the reference markdown (TextNED, character-level Levenshtein distance $\div$ longer-string length), and chunking shape.

The signal. All three RADP-DPO milestones reduce TextNED from Prod’s 0.240 to 0.163–0.185, a 23–32% move toward the reference markdown; R1 and R2 achieve the largest reductions (0.167, 0.163). RADP-aux instead increases TextNED (0.318–0.626) because its hidden-state objective degrades sur-

Δ vs Prod (pp)	Hit@1	Hit@5	Hit@10	MRR@10	nDCG@5
RADP-Distill	+0.88	+1.22	+1.32	+1.01	+1.05
RADP-DPO-R2	+0.53	+0.85	+0.81	+0.70	+0.74
RADP-DPO-R3	+1.31	+1.03	+0.81	+1.17	+1.15

Table 4: OHR-Bench cross-domain Δ vs Prod, in pp (2,264 Q–A over seven English domains; three-retriever macro; 1,000-resample paired bootstrap). The Hit@5 deltas are two-sided significant (95% CIs: RADP-Distill [+0.35, +2.15], R2 [+0.35, +1.43], R3 [+0.24, +1.84]). The other columns are monotone re-cuts of the same per-system ranked list, reported only because practitioners use different cutoffs. RADP-Distill leads at the primary metric Hit@5; R3 reaches higher Hit@1 and MRR@10 point estimates but with overlapping CIs—no evidence the retrieval reward helps at the powered endpoint (§4.4).

Variant (vs Prod = 0.6863)	Hit@5	Δ Hit@5 [95% CI]	$P[\Delta > 0]$	Δ RCS
RADP-DPO-R3	0.7074	+2.11 [−0.96, +5.13]	0.913	+1.72
RADP-DPO-R1	0.7069	+2.06 [−0.96, +5.13]	0.907	+0.57
RADP-DPO-R2	0.7059	+1.96 [−1.06, +5.03]	0.897	+0.47
RADP-SimPO (ctrl)	0.6793	−0.70 [−3.77, +2.31]	0.321	−1.56

Table 5: RADP-DPO milestone progression and the SimPO control on parser-native chunking, 242-page / 663-Q–A fold, 10k paired percentile bootstrap, all against the same Prod baseline (Hit@5 = 0.6863). Macro Hit@ k averages the three retrievers of §3.1. All three milestones are strong directional positives ($P[\Delta > 0] \geq 0.90$) but two-sided non-significant at this fold size; RADP-SimPO is uniformly negative. RADP-Distill is not listed here (it uses a fixed chunking scheme, not parser-native); on this fold it reaches +2.61 pp (exploratory), and its powered confirmation is the OHR-Bench result (+1.22 pp, Table 4). Across three Prod seeds the standard deviation of the mean Δ Hit@5 is 0.90 pp.

face text. TextNED is positively associated with Hit@5 (R3 the one DPO-cluster exception), and RADP-Distill reduces it furthest (0.158) while leading on retrieval—the cleanest demonstration that text fidelity, not the retrieval reward, is the lever.

Cross-domain replication. On all 4,040 English OHR-Bench pages, zero-shot Prod reaches TextNED 0.192—below its 0.240 on Korean, so English leaves less fidelity headroom. R2 reduces it to 0.1894 (a −0.0026 delta, −1.36%, 95% CI [−0.0043, −0.0010], two-sided significant). R3 pushes the English value marginally lower (0.184) yet does not improve KoGov fidelity, which is why R2 is the headline variant.

The non-signal. The MoC chunking signature is unchanged: BC for every DPO variant lands in 0.60–0.66 (Prod 0.63) and CS near 0.47–0.49 (Prod 0.474); chunks-per-page (~ 5) and chunk length (300–321) stay close to Prod’s. The gain comes from what is parsed, not how chunks are split.

Secondary patterns. The gain concentrates on text-evidence (factoid) queries (+1.19 pp)—where the verbatim answer span

must land inside a chunk—and is near-neutral on table-evidence ones (+0.32 pp). Because RADP-Distill ranks by edit-distance and uses no retriever, its gain is near-uniform across the three embedders, confirming a parser-level effect rather than an embedder artefact. RADP-aux stays sub-threshold because its hidden-state signal reaches the deployed markdown only through diffuse $\mathcal{L}_{\text{parse}}$ back-flow, never localising to the surface tokens the retriever rewards.

D Coverage Diagnostic per Chunker

This appendix tabulates the retriever-free coverage diagnostic of §3.2 applied to the production parser Prod (Qwen3-VL-2B) on KoGovDoc-RAG (294 pages, 663 Q–A): each gold answer is *covered* (inside one chunk), *split* (in the page text but cut across chunks), or *absent* (not in the parser output), classified by text matching only (Table 7).

E OHR-Bench Noise-Family Grid

This appendix tabulates the controlled-noise grid behind the cross-domain insensitivity finding of §4.2: twelve OHR-Bench parser-output perturbations (three parser families $\times$

Variant	len	c/pg	clen	BC $\uparrow$	CS $\downarrow$	TextNED $\downarrow$
Prod (ref)	1385	4.82	274	0.630	0.474	0.240
RADP-Distill	1597	5.29	291	0.641	—	0.158
aux $\lambda=0.0$	799	2.96	245	0.553	0.473	0.626
aux $\lambda=0.1$	1380	4.05	321	0.652	0.484	0.423
aux $\lambda=0.3$	1930	6.73	272	0.470	0.475	0.332
aux $\lambda=0.5$	2035	5.82	327	0.556	0.470	0.318
DPO-R1	1606	4.97	311	0.646	0.474	0.167
DPO-R2	1610	4.83	321	0.647	0.476	0.163
DPO-R3	1514	4.88	300	0.656	0.485	0.185
SimPO	1703	5.31	305	0.601	0.470	0.186

Table 6: Chunk-level mechanism statistics on the 242-page fold (len = parse length, c/pg = chunks per page, clen = chunk length). RADP-Distill attains the lowest TextNED of all ($0.158 < R2$'s $0.163 < \text{Prod's } 0.240$) with BC unchanged (0.641, within Prod's range), confirming that text fidelity, not chunk structure, is the operative axis (CS was not measured for RADP-Distill, which uses a fixed chunking scheme). Among retrieval-reward variants, R2 has the lowest TextNED (0.163); R3's KoGov TextNED (0.185) does not beat it.

Chunker	covered	split	absent
md_h3	79.8%	0.0%	20.2%
parser_native	78.1%	1.7%	20.2%
fixed500	77.5%	2.3%	20.2%
fixed500_ov200	79.8%	0.0%	20.2%

Table 7: Answer-coverage diagnostic on Prod's output (294 pages, 663 KoGov Q-A; text matching only, no retriever). Absence is determined on the full parser output, so the 20.2% absent rate is chunker-invariant by construction (four representative rows of eight shown); the chunker-dependent quantity is the split rate, at most 2.3%, vanishing under overlap. Chunkers: $\text{md_h}\{1,2,3\}$ = markdown-header splitting at heading depth k ; parser_native = the parser's own segmentation; $\text{fixed } N[_{\text{ov}}M]$ = fixed N -character windows, optionally with M -character overlap.

Family	BC (clean $\rightarrow$ sev.)	RCPS (clean $\rightarrow$ sev.)
MinerU	0.735/0.708/0.715/0.712	0.496/0.413/0.351/0.243
Qwen2.5-VL	0.619/0.614/0.616/0.610	0.467/0.462/0.460/0.429
GOT	-/0.634/0.495/0.650	-/0.383/0.338/0.257

Table 8: Per-family Boundary Clarity and RCPS across semantic-noise severity (clean/mild/moderate/severe) on the seven OHR-Bench domains—the source for the §4.2 noise numbers. Within each family BC stays roughly flat while RCPS falls (MinerU -51%). GOT has no clean baseline; the GT output and three formatting-noise variants enter only the aggregate scalar (§4.2) and are in the released grid.

four semantic-noise severities), each scored for Boundary Clarity and RCPS over all seven domains (2,264 Q-A, three-retriever average).