Math23C Spring 2018 Final Project

Patrick Watts, David Wihl
May 6, 2018

```
library(xts)

## Loading required package: zoo

##

## Attaching package: 'zoo'

## The following objects are masked from 'package:base':

##

## as.Date, as.Date.numeric

library(quantmod)

## Loading required package: TTR

## Version 0.4-0 included new data defaults. See ?getSymbols.

library(ggplot2)
```

Abstract

Cryptocurrencies such as Bitcoin, Ethereum, etc. generated significant attention in 2017. Cryptocurrencies have significant volalility as there is rampant speculation. Given the high variance in prices, can data science methods explored in this class be used to model the market dynamics?

Data Source

We obtained a history cryptocurrency price data from https://www.kaggle.com/sudalairajkumar/cryptocurrencypricehistory/data for four different cryptocurrencies (BTC, ETH, XMR, XRP)

(REQ: a dataframe, at least two numeric columns, at least 20 rows)

Data Ingestion, clean up and normalization

```
# Read one price history file per currency
BTCdf = read.csv("data/bitcoin_price.csv", stringsAsFactors = F)
ETHdf = read.csv("data/ethereum_price.csv", stringsAsFactors = F)
XMRdf = read.csv("data/monero_price.csv", stringsAsFactors = F)
XRPdf = read.csv("data/ripple_price.csv", stringsAsFactors = F)

# Fix rest of data:
# 1- Make dates native format
# 2- Convert Volume and market cap:
# a) From string ("123,456") to numeric (123456).
# b) Convert "-" to 0.
# 3- Sort chronologically
fixVolCap = function(df) {
```

```
df$Date = as.Date(df$Date,"%b %d, %Y")
  df$Volume = as.numeric(gsub("-","0",gsub(",","",df$Volume)))
  df$Market.Cap = as.numeric(gsub("-","0",gsub(",","",df$Market.Cap)))
  return (df[order(df$Date),])
BTCdf = fixVolCap(BTCdf)
ETHdf = fixVolCap(ETHdf)
XMRdf = fixVolCap(XMRdf)
XRPdf = fixVolCap(XRPdf)
# Ensure that all data start from the same date
earliestCommonDate = max(min(BTCdf$Date),
                          min(ETHdf$Date),
                          min(XMRdf$Date),
                          min(XRPdf$Date))
BTCdf = BTCdf[BTCdf$Date>=earliestCommonDate,]
ETHdf = ETHdf [ETHdf$Date>=earliestCommonDate,]
XMRdf = XMRdf[XMRdf$Date>=earliestCommonDate,]
XRPdf = XRPdf[XRPdf$Date>=earliestCommonDate,]
```

Exploratory Data Analysis

```
plotSeries = function(df){
    dfdata = xts(df[,2:7],order.by = df[,1])
    # TODO fix weekly plot
    #wk = dfdata
    #data.wk = to.weekly(wk)
    #plot(data.wk)
    #plot.new()
    OHLC = as.quantmod.OHLC(dfdata)
    chartSeries(OHLC)
}
plotSeries(BTCdf)
```



plotSeries(ETHdf)








plotSeries(XRPdf)





```
# data.wk = to.weekly(wk)
# plot(data.wk)
# OHLC = as.quantmod.OHLC(BTCdata)
#chartSeries(OHLC)
close.prices = BTCdata$Close
close.prices = cbind(close.prices,ETHdf$Close,XMRdf$Close,XRPdf$Close)
multidf = cbind(index(close.prices), data.frame(close.prices))
names(multidf) = paste(c("Date","BTC","ETH","XMR","XRP"))
multidf$BTC.idx = multidf$BTC / multidf$BTC[1]
multidf$ETH.idx = multidf$ETH / multidf$ETH[1]
multidf$XMR.idx = multidf$XMR / multidf$XMR[1]
multidf$XRP.idx = multidf$XRP / multidf$XRP[1]
plot(x = multidf$Date,y=multidf$BTC.idx,type="1",xlab="Date",col="black",lty=1,lwd=2)
lines(x=multidf$Date,y=multidf$ETH,col="red")
lines(x=multidf$Date,y=multidf$XMR,col="blue")
lines(x=multidf$Date,y=multidf$XRP,col="green")
legend("topleft",c("BTC","ETH","XMR","XRP"),col=c("black","red","blue","green"),
       lty=c(1,1,1,1),
       1wd=c(2,2,2,2))
```














```
# Display a bar plot
overallReturn = function(df){
  return ((df$Close[nrow(df)] - df$Close[1]) / df$Close[1])
}
volIncrease = function(df){
  return ((df$Volume[nrow(df)] - df$Volume[1]) / df$Volume[1])
}
returns = c(overallReturn(BTCdf), overallReturn(ETHdf), overallReturn(XMRdf), overallReturn(XMRdf))
volumes = c(volIncrease(BTCdf),volIncrease(ETHdf),volIncrease(XMRdf),volIncrease(XRPdf))
close.prices = BTCdata$Close
close.prices = cbind(close.prices,ETHdf$Close,XMRdf$Close,XRPdf$Close)
barData = data.frame(Currency =c("BTC","ETH","XMR","XRP"), Returns=returns, Volumes=volumes)
barData
##
     Currency
                Returns
                           Volumes
                          232.6492
## 1
          BTC 39.78868
          ETH 322.23827 15487.8060
## 3
          XMR 409.08121
                          551.9270
          XRP 132.70952 2217.3103
## 4
# REQ: barplot
ggplot(data=barData, aes(x=Currency, y=Returns)) +
  geom_bar(stat="identity",fill="steelblue") +
  ggtitle("Cumulative Return on Investment (not percent!) Aug 2015 - Feb 2018")
```

Cumulative Return on Investment (not percent!) Aug 2015 – Feb 2018



```
ggplot(data=barData, aes(x=Currency, y=Volumes)) +
geom_bar(stat="identity",fill="darkseagreen1") +
ggtitle("Change in Daily Volume Aug 2015 - Feb 2018")
```





[&]quot;' ## Topic 1 - Volalitility Exploration

Topic 2 -

Topic 3 - Correlation between Cryptocurrencies

```
cor(BTCdf$Close, ETHdf$Close)

## [1] 0.9060949

cor(BTCdf$Close, XMRdf$Close)

## [1] 0.9691732

cor(BTCdf$Close, XRPdf$Close)

## [1] 0.8049156

cor(ETHdf$Close, XMRdf$Close)

## [1] 0.9525516

cor(ETHdf$Close, XRPdf$Close)

## [1] 0.8798746


cor(XMRdf$Close, XRPdf$Close)

## [1] 0.8847865
```

```
#Largest correlation between BTC and XMR
plot(BTCdf$Close,XMRdf$Close,pch = ".",cex = 3)
#b is slope
b <- cov(BTCdf$Close,XMRdf$Close)/var(BTCdf$Close)
#a is intercept
a <- mean(XMRdf$Close) - b*mean(BTCdf$Close);a</pre>
```

[1] -10.16858

#We can add this regression line to the plot of the data abline(a, b, col = "red")



Summary of Project Requirements

Required dataset standards

- [x] A dataframe
- [] At least two categorical or logical columns
- [x] At least two numeric columns
- [x] At least 20 rows, preferably more, but real-world data may be limited

Required graphical displays (all graphs must be colored and nicely labeled)

- [x] A barplot
- [x] A histogram
- [] A probability density graph overlaid on a histogram
- [] A contingency table

Required Analysis

- [] A permutation test
- [] A p-value or other statistic based on a distribution function

- [] Analysis of a contingency table
- [] Comparison of analysis by classical methods (chi-square, CLT) and simulation methods

Required submission uploads

- [] A .csv with the dataset
- [] A long, well-commented script that loads the dataset, explores it, and does all the analysis.
- [] A shorter .Rmd with compiled .pdf or .html file that presents highlights in ten minutes.
- [] A one-page handout that explains the dataset and summarizes the analysis.

Additional points for creativity or complexity (up to 10 points)

References

Clifford S. Ang, Analyzing Financial Data and Implementing Financial Models Using R, Springer, 2015 Berlinger et al. Mastering R for Quantitative Finance, Packt Publishing, 2015