

⚠ Document version 0.5 This document is not finished — it is a working draft. Places marked `<...>` and **TODD** need to be filled in with real values (URLs, credentials, sample responses). Assumptions are explicitly flagged in the text.

WebService – Product API

Purpose of this document: A complete description of the SWS/I6 (CyberSoft) WebService for the purposes of handover and integration under ALSO. The document covers the architecture, authentication, request and response formats, naming conventions, and the full catalog of available exports.

Overview

The SWS WebService gives partners machine access to data in the **I6 ERP system (CyberSoft)**. It covers product information (Stoltem), stock levels, prices, images, attributes, presentation trees (categories), documents (invoices, delivery notes) and orders.

The service is built as an **ASP.NET Web Service (.asmx)** and runs as the application directory `/i6ws/` on the distributor's eShop. It can be communicated with using the **SOAP** protocol; for methods with simple parameters (exports) it can also be used over **HTTP GET/POST** — exports can therefore be downloaded with a plain link (URL).

Base URL

The web service runs as the application directory `/i6ws/` on the distributor's eShop:

```
https://terminal.sws.cz/i6ws/
```

```
https://www.sws.cz/i6ws/
```

Main endpoints:

Endpoint	Purpose
<code>Default.asmx</code>	Universal data reads (exports) — methods <code>GetResult</code> (all products), <code>GetResultByCode</code> (a single product), <code>GetResultByFromTo</code>
<code>Order.asmx</code>	Creating and managing orders — method <code>Create</code>
<code>ResultTypeInfo.ashx</code>	Overview of all available exports with descriptions and schemas

Request format

Reading data — `Default.asmx`

Three methods are available, all accessible over HTTP GET (as well as SOAP).

```
GET https://USER:PASSWORD@HOST/i6ws/Default.asmx/GetResult?
resultType=<RESULT_TYPE>
GET https://USER:PASSWORD@HOST/i6ws/Default.asmx/GetResultByCode?
resultType=<RESULT_TYPE>&code=<CODE>
GET https://USER:PASSWORD@HOST/i6ws/Default.asmx/GetResultByFromTo?
resultType=<RESULT_TYPE>&from=<FROM>&to=<TO>
```

Method	Description	Parameters
<code>GetResult</code>	Returns the complete export (all products, everything in stock, etc.)	<code>resultType</code>
<code>GetResultByCode</code>	Filters the export by code — returns a single record for the given product	<code>resultType</code> , <code>code</code>
<code>GetResultByFromTo</code>	Filters the export by date from/to — typically by the record's logged change date	<code>resultType</code> , <code>from</code> , <code>to</code>

Parameters:

Parameter	Type	Required	Description
<code>resultType</code>	String	Yes	Export name, e.g. <code>StoItemBase</code> (see catalog below)
<code>code</code>	String	For <code>GetResultByCode</code>	Filter — product code, tree IdP, condition... Prefix <code>{PartNo}</code> = search by PartNo
<code>from</code>	String/Date	For <code>GetResultByFromTo</code>	Range start — format <code>YYYY-MM-DD</code> or <code>YYYY-MM-DD HH:MM:SS</code>
<code>to</code>	String/Date	For <code>GetResultByFromTo</code>	Range end

Note on the `code` parameter: Searching by PartNo is activated with the `{PartNo}` prefix:

```
GetResultByCode?resultType=StoItemQtyFree&code={PartNo}600623
```

Comparison with the ALSO Product API

The ALSO Product API offers 7 methods. Below is a mapping of which SWS exports cover the same functionality.

#	ALSO Product API method	Description (ALSO)	Corresponding SWS export(s)	Note
1	<code>AllProducts</code>	Basic info on all products available in the e-shop	<code>StoItemBase</code>	SWS returns prices, stock and images (only <code>Id</code> with URL) in one export.
2	<code>AllOfflineProducts</code>	Products in the partner's catalog that are not online		
3	<code>ProductFullInfo</code>	Complete product detail — description, attributes, images, prices	<code>StoItemBase</code> + <code>CpsSti/CpsStiVal</code> + <code>AttSti</code>	SWS requires a combination of multiple exports for the same result
4	<code>ProductNow</code>	Current stock, price and availability for a single product	<code>StoItemSiv</code> , or availability and price separately via <code>StoItemQtyFree</code> , <code>StoItemPriceOrdCur</code>	Called via <code>GetResultByCode</code> with the product code
5	<code>AllProductsNow</code>	Stock, price and availability for all products	<code>StoItemSiv</code> , or availability and price separately via <code>StoItemQtyFree</code> , <code>StoItemPriceOrdCur</code>	Called via <code>GetResult</code> for all products
6	<code>ProductImages</code>	Available product images	<code>StoItemBase</code> or <code>AttSti</code>	SWS returns URLs assembled from <code>UrlBase*</code> + <code>Id</code> ; types distinguished by tag
7	<code>Categories</code>	Complete e-shop category hierarchy	<code>SPresentTree</code> , <code>SCategorySys</code>	SWS uses a flat list with a parent ID and a sort key (3 chars per level)

Export catalog

Each export exists in three variants — they differ only by the suffix in `resultType`:

Suffix	Description	Example
<code>(none)</code>	Data as XML attributes — more compact	name
<code>_El</code>	Data as XML elements — more readable	name_El
<code>_Schema</code>	XSD schema of the export	name_Schema

Example — same data, three variants (`StoItemQtyFree`):

<https://terminal.sws.cz/i6ws/default.asmx/GetResultByCode?code=ASC00511&resultType=StoltemQtyFree>

```
<!-- Attributes (default) -->
<?xml version="1.0" encoding="utf-8"?>
<Result>
  <StoItem Id="685699" Code="ASC00511" PartNo="GU605CX-QR149" PartNo2="90NR0M65-M007X0" EAN="4711636262347" EAN2="" QtyFree="2" />
</Result>
```

https://terminal.sws.cz/i6ws/default.asmx/GetResultByCode?code=ASC00511&resultType=StoltemQtyFree_El

```
<!-- Elements (_El) -->
<?xml version="1.0" encoding="utf-8"?>
<Result>
  <StoItem>
    <Id>685699</Id>
    <Code>ASC00511</Code>
    <PartNo>GU605CX-QR149</PartNo>
    <PartNo2>90NR0M65-M007X0</PartNo2>
    <EAN>4711636262347</EAN>
    <EAN2>
  </EAN2>
    <QtyFree>2</QtyFree>
  </StoItem>
</Result>
```

https://terminal.sws.cz/i6ws/default.asmx/GetResultByCode?code=ASC00511&resultType=StoltemQtyFree_Schema

```
<!-- Schema (_Schema) – definition of all fields and their data types -->
<?xml version="1.0" encoding="utf-8"?>
<Schema name="Schema1" xmlns="urn:schemas-microsoft-com:xml-data"
xmlns:dt="urn:schemas-microsoft-com:datatypes">
  <ElementType name="Result" content="eltOnly" model="closed" order="many">
    <element type="StoItem" maxOccurs="*" />
    <AttributeType name="Void" dt:type="string" />
    <attribute type="Void" />
  </ElementType>
  <ElementType name="StoItem" content="empty" model="closed">
    <AttributeType name="Id" dt:type="i4" />
    <AttributeType name="Code" dt:type="string" />
    <AttributeType name="Code2" dt:type="string" />
    <AttributeType name="PartNo" dt:type="string" />
    <AttributeType name="PartNo2" dt:type="string" />
    <AttributeType name="EAN" dt:type="string" />
    <AttributeType name="EAN2" dt:type="string" />
    <AttributeType name="QtyFreeIs" dt:type="boolean" />
    <AttributeType name="QtyFree" dt:type="i4" />
```

```

        <attribute type="Id" />
        <attribute type="Code" />
        <attribute type="Code2" />
        <attribute type="PartNo" />
        <attribute type="PartNo2" />
        <attribute type="EAN" />
        <attribute type="EAN2" />
        <attribute type="QtyFreeIs" />
        <attribute type="QtyFree" />
    </ElementType>
</Schema>

```

Most-used exports

#	ResultType	Number of companies	Description
1	StoItemBase	130	Complete product catalog
2	StoItemQtyFree	104	Current free quantity in stock
3	StoItemSiv	57	Purchase price and stock status
4	SPresentTree	56	Hierarchical tree of product categories
5	DocTrInv	51	Invoices
6	StoItemPriceOrd	36	Purchase price
7	CpsStiVal	27	Product attributes including parameter definitions
8	StiRelation	19	Relationships between products (accessories, alternatives)
9	StoItemBase_El	18	Output as XML elements. Complete product catalog
10	AttSti	16	Product attachments (images, documents), invoices
11	CpsSti	16	Product parameters
12	StoItemQtyFree_El	16	Output as XML elements. Current free quantity in stock
12	StrStiSync	12	Product tree synchronization

Examples of the most-used exports

StoltemBase

In a single call it returns product descriptions, prices, VAT, stock availability, logistics data and image information. Corresponds to the [AllProducts](#) method (and partly [ProductFullInfo](#)) of the ALSO Product API.

resultType: `StoItemBase · StoItemBase_El · StoItemBase_Schema`

Type legend: `i2/i4/i8` = integer (16/32/64 bit) · `ui1` = byte (0–255) · `fixed.14.4` / `number` = decimal number · `string` = text · `boolean` = 0/1.

Attributes of the `Result` element (envelope, once per document)

Field	Type	Description
<code>UrlBase</code>	string	Base URL of the eshop/website
<code>UrlBaseThumbnail</code>	string	Base URL for thumbnails — resulting URL = <code>UrlBaseThumbnail</code> + <code>StoItem.Id</code>
<code>UrlBaseImg</code>	string	Base URL for images — resulting URL = <code>UrlBaseImg</code> + <code>StoItem.Id</code>
<code>UrlBaseEnlargement</code>	string	Base URL for enlargements
<code>UrlBaseImgGalery</code>	string	Base URL for gallery images — combined with <code>ImgGal.Id</code>
<code>CouCode</code>	string	Default country code
<code>TaxRateLow</code>	ui1	Reduced VAT rate (%)
<code>TaxRateHigh</code>	ui1	Standard/high VAT rate (%)
<code>Void</code>	string	<code><verify></code> (reserved/empty attribute)

Attributes of the `StoItem` element

Field	Type	Description
<code>Id</code>	i4	Internal product ID in I6
<code>Code</code>	string	Main SWS stock code (e.g. <code>ASC00511</code>)
<code>Code2</code>	string	Alternative/second code <code><verify></code>
<code>PartNo</code>	string	Manufacturer's catalog (part) number
<code>PartNo2</code>	string	Second manufacturer part/order number
<code>EAN</code>	string	EAN
<code>EAN2</code>	string	Second EAN
<code>Name</code>	string	Product name
<code>NameAdd</code>	string	Name supplement (extending text) <code><verify></code>
<code>NameE</code>	string	English name
<code>NameDoc</code>	string	Name used on documents
<code>NameShort</code>	string	Short name
<code>NameSeo</code>	string	SEO name (for URLs / search engines)

Field	Type	Description
ManName	string	Manufacturer name
CouCode	string	Country of origin code
UrlExt	string	External URL (e.g. product page at the manufacturer) verify
PriceEU	fixed.14.4	MSRP, list price
PriceB2CMin	fixed.14.4	Minimum B2C selling price (MAP)
PriceDea	fixed.14.4	Dealer price
PriceOrd	fixed.14.4	Order (purchase) price
PriceRef	fixed.14.4	Copyright/author levy
PriceRefInfo	fixed.14.4	Informational value of the reference levy verify
RefProName	string	Reference product name verify
RefCode	string	Reference product code verify
PriceRef2	fixed.14.4	Recycling levy verify
PriceRef2Info	fixed.14.4	Informational value of the second reference levy verify
RefProName2	string	Name of the second reference product verify
RefCode2	string	Code of the second reference product verify
WeightRef	number	Reference weight (for levy calculation?) verify
MeasureRef2	number	Reference measure/quantity verify
TaxRate	fixed.14.4	Product VAT rate (%)
TatCodeE	string	verify
CutCode	string	verify – customs tariff / code?
QtyFreeIs	boolean	Flag indicating whether the available quantity is tracked/valid
QtyFree	i4	Free (available) quantity in stock
QtyPack	number	Quantity per pack (carton)
WarDur	i4	Warranty length (months)
WarDurEU	i4	Warranty length for the end customer / EU (months) verify
SNTrack	ui1	Serial number tracking (0 = no / tracking type)
NonDivQty	number	Indivisible (minimum order) quantity verify
Weight	number	Weight (kg)
XXL	boolean	Oversized goods
XXS	boolean	verify

Field	Type	Description
ScaId	i4	<verify>
ThumbnailIs	boolean	Thumbnail exists
ThumbnailSize	i8	Thumbnail size (B)
ImgIs	boolean	Main image exists
ImgSize	i8	Main image size (B)
EnlargementIs	boolean	Enlargement exists
EnlargementSize	i8	Enlargement size (B)
SisName	string	<verify>
SitId	ui1	<verify>
NonMater	ui1	Flag for a non-material product (service/license/ESD)? <verify>
SttId	ui1	<verify>
NoteShort	string	Short note
StiDemIdDis	string	<verify>
EprelId	i4	Record ID in the EU EPREL database (energy labels)
Note	string	Note (longer text)

Nested **ImgGal** elements (image gallery, 0..N per product)

Field	Type	Description
Id	i4	Gallery image ID; URL = UrlBaseImgGalery + Id
Name	string	Image name/file
Tag	string	Image type/label (distinguishes the kind of image)
Sort	i2	Display order
Size	i8	Image size (B)

StoltemQtyFree

Returns only the product identification and free quantity — no prices, names or images. Suitable for frequent stock queries (smaller data volume than **StoItemBase**). Corresponds to the **AllProductsNow** / **ProductNow** methods of the ALSO Product API.

Example:


```
<?xml version="1.0" encoding="utf-8"?>
<Result>
  <StoItem Id="685699" Code="ASC00511" PartNo="GU605CX-QR149" PartNo2="90NR0M65-
M007X0" EAN="4711636262347" EAN2="" QtyFree="2" />
</Result>
```

Attributes of the **StoItem** element

Field	Type	Description
Id	i4	Internal product ID in I6
Code	string	Main SWS stock code (e.g. ASC00511)
Code2	string	Alternative/second code <verify>
PartNo	string	Manufacturer's catalog (part) number
PartNo2	string	Second manufacturer part/order number
EAN	string	EAN
EAN2	string	Second EAN
QtyFreeIs	boolean	Flag
QtyFree	i4	Free (available) quantity in stock

Example call and response — see the [Export catalog](#) section above (**StoItemQtyFree** is used as the example for all three variants).

StoItemSiv

A combined availability-and-price export — returns stock, order price and basic identification plus logistics data in a single call, without the image gallery or extended names. A compromise between the lightweight **StoItemQtyFree** and the full **StoItemBase**. Corresponds to the **ProductNow** method (via **GetResultByCode**) or **AllProductsNow** (via **GetResult**) of the ALSO Product API — it covers both availability and price in one export.

Example:

```
<?xml version="1.0" encoding="utf-8"?>
<Result UrlBase="https://terminal.sws.cz/default.asp?cls=stoitem&stiid="
UrlBaseImg="https://terminal.sws.cz/img.asp?stiid=">
  <StoItem Id="230726" Code="578307" Code2="ZB0788" PartNo="A76/01B"
EAN="8711500802521" EAN2="4895229106093" Name="Philips baterie knoflíková A76,
alkalická - 1ks (LR44)" ManName="Philips" SiuCode="ks" UrlSuffix="230726"
UrlExt="http://www.consumer.philips.com/c/zvlastni-baterie/alkalicke-
a76_01b/prd/cz/" QtyFree="9" PriceEU="28.1000" PriceOrd="11.5000"
PriceRef="0.0000" PriceRef2="0.0000" WarDur="744" ImgSize="16384"
```

```
CutCode="85065030" Weight="0.00400" />
</Result>
```

Attributes of the **Result** element (envelope)

Field	Type	Description
UrlBase	string	Base URL of the eshop/website
UrlBaseImg	string	Base URL for the main image — resulting URL = UrlBaseImg + StoItem.Id
Void	string	⋖verify⋗ (reserved/empty attribute)

Attributes of the **StoItem** element

Field	Type	Description
Id	i4	Internal product ID in I6; used to build the image URL
Code	string	Main SWS stock code
Code2	string	Alternative/second code ⋖verify⋗
PartNo	string	Manufacturer's catalog (part) number
PartNo2	string	Second manufacturer part/order number
EAN	string	EAN (barcode)
EAN2	string	Second EAN
Name	string	Product name
ManName	string	Manufacturer name
SisName	string	⋖verify⋗
SiuCode	string	⋖verify – unit of measure code (pcs/pack)?⋗
UrlSuffix	string	Suffix appended to UrlBase (completes the product URL) ⋖verify⋗
UrlExt	string	External URL ⋖verify⋗
QtyFreeIs	boolean	Flag indicating whether the available quantity is tracked/valid
QtyFree	i4	Free (available) quantity in stock
PriceEU	fixed.14.4	⋖verify – end/recommended price (MSRP)?⋗
PriceOrd	fixed.14.4	Order (purchase) price
PriceRef	fixed.14.4	Price of the linked reference levy (recycling/copyright?) ⋖verify⋗
PriceRefInfo	fixed.14.4	Informational value of the reference levy ⋖verify⋗
PriceRef2	fixed.14.4	Price of the second reference levy ⋖verify⋗

Field	Type	Description
PriceRef2Info	fixed.14.4	Informational value of the second reference levy <verify>
WarDur	i4	Warranty length (months)
ImgSize	i8	Main image size (B); 0 = no image
SitId	ui1	<verify>
NonMater	ui1	Flag for a non-material product (service/license/ESD)? <verify>
CutCode	string	<verify – customs tariff / code?>
Weight	number	Weight (kg)
XXL	boolean	Oversized goods
XXS	boolean	<verify>

SPresentTree

Export of the presentation (category) tree. It returns a **flat list of tree nodes**, where the hierarchy is reconstructed on the client side from the sort key — **each level has 3 reserved characters** (AAA = level 1, AAABBB = level 2, and so on). The parent link is carried by IdP (empty = root node). Top-level nodes correspond to *tree types* (price-list trees); their Id is derived as a negative value (-2147483648 + type). Corresponds to the **Categories** method of the ALSO Product API.

Thanks to **FOR XML AUTO** the structure is **two-level**: a **SPresentTree** node contains 0..N nested **StoItem** elements — i.e. the products placed directly in the given node. Categories without products that also have no product beneath them (at any sublevel) are removed from the output.

Filtering via GetResultByCode: the **code** parameter = IdP (node ID) — returns the given subbranch of the tree. A negative **code** filters by *tree type*.

Example:

```
<?xml version="1.0" encoding="utf-8"?>
<Result UrlBase="https://terminal.sws.cz/default.asp?cls=sresenttrees&strid="
UrlBaseImg="https://terminal.sws.cz/img.asp?strid="
<SPresentTree Id="21224" IdP="12695" Sort="001Z6WKCC" Name="5G/LTE">
  <StoItem Code="447665" Id="640646"/>
  <StoItem Code="ZXL00038" Id="666764"/>
  <StoItem Code="ZXL00105" Id="686879"/>
  <StoItem Code="ZXL00109" Id="691042"/>
  <StoItem Code="ZXL00123" Id="697709"/>
</SPresentTree>
<SPresentTree Id="21409" IdP="21353" Sort="001ZBW126" Name="Acar">
  <StoItem Code="398242" Id="561103"/>
  <StoItem Code="398423" Id="561108"/>
</SPresentTree>
</Result>
```

Attributes of the **Result** element (envelope)

Field	Type	Description
UrlBase	string	Base category URL; resulting URL = UrlBase + SPresentTree.Id (link ... default.asp?cls=spresenttrees&strid=)
UrlBaseImg	string	Base product image URL; resulting URL = UrlBaseImg + StoItem.Id (or Code)
Void	string	Reserved empty attribute (always NULL)

SPresentTree element (tree node / category)

Field	Type	Description
Id	i4	Node ID (StrId). For top-level tree types it is derived as -2147483648 + type
IdP	i4	Parent node ID; empty/NULL = root level
Sort	string	Sort key for ordering and hierarchy reconstruction — 3 chars per nesting level
Name	string	Category name (localized — the partner's login language applies)
Tag	string	Optional node label/tag (only when filled)
ImgSize	i8	Category image size in B (only when an image is present)
NameSEO	string	Category SEO name (for URLs / search engines)
Note	string	Note on the node
NameAdd	string	Supplementary name / extending text
StrWWW	string	Custom WWW link for the category (if set)

Nested **StoItem** element (products in the node, 0..N)

Field	Type	Description
Id	i4	Internal product ID (StiId); for building the image URL
Code	string	Product stock code (StiCode)

Note on contents: Only products that pass the standard Webservice visibility filters (product stock/sale flags, partner row permissions) enter the output. The set of products may therefore differ between partners according to their permissions.

DocTrInv

An invoice transfer format — **"Document Transfer – Invoice"** — which, per the export definition, is intended for **import into another I6 instance** (cross-system document exchange). It returns the complete invoice including the VAT recap, line items, serial numbers (warranties), linked delivery notes and the order, including end-customer data for dropshipment.

Unlike the product exports, it uses **FOR XML EXPLICIT** — the output is therefore strictly **hierarchical** (nested elements with attributes), not a flat list:

```
Result
├─ Invoice (invoice - header)
│   ├── DocTaxSum (VAT recap - 0..N)
│   ├── InvItem (invoice line items - 0..N)
│   ├── Warranty (serial numbers / warranties - 0..N)
│   ├── Delivery (delivery notes - 0..N)
│   └─ Order (order + dropshipment end customer - 0..N)
```

resultType: `DocTrInv` (variants `_El` / `_Schema` — `<verify>`; with **FOR XML EXPLICIT** the three-variant convention may not apply the same way as with other exports)

Filtering and scope:

Call	Behavior
<code>GetResultByCode</code>	<code>code</code> = invoice number (<code>InvCode</code> , e.g. <code>CRDC120009</code>)
<code>GetResultByFromTo</code>	<code>from/to</code> filters by the invoice creation date (<code>InvC</code>) and by the last confirmed delivery note (<code>DelDateConf</code>)
<code>GetResult</code> (no params)	Returns only invoices created in the last ~1–2 days (<code>InvC >= today - 1</code>)

The export is always **restricted to the logged-in partner's company** (`InvComId`) and returns only **completed, non-internal** invoices (`InvState = 1`, `InvInt = 0`). A partner thus sees only their own documents.

Invoice element (invoice header)

Attribute	Type	Description
<code>Id</code>	i4	Internal invoice ID (<code>InvId</code>)
<code>Code</code>	string	Invoice number
<code>ZCode</code>	string	Invoice number for dropship/end customer (only when present) <code><verify></code>
<code>Code0</code>	string	External invoice number (number at the buyer, only when present)
<code>SymCon</code>	string	Payment matching/variable symbol <code><verify></code>
<code>Tag</code>	string	Invoice label/flag (only when present)
<code>OrdId</code>	i4	ID of the linked order
<code>OrdCode</code>	string	Number of the linked order
<code>OrdCode0</code>	string	External order number
<code>OrdC</code>	datetime	Order creation date

Attribute	Type	Description
Type	—	Invoice type (enumeration; e.g. invoice/credit note) verify values
DateAcc	date	Accounting case date / tax point (DUZP) verify
DateDue	date	Due date
CurCode	string	Currency code (ISO, UsdCodeE)
Val	fixed.14.4	Total value in home currency
ValCur	fixed.14.4	Total value in invoice currency
ValRnd	fixed.14.4	Rounding (home currency)
ValRndCur	fixed.14.4	Rounding (invoice currency)
ValPaid	fixed.14.4	Paid (home currency)
ValPaidCur	fixed.14.4	Paid (invoice currency)
ZVal	fixed.14.4	Value for the end customer (dropship) verify
C	datetime	Invoice creation date (created)
IdC	i4	ID of the related invoice (original invoice for a credit note)
CodeC	string	Number of the related invoice (original invoice for a credit note)

DocTaxSum element (VAT recap, 0..N)

Attribute	Type	Description
Id	i4	Recap row ID (DtsId)
TaxRate	fixed.14.4	VAT rate (%)
Base	fixed.14.4	Tax base (home currency)
ValTax	fixed.14.4	Tax amount (home currency)
BaseCur	fixed.14.4	Tax base (invoice currency)
ValTaxCur	fixed.14.4	Tax amount (invoice currency)

InvItem element (invoice line items, 0..N)

Attribute	Type	Description
Id	i4	Invoice line item ID (IniId)
StiId	i4	Product ID
StiCode	string	Product stock code
StiCode2	string	Alternative product code

Attribute	Type	Description
StiPartNo	string	Part number
StiPartNo2	string	Second part number
StiEAN	string	EAN (added per the partner's WsEAN parameter, otherwise empty)
StiEAN2	string	Second EAN
StiName	string	Product name (stock)
Name	string	Name on the invoice line (line's own text, only when present)
OrdId	i4	Order ID of the item
OrdCode	string	Order number of the item
OrdCode0	string	External order number of the item
OriC	datetime	Creation date of the order item
Qty	number	Quantity
TaxRate	fixed.14.4	Line VAT rate (%)
Prc	fixed.14.4	Unit price excl. VAT (home currency)
PrcTax	fixed.14.4	Unit price incl. VAT (home currency)
CurCode	string	Line currency code
PrcCur	fixed.14.4	Price excl. VAT (invoice currency)
PrcTaxCur	fixed.14.4	Price incl. VAT (invoice currency)
PrcRefCur	fixed.14.4	Recycling levy (invoice currency)
RefCode	string	Recycling levy code
RefProCode	string	Product code of the recycling levy
PrcRefCur2	fixed.14.4	Second recycling levy (invoice currency)
RefCode2	string	Code of the second recycling levy
RefProCode2	string	Product code of the second levy
ZPrc	fixed.14.4	Price excl. VAT for the end customer (dropship)
ZPrcTax	fixed.14.4	Price incl. VAT for the end customer
ZPrcRef	fixed.14.4	Recycling levy – dropship
ZPrcRef2	fixed.14.4	Second recycling levy – dropship
RefIs	boolean	Flag that the row is a recycling levy (not a product)

Warranty element (serial numbers / warranties, 0..N)

Attribute	Type	Description
Id	i4	Warranty ID (WarId)
Qty	number	Quantity for the given serial number
SerialNo	string	Serial number (only for products with SN tracking)
StiId	i4	Product ID
StiCode	string	Product stock code
Dur	i4	Warranty length (days; NULL = not specified)

Delivery element (delivery notes, 0..N)

Attribute	Type	Description
Id	i4	Delivery note ID (DelId)
Code	string	Delivery note number
ZCode	string	Delivery note number for dropship (only when present)
OrdId	i4	Order ID
OrdCode	string	Order number
CstId	i4	Delivery address ID; if delivery to the company's registered seat = -ComId
CstName	string	Delivery address name (otherwise the buyer company's name)
CstNameAdd	string	Name supplement
CstNameAdd2	string	Second name supplement
CstStreet	string	Street
CstCity	string	City
CstPostCode	string	Postal code
CstCouName	string	Country

Order element (order + dropshipment end customer, 0..N)

The **Cst*** address = the order's delivery address. The prefix **ZCm*** / **ZCst*** = the **end customer's** data in direct dropshipment (where the goods are delivered on the partner's behalf).

Attribute	Type	Description
Id	i4	Order ID (OrdId)
Code	string	Order number
Code0	string	External order number (from the buyer)

Attribute	Type	Description
Tag	string	Order label
NoteExt	string	External note on the order
C	datetime	Order creation date
OrwName	string	Order status / processing method verify
CstId	i4	Order delivery address ID (-ComId = company seat)
CstName	string	Delivery address name
CstNameAdd	string	Name supplement
CstNameAdd2	string	Second name supplement
CstStreet	string	Street
CstCity	string	City
CstPostCode	string	Postal code
CstCouName	string	Country
ZDirect	—	Direct dropshipment flag (shipped directly to the end customer)
ZIPrn	—	Flag to print the invoice into the shipment verify
ZDPrn	—	Flag to print the delivery note into the shipment verify
ZCmId	i4	End customer ID (dropship)
ZCmRegId	string	End customer company registration number (IČO)
ZCmTaxNum	string	End customer VAT number (DIČ)
ZCmName	string	End customer name
ZCmNameAdd	string	Name supplement
ZCmStreet	string	Street
ZCmCity	string	City
ZCmPostCode	string	Postal code
ZCmTitle	string	Salutation / title
ZCmFName	string	First name
ZCmLName	string	Last name
ZCmTel	string	Phone
ZCmTelMob	string	Mobile
ZCmFax	string	Fax
ZCmEMail	string	E-mail

Attribute	Type	Description
ZCstName	string	Dropship delivery address – name (if it differs from ZCm*)
ZCstNameAdd	string	Name supplement
ZCstNameAdd2	string	Second name supplement
ZCstStreet	string	Street
ZCstCity	string	City
ZCstPostCode	string	Postal code
ZCstCouName	string	Country

StoltemPriceOrd

A price export — the partner's **order (purchase) prices**. It returns the order price, reference (recycling and copyright) levies and the VAT rate, per the export definition.

Covers the pricing part of the **ProductNow** / **AllProductsNow** methods of the ALSO Product API (availability is handled by **StoItemQtyFree**).

Filtering via **GetResultByCode — **code** prefixes**

This export supports **extended search** by code type. A prefix at the start of the **code** parameter determines which field is filtered on (no prefix = main code **StiCode**):

Prefix	Filters by	Example
(none)	Main stock code (StiCode)	code=0320663
{ StiId }	Internal product ID	code={StiId}685699
{ PartNo }	Part number	code={PartNo}GU605CX-QR149
{ PartNo2 }	Second part number	code={PartNo2}90NR0M65-M007X0
{ CodeEAN }	EAN	code={CodeEAN}4711636262347
{ ManName }	Manufacturer name (category of type MAN)	code={ManName}ASUS
{ CodeAll }	Any logged product code (StoItemCode)	code={CodeAll}...

Bulk query: Multiple values separated by a tab (\t) can be placed in **code** — records for all of them are returned. The prefix is given once at the start and applies to the whole batch.

```
##### Example:
<?xml version="1.0" encoding="utf-8"?>
<Result>
  <StoItem Id="685699" Code="ASC00511" PartNo="GU605CX-QR149" PartNo2="90NR0M65-M007X0" EAN="4711636262347" PriceOrd="81144.2200" PriceEU="90900.8300"
```

```
PriceRef="11.3400" PriceRef2="33.0000" TaxRate="21.0000" />
</Result>
```

Attributes of the **StoItem** element

Field	Type	Description
Id	i4	Internal product ID (StiId)
Code	string	Main SWS stock code
Code2	string	Alternative/second code
PartNo	string	Part (catalog) number
PartNo2	string	Second part number
EAN	string	EAN
EAN2	string	Second EAN
PriceOrd	money	Order (purchase) price of the partner — the main price of this export
PriceEU	money	End/recommended price (converted to the partner's currency, if configured) <verify meaning - MSRP?>
PriceRef	money	Recycling levy linked to the product
PriceRefInfo	money	Informational value of the recycling levy
PriceRef2	money	Second recycling levy
PriceRef2Info	money	Informational value of the second levy
TaxRate	fixed.14.4	VAT rate (%); in a cross-border regime recalculated by the destination country (TaxMeCouId)
PriceFullIs	boolean	Flag that the partner is authorized to see the complete set of fixed prices (Price*)
PriceList	money	List (fixed) price — only with special permission , otherwise empty
Price0	money	Fixed price level 0 — only with special permission
Price1	money	Fixed price level 1 — only with special permission
Price2	money	Fixed price level 2 — only with special permission
Price3	money	Fixed price level 3 — only with special permission
Price4	money	Fixed price level 4 — only with special permission
Price5	money	Fixed price level 5 — only with special permission
PriceB2CMin	money	Minimum B2C selling price (MAP), converted to the partner's currency

Notes on prices

- Prices are returned only for products with a **positive order price** (`PriceOrd > 0`).
- Depending on the partner's settings (`WsPriceCur`), prices may be converted to their **currency** at the current exchange rate; in that case `PriceEU` and `PriceB2CMin` are converted to the same currency.
- `PriceFullIs = 1` signals that the `PriceList/Price0-5` fields are available (subject to permission). Without permission these fields are empty even when `PriceFullIs = 0`.

Note for ALSO: A standard partner receives `PriceOrd`, `PriceRef*`, `TaxRate` and `PriceB2CMin`; the `PriceList/Price0-5` set is an add-on tied to special permission.

CpsStiVal

Export of **product parameters (attributes)** — technical specifications in **name × value** format. Per the export definition: "Export parameters of *Stoltems* – Name × Value only (filtered by Code of *Stoltem*).". Each element corresponds to one parameter of one product; a product with N parameters returns N elements. Together with `StoItemBase` it covers the `ProductFullInfo` method of the ALSO Product API (the attribute part).

Usage recommendation: The export is primarily intended for **filtering by product code** (`GetResultByCode`). Via `GetResult` it returns the parameters of all products — this can be a large volume of data.

Attributes of the `Row` element (one product parameter)

Field	Type	Description
<code>Id</code>	i4	ID of the specific parameter value on the product (<code>CpsId</code>) — the row's unique key
<code>StiId</code>	i4	Internal product ID
<code>StiCode</code>	string	Main product stock code
<code>StiCode2</code>	string	Alternative product code
<code>StiPartNo</code>	string	Part number
<code>StiPartNo2</code>	string	Second part number
<code>StiEAN</code>	string	EAN (added per the partner's <code>WsEAN</code> parameter, otherwise empty)
<code>StiEAN2</code>	string	Second EAN
<code>CpaId</code>	i4	Parameter definition ID (shared by all products with the same parameter)
<code>Code</code>	string	Parameter code (<code>CpaCode</code>) — the parameter's machine identifier
<code>Grp</code>	string	Parameter group (<code>CpaGrp</code>) for grouping into sections (only when filled)
<code>Name</code>	string	Parameter name (localized) — e.g. "Diagonal", "Weight"
<code>NameAdd</code>	string	Supplementary parameter description (only when present)
<code>Single</code>	—	Flag that the parameter has only a single value (only when non-null) <code><verify></code>
<code>Ord</code>	i4	Parameter order for listing (only when non-zero)

Field	Type	Description
Value	string	Parameter value — either from an enumeration (CpvValue) or free text (CpsTag)
ValueAdd	string	Supplementary value / note on the value (only when present)
Measure	number	Unit of measure / numeric measure of the value (only when non-zero) <verify - unit vs. numeric value?>
CprOrd	i4	Order of the value within the parameter's enumeration (only when non-zero)

AttSti

Export of **product attachments** — images, datasheets, documentation and other files linked to a product. Each element = one attachment; a product with N attachments returns N elements. Covers the **ProductImages** method of the ALSO Product API (and, in general, non-media attachments as well, if they are logged on the product).

Supports the same set of prefixes as **StoItemPriceOrd** (see [Request format](#)): no prefix = **StiCode**, plus **{StiId}**, **{PartNo}**, **{PartNo2}**, **{CodeEAN}**, **{ManName}**, **{CodeAll}**. Multiple values can be separated by a tab (**\t**).

```
GetResultByCode?resultType=AttSti&code={ManName}DATAWAY
```

Building the attachment URL

The **Url** field is returned **ready to use**, but it is produced in two ways depending on the attachment type:

- **External attachment** (**AttUrl** contains **://**) → **Url** = the external link directly.
- **Internal attachment** (a file in I6) → **Url** = **UrlBaseImgGalery** + **Id** (i.e. **.../img.asp?attid=<Id>**). The client can therefore use **Url** directly without assembling it.

Attributes of the AttSti element (one attachment)

Field	Type	Description
Id	i4	Attachment ID (AttId); also used to build Url for internal attachments
StiId	i4	Internal product ID
StiCode	string	Main product stock code
StiCode2	string	Alternative product code
StiPartNo	string	Part number
StiPartNo2	string	Second part number
StiEAN	string	EAN (added per the partner's WsEAN parameter, otherwise empty)

Field	Type	Description
StiEAN2	string	Second EAN
Name	string	Attachment name (only when filled) — e.g. "Thumbnail", "Enlargement", caption
Tag	string	Attachment label/type (only when present) — distinguishes the kind of attachment <i><verify values></i>
File	string	Attachment file name (without path; the directory is stripped from AttUrl)
Url	string	Ready-to-use attachment URL — external link, or internal <code>.../img.asp?attid=<Id></code>
Size	i8	Attachment size in bytes (may be empty for external ones)
Sort	i2	Attachment order for sorting (only when non-zero)

CpsSti

Export of **product parameters including their definitions** — the normalized (relational) variant of `CpsStiVal`. Per the export definition: *"Export parameters of Stoltems include parameter's definition."* Unlike `CpsStiVal`, which repeats the name and value on every row, `CpsSti` returns the **parameter definitions and value enumeration separately** and the product assignments only reference them by ID. Suitable when the client wants to build its own parametric database (download the definitions once, products reference them). Together with `StoItemBase` it covers the attribute part of the `ProductFullInfo` method of the ALSO Product API.

⚠ CpsStiVal vs. CpsSti: If a plain "product → parameter → value" list is enough for you, use `CpsStiVal` (simpler, flat). Use `CpsSti` only when you also need the **definition metadata** (types, enumerations, language variants, category links).

Output structure

The output is **hierarchical (FOR XML EXPLICIT)**. Under the `Result` root there are five separate collections, each with `Row` elements distinguished by level:

```

Result
├── ConPar      → Row (parameter definitions)      [level 7]
├── ConParValue → Row (value enumeration)          [level 8]
├── ConParRange → Row (allowed values of a parameter) [level 9]
├── ConParSet   → Row (value assignments to products) [level 10]
└── ConParStr   → Row (parameter-to-category links)  [level 11]
```

Linking on the client side: `ConParSet.CpaId → ConPar.Id`, `ConParSet.CpvId → ConParValue.Id`; `ConParRange` restricts which values (`CpvId`) belong to which parameter (`CpaId`); `ConParStr` maps a parameter to a presentation-tree node (see `SPresentTree`).

`ConPar → Row` — **parameter definition**

Field	Type	Description
Id	i4	Parameter ID (CpaId)
Type	ui1	Parameter type (CpaType ; types 0 and 2 are returned) <verify values>
Single	—	Flag that the parameter has a single value <verify>
Code	string	Machine code of the parameter
Grp	string	Parameter group (for grouping into sections)
Ord	i4	Parameter order for sorting
Name	string	Parameter name (localized)
AddName	string	Supplementary name (note: in the Row!7!AddName attribute = CpaNameAdd)
NameE	string	English name
NameAddE	string	Supplementary English name
Note	string	Note on the parameter

ConParValue → **Row** — enumeration value

Field	Type	Description
Id	i4	Value ID (CpvId)
Measure	number	Unit of measure / value measure <verify>
Code	string	Machine code of the value
Value	string	Value (localized)
ValueAdd	string	Value supplement
ValueE	string	Value in English
ValueAddE	string	Value supplement in English

ConParRange → **Row** — allowed parameter value

Field	Type	Description
Id	i4	Link ID (CprId)
CpaId	i4	Parameter ID (ConPar.Id)
CpvId	i4	Allowed value ID (ConParValue.Id)

ConParSet → **Row** — value assignment to a product

Field	Type	Description
Id	i4	Assignment ID (CpsId)
StiId	i4	Product ID
CpaId	i4	Parameter ID (ConPar.Id)
CpvId	i4	Enumeration value ID (ConParValue.Id); empty = the value is free text
StiCode	string	Product stock code
Value	string	Value — from the enumeration (CpvValue) or free text (CpsTag)
Measure	number	Numeric value measure (only when non-zero) <verify>

ConParStr → **Row** — **parameter-to-category link**

Field	Type	Description
Id	i4	Link ID (CosId)
StrId	i4	Presentation-tree node ID (SPresentTree.Id)
CpaId	i4	Parameter ID (ConPar.Id)
StrSort	string	Node sort key (3 chars/level) — determines the category where the parameter is used

Notes

- Only parameters **published** for the web are returned (**CpaPublishWS/CpaPublish = 1**, **CpaHide = 0**) with a non-empty value; parameter types **CpaType IN (0, 2)**.
- The product set (**ConParSet**) respects the partner's **row permissions** — a different partner may see different products.
- ConParStr** (the category link) returns only nodes from **visible** branches of the presentation tree.