

Database Systems

Instructor: Bilal Khalid Dar



Agenda

- Normalization

Normalization Agenda

- We first discuss informal guidelines for good relational design
- Then we discuss formal concepts of functional dependencies and normal forms
 - - 1NF (First Normal Form)
 - - 2NF (Second Normal Form)
 - - 3NF (Third Normal Form)
 - - BCNF (Boyce-Codd Normal Form)

A simplified COMPANY relational database schema

EMPLOYEE					F.K.
Ename	<u>Ssn</u>	Bdate	Address	Dnumber	

P.K.

DEPARTMENT			F.K.
Dname	<u>Dnumber</u>	Dmgr_ssn	

P.K.

DEPT_LOCATIONS	
----------------	--

F.K.

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

P.K.

PROJECT				F.K.
Pname	<u>Pnumber</u>	Plocation	Dnum	

P.K.

WORKS_ON		
----------	--	--

F.K.

F.K.

<u>Ssn</u>	<u>Pnumber</u>	Hours
------------	----------------	-------

P.K.

Guidelines for good relational design

Semantics of the Relational Attributes must be clear

- GUIDELINE 1: Informally, each tuple in a relation should represent one entity or relationship instance. (Applies to individual relations and their attributes).
 - Attributes of different entities (EMPLOYEEs, DEPARTMENTs, PROJECTs) should not be mixed in the same relation
 - Only foreign keys should be used to refer to other entities
 - Entity and relationship attributes should be kept apart as much as possible.
- Bottom Line: *Design a schema that can be explained easily relation by relation. The semantics of attributes should be easy to interpret.*

Redundant Information in Tuples and Update Anomalies

- Information is stored redundantly
 - Wastes storage
 - Causes problems with update anomalies
 - Insertion anomalies
 - Deletion anomalies
 - Modification anomalies

EXAMPLE OF AN UPDATE ANOMALY


- Consider the relation:
 - EMP_PROJ(Emp#, Proj#, Ename, Pname, No_hours)
- Update Anomaly:
 - Changing the name of project number P1 from “Billing” to “Customer-Accounting” may cause this update to be made for all 100 employees working on project P1.

Two relation schemas suffering from update anomalies

Figure 14.3
Two relation schemas suffering from update anomalies. (a) EMP_DEPT and (b) EMP_PROJ.


(a)

EMP_DEPT



(b)

EMP_PROJ



Sample states for EMP_DEPT and EMP_PROJ

Redundancy

EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

Sample states for EMP_DEPT and EMP_PROJ

EMP_PROJ			Redundancy	Redundancy	
<u>Ssn</u>	<u>Pnumber</u>	Hours	Ename	Pname	Plocation
123456789	1	32.5	Smith, John B.	ProductX	Bellaire
123456789	2	7.5	Smith, John B.	ProductY	Sugarland
666884444	3	40.0	Narayan, Ramesh K.	ProductZ	Houston
453453453	1	20.0	English, Joyce A.	ProductX	Bellaire
453453453	2	20.0	English, Joyce A.	ProductY	Sugarland
333445555	2	10.0	Wong, Franklin T.	ProductY	Sugarland
333445555	3	10.0	Wong, Franklin T.	ProductZ	Houston
333445555	10	10.0	Wong, Franklin T.	Computerization	Stafford
333445555	20	10.0	Wong, Franklin T.	Reorganization	Houston
999887777	30	30.0	Zelaya, Alicia J.	Newbenefits	Stafford
999887777	10	10.0	Zelaya, Alicia J.	Computerization	Stafford
987987987	10	35.0	Jabbar, Ahmad V.	Computerization	Stafford
987987987	30	5.0	Jabbar, Ahmad V.	Newbenefits	Stafford
987654321	30	20.0	Wallace, Jennifer S.	Newbenefits	Stafford
987654321	20	15.0	Wallace, Jennifer S.	Reorganization	Houston
888665555	20	Null	Borg, James E.	Reorganization	Houston

EXAMPLE OF AN INSERT ANOMALY

- Consider the relation:
 - EMP_PROJ(Emp#, Proj#, Ename, Pname, No_hours)
- Insert Anomaly:
 - Cannot insert a project unless an employee is assigned to it.
- Conversely
 - Cannot insert an employee unless an he/she is assigned to a project.

EXAMPLE OF A DELETE ANOMALY

- Consider the relation:
 - EMP_PROJ(Emp#, Proj#, Ename, Pname, No_hours)
- Delete Anomaly:
 - When a project is deleted, it will result in deleting all the employees who work on that project.
 - Alternately, if an employee is the sole employee on a project, deleting that employee would result in deleting the corresponding project.

Guideline for Redundant Information in Tuples and Update Anomalies

- GUIDELINE 2:
 - Design a schema that does not suffer from the insertion, deletion and update anomalies.
 - If there are any anomalies present, then note them so that applications can be made to take them into account.

Null Values in Tuples

- GUIDELINE 3:
 - Relations should be designed such that their tuples will have as few NULL values as possible
 - Attributes that are NULL frequently could be placed in separate relations (with the primary key)
- Reasons for nulls:
 - Attribute not applicable or invalid
 - Attribute value unknown (may exist)
 - Value known to exist, but unavailable

Generation of Spurious Tuples – avoid at any cost

- Bad designs for a relational database may result in erroneous results for certain JOIN operations
- The "lossless join" property is used to guarantee meaningful results for join operations
- GUIDELINE 4:
 - The relations should be designed to satisfy the lossless join condition.
 - No spurious tuples should be generated by doing a natural-join of any relations.

- **Before Normalization**

- Begin with a list of all of the fields that must appear in the database. Think of this as one big table.
 - Do not include computed fields
 - One place to begin getting this information is from a printed document used by the system.
 - Additional attributes besides those for the entities described on the document can be added to the database.

Some Important Concepts

Functional Dependencies

Functional Dependencies

We say an attribute, B, has a *functional dependency* on another attribute, A, if for any two records, which have the same value for A, then the values for B in these two records must be the same. We illustrate this as:

$$A \rightarrow B$$

Example: Suppose we keep track of employee email addresses, and we only track one email address for each employee. Suppose each employee is identified by their unique employee number. We say there is a functional dependency of email address on employee number:

$$\text{employee number} \rightarrow \text{email address}$$

Functional Dependencies

<u>EmpNum</u>	EmpEmail	EmpFname	EmpLname
123	jdoe@abc.com	John	Doe
456	psmith@abc.com	Peter	Smith
555	alee1@abc.com	Alan	Lee
633	pdoe@abc.com	Peter	Doe
787	alee2@abc.com	Alan	Lee

If EmpNum is the PK then the FDs:

EmpNum \rightarrow EmpEmail

EmpNum \rightarrow EmpFname

EmpNum \rightarrow EmpLname

must exist.



Functional Dependencies

$\text{EmpNum} \rightarrow \text{EmpEmail}$

$\text{EmpNum} \rightarrow \text{EmpFname}$

$\text{EmpNum} \rightarrow \text{EmpLname}$

*3 different ways
you might see FDs
depicted*



Determinant

Functional Dependency

$\text{EmpNum} \rightarrow \text{EmpEmail}$

Attribute on the LHS is known as the *determinant*

- EmpNum is a determinant of EmpEmail

Transitive dependency

Transitive dependency

Consider attributes A, B, and C, and where

$$A \rightarrow B \text{ and } B \rightarrow C.$$


Functional dependencies are transitive, which means that we also have the functional dependency

$$A \rightarrow C$$



We say that C is transitively dependent on A through B.

Transitive dependency

$\text{EmpNum} \rightarrow \text{DeptNum}$



$\text{DeptNum} \rightarrow \text{DeptName}$



DeptName is *transitively dependent* on EmpNum via DeptNum

$\text{EmpNum} \rightarrow \text{DeptName}$

Normalization

Definition

- This is the process which allows you to winnow out redundant data within your database.
 - The results of a well executed normalization process are the same as those of a well planned E-R model
- This involves restructuring the tables to successively meeting higher forms of Normalization.
- A properly normalized database should have the following characteristics
 - Scalar values in each fields
 - Absence of redundancy.
 - Minimal use of null values.
 - Minimal loss of information.

(Note: Winnow(Webster): To get rid of / eliminate inferior material

Normalization


Process

- Eliminate Repeating Groups
 - Make a separate table for each set of related attributes and give each table a primary key.
- Eliminate Redundant Data
 - If an attribute depends on only part of a multivalued key, remove it to a separate table.
- Eliminate Columns not dependent on key
 - If attributes do not contribute to a description of the key, remove them to a separate table.
- Isolate Independent multiple relationships
 - No table may contain two or more 1:n or n:m relationships that are not directly related.
- Isolate Semantically Related Multiple Relationships
 - There may be practical constraints on information that justify separating logically related many-to-many relationships

Normalization

Levels


- Levels of normalization based on the amount of redundancy in the database.
- Relational theory defines a number of structure conditions called Normal Forms that assure that certain data anomalies do not occur in a database.
- Various levels of normalization are:
 - First Normal Form (1NF)
 - Second Normal Form (2NF)
 - Third Normal Form (3NF)
 - Boyce-Codd Normal Form (BCNF)
 - Fourth Normal Form (4NF)
 - Fifth Normal Form (5NF)
 - Domain Key Normal Form (DKNF)



Most databases should be 3NF or BCNF in order to avoid the database anomalies.

Normalization

Levels



1NF	<i>Keys; No repeating groups or multi-valued</i>
2NF	<i>No partial dependencies</i>
3NF	<i>No transitive dependencies</i>
BCNF	<i>Determinants are candidate keys</i>
4NF	<i>No multivalued dependencies</i>
5NF	<i>No multivalued dependencies</i>
4NF	<i>No multivalued dependencies</i>

Each higher level is a subset of the lower level

Normalization

First Normal Form (1NF)

A table is considered to be in 1NF if all the fields contain only scalar values (as opposed to list of values).

Example (Not 1NF)

ISBN	Title	AuName	AuPhone	PubName	PubPhone	Price
0-321-32132-1	Balloon	Sleepy, Snoopy, Grumpy	321-321-1111, 232-234-1234, 665-235-6532	Small House	714-000-0000	\$34.00
0-55-123456-9	Main Street	Jones, Smith	123-333-3333, 654-223-3455	Small House	714-000-0000	\$22.95
0-123-45678-0	Ulysses	Joyce	666-666-6666	Alpha Press	999-999-9999	\$34.00
1-22-233700-0	Visual Basic	Roman	444-444-4444	Big House	123-456-7890	\$25.00

Author and AuPhone columns are not scalar

Normalization

1NF: Decomposition

1. Place all items appearing in the repeating group in a new table
2. Designate a primary key for each new table produced.
3. Create a relationship between the two tables
 - For 1:N relation duplicate the P.K. from 1 side to many side
 - For M:N relation create a new table with P.K. from both tables

Example (1NF)

ISBN	Title	PubName	PubPhone	Price
0-321-32132-1	Balloon	Small House	714-000-0000	\$34.00
0-55-123456-9	Main Street	Small House	714-000-0000	\$22.95
0-123-45678-0	Ulysses	Alpha Press	999-999-9999	\$34.00
1-22-233700-0	Visual Basic	Big House	123-456-7890	\$25.00

ISBN	AuName	AuPhone
0-321-32132-1	Sleepy	321-321-1111
0-321-32132-1	Snoopy	232-234-1234
0-321-32132-1	Grumpy	665-235-6532
0-55-123456-9	Jones	123-333-3333
0-55-123456-9	Smith	654-223-3455
0-123-45678-0	Joyce	666-666-6666
1-22-233700-0	Roman	444-444-4444

Normalization

Functional Dependencies

1. If one set of attributes in a table determines another set of attributes in the table, then the second set of attributes is said to be functionally dependent on the first set of attributes.

Example 1

ISBN	Title	Price
0-321-32132-1	Balloon	\$34.00
0-55-123456-9	Main Street	\$22.95
0-123-45678-0	Ulysses	\$34.00
1-22-233700-0	Visual Basic	\$25.00

Table Scheme: {ISBN, Title, Price}

Functional Dependencies: {ISBN} → {Title}

{ISBN} → {Price}

Normalization

Functional Dependencies

Example 2

PubID	PubName	PubPhone
1	Big House	999-999-9999
2	Small House	123-456-7890
3	Alpha Press	111-111-1111

Table Scheme: {PubID, PubName, PubPhone}

Functional Dependencies: {PubId} \rightarrow {PubPhone}
{PubId} \rightarrow {PubName}

Example 3

AuID	AuName	AuPhone
1	Sleepy	321-321-1111
2	Snoopy	232-234-1234
3	Grumpy	665-235-6532
4	Jones	123-333-3333
5	Smith	654-223-3455
6	Joyce	666-666-6666
7	Roman	444-444-4444

Table Scheme: {AuID, AuName, AuPhone}

Functional Dependencies: {AuId} \rightarrow {AuPhone}
{AuId} \rightarrow {AuName}

1NF Repeat

First Normal Form

First Normal Form

We say a relation is in **1NF** if all values stored in the relation are single-valued and atomic.

1NF places restrictions on the structure of relations. Values must be simple.

First Normal Form

The following is **not** in 1NF

<u>EmpNum</u>	EmpPhone	EmpDegrees
123	233-9876	
333	233-1231	BA, BSc, PhD
679	233-1231	BSc, MSc

EmpDegrees is a multi-valued field:

employee 679 has two degrees: *BSc* and *MSc*

employee 333 has three degrees: *BA*, *BSc*, *PhD*

First Normal Form

<u>EmpNum</u>	EmpPhone	EmpDegrees
123	233-9876	
333	233-1231	BA, BSc, PhD
679	233-1231	BSc, MSc

To obtain 1NF relations we must, without loss of information, replace the above with two relations - see next slide

First Normal Form

Employee

EmpNum	EmpPhone
123	233-9876
333	233-1231
679	233-1231

EmployeeDegree

EmpNum	EmpDegree
333	BA
333	BSc
333	PhD
679	BSc
679	MSc



Thank
You

A blue paper cutout of the words "Thank You" in a stylized, rounded font. The text is white with a blue outline. The cutout is hanging from a thin brown string that is tied in a loop at the top. The background is white.