

RECURRENT NEURAL NETWORK

IA FRAMEWORKS

TABLE OF CONTENTS

INTRODUCTION

RNN


MEMORY CELL - GRU/LSTM

OTHER PROPERTIES

TP

GOOGLE CLOUD PLATFORM

ML Python Libraries



Python Environment



Viz' Python Libraries



Framework & Tool



INTRODUCTION


MOTIVATIONS

PROBLEM: Various text problem required to handle sequence data.

Type	X	Y
Text Generation	empty, scalar Ø,1,2	text sequence <i>this is a text generated</i>
Sentiment Classification	text sequence <i>It wasn't that good</i>	empty, scalar 2(15)
Translation	text sequence <i>How are you?</i>	text sequence <i>Comment tu vas?</i>
Identity Recognition	text sequence <i>Harry potter is a wizard</i>	boolean sequence [1,1,0,0,0]

MOTIVATIONS


Machine learning and Deep learning algorithms are **not adapted** !



Dictionary size: $V = 12$


MOTIVATIONS

- **Size of sequences** varies from one example to an other.
- Information between words like their position are **not used**.



RNN

RNN - NOTATION - IDENTITY RECOGNITION




Activation Function

$$\begin{aligned}
 a_t &= g_a(a_{t-1}W_{aa} + x_tW_{xa} + ba) \\
 &= g_a([a_{t-1}, x_t] \cdot [W_{aa} + W_{xa}]^T + ba) \\
 &= g_a([a_{t-1}, x_t]W_y + b_y) \\
 \hat{y} &= g_y(a_t \cdot W_{xa} + by)
 \end{aligned}$$

- $x_t, (1 \times V)$: OHE representation.
- V : Dictionary's size.
- $y_t(1 \times 1)$: 0 or 1.
- $a_t : 1 \times H$.
- H : Number of neurons.
- N : Number of timestep (Not layer!).
- g_a : Activation Function (**tanh/Relu**).
- g_y Activation Function (**sigmoid**).
- $W_{aa}, (H \times H, \forall t \in [1, \dots, n])$
- $W_{xa}, (V \times H, \forall t \in [1, \dots, n])$
- $W_y, (H \times 1, \forall t \in [1, \dots, n])$
- $W_a, (H + V \times H, \forall t \in [1, \dots, n])$

RNN - NOTATION - TEXT GENERATION




Activation Function

$$a_t = g_a([a_{t-1}, x_t] \cdot W_a + b_a)$$

$$\hat{y} = g_y(a_t \cdot W_y + b_y)$$


- $x_t, (1 \times V)$: OHE representation.
- V : Dictionary's size.
- $y_t, \hat{y}(1 \times V)$: OHE representation.
- $a_t : 1 \times H$.
- H : Number of neurons.
- N : Number of timestep (Not layer!).
- g_a : Activation Function (**tanh/Relu**).
- g_y Activation Function (**Softmax**).
- $W_y, (H \times V, \forall t \in [1, \dots, n])$
- $W_a, (H + V \times H, \forall t \in [1, \dots, n])$

RNN UNIT




- $a_t = \tanh([a_{t-1}, x_t]W_a + b_a)$.
- $\hat{y}_t = \text{softmax}(a_tW_y + b_y)$.


DIFFERENT TYPE OF RNN




MANY TO ONE
Text classification



MANY TO MANY
Identity recognition



ONE TO MANY
Text generation




MANY TO MANY
Automatic translation

DIFFERENT TYPE OF RNN

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1)))  
model.add(kl.Dense(1))  
model.summary()
```


Layer (type)	Output Shape	Param #
simple_rnn_2 (SimpleRNN)	(None, 10)	120
dense_1 (Dense)	(None, 1)	11
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		

MANY TO ONE
Text classification




ONE TO MANY
Text generation

MANY TO MANY
Identity recognition



MANY TO MANY
Automatic translation




DIFFERENT TYPE OF RNN

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1)))  
model.add(kl.Dense(1))  
model.summary()
```

Layer (type)	Output Shape	Param #
simple_rnn_2 (SimpleRNN)	(None, 10)	120
dense_1 (Dense)	(None, 1)	11
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		

MANY TO ONE
Text classification




ONE TO MANY
Text generation

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1),  
return_sequences=True))  
model.add(kl.TimeDistributed(kl.Dense(1)))  
model.summary()
```

Layer (type)	Output Shape	Param #
simple_rnn_4 (SimpleRNN)	(None, 3, 10)	120
time_distributed (TimeDistri	(None, 3, 1)	11
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		

MANY TO MANY
Identity recognition



MANY TO MANY
Automatic translation

DIFFERENT TYPE OF RNN

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1)))  
model.add(kl.Dense(1))  
model.summary()
```

Layer (type)	Output Shape	Param #
=====	=====	=====
simple_rnn_2 (SimpleRNN)	(None, 10)	120
dense_1 (Dense)	(None, 1)	11
=====	=====	=====
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		

MANY TO ONE
Text classification

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1),  
return_sequences=True))  
model.add(kl.TimeDistributed(kl.Dense(1)))  
model.summary()
```

Layer (type)	Output Shape	Param #
=====	=====	=====
simple_rnn_4 (SimpleRNN)	(None, 3, 10)	120
time_distributed (TimeDistri	(None, 3, 1)	11
=====	=====	=====
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		

MANY TO MANY
Identity recognition

```
model = km.Sequential()  
model.add(kl.SimpleRNN(units=10 ,activation="relu", input_shape=(3, 1),  
return_sequences=True))  
model.add(kl.TimeDistributed(kl.Dense(1)))  
model.summary()
```

Layer (type)	Output Shape	Param #
=====	=====	=====
simple_rnn_4 (SimpleRNN)	(None, 3, 10)	120
time_distributed (TimeDistri	(None, 3, 1)	11
=====	=====	=====
Total params: 131		
Trainable params: 131		
Non-trainable params: 0		


ONE TO MANY
Text generation

MANY TO MANY
Automatic translation

MEMORY CELL


VANISHING GRADIENT

PROBLEM : Long time dependency. *The cat, which already ate ..., was full.*




VANISHING GRADIENT

PROBLEM : Long time dependency. *The **cats**, which already ate ..., **were** full.*



SOLUTION : Memory cell.


GRU UNIT - CHO ET AL. [2014], CHUNG ET AL. [2014]



- c_t : memory cell.
- $c_t = a_t$.
- $\Gamma_r = \sigma([c_{t-1}, x_t]W_r + b_r)$.
- $\tilde{c}_t = \tanh([\Gamma_r * c_{t-1}, x_t]W_c + b_c)$.
- $\Gamma_u = \sigma([c_{t-1}, x_t]W_u + b_u)$.
- $c_t = \Gamma_u * \tilde{c}_t + (1 - \Gamma_u) * c_{t-1}$.
- $\hat{y}_t = \text{softmax}(c_t W_y + b_y)$.

the	cats	which	already	ate	...	were	full
$c_1^i = 0$	$c_2^i = 1$	$c_1^i = 1$	$c_1^i = 1$	$c_1^i = 1$...	$c_1^i = 0$	$c_1^i = 0$
$\Gamma_u^i = 0$	$\Gamma_u^i = 1$	$\Gamma_u^i = 0$	$\Gamma_u^i = 0$	$\Gamma_u^i = 0$...	$\Gamma_u^i = 1$	$\Gamma_u^i = 0$

LSTM UNIT - HOCHREITER AND SCHMIDHUBER [1997]




- c_t : memory cell.
- $c_t \neq a_t$.
- $\tilde{c} = \tanh([a_{t-1}, x_t]W_a + b_a)$.
- $\Gamma_u = \sigma([a_{t-1}, x_t]W_u + b_u)$.
- $\Gamma_f = \sigma([a_{t-1}, x_t]W_u + b_f)$.
- $c_t = \Gamma_u * \tilde{c}_t + \Gamma_f * c_{t-1}$.
- $\Gamma_o = \sigma([a_{t-1}, x_t]W_r + b_o)$.
- $a_t = \Gamma_o * \tanh(c_t)$.
- $\hat{y}_t = \text{softmax}(a_t W_y + b_y)$.

OTHER PROPERTIES

BIDIRECTIONAL RNN (BRNN)

PROBLEM : Long time dependency.

EXAMPLE (Identity recognition): *Holland is a European's country.*
Holland is a European's president.




$$\vec{a}_t = \tanh([\vec{a}_{t-1}, x_t]W_{\vec{a}} + b_{\vec{a}})$$

$$\overleftarrow{a}_t = \tanh([\overleftarrow{a}_{t-1}, x_t]W_{\overleftarrow{a}} + b_{\overleftarrow{a}})$$

$$\hat{y} = \text{softmax}([\vec{a}_t, \overleftarrow{a}_t]W_y + b_y)$$

DEEP RNN



$$a_{L_1,t} = \tanh([a_{L_1,t-1}, x_t]W_{L_1,a} + b_{L_1,a})$$

$$a_{L_i,t} = \tanh([a_{L_i,t-1}, a_{L_{i-1},t}]W_{L_i,a} + b_{L_i,a}), \forall i > 1$$

$$\hat{y} = \text{softmax}(a_{L_3,t}W_y + b_y)$$

DEEP BIDIRECTIONAL RNN WITH TENSORFLOW

```
model = km.Sequential()  
model.add(kl.LSTM(units=10 ,activation="relu", input_shape=(3, 1), return_sequences=True))  
model.add(kl.Bidirectional(kl.GRU(units=10 ,activation="relu", return_sequences=True)))  
model.add(kl.TimeDistributed(kl.Dense(1)))  
model.summary()
```

Layer (type)	Output Shape	Param #
=====		
lstm (LSTM)	(None, 3, 10)	480

bidirectional (Bidirectional	(None, 3, 20)	1320

time_distributed_2 (TimeDist	(None, 3, 1)	21
=====		
Total params: 1,821		
Trainable params: 1,821		
Non-trainable params: 0		

TP


EXAMPLE: TEXT CLASSIFICATION

$x =$ Pour apple iPhone 4: coque bumper silicone blanc - cet étui en silicone rigide..


$x = [x_1, x_2, x_3, x_4, \dots, x_n]$

$x = [start, OHE(P), OHE(o), OHE(u), \dots, End]$

$vocabulary = [a, \dots, z, A, \dots, Z, 0, \dots, 9, ?, ;, \dots, /, +]$



MANY TO ONE
Learning



MANY TO ONE
Prediction


EXAMPLE: TEXT GENERATION

$x =$ Pour apple iPhone 4: coque bumper silicone blanc - cet étui en silicone rigide..


$x = [x_1, x_2, x_3, x_4, \dots, x_n]$

$x = [start, OHE(P), OHE(o), OHE(u), \dots, End]$

$vocabulary = [a, \dots, z, A, \dots, Z, 0, \dots, 9, ?, ;, \dots, /, +]$



MANY TO MANY
Learning



ONE TO MANY
Generation