

Screenshot 1:

This screenshot shows the main page of a GitHub repository named 'git_test' owned by 'MauSantiago05'. The repository is public and has 1 branch (main) and 0 tags. The commit history shows two commits: 'Initial commit' (3 weeks ago) and 'commit test' (3 weeks ago). The README file is visible, containing the text 'git_test'.

Repository: **git_test** (Public)

Branches: **main** (1 Branch) | Tags: 0 Tags

Search: | **Add file** | **<> Code**

Commit history:

Commit	Author	Message	Time
c399aa4	MauSantiago05	commit test	3 weeks ago
Initial commit	MauSantiago05	Initial commit	3 weeks ago

Files:

- [README.md](#) (Initial commit, 3 weeks ago)
- [hello_world.txt](#) (commit test, 3 weeks ago)

README

git_test

Screenshot 2:

This screenshot shows the 'hello_world.txt' file page in the 'git_test' repository. The file is located at 'git_test/blob/main/hello_world.txt'. The commit history shows two commits: 'Initial commit' (3 weeks ago) and 'commit test' (3 weeks ago). The file content is 'Hello World!'.

Repository: **git_test** (Public)

Branches: **main** (1 Branch) | Tags: 0 Tags

Search: | **Add file** | **<> Code**

Commit history:

Commit	Author	Message	Time
c399aa4	MauSantiago05	commit test	3 weeks ago
Initial commit	MauSantiago05	Initial commit	3 weeks ago

Files:

- [README.md](#) (Initial commit, 3 weeks ago)
- [hello_world.txt](#) (commit test, 3 weeks ago)

git_test / hello_world.txt

Commit: **commit test** (c399aa4)

Code | Blame | 1 lines (1 loc) · 12 Bytes | [Code 55% faster with GitHub Copilot](#)

```
1 Hello World!
```