Search models, datasets, users...

tachiwin / **tokenizer_64k** Like 0 Follow Tachiwin 4

tokenizers tokenizer multilingual byte-level-bpe indigenous-languages tachiwin

Copy to bucket NEW

Model card Files xet Community

Downloads last month

-

Downloads are not tracked for this model. How to track

Inference Providers NEW

This model isn't deployed by any Inference Provider. Ask for provider support

Model tree for `tachiwin/tokenizer_64k`

Finetunes 1 model

Tachiwin multilingual tokenizer

A multilingual ByteLevel-BPE tokenizer trained with Hugging Face Tokenizers.

Corpus weighting

Component	Target
Modern + old exotic-language data	70%
English	10%

Component	Target
Spanish	10%
Code	10%

The complete available exotic-language corpus is used as the 70% anchor. Its existing modern/old composition is preserved.

Tokenizer

- Model: BPE, trained via `Tokenizer.train_from_iterator` over a streaming line generator (constant memory regardless of corpus size)
- Vocabulary target: 64,000
- Initial alphabet: complete ByteLevel alphabet
- ByteLevel GPT-2 regex: disabled
- Unicode normalizer: none
- Special tokens: 282
- Human-language tags: 248

Corpus size

Total materialized corpus: 457,300,912 bytes (0.426 GiB)

Evaluation

The tokenizer was evaluated against the Tachiwin language catalogue. Languages without text samples are skipped. For each language, all available samples are concatenated ONLY within that language for aggregate fertility statistics. Metrics: characters/token, tokens/character, UTF-8 bytes/token, tokens/UTF-8 byte, exact round-trip preservation.

Important training note

The Hugging Face BPE trainer does not expose an internal resumable merge-state checkpoint. The recipe therefore treats the completed `tokenizer.json` as the training checkpoint:

- corpus preparation is resumable (both the exotic streaming pass and the capped external-corpus downloads reuse existing shards);
- recipe/statistics/checksums are stored in `recipe/`;
- if `tokenizer.json` already exists, subsequent runs skip BPE training;
- an interrupted BPE computation itself must be restarted.

Repository evaluation artifacts

- evaluation/catalogue.json
- evaluation/language_fertility.csv
- evaluation/language_fertility.json
- evaluation/evaluation_summary.json

System theme

Company

TOS

Privacy

About

Careers

Website

Models

Datasets

Spaces

Pricing

Docs

