

Module	Description	Example	Script
collections	defaultdict, creating for lists	<code>by_zone = defaultdict(list)</code>	<code>g10/demo.py</code>
collections	defaultdict, importing	<code>from collections import defaultdict</code>	<code>g10/demo.py</code>
core	dictionary, adding a new entry	<code>co['po'] = 'CO'</code>	<code>g05/demo.py</code>
core	dictionary, checking for existing key	<code>if fips in name_by_fips:</code>	<code>g09/demo.py</code>
core	dictionary, creating	<code>co = {'name':'Colorado', 'capital':'Denver'}</code>	<code>g05/demo.py</code>
core	dictionary, deleting an entry	<code>del name_by_fips["00"]</code>	<code>g09/demo.py</code>
core	dictionary, iterating over keys	<code>for fips in name_by_fips.keys():</code>	<code>g09/demo.py</code>
core	dictionary, iterating over values	<code>for rec in name_by_fips.values():</code>	<code>g09/demo.py</code>
core	dictionary, looking up a value	<code>name = ny['name']</code>	<code>g05/demo.py</code>
core	dictionary, making a list of	<code>list1 = [co,ny]</code>	<code>g05/demo.py</code>
core	dictionary, obtaining a list of keys	<code>names = super_dict.keys()</code>	<code>g05/demo.py</code>
core	dictionary, sorting keys	<code>for tz in sorted(by_zone.keys()):</code>	<code>g10/demo.py</code>
core	f-string, using a formatting string	<code>print(f"PV of {payment} with T={year} and r={r} is \${p. . .</code>	<code>g07/demo.py</code>
core	file, closing	<code>fh.close()</code>	<code>g02/demo.py</code>
core	file, opening for reading	<code>fh = open('states.csv')</code>	<code>g05/demo.py</code>
core	file, opening for writing	<code>fh = open(filename,"w")</code>	<code>g02/demo.py</code>
core	file, output using print	<code>print("It was written during",year,file=fh)</code>	<code>g02/demo.py</code>
core	file, output using write	<code>fh.write("Where was this file was written?\n")</code>	<code>g02/demo.py</code>
core	file, print without adding spaces	<code>print('\nOuter:\n', join_o['_merge'].value_counts(), s. . .</code>	<code>g15/demo.py</code>
core	file, reading one line at a time	<code>for line in fh:</code>	<code>g05/demo.py</code>
core	for, looping through a list	<code>for n in a_list:</code>	<code>g04/demo.py</code>
core	function, calling	<code>d1_ssqr = sumsq(d1)</code>	<code>g06/demo.py</code>
core	function, calling with an optional argument	<code>sample_function(100, 10, r=0.07)</code>	<code>g07/demo.py</code>
core	function, defining	<code>def sumsq(values):</code>	<code>g06/demo.py</code>
core	function, defining with optional argument	<code>def sample_function(payment,year,r=0.05):</code>	<code>g07/demo.py</code>
core	function, returning a result	<code>return values</code>	<code>g06/demo.py</code>
core	if statement, testing for equality	<code>if fips == "36":</code>	<code>g09/demo.py</code>
core	list, appending an element	<code>a_list.append("four")</code>	<code>g03/demo.py</code>
core	list, create via comprehension	<code>cubes = [n**3 for n in a_list]</code>	<code>g04/demo.py</code>
core	list, creating	<code>a_list = ["zero","one","two","three"]</code>	<code>g03/demo.py</code>

Module	Description	Example	Script
core	list, determining length	<code>n = len(b_list)</code>	g03/demo.py
core	list, extending with another list	<code>a_list.extend(a_more)</code>	g03/demo.py
core	list, generating a sequence	<code>b_list = range(1,6)</code>	g04/demo.py
core	list, joining with spaces	<code>a_string = " ".join(a_list)</code>	g03/demo.py
core	list, selecting an element	<code>print(a_list[0])</code>	g03/demo.py
core	list, selecting elements 0 to 3	<code>print(a_list[:4])</code>	g03/demo.py
core	list, selecting elements 1 to 2	<code>print(a_list[1:3])</code>	g03/demo.py
core	list, selecting elements 1 to the end	<code>print(a_list[1:])</code>	g03/demo.py
core	list, selecting last 3 elements	<code>print(a_list[-3:])</code>	g03/demo.py
core	list, selecting the last element	<code>print(a_list[-1])</code>	g03/demo.py
core	list, sorting	<code>c_sort = sorted(b_list)</code>	g03/demo.py
core	list, summing	<code>tot_inc = sum(incomes)</code>	g08/demo.py
core	math, raising a number to a power	<code>a_cubes.append(n**3)</code>	g04/demo.py
core	math, rounding a number	<code>rounded = round(ratio,2)</code>	g05/demo.py
core	string, concatenating	<code>name = s1+" "+s2+" "+s3</code>	g02/demo.py
core	string, converting to an int	<code>values.append(int(line))</code>	g06/demo.py
core	string, converting to title case	<code>name = codes[key].title()</code>	g11/demo.py
core	string, creating	<code>filename = "demo.txt"</code>	g02/demo.py
core	string, including a newline character	<code>fh.write(name+"!\n")</code>	g02/demo.py
core	string, splitting on a comma	<code>parts = line.split(',')</code>	g05/demo.py
core	string, splitting on whitespace	<code>b_list = b_string.split()</code>	g03/demo.py
core	string, stripping blank space	<code>clean = [item.strip() for item in parts]</code>	g05/demo.py
core	tuple, creating	<code>this_tuple = (med_density,state)</code>	g10/demo.py
core	tuple, creating via split	<code>(last,first) = name.split(',')</code>	g11/demo.py
core	tuple, looping over	<code>for (den,state) in sorted(by_density):</code>	g10/demo.py
core	tuple, sorting	<code>for key in sorted(codes):</code>	g11/demo.py
core	tuple, testing equality of	<code>if key == (29,'VA'):</code>	g11/demo.py
csv	opening a file for use with DictWriter	<code>fh = open(outfile,'w',newline="")</code>	g09/demo.py
csv	setting up a DictReader object	<code>reader = csv.DictReader(fh)</code>	g08/demo.py
csv	setting up a DictWriter object	<code>writer = csv.DictWriter(fh,fields)</code>	g09/demo.py
csv	using DictReader with a list	<code>reader = csv.DictReader(lines)</code>	g10/demo.py
csv	writing a header with DictWriter	<code>writer.writeheader()</code>	g09/demo.py
csv	writing a record with DictWriter	<code>writer.writerow(name_rec)</code>	g09/demo.py

Module	Description	Example	Script
fiona	importing the module	<code>import fiona</code>	g24/demo.py
fiona	list layers in a geopackage	<code>layers = fiona.listlayers(demo_file)</code>	g24/demo.py
geopandas	clip a layer	<code>zips_clip = zips.clip(county,keep_geom_type=True)</code>	g24/demo.py
geopandas	combine all geographies in a layer	<code>water_dis = water_by_name.dissolve()</code>	g24/demo.py
geopandas	combine geographies by attribute	<code>water_by_name = water.dissolve('FULLNAME')</code>	g24/demo.py
geopandas	construct a buffer	<code>near_water = water_dis.buffer(1600)</code>	g24/demo.py
geopandas	drawing a map	<code>sel.plot('NAME',cmap='Dark2',ax=ax1)</code>	g22/demo.py
geopandas	extracting geometry from a geodataframe	<code>wv_geo = wv['geometry']</code>	g22/demo.py
geopandas	importing the module	<code>import geopandas as gpd</code>	g22/demo.py
geopandas	merging data onto a geodataframe	<code>conus = conus.merge(trim,on='STATEFP',how='left',valida...</code>	g22/demo.py
geopandas	obtaining coordinates	<code>print('Number of points:', len(wv_geo.exterior.coords). ...</code>	g22/demo.py
geopandas	plotting a boundary	<code>zips_clip.boundary.plot(color='black',linewidth=0.5,ax=...</code>	g24/demo.py
geopandas	project a layer	<code>county = county.to_crs(epsg=utm18n)</code>	g24/demo.py
geopandas	reading a shapefile	<code>states = gpd.read_file("cb_2019_us_state_500k.zip")</code>	g22/demo.py
geopandas	setting the color of a plot	<code>county.plot(color='tan',ax=ax1)</code>	g24/demo.py
geopandas	setting transparency via alpha	<code>near_clip.plot(alpha=0.25,ax=ax1)</code>	g24/demo.py
geopandas	spatial join, contains	<code>c_contains_z = county.sjoin(zips,how='right',predicate=...</code>	g25/demo.py
geopandas	spatial join, crosses	<code>i_crosses_z = inter.sjoin(zips,how='right',predicate='c...</code>	g25/demo.py
geopandas	spatial join, intersects	<code>z_intersect_c = zips.sjoin(county,how='left',predicate=...</code>	g25/demo.py
geopandas	spatial join, overlaps	<code>z_overlaps_c = zips.sjoin(county,how='left',predicate='...</code>	g25/demo.py
geopandas	spatial join, touches	<code>z_touch_c = zips.sjoin(county,how='left',predicate='tou...</code>	g25/demo.py
geopandas	spatial join, within	<code>z_within_c = zips.sjoin(county,how='left',predicate='wi...</code>	g25/demo.py
geopandas	testing if rows touch a geometry	<code>touches_wv = conus.touches(wv_geo)</code>	g22/demo.py
geopandas	writing a layer to a geodatabase	<code>conus.to_file("conus.gpkg",layer="states")</code>	g22/demo.py
io	converting a byte stream to characters	<code>inp_handle = io.TextIOWrapper(inp_byte)</code>	g11/demo.py
json	importing the module	<code>import json</code>	g05/demo.py
json	using to print an object nicely	<code>print(json.dumps(list1,indent=4))</code>	g05/demo.py
matplotlib	axes, setting a title	<code>ax1.set_title('Population')</code>	g13/demo.py
matplotlib	axis, labeling X axis	<code>ax1.set_xlabel('Millions')</code>	g13/demo.py
matplotlib	figure, saving	<code>fig1.savefig('figure.png')</code>	g13/demo.py
matplotlib	figure, tuning the layout	<code>fig1.tight_layout()</code>	g13/demo.py
matplotlib	importing pyplot	<code>import matplotlib.pyplot as plt</code>	g13/demo.py

Module	Description	Example	Script
matplotlib	setting a figure title	fig1.suptitle('Electric Power Plants in Onondaga and Os. . .	g16/demo.py
matplotlib	setting the default resolution	plt.rcParams['figure.dpi'] = 300	g18/demo.py
matplotlib	using subplots to set up a figure	fig1, ax1 = plt.subplots()	g13/demo.py
numpy	computing a median	med_density = round(np.median(this_list), 2)	g10/demo.py
numpy	importing	import numpy as np	g10/demo.py
os	delete a file	os.remove(out_file)	g24/demo.py
os	importing the module	import os	g24/demo.py
os	test if a file or directory exists	if os.path.exists(out_file):	g24/demo.py
pandas	RE, replacing a digit or space	unit_part = values.str.replace(r'\d\s', "", regex=True)	g23/demo.py
pandas	RE, replacing a non-digit or space	value_part = values.str.replace(r'\D\s', "", regex=True)	g23/demo.py
pandas	RE, replacing a non-word character	units = units.str.replace(r'\W', "", regex=True)	g23/demo.py
pandas	columns, dividing with explicit alignment	normed2 = 100*states.div(pa_row,axis='columns')	g12/demo.py
pandas	columns, listing names	print('\nColumns:', list(states.columns))	g12/demo.py
pandas	columns, renaming	county = county.rename(columns={'B01001_001E':'pop'})	g14/demo.py
pandas	columns, retrieving one by name	pop = states['pop']	g12/demo.py
pandas	columns, retrieving several by name	print(pop[some_states]/1e6)	g12/demo.py
pandas	dataframe, appending	gen_all = pd.concat([gen_oswego, gen_onondaga])	g16/demo.py
pandas	dataframe, dropping a column	both = both.drop(columns='_merge')	g16/demo.py
pandas	dataframe, dropping duplicates	flood = flood.drop_duplicates(subset='TAX_ID')	g15/demo.py
pandas	dataframe, finding duplicate records	dups = parcels.duplicated(subset='TAX_ID', keep=False . . .	g15/demo.py
pandas	dataframe, inner 1:1 merge	join_i = parcels.merge(flood,	g15/demo.py
pandas	dataframe, left 1:1 merge	join_l = parcels.merge(flood,	g15/demo.py
pandas	dataframe, left m:1 merge	both = gen_all.merge(plants,	g16/demo.py
pandas	dataframe, making a copy	subset_copy = sample[keepvars].copy()	g17/demo.py
pandas	dataframe, moving the index to a column	water_by_name = water_by_name.reset_index()	g24/demo.py
pandas	dataframe, outer 1:1 merge	join_o = parcels.merge(flood,	g15/demo.py
pandas	dataframe, reading zipped pickle format	sample2 = pd.read_pickle('sample_pkl.zip')	g17/demo.py
pandas	dataframe, resetting the index	hourly = hourly.reset_index()	g18/demo.py
pandas	dataframe, right 1:1 merge	join_r = parcels.merge(flood,	g15/demo.py
pandas	dataframe, saving in zipped pickle format	sample.to_pickle('sample_pkl.zip')	g17/demo.py
pandas	dataframe, selecting rows via boolean	dup_rec = flood[dups]	g15/demo.py
pandas	dataframe, selecting rows via query	ngcc = both.query("Technology == 'Natural Gas Fired Com. . .	g16/demo.py

Module	Description	Example	Script
pandas	dataframe, sorting by a column	<code>county = county.sort_values('pop')</code>	g14/demo.py
pandas	dataframe, sorting by index	<code>summary = summary.sort_index(ascending=False)</code>	g16/demo.py
pandas	dataframe, unstacking an index level	<code>bymo = bymo.unstack('month')</code>	g18/demo.py
pandas	datetime, building via <code>to_datetime()</code>	<code>date = pd.to_datetime(recs['ts'])</code>	g15/demo.py
pandas	datetime, building with a format	<code>ymd = pd.to_datetime(sample['TRANSACTION_DT'], format=...</code>	g17/demo.py
pandas	datetime, extracting day attribute	<code>recs['day'] = date.dt.day</code>	g15/demo.py
pandas	datetime, extracting hour attribute	<code>recs['hour'] = date.dt.hour</code>	g15/demo.py
pandas	displaying all columns	<code>pd.set_option('display.max_columns',None)</code>	g17/demo.py
pandas	displaying all rows	<code>pd.set_option('display.max_rows', None)</code>	g12/demo.py
pandas	dropping rows using a list	<code>conus = states.drop(not_conus)</code>	g22/demo.py
pandas	groupby, counting records via size	<code>summary['units'] = tech_by_kv.size()</code>	g16/demo.py
pandas	groupby, summing a variable	<code>state = county.groupby('state')['pop'].sum()</code>	g14/demo.py
pandas	groupby, using with one grouping variable	<code>by_reg = state_data.groupby('Region')</code>	g13/demo.py
pandas	importing the module	<code>import pandas as pd</code>	g12/demo.py
pandas	index, creating with two-levels	<code>county = county.set_index(['state','county'])</code>	g14/demo.py
pandas	index, listing names	<code>print('\nIndex (rows):', list(states.index))</code>	g12/demo.py
pandas	index, renaming values	<code>div_pop = div_pop.rename(index=div_names)</code>	g13/demo.py
pandas	index, retrieving a row by name	<code>pa_row = states.loc['Pennsylvania']</code>	g12/demo.py
pandas	index, retrieving first rows by location	<code>print(low_to_high.iloc[0:10])</code>	g12/demo.py
pandas	index, retrieving last rows by location	<code>print(low_to_high.iloc[-5:])</code>	g12/demo.py
pandas	index, setting to a column	<code>new_states = states.set_index('name')</code>	g12/demo.py
pandas	index, setting to a column in place	<code>states.set_index('name',inplace=True)</code>	g12/demo.py
pandas	plotting, bar plot	<code>reg_pop.plot.bar(ax=ax1)</code>	g13/demo.py
pandas	plotting, disabling legend	<code>summary.plot.barh(y='mw',ax=ax1,legend=None)</code>	g16/demo.py
pandas	plotting, horizontal bar plot	<code>div_pop.plot.barh(ax=ax1)</code>	g13/demo.py
pandas	reading, csv data	<code>states = pd.read_csv('state-data.csv')</code>	g12/demo.py
pandas	reading, csv using dtype	<code>geocodes = pd.read_csv('state-geocodes.csv',dtype=str)</code>	g13/demo.py
pandas	series, applying a function to each element	<code>name_clean = name_parts.apply(' '.join)</code>	g23/demo.py

Module	Description	Example	Script
pandas	series, combining via where()	mod['comb_units'] = unit_part.where(unit_part!="", mo. . .	g23/demo.py
pandas	series, converting strings to title case	fixname = subset_view['NAME'].str.title()	g17/demo.py
pandas	series, converting to float	sample['dollars'] = sample['TRANSACTION_AMT'].astype(fl. . .	g17/demo.py
pandas	series, converting to lower case	name = mod['name'].str.lower()	g23/demo.py
pandas	series, element-by-element or	is_either = is_ca is_tx	g17/demo.py
pandas	series, filling missing values	mod['comb_units'] = mod['comb_units'].fillna('feet')	g23/demo.py
pandas	series, removing spaces	units = units.str.strip()	g23/demo.py
pandas	series, replacing values using a dictionary	units = units.replace(spellout)	g23/demo.py
pandas	series, retrieving an element	print("\nFlorida's population:", pop['Florida']/1e6)	g12/demo.py
pandas	series, sorting by value	low_to_high = normed['med_pers_inc'].sort_values()	g12/demo.py
pandas	series, splitting strings on whitespace	name_parts = name.str.split()	g23/demo.py
pandas	series, summing	reg_pop = by_reg['pop'].sum()/1e6	g13/demo.py
pandas	series, unstacking	tot_wide = tot_amt.unstack('PGI')	g17/demo.py
pandas	series, using isin()	fixed = flood['TAX_ID'].isin(dup_rec['TAX_ID'])	g15/demo.py
pandas	series, using value_counts()	print('\nOuter:\n', join_o['_merge'].value_counts(), s. . .	g15/demo.py
pandas	setting the index keeping the column	states = states.set_index('STUSPS',drop=False)	g22/demo.py
pandas	using head to select initial records	print(water['FULLNAME'].value_counts().head())	g24/demo.py
pandas	using qcut to create deciles	dec = pd.qcut(county['pop'], 10, labels=range(1,11))	g14/demo.py
pandas	using the shape attribute	print('number of rows, columns:', conus.shape)	g22/demo.py
pandas	using xs to select from an index	print(county.xs('04',level='state'))	g14/demo.py
requests	calling the get() method	response = requests.get(api,payload)	g19/demo.py
requests	checking the URL	print('url:', response.url)	g19/demo.py
requests	checking the response text	print(response.text)	g19/demo.py
requests	checking the status code	print('status:', response.status_code)	g19/demo.py
requests	decoding a JSON response	rows = response.json()	g19/demo.py
requests	importing the module	import requests	g19/demo.py
scipy	calling newton's method	cr = opt.newton(find_cube_root,xinit,maxiter=20,args=[y. . .	g07/demo.py
scipy	importing the module	import scipy.optimize as opt	g07/demo.py
seaborn	adding a title to a grid object	jg.fig.suptitle('Distribution of Hourly Load')	g18/demo.py
seaborn	barplot	sns.barplot(data=hourly,x='hour',y='usage',hue='month',. . .	g18/demo.py
seaborn	basic violin plot	sns.violinplot(data=janjul,x="month",y="usage")	g18/demo.py
seaborn	boxenplot	sns.boxenplot(data=janjul,x="month",y="usage")	g18/demo.py

Module	Description	Example	Script
seaborn	calling tight_layout on a grid object	jg.fig.tight_layout()	g18/demo.py
seaborn	drawing a heatmapped grid	sns.heatmap(data,annot=True,fmt=".0f",ax=ax1)	g20/demo.py
seaborn	importing the module	import seaborn as sns	g18/demo.py
seaborn	joint distribution hex plot	jg = sns.jointplot(data=bymo,x=1,y=7,kind='hex')	g18/demo.py
seaborn	setting axis titles on a grid object	jg.set_axis_labels('January','July')	g18/demo.py
seaborn	setting the theme	sns.set_theme(style="white")	g18/demo.py
seaborn	split violin plot	sns.violinplot(data=eights,x="hour",y="usage",hue="mont. . .	g18/demo.py
zipfile	creating a ZipFile object	zip_object = zipfile.ZipFile(zipname)	g11/demo.py
zipfile	importing module	import zipfile	g11/demo.py
zipfile	opening a file in a zip in bytes mode	inp_byte = zip_object.open(csvname)	g11/demo.py