


10K	=	100mA
5.0K	=	200mA
2.0K	=	500mA
1.0K	=	1000mA



U5
MAX17048G_T10



The diagram shows the MAX17048 chip with the following connections:

- V_{DD}** and **CELL** pins are connected to a battery.
- CTG** pin is connected to a capacitor, which is labeled "ONLY ONE EXTERNAL COMPONENT".
- GND** pin is connected to ground.
- ALRT** pin is connected to the **SYSTEM μ P** (represented by a dashed box).
- SDA** and **SCL** pins are connected to the **SYSTEM μ P**.
- QSTRT** pin is connected to ground.

PIMB/WLP		NAME	FUNCTION
TDFN	A1		
1	A1	CTG	Connect to Ground
2	A2	CELL	Connect to the Positive Battery Terminal. MAX17046: Not internally connected. MAX17049: Voltage sense input.
3	A3	V _{DD}	Power-Supply Input. Bypass with 0.1µF to GND. MAX17046: Voltage sense input. Connect to positive battery terminal. MAX17049: Connect to regulated power-supply voltage.
4	A4	GND	Ground. Connect to negative battery terminal.
5	B4	ALRT	Open-Drain, Active-Low Alert Output. Optionally connect to interrupt input of the system microcontroller.
6	B3	QSTRT	Quick-Start Input. Allows reset of the device through hardware. Connect to GND if not used.
7	B2	SCL	I ² C Clock Input. SCL has an internal pulldown (ppp) for sensing disconnection.
8	B1	SDA	Open-Drain I ² C Data Input/Output. SDA has an internal pulldown (ppp) for sensing disconnection.
—	—	EP	Exposed Pad (TDFN Only). Connect to GND.

[illegible]

GNSS

These capacitors and the inductor will need to be tuned if an external antenna ends up being used. For now, it's not, but they're here anyway.

V_BCKP enables much faster location acquisition
30s → 2s

The diagram shows the following components and connections:

- J5 IPEX:** A yellow box labeled "CENTRE" with pins 4, 3, 2, 1. Pin 4 is connected to GND. Pin 3 is connected to GND_2. Pin 2 is connected to GND_1. Pin 1 is connected to GND.
- D25 TPD1E05U06DPYR:** A yellow box labeled "I/O GND" with pins 1, 2. Pin 1 is connected to GND. Pin 2 is connected to GND.
- U8 LC86LICMD:** A yellow box with pins 11, 10, 7, 1, 2, 3, 4, 5, 6, 8, 9. Pin 11 is connected to GND. Pin 10 is connected to GND. Pin 7 is connected to GND. Pin 1 is connected to GND. Pin 2 is connected to GND. Pin 3 is connected to GND. Pin 4 is connected to GND. Pin 5 is connected to GND. Pin 6 is connected to GND. Pin 8 is connected to GND. Pin 9 is connected to GND.
- Capacitors:** C50, C51, C52 (100mF), C53 (1K), C54 (1K), C55 (1K).
- Resistors:** R22 (OR), R23 (5K), R24 (1K), R25 (1K), R21 (1K).
- Antenna:** BAV199, D24.
- Other components:** VCC, V_BCKP, 1PPS, AADET_N, EX_ANT, RESET, WAKE_UP, RXD, TXD, RESERVED, GND.