Index

Editor's Note: Except for commonly used phrases and abbreviations, topics are indexed by their noun names. Many topics are also cross-indexed.

The letters "ff" after a page number indicate coverage of the indexed topic on succeeding pages.

A separate Project Index and Author Index follow the main index.

10 meter Yagis:	Source:	8.15
12 meter Yagis:	Stepped wire diameters:	8.4
15 meter Yagis: 11.14	Wires below ground:	
17 meter Yagis:	Antenna system design:	
20 meter Yagis:	Effects of terrain:	14.17
2200 meter band:	Elevation angles:	
30 meter Yagis:	Propagation:	
40 meter Yagis:	Site planning:	
4nec2:	Antenna testing:	
630 meter band:	Antenna tuner:	
	Adjusting T network:	
	Balanced:	
Δ	Balun:	
A index:	General-purpose designs:	
AB-577 mast: 26.8		
Active antennas: 22.17	Hairpin:	
Atmospheric noise: 22.17	High-power ARRL tuner:	
Adcock antenna: 22.22	Location in system:	
Aluminum tubing: 25.8	Maritime HF antennas:	
	Anti-resonance:	
Alloy strength:	Antioxidation compound:	26.53
Alloys:	Array	
Construction techniques:	4-element driven:	
Sizes:	8-element driven:	
AMSAT:	Bi-square:	12.18
Anchors, guy:	Bidirectional:	6.2
Anchors, tree:	Bobtail curtain:	12.13
Antenna	Broadside:	6.2
Building on tower:	Bruce array:	12.14
Center-fed: 10.3	Collinear:	
Field measurement:	Direction-finding:	
Gain measurement:	Directional switching:	
Grounding:	Directive:	
J-pole:	Driven:	
Raising and lowering:	End-fire:	
Resonance: 24.27	Extended double Zepp (EDZ):	
Rotator: 26.21	Franklin:	
Static dissipation: 26.47	Half-square:	
Wind load: 26.57	Lazy H:	
Antenna analysis	Parallel:	
Ground parameters: 3.29		
Measuring ground properties: 3.31	Parasitic:	
Antenna analyzer: 27.20	Phased:	
Antenna comparison: 27.20 Antenna comparison: 14.7	Phasing arrows:	
	Receiving:	
Antenna Model:	Sterba curtain:	
Antenna modeling:	Transposed coax:	
Accuracy test: 8.17	W8JK array:	
Average Gain Test:	Yagis, space communication:	17.14f
Basics:	ARRL log coordinate system:	
Dipole antennas:	Artificial ground:	10.2
Frequency scaling: 8.15	Attenuation measurement:	
Ground:	Attenuator:	
Limitations:	Attic antennas:	
Load:	Aurora:	
Maritime HF antennas:	Auroral propagation:	
Near field: 8.20	AutoEZ:	
Program inputs: 8.7	Axial ratio:	
Segmentation: 8.8	Azimuth angle:	
5	1 121111dui diigic	1.3

Azimuth pattern:		Broadband arrays:	6.21
Azimuth-elevation position control:	17.31	Broadband dipole:	9.7
Azimuthal diversity:	14.42	Broadband transformer	
		Impedance matching:	
В		Broadside array:	
	4.20	4-element:	
Backstay vertical:		Parallel:	
Balanced tuner:		Bruce array:	
Balun	24.0	Burying cable.	20.43
Antenna tuner:	24.8		
At VHF and UHF:		C	
Choke:		C-pole antenna:	9.11
Coiled-coax:	24.44	Cable clamps:	
Current:	24.42	Cable entrance panel:	26.48
Detuning sleeve:		Cable grip:	26.22
Impedance step-up/step-down:	24.53	Cable ties:	
Matching stub:		CADWELD:	
Phased array:		Cage dipole:	
Quarter/Three-quarter wave:		Capacitance hat:	
Transmission line:		Mobile HF antenna:	
Bandwidth:		Carabiner:	
Base loaded vertical:	0 22	Cassegrain antenna:	
Basic Wind Speed:		Cavity resonator:	
Beacon, NCDXF/IARU system:	4 24	Center-fed (off-center fed) dish:	
Beamwidth:	1 14	Center-fed dipole:	
Bending radius (cable):		Central States VHF Society (CSVHFS):	
Beta match:		Characteristic impedance (Z_0):	
Beverage antennas:	22.3	Measurement:	27.22
Beverage on ground (BOG):	22.8	Choke balun: 6.21, 9.16, 1	11.5, 15.5, 24.28, 24.42
Construction techniques:		Coiled-coax:	24.44
Crossfire phasing:		Ferrite bead:	
Echelon:		Ferrite core:	
Feed point transformer:		Measuring impedance:	24.50
Terminating impedance:		Self-resonance:	
Two wire:		SWR:	
Bi-square antenna:	12.18	Christmas tree stack: Yagi antenna:	
Antenna and transmission line measurements:	27.42	Circular polarization:	1.4 1.15 17.5 17.6ff
Antenna fundamentals:		Climbing shield:	26 37
Antenna materials and construction:		Climbing technique	20.37
Broadside and end-fire arrays:		Tower:	
Building antenna systems and towers		Tree:	
Dipoles and monopoles		Coaxial cable:	23.2, 23.20
Direction finding:		Attenuation:	23.21, 23.31
Effects of ground:		Bend radius:	
HF Yagi and quad antennas:		Burying:	
Log-periodic dipole array (LPDA):		Characteristics:	
Long-wire and traveling-wave antennas:	13.17	Deterioration:	
Loop antennas:	5.24	Equations:	
Maritime HF antennas:		Installing:RG-8, RG-213 and type cables:	
Mobile HF antennas:		Specifications:	
Multielement arrays:		Cold galvanizing:	
Portable antennas:		Collinear arrays:	
Propagation:		2-element broadside:	12.1
Receiving antennas:		3- and 4-element broadside:	
Repeater antenna systems:		4-element end-fire:	
Single-band MF and HF antennas:		Adjustment:	
Space communications antenna systems:		Dipoles:	15.11
Stealth and limited-space antennas:	20.14	Come-along:	26.22
Transmission line system techniques:		Common-mode current:	
Transmission lines:		Asymmetric feed line:	
Bidirectional array:		Effect on SWR:	
Big wheel antenna:		Feed line:	
2 meters:		Pattern distortion:	
Big-Grips:		Computer model:	
Binomial array:		Yagi antenna: Conduction current:	
Bobtail curtain:		Connectors	1.2
Bonding:		BNC:	23 27
Earth connections:		F:	
Boom construction:		Hardline:	
Boom length, Yagi antenna:		N:	
Boots, climbing:		SMA:	23.30

Weatherproofing	UHF:	23.25	Portable whip:	19.4
Sopring Sopr			Radiation pattern:	2.3, 2.9
ARRI (oganthmic				
Jinear				
Logarithmic:				
Recinagular				
Coplara pair				
Copperveld:				
Ground-plane: 15.54 Coronal hole: 21.15 Coronal hole: 4.25 Coronal hole: 4.25 Coronal hole: 4.25 Coronal mass ejection (CME): 4.11 Coronal mass ejection (CME): 4.25 Coupling: 4.25 Cou				
Adock antenna				
Arrays 22.2	*		80 meter system:	22.29
Authorstrain Auth			Adcock antenna:	22.22
Corrosion:				
Counterpoise: 2.13 30/17/2 meter 10.30 30/17				
Coupled-resonator (C-R) dipole: 10.27			Frame loop:	22.25
10,000 1			Goniometer:	22.24
Mutual:				
Transmission line:			Loops:	22.20
Crank-up tower				
Critical rangle:				
Critical frequency:				
Cross-band coupler				
Cross-polarization:				
Crossfire phasing:	Cross polarization:	17.4		
Feed system				
Phased array:			<u> </u>	
Disconce antenna Current distribution: 6.7 20-10 meter, A-frame: 10.3 40-10 meter				
Current distribution:				
Quarter-wave lines:		6.7	20-10 meter, A-frame:	10.35
Current measurement:			40-10 meter:	10.36
Cushcraft XM240:				
Feed system:				
Day	Cushcraft XM240:	11.29		
Dayer (D region):				
Displacement current:	D			
Deciber 1.10 Diversity Repeater antennas: 18.1 Deciber 1.10 Detail policy Section 1.00 Deciber 1.00		4 17		
Decibel:				1.2
Delay lines:				
Electrical length:	Delay lines:	6.14ff		
Feed point	Electrical length:	6.38		
Polarization:				
Delta match:				
Detuning sleeve:			5	,
Diffraction:				
Geometric Theory of Diffraction:				
Incident-Shadow Boundary:				
Reflection-Shadow Boundary:				
Dipole:			DASullillit.ii.	7.29
135 foot, 80-10 meter:			_	
30/17/12 meter, coupled-resonator:			E	
Broadband: 9.7 E-plane: 1.1 C-pole: 9.11 Earth-Moon-Earth (EME) Cage: 9.7 Power requirements: 17. Cage, 80 meter: 9.9 SHF challenges: 17.2 Center-fed: 2.5 Side lobes: 17. Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Height above ground: 2.1, 9.4 Effective radiated power (ERP): 1.1 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 <td></td> <td></td> <td></td> <td></td>				
Broadband: 9.7 E-plane: 1.1 C-pole: 9.11 Earth-Moon-Earth (EME) Cage: 9.7 Power requirements: 17. Cage, 80 meter: 9.9 SHF challenges: 17.2 Center-fed: 2.5 Side lobes: 17. Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Height above ground: 2.1, 9.4 Effective radiated power (ERP): 1.1 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 <td></td> <td></td> <td>E layer (E region):</td> <td> 4.17</td>			E layer (E region):	4.17
Cage: 9.7 Power requirements: 17. Cage, 80 meter: 9.9 SHF challenges: 17.2 Center-fed: 2.5 Side lobes: 17. Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fen (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective projected area (EPA): 26.1 Folded: 2.11, 9.4 Effective radiated power (ERP): 1.1 Height above ground: 2.1, 2.8 Ray tracing: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Of				1.11
Cage, 80 meter: 9.9 SHF challenges: 17.2 Center-fed: 2.5 Side lobes: 17. Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power) <td> *</td> <td></td> <td>· /</td> <td></td>	*		· /	
Center-fed: 2.5 Side lobes: 17. Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.8 10.9 Worksheet: 26.1 Feed point impedance: 2.5 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.1, 2.8 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated powe				
Conductor diameter: 2.1 Yagi arrays: 17.1 Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.2 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Coupled-resonator (C-R): 10.27 Effective isotropic radiated power (EIRP): 1.1 Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.2 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Fan (multiple dipole antennas): 9.8, 10.9 Worksheet: 18.1 Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.2 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Feed point: 9.3 Effective projected area (EPA): 26.1 Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Feed point impedance: 2.5 Effective radiated power (ERP): 1.1 Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)	> 1 1 /	· · · · · · · · · · · · · · · · · · ·		
Folded: 2.11, 9.4 Effects of terrain: 14.17 Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17 Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Height above ground: 2.1, 2.8 Ray tracing: 14.1 Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Inductively loaded: 9.28 Simulation: 14.2 Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Inverted-V: 9.5 Stacking Yagis: 14.3 Linearly loaded: 9.27 Terrain files: 14.2 Multiband: 10.3 Efficiency, radiation: 6.1 Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Multiband:10.3Efficiency, radiation:6.1Off-center-fed (OCF):2.6, 10.8Eggbeater antenna:17.2, 17.Over real ground:3.25EIRP (see Effective isotropic radiated power)	Inverted-V:	9.5		
Off-center-fed (OCF): 2.6, 10.8 Eggbeater antenna: 17.2, 17. Over real ground: 3.25 EIRP (see Effective isotropic radiated power)				
Over real ground:				
	· /	,	Eggbeater antenna:	17.2, 17.8
			EIRP (see Effective isotropic radiated power)	

Electrical length		Filters	
Feed line:		Transmission line:	
Measurement:		Flag receiving antenna:	22.15
Electrical tape:		Flat Projected Area (FPA):	
Electromagnetic field:		Flyswatter antenna:Focal length (dish antenna):	
E field:		Focal ratio:	
H field:		Folded dipole:	
Safety:		Folded monopole:	2.15. 9.16
Electromagnetic wave:		Force 12 C-3 triband Yagi:	
Attenuation:		Forward stagger	
Electrostatic field:		Yagi antenna:	11.26
Field intensity:	1.4	Four-square array:	6.20, 6.28
Phase:	1.4	Franklin array:	
Polarization:	1.4	Frequency coordination:	18.15
Velocity factor:		Frequency scaling:	
Velocity of propagation:		Front-to-back ratio (F/B):	
Wavefront:		Yagi antenna:	
Electron density profile:		Front-to-rear ratio (F/R):	
Electronic beam forming:	22.24	Front-to-side ratio:	1.14
Element	6.2		
Array:		G	
Length correction:		G5RV multiband antenna:	10 6
Taper:		Gain:	
Elevated ground system:		At VHF and UHF:	
Elevated radials:		Boom length:	
Elevation angle:		Broadside array:	
Antenna system design:		Calculated from beamwidth:	6.3
HF propagation:		dBi:	
Elevation pattern:		Dish antenna:	15.61
Elliptical polarization:	1.4	Measurement:	27.39
End effect:	1.6, 2.1, 21.5	Power:	
End loading		Relative to single element:	
Yagi antenna:		Stacking:	
End-fed Half-wave (EFHW, see End-fed Zepp):		Yagi antenna:	
End-fed Zepp:		Gain/Noise Temperature (G/T):	
End-fire array:	· ·	Galvanic series:	
Equalizer plate:	20.33	Geomagnetic storm:	
Erection fixture (see Gin pole) ERP (see Effective radiated power)		Geometric optics (GO):	
EWE receiving antenna:	22 11	Gin pole:	
Extended double Zepp (EDZ):		Glass mount VHF/UHF antenna:	
Extraordinary wave:		Gloves:	
EZNEC-Pro/2,Pro/4:		GNEC:	8.2
EZNEC 6.0:		Goggles:	26.5
EZNEC-ARRL:	8.1	Goniometer:	
		Gray-line propagation:	
=		Great circle path:	
F	22.27	Gregorian antenna:	17.16
F connectors:		Ground	0.17
Flayer (F region):		Antenna modeling:	
Fading:Stacked Yagis:		Conductivity map: Electrical characteristics:	
Fall-arrest harness (FAH):		Power loss:	
Fan dipole:		Soil types:	
Far field:		Ground loss:	
Effects of ground:		Ground plane:	
Reflections:	3.21	Ground properties	
Faraday rotation:	1.4, 17.4, 17.11	CCIR Recommendation 368:	
FCC RF exposure regulations:	1.20	Direct measurement:	3.32
Feed point impedance:		Indirect measurement with dipole:	
Height above ground:		Low-frequency measurement:	3.31
Mutual impedance:		Ground reflections	
Self impedance:		Horizontal antennas:	
Yagi antenna:		Vertical antennas:	
Ferrite choke balun:		Ground systems	3.10
Ferrite core loop antenna:Leakage flux:		Ground systems Elevated:	2 124
Fiberglass antenna materials:	J.18		
		Maritime HF antennac:	// /-
	25.15	Maritime HF antennas:	
Fiberglass pole:	25.15 26.9	Multiband:	3.19
Field cancellation and reinforcement:			3.19
ribergiass pole: Field cancellation and reinforcement: Field strength: Field strength gain (FSG):		Multiband:Radials:	3.19 3.10 3.6

Ground-plane antenna:	9.14	Omega match:	
Corner reflector:		Resonant circuit:	
Elevated radials:		Stubs:	
VHF and UHF:	15.5	T match:	,
Grounding	26.4666	Universal stub:	
Antennas:		Indoor antennas:	
Braid and strap:CADWELD:		Insulators:	
Service entrance ground:		Feed point:	
Tower and feed line:		Parallel wire line:	
Ufer ground:		Insurance:	
Guy wire	20.40	Interaction, antenna system	20.0, 20.33
Cutting:	26.31	Modeling:	14 3
Phillystran:		Interference of waves:	14.20
Preforms:		Interferometer:	
Resonance:		Interlaced elements	
Swaged fittings:		Yagi antenna:	11.26
Tension:		Inverted-L:	
Types and grades:		Tower based:	
Guyed tower:		Inverted-V dipole:	
Guying:		IONCAP:	
Anchors:		Ionizing radiation:	1.18
Design:		Ionosonde:	
Material:	26.10	Ionosphere:	
Tension:		D layer (D region):	4.17
Gyro frequency:	4.19	E layer (E region):	
•		F layer (F region):	4.17
		Ionospheric propagation	
H		Bending:	4.17
H field:	1.1	Disturbed conditions:	
H-plane:	1.11	Geomagnetic storm:	4.26
Hairpin match:	15.4, 24.32	Lowest usable frequency (LUF):	
Hairpin tuner:	24.9	Maximum usable frequency (MUF):	4.23
Half-power points:	6.2	Multi-hop:	4.22
Half-sloper antenna:		Scatter:	4.5
1.8 MHz:		Skip zone:	
Half-square antenna:		Ionospheric sounding:	4.18
Halo antenna:		Isolation	
6 meters:		Repeater antennas:	
Hard hat:		Isotropic radiator:	1.7, 6.12
Hardline:			
Hardline connectors:		ī	
Hardware:		J	
Harmonic suppression by tuners:	24.3	J-pole antenna:	
Height above average terrain (HAAT):		For bicycles:	
Helical antenna:			
Helical-wound mobile HF antenna:		K	
HFTA:			1.12
Generating DEM files:		K index:	
K6TU data service:		1	
Terrain profile data:		K9AY loop:Kellems grips:	
High-altitude Elliptical Orbit (HEO) satellites:		Knife-edge diffraction:	
Hog horn antenna:		Č	
Horizontal polarization:		Knots:	20.20
Safety:		L	
Hose clamps:		L network:	24.2. 24.4
Hy-Gain Yagi:		Array feed:	· ·
Hybrid coupler:		Lanyard:	
Tryona coupler	0.10	Lazy H antenna:	
		Leakage flux:	
		Length-to-diameter radio (l/d):	
Impedance:	1.5ff	Lightning protection:	
Measurement:		Arrestors, surge suppressors:	
Impedance matching:		Cable entrance panel:	
At the antenna:		Gas discharge tube:	
At VHF and UHF:		Polyphaser:	
Beta match:		Upper floor station:	
Broadband matching:		Limited space antennas (see Stealth antennas)	
Delta match:		Lindenblad antenna:	17.9
Folded dipole:	· ·	Line launcher:	
Frequency range:		Linear actuator:	
Gamma match:		Linear coordinate system:	1.12
Hairpin match:		Linear loading:	
Mobile HF antenna:	21.11	Yagi antenna:	11.28

Linear polarization:	1.4	Maritime HF antennas:	
Litz wire:	5.16	Backstay vertical:	
Loading coil		Ground system:	21.25
Mobile HF antenna:	21.6	Power boats:	21.26
Lobes		Tuners:	21.23
Major and minor:	6.2	Mast	
Log-periodic dipole array (LPDA)		AB-577:	26.8
3.5 or 7 MHz:	10.31	Design:	
5-band, 13-30 MHz:		Guying:	
At VHF and UHF:		Material strength:	
Construction:		C	
		Portable:	
Design:		Push-up:	
Design corrections:		TV:	
Design process:	7.11	Wind load:	26.59
Feeding:	7.8	Matchbox:	
Software:	7.4	Matched transmission lines:	23.4
Wideband performance:		Loss:	
Logarithmic coordinate system:		Matching	
Long path propagation:		Impedance:	24.2ff
	4.27		
Long wire antennas	12.1	Networks:	
Characteristics:		Maximum permissible exposure (MPE):	
Directivity:		Antenna modeling:	
Feed methods:		Maximum usable frequency (MUF):	4.23
Length:	13.5	Measurement	
Parallel:	13.6	Element current:	
Radiation patterns:		Feed line electrical length:	
Terminated:		Self and mutual impedance:	6 30
V-beam:		Mechanical beamtilt:	
	13.0		
Loop antennas	22.15	Meteor scatter antennas:	
1.8 MHz receiving loop:		Method of moments:	
14 MHz, vertically polarized:		MicroDEM:	
7 MHz, full size:	9.36	Microwave antennas:	15.57ff
Arrays:	5.20	Patch:	15.66
Compact 40 m loop for recreational vehicle:		Periscope:	15.67
Construction, small loops:		Vivaldi:	
Crossed loops:	5 20	MININEC:	
Delta:		MININEC ground:	
Direction-finding:		MMDS dish antenna:	
Feeding large loops:	5.9	Mobile flutter:	4.3
Ferrite core:	5.18	Mobile HF antennas	
Ferrite core for direction finding:	22.27	Base loading:	21.3
Frame loop for direction finding:		Center loading:	
Half-wave:		Controller:	
Horizontal:		Efficiency:	
Indoor:		Equivalent circuit:	
K6STI receiving loop:		Helical wound:	
K9AY receiving loop:		Impedance matching:	
Large loops:	5.1	Indoor use:	20.6
Loop Skywire:	10.11	Linear loading:	21.14
Losses:		Loading coil:	
One wavelength:		Mounting:	
Q:		Radiation resistance:	
Quad:		Screwdriver:	
			21.14
Rectangular, horizontally polarized:		Mobile VHF/UHF antennas	
Shielded:		1/4 wavelength whip:	
Small:		6 meter FM:	16.4
Small transmitting:	5.22	Angle bracket:	
Transmitting, small loops:		Bicycle antennas for VHF and UHF:	
Tuned:		Big wheel for 2 meters:	
Loop Yagi:		Glass mount:	
1 0	13.74	Halo for 6 meters:	
Loss Matching naturalism	24.4		
Matching networks:		Hand-held transceiver:	
Loss resistance:		Horizontally polarized for SSB/CW:	16.3
Low Earth Orbit (LEO) satellites:		Lip mount:	
Lowest usable frequency (LUF):	4.24	Magnetic (mag) mount:	
LPCAD software:		Mounts for whip antennas:	
LXC Prime Directive:		Rubber ducky:	
	20.20	SO-239 mount:	
		Stud mount:	
M			
		Mode, waveguide:	15.5/
Magnetic (mag) mount	** **	Monopole	
Mobile HF antenna:		Characteristics:	
VHF/UHF antenna:		Folded:	2.15, 9.16
Magnetosphere:	4.11	Moxon rectangle:	11.29
Main lobe:		40 meter:	
Major and minor lobes:		Portable 15 meter beam:	19 14
J			17.17

Multicoupler, transmitter:		Phasing lines:	
Mutual coupling:		Electrical length:	6.38
Mutual impedance:		Phillystran:	
Measurement:	6.39	Pi network:	24.2, 24.5
		Pier-pin tower base:	
N		Plane wave:	
	22.27	Plastic antenna materials:	
N connectors:		Plumber's delight:	
National Electrical Code (NEC):		Polaplexer:	
Conductor sizes:		Polar cap absorption (PCA):	
NCDXF/IARU beacon system:		Polar mount:	
Near field:		Polarity:	
Antenna modeling:	8.20	Polarization:	
Near Vertical Incidence Skywave (NVIS):		At VHF and UHF:	
Antenna height:		Circular:	
Frequency selection:		Elliptical:	
NEC:		Horizontal:	
NEC-2 and NEC-4 Comparison:		Instantaneous:	
NEC-Win Plus:		Linear:	
NEC-Win Pro:		Repeater antennas:	
NEMA 4 enclosure:	17.30	Sense:	
Network	24.455	Switching:	
Impedance matching:		Vertical:	
L, T, Pi:		VHF/UHF antennas:	4.5
Matching:		Portable antennas	10.10
New Motorola Mount (NMO):		2-element 20/15/10 meter Yagi:	
NOAA scales (solar disturbances):		2-element 6 meter quad:	
Noise bridge:		6 meter Yagi:	
Noise temperature:		Compact 40 m loop for recreational vehicle:	
Nonionizing radiation:		Five-band portable vertical antenna:	19.8
Null:		HF vertical travel antenna:	
Pattern:	0.12	Horizontal:	
		Inverted V:	
0		Masts and antenna supports:	19.15
Off-center-fed (OCF) dipole:	26 108 105	Off-center-fed (OCF) dipole:	
Ohmic loss:		Portable 15 meter beam:	
Omega match:		Tree mounted HF ground plane:	
Omnidirectional:		Twinlead folded dipole:	19.3
Open sleeve antenna:		Whip dipole:	
Open wire transmission line:		Zip cord:	
Ordinary wave:		Power absorber:	
OSHA:		Power density:	
OSIIA	20.2	Prop-pitch rotator:	20.21
		Propagation Antenna elevation patterns:	1.26
P			
Parabolic reflector (dish):	15.60, 17.5, 17.16ff	Antenna polarization:	4.4
Feed systems:		Elevation angles:	
Kit:		Gray-line:	
Use with satellites:			
Parallel wire transmission line:		Ground wave:HF:	
Installing:		HF scatter modes:	
Parasitic array:		Ionospheric scatter:	4.29
Parasitic element:		Knife-edge diffraction:	
Patch antenna:		Long path:	
Pattern (see Radiation pattern)	,	One way:	
Pedersen ray:	4.21	Prediction:	
Pennant receiving antenna:	22.15	Short path:	
Periscope antenna:		Skip:	
Phase		Sky-wave:	
Element current:		Software:	
Phased array:	6.10ff	Solar activity data:	
120° fed, 60° spaced dipole:	6.31	Sporadic E (E _s):	
4-element rectangular:		Tables:	
90° fed, 90° spaced:		Transequatorial:	
Adjustment:		Tropospheric bending:	
Binomial:	6.27	Tropospheric propagation:	
Crossfire phasing:		Tropospheric scatter:	
Design examples:		VHF/UHF:	
Effect of load reactance:	6.15	Weather effects:	
Feeding and feed systems:		Pseudo-Brewster Angle (PBA):	
Four-square:		Pulley:	
Measurement:	27.30	PVRC mount:	
Use of baluns:			20.11
Use of delay lines:	6.14ff		

Q		Beverage on ground (BOG):	22.8
Q (antenna):	1.17	Circle arrays:	
Q-section:	15.15, 24.23	Coupling:	
Quad antennas:		Directivity Merit Figure (DMF):	
2-element for 20/17/15/12/10 meters:	11.38	EWE:Flag:	
5-element for 20/15/10 meters: At VHF and UHF:		K6STI loop:	
Construction:		K9AY loop:	22.11
Cubical versus concentric:		Pennant:	22.15
Diamond versus square:		Receiving Directivity Factor (RDF):	
Feed point:	11.33	Receiving arrays:	6.21
Multiband:		Receiving Directivity Factor (RDF):	
Performance parameters:		Reciprocity: Rectangular grid:	
Portable 2-element 6 meter:		Reflection:	
Versus Yagis:		Reflection coefficient:	
Quad loop:Feed point:		Reflectometer:	
Polarization:		Reflector:	11.1
Quadrifilar helix (QFH) antenna:		Reflector antenna:	15.52
Quagi antenna:		Refraction:	
At VHF and UHF:	15.41	Refurbishing aluminum antennas:	
Quarter-wave impedance transformer:		Reinforcing bar (rebar):	
Quarter-wave section:	24.23, 24.26	Relative permittivity (e _r):	3.2
		Cavity resonator:	18.9
R		Couplers:	
Radial:	2 13 3 10 25 7	Coverage area:	
Burying under grass:		Duplexer:	18.10
Elevated:		Horizontal versus vertical polarization:	18.1
Elevated ground plane:		Isolation:	
Multiband:		Mounting:	
Optimized length:	3.12	Radiation pattern:	18.3
Shortened:		Transmission lines:	
Spacing:	9.14	Resistance (ohmic)	10.1
Feed line:	96 103 104	Loss:	6.10
Ionizing:		Resonance:	1.6, 23.9
Nonionizing:		Antenna:	
Radiation efficiency:	6.11	Choke balun:	24.45
Radiation pattern:		Resonant circuit	24.27
At VHF and UHF:		Impedance matching:	24.37
Azimuth:		RF ammeter:	
Beamwidth: Coordinate scale:		RF connector:	
Dipole antennas:		Chart:	
E-plane:		Weatherproofing:	26.44
Elevation:		RF current measurement:	
Front-to-back ratio (F/B):	1.14	RF current meter:	
Front-to-rear ratio (F/R):		RF current probe:	27.3
Front-to-side ratio:		RF interference	20.2
H-plane:		Stealth antennas:	
Long-wire antennas:		RF power measurement:	
Main lobe:		RF safety:	
Null:	· · · · · · · · · · · · · · · · · · ·	ANSI standard:	
Omnidirectional:		Awareness guidelines:	1.24
Over real ground:		Dish and horn antennas:	
Repeater antennas:		FCC regulations:	
Side lobe:		IEEE standard:	
Terminated long wire:		Maximum permissible exposure (MPE):	
V-beam:		Power density:	
Yagi antenna:		Specific absorption rate (SAR):	
Radiation resistance:		Station evaluation:	
Mobile HF antenna:		RF sampler:	
Radio blackouts:		RF step attenuator:	
Radio horizon:		RF voltmeter:	
Random wire antenna:		RF wattmeter:	
Ray:	4.1	Rhombic:	
Ray tracing:	14.19	Feed methods:	
Receiving antennas	22.17	Multi-wire:	
1.8 MHz loop:		Terminated:	
Active antennas:		Terminated:	
Beverage:		Right/Left-Hand Polarization (RH/LHCP):	
20.01480.		Ring rotator:	

Rope		<i>NEC</i> :	
Care:		NEC-Win Plus:	
For pulleys:		NEC-Win Pro:	
Knots:	26.26	Propagation prediction:	
Selection:		SCALE.EXE:	
Rotation loop:	26.39	VOACAP:	4.26
Rotator:	26.21	<i>YW</i> :	11.2
Control cable:		Soil conductivity (σ):	3.2
Installation:	26.38	Soil types:	3.3
Maintenance:	26.55	Solar activity data:	4.43
Thrust bearing:		Solar flux:	
Rubber ducky antenna:		Solar radiation storm:	
reador ducky unterma.		Solar wind:	
		Somerfeld-Norton ground:	
S		Sommerfeld ground:	
S parameter:	27.20		
~ *a		Space wave:	
Safety After a failure:	26.55	Spatial polarization offset:	
		Specific absorption rate (SAR):	
Electrical:		Split-bolts:	
Electrical lines near antennas:		Sporadic E (E _s) propagation:	
Principles of working safely:		Squalo antenna:	
RF exposure:		Stacking Yagis:	
Tips for tower work:		Azimuthal diversity:	
Tower:	26.1ff	BIP/BOP:	
Safety belt:		Cross-polarization:	
Safety equipment:		Dissimilar Yagis:	
Suppliers:		Distance between antennas:	
Safety wire:		DL6WU formula:	
Satellite band designations:	17.3	Effect of nulls:	
SCALE.EXE:		Effect of terrain:	14.36
Scatter:	4.1	Effective aperture:	
HF propagation modes:		Elevation coverage:	
Screwdriver antenna:		Fading:	14 40
Self impedance:		Gain:	
Measurement:		H frame:	
Self-resonance:		Higher elevation angles:	
Sensing antenna:		Multiband Yagis:	
Sensing element (antenna):		Precipitation static:	
Series-section transformer:		Space communications:	
Shadow area:		SWR changes:	
Shielded loop antenna:		VHF and UHF Yagis:	15.10
Short path propagation:		WXØB:	
Short skip:			14.41
Shortened Yagi antenna:		Standing wave ratio (see SWR) Standing waves:	22.0
Shunt-feed:		Static dissipation:	25.0
Side lobe:			
Side lobe. Sidescatter:		Stauff clamps:	13.21
Silicone sealant:			20.5
		Attic antenna:	
Site planning:		Disguised:	
Skin depth in soil:		Indoor loop:	
Skip zone:		Invisible:	
Sky-wave propagation:		Mobile HF antennas:	
Sling:		Outdoor:	
Slinky antenna:		Radials:	
Sloper:		RF interference:	
Half-sloper:		Safety:	20.1
Sloping dipole:		Slinky antenna:	20.5
SMA connectors:		Small loops:	20.10
Smith chart:	24.35, 27.31	VHF and UHF antennas:	
Smoothed sunspot number (R ₁₂):	4.14	Sterba curtain:	12.7
Snatch-block:		Stubs (transmission line):	
Snell's law:	14.20	Connecting:	
Software		Filters:	
4nec2:	8.3	Measuring:	
Antenna Model:	8.2	Placement:	
Antenna modeling:		Tuning:	
AutoEZ:		Sunspot:	
EZNEC-Pro/2,Pro/4:		Sunspot cycle:	
EZNEC 6.0:		Sunspot cycle: Sunspot number:	
EZNEC-ARRL:		International (ISN):	
GNEC:		Smoothed (R ₁₂):	
HFTA:		Supporting cables:	
IONCAP:		Switching systems	23.1
LPCAD:	The state of the s	BIP/BOP:	14.42
MicroDEM:		Yagi stacks:	
MININEC:		1 ag1 stacks	14.2011
17211 ¥11 ¥LC	o.1		

SWR:	23.9	Open wire:	23.2
Antenna analyzer:	27.20	Open wire transmission line:	23.19
Bridge circuits:	27.4	Parallel wire:	
Choke balun:	27.9	Parallel wire transmission line:	23.19
Common-mode current:	24.40, 27.9	Power loss due to SWR:	23.11
Determination at antenna:	24.16	Quarter-wave impedance transformer:	23.16
Measurement:		Reactive load:	
Myths about:		Reflection coefficient:	
Nomograph:		Repeater antennas:	
Power loss:		Selection:	
Protection of transmitter:		Standing waves:	
1 Total of transmitter.		Standing-wave ratio (SWR):	
		Stubs:	
T		System design:	
T match:	15 4 24 29	, .	
T network:		Tapered line:	
		Testing:	
Adjusting tuner:	24.7	Twinlead:	
Tape measure Yagi	22.22	Velocity factor (VF):	
Direction-finding:		Velocity of propagation:	
Tapered element:		Voltage and current:	
Tapered line:		Zip cord:	
Terminated folded dipole (TFD):	10.20	Transmitter power output (TPO):	1.18
Terminator:	4.28	Transverse electric (TE):	
Texas Potato Masher antenna:	17.2	Transverse magnetic (TM):	
Thrust bearing:		Trap antennas:	
TIA-222 standard:		Losses:	
Tilt angle:		Vertical:	
Tilt-over tower:		W3DZZ:	
Time difference of arrival (TDOA):			
Time-domain reflectometer (TDR):	27.24	W8NX multiband dipole:	
* /		Yagi:	
TLW:		Trees:	
Top loaded vertical:		Anchors:	
Torque compensator:	11.11	Pulleys:	26.7
Tower		Triangulation:	22.19
Assembly:	26.37	Triband Yagis	
Base:	26.19, 26.28	Stacking:	14.39
Climbing shield:		Troposphere:	
Crank-up:		Tropospheric propagation	
Engineering:		Bending:	4.2
Ground and tower crew:		Ducting:	
Guyed:	26.14ff	Scatter:	
House bracket:			4.3
		Troubleshooting	20.7.20.0
Inspection:		Feed system:	
Maintenance:		Measurements:	
Pier-pin base:		Mechanical:	
Preparation:		Records:	
Removing and refurbishing:	26.54	SWR:	28.8, 28.10
Roof-mounted:	26.12	Test steps:	28.2
Selection:	26.16	Yagi antennas:	28.10
Self-supporting:	26.12	Trough reflector:	
Tilt-over:		Tuned feeders:	
Tools:		Tuner:	
Tram (trolley) system:		Turnbuckle:	
Transequatorial propagation:	A 5	Safety wire:	
Transformer	т.Э		
Broadband matching:	24.27	Turnstile antenna:	
		TV antenna conversion:	
Series-section:		TVRO dish antennas:	17.16, 17.25ff
Transmatch:		Twelfth-wave section:	
Transmission lines:		Twilight zone:	
Air insulated:		Twinlead:	23.19
At VHF and UHF:	15.2		
Attenuation:	23.6		
Balun:	24.51	U	
Baluns:		Uda, Dr. Shintaro:	11.1
Characteristic impedance (Z ₀):		UHF connectors:	
Coaxial cable:		Universal stub:	
Current and voltage:		US Geologic Survey (USGS):	14.25
Half-wavelength:		Utility locator service:	74.2J
		Utility locator service:	
Hardline:		Utility pole:	20.9
Impedance matching:			
Impedance transformation:		V	
Input impedance:			
Loss, effect on system:		V-beam antenna:	
Matched:		Steerable, 10-40 meters:	13.16
Matched line loss:	23.6	Vapor wrap:	
Mismatched:	23.5	VE7BQH antenna tables:	15.16

Vector Network Analyzer (VNA):	27.28	Split-bolts:	25.4
Velocity factor (VF):		Strap and braid:	25.2
Measurement:		Tension:	25.3
Velocity of propagation:		Wood antenna materials:	
Transmission lines:	23.3	Wullenweber antenna:	
1.8 to 3.5 MHz using tower:	9 18		
43 foot, multiband:		Y	
Base loading:	9.22	Yagi antennas	
Dipole:		10 meter Yagis:	
Efficiency:		12 meter Yagis:	
Elevated radials:		15 meter Yagis:	
Examples:Fan (multiple vertical antennas):		20 meter Yagis:	
Far field ground reflections:		30 meter Yagis:	
Folded monopole:		40 meter Yagis:	
Ground plane radials:	9.12	50 MHz:	
Ground systems:		At VHF and UHF:	
HF travel antenna:		Bent element:	
Loading techniques:		Beta match:	
Monopoles:		Boom length:	
Multiband:		Cheap Yagis by WA5VJB:	15.27
Over real ground:		Christmas tree stack:	11.26
Shortened:	9.21, 10.22	Construction at VHF and UHF:	15.20
Shortening radials:		Correction for boom diameter:	
Top loading:		Direct feed:	
Trap: Tree mounted HF ground plane:		Direction-finding: Director:	
Vertical dipole:		Driven element:	
Vertical polarization:		Element construction:	
Vertical-beam downtilt:		Element spacing:	
VHF/UHF		Element tuning:	
Antenna polarization:	4.5	End loading:	
Antenna systems:		Feed point impedance:	
Indoor antennas:		Force 12 C-3 tribander: Forward stagger:	
Propagation:		Front-to-back ratio:	
Reliable coverage distances:		Front-to-rear radio:	
Repeater antennas:		Gain:	
Satellite antennas:		Gain/Noise Temperature (G/T):	
Station gain:		High-performance at VHF and UHF:	
Vivaldi antenna:		Impedance matching:	
VOACAP: Voltage balun:		Interlaced elements:	
Vortex shedding:		Linear loading:	
voice shedding.		Loop:	
***		Loop-fed Array (LFA):	
W		Modeling:	11.2
W1AW 80 meter cage dipole:		Monoband designs:	
WSIV ormani		Moxon rectangle:	
W8JK array:		Multiband: Noise reception and sidelobes:	
Waveguide:		Optimization:	
Circular:		OWA, OWL, OWM:	
Coupling:		Parasitic element:	
Mode:	15.57	Portable 15 meter beam:	
Wavelength	2.4	Portable 2-element 20/15/10 meter:	
In soil:	3.4	Portable 6 meter:	
Weatherproofing Connectors:	26.44	Reflector:	
NEMA 4 enclosure:		Self-matched (see also Direct feed):	
Relays and preamplifiers:		Torque compensator:	
Whip antenna, VHF/UHF:	16.7	Trap antenna:	
Wig-wag system:		Troubleshooting:	
Wilkinson divider:		Utility, 144 and 432 MHz:	
Wind load:		Versus quads:	
Windom:	10.7	Yagi, Dr. Hidetsugu: Yield strength:	
Antenna:	25.1	YW:	
Copperweld:		- · · ·	11.2
Hard drawn:		_	
Radials:		Z	
Sag:		Zepp:	
Soft drawn:		End-fed:	
Specifications:		Zip cord antenna:ZS6BKW multiband antenna:	
Splice:	23.4	20001111 munitodia differina.	10.7

Project Index

Bicycle antennas		Quad	
J-poles for VHF and UHF:	16-7	144-MHz 4-Element Quad:	15-47
Direction-finding antennas		Five-element, 26-foot boom Triband Quad:	11-35
Double-Ducky VHF Direction Finder:	22-27	Two-element, 8-foot boom Pentaband Quad:	
Ferrite-core Loop for 160 Meters':		Quagi	
Frame Loop:	22-23	Quagi antennas for 144 through 1296 MHz:	15-41
Simple Direction-Finding System for 80 Meters:	22-27	Receiving antennas	
Tape-Measure Element Yagi for 2 Meters:		K6STI Loop:	22-9
Discone		K9AY Loop:	
VHF/UHF Discone:	15-52	Receiving Loop for 1.8 MHz:	
Filters		Reflector antennas	
144 MHz Duplexer Cavities:	18-11	Corner reflectors for VHF and UHF:	15-54
Indoor antennas		Trough reflectors for 432 and 1296 MHz:	
Attic Screwdriver Antenna:	20-7	Single-band HF antennas	
Indoor Stealth Loop:		1.8 to 3.5 MHz Vertical Using an Existing Tower:	9-18
Slinky Antenna:		C-Pole Vertical:	
Log-periodic		Full-size Loop for 7 MHz:	
Log-periodic for 144, 222, and 432 MHz:	15-51	Ladder-Line Linear-Loaded Dipole:	9-27
TV Antenna Conversion:	15-51	Tower-based Inverted-L:	
Loops	10 01	Vertically Polarized Delta Loop for 14 MHz:	
QRP Transmitting Loop:	20-12	W1AW 80 Meter Cage Dipole:	
Microwave antennas	20 12	Stealth antennas	
12-Foot Stressed Parabolic Dish:	17-28	Attic antenna	
Helix Feed for an Offset-Dish Antenna:		Clothesline antenna:	20-9
Horn Antenna for 10 GHz:		Flagpole antenna:	
Patch Antenna for 23 cm:		Test Instruments	20-7
Periscope Antenna:		Calibration Loads:	27 21
Portable Satellite Antenna Positioning System:		Clamp-on RF Current Probe:	
TVRO Dish Positioning Controller:		Directional Power/SWR Meter:	27 11
Vivaldi Antenna for 1 to 10 GHz:			
Mobile antennas	13-03	High-Power RF Samplers: Inexpensive VHF Directional Coupler:	27-13
	16.7	Downship Field Strongth Matery	27 17
1/4-wavelength Whips for VHF and UHF:		Portable Field Strength Meter: Power absorber:	27-17
Big Wheel for Two Meters:		Reflectometer:	
Halo for Six Meters:		RF Current Meter:	
Screwdriver Antenna for HF:	21-14	RF Step Attenuator:	
40-10 Meter Discone:	10.26	RF Voltmeter:	
		Standard Gain Antenna:	
A-Frame 20-10 Meter Discone:		SWR Resistance Bridge:	
Dual-band Vertical for 80 and 160:		Time-Domain Reflectometer:	21-24
Five-Band Log Periodic Dipole Array:		Transmission lines	24.52
Five-band W3DZZ Trap Antenna:		4:1 Voltage Baluns:	
Four-Wire Steerable V Beam for 10 through 40 Meters: .		Broadband Matching Transformers:	
LPDAs for 3.5 or 7 MHz:		Coiled Coax Choke Baluns:	
Nested Loop Antennas for Multiple Bands:		Detuning Sleeves:	
The Bob Zepp:		High-Power ARRL Antenna Tuner:	
W8NX Multiband, Coax-Trap Dipoles:	10-16	Hybrid Coiled-Coax and Bead Choke Balun:	
Portable antennas	10.11	Quarter/Three-Quarter-Wave Balun:	
Black Widow 15 Meter Beam:		Transmitting Ferrite-Core Choke Baluns:	24-43
Compact 40 Meter Loop for Recreational Vehicles:	400	VHF/UHF miscellaneous antennas	15.6
Five-band portable vertical antenna:		144-MHz, 222-MHz, and 440-MHz Ground-planes:	
HF Vertical Travel Antenna:		50-MHz, 144-MHz, 222-MHz, and 440-MHz J-poles:	
Off-center-end-fed Dipole for 40 to 6 meters:	19-5	Collinear array for 23 cm by F5JIO:	
Portable Inverted V Antenna:		NOAA Satellite Double-Cross Antenna:	
Portable Mast Tripod:		Portable Helix for 435 MHz:	17-13
Portable Two-Element Six Meter Quad:		Yagi	11.00
Portable Whip Dipole:		40 Meter Moxon Rectangle:	
Tree-mounted HF Ground-Plane Antenna:		50 MHz:	
Twinlead Folded Dipole:	19-3	Cheap Yagis for VHF and UHF:	
Two-element 20/15/10 Meter Triband Yagi:	19-10	High-performance Yagis for 50, 144, 222, and 432 MHz: .	15-35
		Loop Yagi for 1296 MHz:	
		Monoband HF Yagis:	
		Utility Yagis for 144 and 432 MHz:	15-24

Author Index

The following authors contributed material new to or referenced by this edition of the *ARRL Antenna Book* or material from previous editions that is included here. Note that in some cases the authors have changed call signs, or have become Silent Keys and their call signs have been reassigned.

Author	Call Sign	Page Ref	Author	Call Sign	Dogo Dof
	K3CXZ	14.20	Ferguson, Tom	Call Sign	Page Ref 14.27
Adler, Dick	N6CA N6CA	15.42	Ford, Steve	WBØDHB	20.1
Angle, Chip	KØBG		· · · · · · · · · · · · · · · · · · ·	WB8IMY WA2ANU	22.27
Applegate, Alan Armstrong, Ted	WA6RNC	9.9			22.15
	W1CF	9.31	Gentges, Frank	KØBRA	24.43
Atchley, Dana Atkins, Bob	KA1GT		Gilbert, Ed Gillette, R. F.	K2SQ W9PE	22.30
Austin, Brian	GØGSF	15.62, 15.67 10.7	Gold, Robert	WBØKIZ	1.18
,		27.22	,	K4VX	
Badger, George Baker, Allen	W6TC KG4JJH	19.11, 20.8	Gordon, Lew Grebenkemper, John	KI6WX	11.28 27.12
Barrett, Lee	K7NM	18.4	Greene, Clarke	K1JX	14.17
Beezley, Brian	K6STI	9.33, 22.8	Grover, F. W.	KIJA	5.14
Belcher, D.	WA4JVE	5.1	Guth, Peter		14.26, 18.2
Belrose, Jack	VE2CV	9.32	Hagn, George		3.4
Beverage, Harold	W2BML	22.3ff	Haigwood, Jerry	W5JH	12.4
Bolljahn, J. T.	W ZDIVIL	10.22	Haines, Geoff	N1GY	20.9
Boyer, Joseph	W6UYH	10.33	Hall, Jerry	K1TD	19.2ff
Bramwell, Denton	K7OWJ	27.15	Hallas, Joel	W1ZR	9.7, 21.24, 24.3ff
Bray, D. W.	K2LMG	4.8	Hallidy, Dave	K2DH	17.1ff
Breakall, Jim	WA3FET	14.20	Hansen, Markus	VE7CA	19.9ff
Breed, Gary	K9AY	10.24, 22.9	Harbach, Allen	WA4DRU	9.9
Britain, Kent	WA5VJB	15.23, 15.66	Hart, Ted	W5QJM	5.21, 20.10ff
Brown, Bruce	W6TWW	21.2	Hauff, Frederick	W3NZ	27.22
Brown, Fred	W6HPH	20.3	Haviland, R. P.	W4MB	3.29, 8.1, 11.30
Brown, Gerald	K5OE	17.2ff	Healy, Rus	K2UA	22.1ff
Brown, Jim	K9YC	20.3, 24.42	Herring, Ron	W7HD	19.4
Buchanan, Chester	W3DZZ	10.15,11.26	Heslin, Robert	K7RTY	15.49
Butler, Don	N4UJW	10.10	Hoch, Gunter	DL6WU	15.27
Buxton, Al	W8NX	10.16	Hollister, Robert	N7INK	19.4
Cadwallader, Joe	K6ZMW	17.12	Hood, Michael	KD8JB	15.8
Cain, Jim	K1TN	12.7	Hopengarten, Fred	K1VR	14.40, 26.15
Cake, Brian	KF2YN	9.11, 20.12	Hunkeler, Noel	F5JIO	15.13
Capon, Robert	WA3ULH	20.12	Hunt, Dale	WB6BYU	22.27
Carcia, Joe	NJ1Q	9.9	Hutchinson, Chuck	K8CH	14.2, 19.6
Caspar, P.	K4HKX	5.1	Jansson, Dick	KD1K	17.1ff
Cebik, L. B.	W4RNL	5.10, 7.1ff, 8.3, 11.33,	Jenkinson, Garth	VK3BBK	23.30
		11.29, 15.20, 15.21,	Johnson, Don	W6AAQ	21.14
		15.49, 16.9	Johnson, Justin	GØKSC	15.30
Cerreto, Bob	WA1FXT	16.9	Johnston, W.	K5ZI	4.26
Collings, Cole	WØYNF	11.28	Jones, Bill	K8CU	10.29
Connelly, Mark	WA1ION	22.13	Karl, Ed	KØKL	18.1ff
Cooper, Clarke	K8BP	19.5	Kaune, Bill	W7IEQ	27.11
Coudé, Roger	VE2DBE	18.2	Keller, J. B.		14.21
Cox, Roger	WBØDGF	7.4, 10.22	Kennedy, Hal	N4GG	12.14
Cunningham, Earl	K6SE	5.10, 9.18, 22.13	King, Tom	KD5HM	27.24
Cutsogeorge, George	W2VJN	24.4ff	Kirby, Tom	W1EJ	15.29
D'Agostino, Philip	W1KSC	15.45	Knadle, Dick	K2RIW	17.28
Danzer, Paul	N1II	16.12	Koontz, Floyd	WA2WVL	22.9
Daso, Don	K4ZA	26.1	Kouyournjian, R. G.		14.22
Demaw, Doug	W1FB	5.10, 9.28, 22.23ff, 27.10	Kraus, John	W8JK	12.21, 17.10
Dietrich, James.	WAØRDX	5.1	Krome, Ed	K9EK	15.25, 17.3
Dixon, Bob	W8ERD	19.12	Krupp, Daniel	W8NWF	10.33
Donovan, Frank	W3LPL	23.30	Lahlum, Robye	W1MK	6.20, 22.1ff
Duffy, Tim	K3LR	9.7	Lambert, Edgar	WA4LVB	10.7
Ehrenfried, Martin	G8JNJ	20.10	Lattin, William	W4JRW	10.15
Ehrhart, Rod	WN8R	9.14	Lau, Zack	W1VT	15.22
Elengo, John	W1DQ	25.3	Lawson, Jim	W2PV	6.6, 11.2ff
Emerson, Darrell	AA7FV	25.3	Lee, Paul		6.16
Emery, Geoff	VK4ZPP	28.1ff	Leeson, Dave	W6NL	8.16, 11.10ff, 11.29,
Evans, Paul	VP9KF	20.2			24.29, 25.8
Fenwick, Richard	K5RR	11.26	Leggio, Joe	WB2HOL	22.30

Author	Call Sign	Page Ref	Author	Call Sign	Page Ref	
Leutzelschwab, Carl	K9LA	4.1ff	Rusgrove, Jay	W1VD	19.3	
Lewallen, Roy	W7EL	6.7, 6.10ff, 11.2	Russell, Thomas	N4KG	9.19	
Littlepage, Joseph	WE5Y	19.3	Salas, Phil AD5X		19.8, 24.11. 26.50	
Loukides, Mike	W1JQ	12.7	Schiller, Tom N6BT		26.39, 28.1ff	
Lux, Jim	W6RMK	26.19	Schmidt, Kevin	W9CF	6.16	
Mallette, Malcolm	WA9BVS	22.23	Schulz, Walter	K3OQF	9.23	
Mallozzi, Dominic	N1DM	5.1ff, 18.1ff, 20.10ff	Severns, Rudy	N6LF	3.1ff, 9.8, 10.24, 12.1ff,	
Malowanchuk, Barry	VE4MA	17.28	2012		21.1ff, 27.30	
Marshall, Joe	WA4EPY	4.5	Sevick, Jerry	W2FMI	3.31, 10.20	
Mata, Jose	EA3VY	22.13	Seybold, Mack	W2RYI	10.33	
Maxwell, Walt	W2DU	3.32	Seydler, Bob	K5GNA	17.18	
McClain, David	N7AIG	23.13	Shuck, Peter	WB2UAQ	27.22	
McCoy, Lew	W1ICP	5.21, 27.18	Shulman, Ivan	WC2S	1.24	
McEneaney, Joe	KG6PCI	21.17	Silver, Ward	NØAX	22.7	
McKim, Jim	WØCY	17.13	Siwiak, Kai	KE4PT	19.5	
Meister, Robert	WA1MIK	27.11	Smith, Woodrow	W6BCX	12.13	
Messenger, George	K6CT	4.5	Spencer, Mark	WA8SME	17.34	
Michaels, Charles	W7XC	3.22	Stanford, John	NNØF	9.25	
Miller, Dennis	KM9O	7.4	Stanley, John	K4ERO	7.1ff, 15.48, 24.11	
Miller, James		17.3	Stockton, Stan	K5GO	25.10	
Mitchell, Bob	N5RM	14.38	Straw, Dean	N6BV	3.21, 4.29, 8.1, 11.2ff,	
Moore, Clarence	W9LZX	11.30			14.7ff, 24.13	
Moore, Sam	NX5Z	13.16	Stroud, Dick	W9SR	16.13	
Morris, Steve	K7LXC	26.1ff	Suding, Robert	WØLMD	17.21	
Moss, T.J.	G3RUH	17.17	Sykes, B	G2HCG	4.5	
Moxon, Les	G6XN	11.29	Tabor, Jim	KU5S	4.37	
Mueller, Dave	N2NL	10.24	Taylor, Joe	K1JT	15.21, 17.1ff	
Muggli, Ken	KØHL	21.16	Terleski, Jay	WXØB	14.39	
Myers, Bob	W1XT	11.26	Thompson, Tom	WØIVJ	27.13	
Neece, Bob	KØKR	24.4	Thrift, Ted	VK2ARA	28.1ff	
Nelson, R. A.	WBØIKN	24.29	Tilton, Ed	W1HDQ	16.13	
Nichols, Steve	GØYKA	201ff	Tolles, H. F.	W7ITB	24.29	
Ordy, Greg	W8WWV W6SAI	8.3	Toman, Don	K2LQ	10.10	
Orr, Bill	N6NB	11.30 15.39	Trask, Chris	N7ZWY	5.16, 5.22	
Overbeck, Wayne Parker, Albert	N4AQ	20.9	Turrin, Dick Uda, Shintaro	W2IMU	27.35 11.1	
Parmley, William	KR8L	19.2	Uhl, John	KV5E	10.29	
Pathak, P. H.	KKOL	14.22	Varney, Louis	G5RV	10.29	
Patterson, Bob	K5DZE	15.50	Wade, Paul	W1GHZ	17.17	
Peterson, Arthur	W7CZB	20.5	Walters, Mike	G3JVL	15.42	
Phelps, Ted	W8TP	20.4	Waltz, M. C.	W2FMQ	3.31	
Pietraszewski, David	K1WA	9.7	White, Ian	GM3SEK	15.13	
Pittard, Ross	VK3CE	28.1ff	Wilkie, Jim	WY4R	10.7	
Portune, John	W6NBC	17.10, 19.7	Williams, Tom	WA1MBA	23.30	
Powlishen, Steve	K1FO	15.27	Wilson, Paul	W4HHK	15.51, 15.59	
Rauch, Tom	W8JI	6.16, 6.22, 6.35,	Wilson, Robert	AL7KK	10.24	
		22.8, 27.2	Windom, Loren	W8GZ	10.7	
Regier, Frank	OD5CG	24.22	Witt, Frank	AI1H	24.35, 24.41	
Rhea, Randy		24.24	Wolff, Ken	K1EA	14.30	
Richard, Louis	ON4UF	10.10	Wright, Joe	W4UEB	10.7	
Richardson, Don	K6MHE	16.3	Yagi, Hidetsugu		11.1	
Rockwell, Paul	W3AFM	14.17	Yang, Richard		27.39	
Rohde, Ulrich	N1UL	22.15	Yates, Steve	AA5TB	10.3	
Romander, Hugo	W2NB	12.4	Young, Joel		14.20	
Ruperto, Eugene	W3KH	17.10	-			
_ _						

FEEDBACK

We're interested in hearing your comments on this book and what you'd like to see in future editions. Please email comments to us at pubsfdbk@arrl.org, including your name, call sign, email address and the title, edition and printing of this book. Or you can copy this form, fill it out, and mail to ARRL, 225 Main St, Newington, CT 06111-1494.

Where did you purchase this book? Li From ARRL directly				J From an ARRL dealer				
Is there a deal	er who carries AR	RL publication	s within:					
□5 miles	□15 miles	□30 miles	of your locati	ion? [Not sure.			
License clas	SS:							
□Novice	☐ Technician	☐ Technicia	n with code	☐ Gene	ral □ Adv	vanced	☐ Amate	eur Extra
Name					_ ARRL me	mber? □	Yes □No	
					C	all Sign _		
Address								
City, State/Prov	rince, ZIP/Postal C	ode						
Daytime Phone	()				A	ge		
If licensed, how	/ long?							
Other hobbies				E-mail				
						For ARRL	. use only	2016 ANT
Occupation								25 26 27 28 29
						Finding	123450	6789101112