



A CASE STUDY

5½

CS/COE 0449
Introduction to
Systems Software

wilkie

Spring 2019/2020

HISTORY AND OVERVIEW

I swear C is not really as hellish as this makes it seem.

Basic information

- First published as a mail-order shareware title in 1993 by Id Software; published by Apogee.
- A gritty-for-its-era early first-person action video game eventually defining the First-Person-Shooter genre (FPS)
- You play as a lone space marine in a survival-horror setting, albeit cartoony by today's standards, attempting to get to the exit of each level.



Yes, it was distributed on save icons

- DOOM originally came via mail-order purchase on four high-density floppy disks, a relatively large number at the time.
 - 1.44MB (or 1.41MiB) per disk is still quite the constraint.
 - Some modern websites download more data just to load their front page.
 - Yes. I have... every single version they ever released. On disks. Shut up.



An evergreen controversy

- Although cartoony today, the game's violent aesthetic stood alone upon release causing a stir still reverberating today.
 - The violence and satanic depictions throughout the game caused a stir among more conservative crowds.
 - The game was famously used by now-disgraced lawyer and activist Jack Thompson in his effort to highlight a possible (likely slightly true) correlation between games and real-world violent acts.
 - It was also infamously referenced by at least one of the perpetrators of the Columbine school shooting who was an avid player of the game.
 - It was one of the most popular games of its time... so that's not saying much.



Me, when I get
a migraine

Indeed, we have many good modern ports!

I don't have a real good guess at how many people are going to be playing with this, but if significant projects are undertaken, it would be cool to see a level of community cooperation. I know that most early projects are going to be rough hacks done in isolation, but I would be very pleased to see a coordinated 'net release of an improved, backwards compatible^{*} version of DOOM on multiple platforms next year.

Have fun.

John Carmack

12-23-97

^{*} John's typo, not mine. Spell-checking cost extra back then.

Free and Open Source: “It Runs Doom”

- The DOOM source code has long been available to anyone since late 1997 and under an aggressively open license (GPL) since 1999.
 - Mirrored on GitHub: <https://github.com/id-Software/DOOM/tree/master/linuxdoom-1.10>
 - The modern port is GZDoom: <https://zdoom.org/downloads>
- The availability has allowed it to be studied by academics such as myself.
 - And it has been ported to ATMs and such because why not. “It Runs Doom”
 - It lives forever, essentially, as is the power of the open-source community.

Doom running on a (decommissioned) bank ATM



THE DESIGN


A multi-dimensional illusion in a game about teleporter mishaps. Fun!

The game, at a high-level

- A faux-3D textured environment.
 - Controlled movement only happens on X and Y axis (That is, no jumping.)
 - No slopes. All walls come to right angles with floors and ceilings.
- Fixed angle of view. Cannot look up or down or tilt the “camera.”
 - However, you can ascend vertically via stairs or simple elevators.
- Monsters populate each level and have minor intelligence to follow you by sight or sound and attack you or other monsters.
 - When monsters are struck by another’s projectile, they start attacking each other. Called “monster infighting”.
- Items populate the level and are picked up by colliding with them.
 - These include common genre tropes: ammo, health, armor.

Faux-3D Simplicity

- Level is 2D
 - Simplifies a lot of geometry math.



- Goal: Get to exit.

First level of Doom (E1M1) via doomwiki.org

LAYOUT AND CONVENTIONS

This showcases some weird C styling generally for greater speed/portability.

Coding Style

```
//  
// A_TroopAttack  
//  
void A_TroopAttack (mobj_t* actor)  
{  
    int damage;  
  
    if (!actor->target)  
        return;  
  
    A_FaceTarget (actor);  
    if (P_CheckMeleeRange (actor))  
    {  
        S_StartSound (actor, sfx_claw);  
        damage = (P_Random()%8+1)*3;  
        P_DamageMobj (actor->target, actor, actor, damage);  
        return;  
    }  
  
    // launch a missile  
    P_SpawnMissile (actor, actor->target, MT_TROOPSHOT);  
}
```

- **UpperCase function names.**
 - A_ prefix denotes subsystem or category.
- **Allman/BSD style**
 - Braces on their own line.
- **ANSI C (C89) dialect.**
 - Variables declared at top.
- **Passes arguments by-ref**
 - Avoids return values often.
 - Prefers pointers to structs.

Header files and global variables...

doomdef.h

```
// Game mode handling - identify IWAD version
// to handle IWAD dependend animations etc.
typedef enum
{
    shareware,    // DOOM 1 shareware, E1, M9
    registered,   // DOOM 1 registered, E3, M27
    commercial,   // DOOM 2 retail, E1 M34 retail,
                  // DOOM 1 retail, E4, M36
    indetermined  // Well, no IWAD found.
} GameMode_t;
```

doomstat.h

```
// -----
// Game Mode - identify IWAD as shareware,
// retail etc.
extern GameMode_t gamemode; // Says there is a
                             // gamemode variable
                             // somewhere...
```

doomstat.c

```
GameMode_t gamemode; // The ACTUAL gamemode variable
```

- Separating C code into multiple files:
 - *.h files contain types/enums and function declarations.
 - *.c files will contain function implementations.
- The `extern` defines a global variable.
 - It makes it available to other C files without declaring it twice.
 - It declares it once (without `extern`) in the corresponding C file.
 - Therefore, it shares the data.

Header files and global variables...

g_game.h

```
//  
// GAME  
//  
void G_DeathMatchSpawnPlayer (int playernum);  
  
void G_InitNew (skill_t skill, int episode, int map);  
  
// Can be called by the startup code or M_Responder,  
// calls P_SetupLevel or W_EnterWorld.  
void G_LoadGame (char* name);  
  
void G_DoLoadGame (void);  
  
// Called by M_Responder.  
void G_SaveGame (int slot, char* description);  
  
void G_ExitLevel (void);  
void G_SecretExitLevel (void);  
  
void G_WorldDone (void);
```

- Separating C code into multiple files:
 - *.h files contain types/enums and function declarations.
 - *.c files will contain function implementations.
- You can declare functions without implementations.
 - Typically for header files.
 - Implement them in their *.c file.
 - g_game.c in this case
 - Including this header file will allow use of this function.

Header files and global variables...

g_game.c

```
// wilkie's note: remember boolean isn't defined by C!
```

```
boolean      secretexit;
```

```
// wilkie's note: gameaction_t defined elsewhere
```

```
gameaction_t gameaction;
```

```
void G_ExitLevel (void)
```

```
{
```

```
    secretexit = false;
```

```
    gameaction = ga_completed;
```

```
}
```

```
// Here's for the german edition.
```

```
void G_SecretExitLevel (void)
```

```
{
```

```
    // IF NO WOLF3D LEVELS, NO SECRET EXIT!
```

```
    if ( (gamemode == commercial)
```

```
        && (W_CheckNumForName("map31")<0))
```

```
        secretexit = false;
```

```
    else
```

```
        secretexit = true;
```

```
    gameaction = ga_completed;
```

```
}
```

- Here we see the implementations of some of the functions.
 - Doom likes its private global data!
 - No file in the Doom source code defines `secretexit` as `extern` so only this file can use it!
- Cultural artifacts become code.
 - Code reflects culture.
 - The secret levels in Doom are in the style of their earlier WWII-era game, Wolfenstein 3D.
 - They need to special case some code because German law does not allow Nazi imagery.

Bugs happen to all of us...

d_main.c

```
#include "doomdef.h"
#include "doomstat.h"
#include <unistd.h> // for 'access'
#include <stdlib.h> // for 'getenv'
#include <stdio.h> // for 'sprintf'
```

```
// Checks availability of IWAD files by name,
// to determine whether registered/commercial features
// should be executed (notably loading PWAD's).
```

```
void IdentifyVersion (void) {
```

```
    char* doom1wad;
    char* plutoniawad;
    char* doomwaddir = getenv("DOOMWADDIR");
```

```
    if (!doomwaddir)
        doomwaddir = ".";    sprintf is like printf,
                             but prints to a buffer.
```

```
    // Shareware.
```

```
    doom1wad = malloc(strlen(doomwaddir)+1+9+1);
    sprintf(doom1wad, "%s/doom1.wad", doomwaddir);
```

```
    // Bug, dear Shawn.
```

```
    // Insufficient malloc, caused spurious realloc errors.
```

```
    plutoniawad = malloc(strlen(doomwaddir)+1+/*9*/12+1);
    sprintf(plutoniawad, "%s/plutonia.wad", doomwaddir);
```

```
if ( !access (plutoniawad, R_OK ) )
{
    gamemode = commercial;    checks if file exists
    D_AddFile (plutoniawad);    (0 on success)
    return;
}
```

```
if ( !access (doom1wad,R_OK) )
{
    gamemode = shareware;    sets the gamemode global
    D_AddFile (doom1wad);
    return;
}
```

- Apparently, somebody corrected Shawn Green's copy-and-paste of malloc.
 - It was not allocating enough space for the string copy!
 - Try not to copy and paste!!

The culture of bug hunting

- A person that studies insects is called an entomologist.
 - However, the first documented case of a real-life insect causing an error in a computer was a moth. A story chronicled by Grace Hopper.
 - Somebody who studies moths/butterflies is called a lepidopterist.
 - (This will not be on the exam)
- Ok... ok... the word bug in engineering is hundreds of years old.
 - We're not sure where it actually comes from.
 - However, today, we call the modern bug hunter a "speedrunner."
- It's a bit of an artform of its own these days.



The fear of moths is called Mottephobia.

Looking at things at another angle...



4shockblast, E1M1 UV/Pacifist, 0:08s - Record set in 2019 after 22 years unbroken

<https://www.youtube.com/watch?v=1UkeFwJ-yHI>

- Consider:

- In what weird way is the player moving?
- Do you believe this to be intentional? Why might that be faster?

SPEEDRUNNING

Gotta go fast. Speedrunning is just a mistake made beautiful.

Going fast is not always “straight-forward”

- If you notice from the video, the speedrunner is running at an angle.
 - This allows them to move at a higher speed.
- To figure out why this works, we can consult the source code.
- First, some information:
 - Doom lets you move forward and backward and turn left and right.
 - There is also the ability to use keys to strafe left and right instead.
 - Strafing moves you side by side (like a crabwalk)
- Let's see how Doom implements movement!

We're drifting in two directions

p_user.c

```
boolean onground;
```

```
//
```

```
// P_MovePlayer
```

```
//
```

```
void P_MovePlayer (player_t* player)
```

```
{
```

```
    ticcmd_t*    cmd;
```

```
    cmd = &player->cmd;
```

```
    player->mo->angle += (cmd->angleturn<<16);
```

```
    // Do not let the player control movement
```

```
    // if not onground.
```

```
    onground = (player->mo->z <= player->mo->floorz);
```

```
    if (cmd->forwardmove && onground)
```

```
        P_Thrust (player, player->mo->angle, cmd->forwardmove*2048);
```

```
    if (cmd->sidemove && onground)
```

```
        P_Thrust (player, player->mo->angle-ANG90, cmd->sidemove*2048);
```


```
}
```

The 2048 is a scalar; to avoid floating point! ↗

- First, it makes sure the player is on the ground.
- If so, and you are pressing “forward” move the player forward!
- If so, and you are pressing “strafe” (sidemove), move the player sideways!
- Wait! What if both happen?

What's the Hypotenuse

- Holding both forward and strafe keys down moves the player.
- These are both independent movement.
 - The `cmd->forwardmove` is, at most, 50
 - The `cmd->sidemove` is, at most, 40
 - (These are set in `g_game.c`)
- Therefore, you are moving:
 - 50 units forward
 - 40 units sideways
 - Hence, we call this trick “strafe 40” or SR-40
- For a total speed of:
 - 64 units/second



Can we do better?

- Doom lets you use a single key to strafe left and right.
- It also lets you press a toggle to repurpose the left and right keys.
 - So, if you press this “strafe toggle” key, left and right no longer turn you.
 - They strafe you.
- Let's look at the Doom code for how this is implemented.

Let's go even faster!

g_game.c

```
#define MAXPLMOVE 50
```

```
void G_BuildTiccmd (ticcmd_t* cmd) {
```

```
    boolean strafe;
```

```
    int      speed;
```

```
    int      forward;
```

```
    int      side;
```

← **Whether or not the "strafe toggle" is on**

```
    strafe = gamekeydown[key_strafe];
```

```
    speed = gamekeydown[key_speed];    // The "run" button
```

```
    forward = side = 0;
```

```
    // let movement keys cancel each other out
```

if (strafe) { ← **If so, "right" strafes right.**

```
    if (gamekeydown[key_right]) {
```

```
        side += sidemove[speed];    // This is 40
```

```
    }
```

```
    if (gamekeydown[key_left]) {
```

```
        side -= sidemove[speed];
```

```
    }
```

} ← **I removed the else which turned the player**

```
    if (gamekeydown[key_up])
```

```
        forward += forwardmove[speed];
```

```
    if (gamekeydown[key_down])
```

```
        forward -= forwardmove[speed];
```

← **The normal strafe key.**

```
    if (gamekeydown[key_straferight])
```

```
        side += sidemove[speed];    // This is 40
```

```
    if (gamekeydown[key_strafeleft])
```

```
        side -= sidemove[speed];
```

```
    if (forward > MAXPLMOVE)
```

```
        forward = MAXPLMOVE;
```

```
    else if (forward < -MAXPLMOVE)
```

```
        forward = -MAXPLMOVE;
```

```
    if (side > MAXPLMOVE)
```

```
        side = MAXPLMOVE;    // What is this, at most?
```

```
    else if (side < -MAXPLMOVE)
```

```
        side = -MAXPLMOVE;
```


```
    cmd->forwardmove += forward;
```

```
    cmd->sidemove += side;
```

```
}
```

What's the Hypotenuse (revisited)

- Forward and both types of strafe moves the player very quickly.
- These are both independent movement.
 - The `cmd->forwardmove` is, at most, 50
 - The `cmd->sidemove` is now, mistakenly, 50
 - (These are set in `g_game.c`)
- Therefore, you are moving:
 - 50 units forward
 - 50 units sideways
 - Hence, we call this trick “strafe 50” or SR-50
- For a total speed of:
 - 71 units/second




Out-running Rockets: GOING FASTER STILL



The WALLRUN.LMP demo file from E2M8.
<https://www.youtube.com/watch?v=xJ7PgOJKbEk>

The “Wall Run”

- The reason behind this behavior was unknown for quite some time.
- However, the wall-run has to do with improper collision handling.
- When you hit a wall, you slide along it.
 - There is some friction (you should SLOW down)
 - And some code to carry your momentum along the angle of the wall. (a vector projection)
- However, for certain walls it speeds up.
 - Going exactly north along a wall.
 - Going exactly east along a wall.



Intended Behavior

Let's go even faster!

- This function moves objects given their momentum.

p_mobj.c

```
#define MAXMOVE 30
```

```
void P_XYMovement (mobj_t* mo) {
```

```
    fixed_t  ptryx; // Position-try-x,  
    fixed_t  ptryy; // "-try-y: The possible new position  
    fixed_t  xmove; // Amount to move along x  
    fixed_t  ymove; // Amount to move along y
```

```
    if (mo->momx > MAXMOVE)  
        mo->momx = MAXMOVE;  
    else if (mo->momx < -MAXMOVE)  
        mo->momx = -MAXMOVE;
```

```
    if (mo->momy > MAXMOVE)  
        mo->momy = MAXMOVE;  
    else if (mo->momy < -MAXMOVE)  
        mo->momy = -MAXMOVE;
```

```
    xmove = mo->momx;  
    ymove = mo->momy;
```


When moving quickly, it moves half-way twice. →

However, the slide-along-walls function did not get the memo! →

```
do {  
    if (xmove > MAXMOVE/2 || ymove > MAXMOVE/2) {  
        ptryx = mo->x + xmove/2; // Move half-way  
        ptryy = mo->y + ymove/2;  
        xmove >>= 1; // Divides by two,  
        ymove >>= 1; // we move this much next time  
    }  
    else {  
        ptryx = mo->x + xmove; // Move the  
        ptryy = mo->y + ymove; // whole way.  
        xmove = ymove = 0; // We are done moving  
    }  
  
    if (!P_TryMove (mo, ptryx, ptryy)) {  
        // blocked move  
        if (mo->player) {  
            // try to slide along it  
            P_SlideMove (mo);  
        }  
        else  
            mo->momx = mo->momy = 0;  
    }  
} while (xmove || ymove);
```

The “Wall Run” visualized

- When going North or East, you’ve maximized your X or Y momentum respectively.
- Going slightly north-east also works, but your momentum is, then, slightly split along X and Y.
 - This code looks at each momentum individually.
- When the slide function is called twice with your original momentum... it causes...
... well ... dramatic results.
- We call this an “Oops” in the trade.



Unintended Behavior

Hmm, only North? Only East? Oh... Oops!

- This function moves objects given their momentum.

p_mobj.c

```
#define MAXMOVE 30
```

```
void P_XYMovement (mobj_t* mo) {
```

```
    fixed_t  ptryx; // Position-try-x,  
    fixed_t  ptryy; // "-try-y: The possible new position  
    fixed_t  xmove; // Amount to move along x  
    fixed_t  ymove; // Amount to move along y
```

```
    if (mo->momx > MAXMOVE)  
        mo->momx = MAXMOVE;  
    else if (mo->momx < -MAXMOVE)  
        mo->momx = -MAXMOVE;
```

```
    if (mo->momy > MAXMOVE)  
        mo->momy = MAXMOVE;  
    else if (mo->momy < -MAXMOVE)  
        mo->momy = -MAXMOVE;
```

```
    xmove = mo->momx;  
    ymove = mo->momy;
```



Momentum can be negative, yet...

How many times does this get called when momentum is VERY positive? And, VERY negative?

```
do {  
    if (xmove > MAXMOVE/2 || ymove > MAXMOVE/2) {  
        ptryx = mo->x + xmove/2; // Move half-way  
        ptryy = mo->y + ymove/2;  
        xmove >>= 1; // Divides by two,  
        ymove >>= 1; // we move this much next time  
    }  
    else {  
        ptryx = mo->x + xmove; // Move the  
        ptryy = mo->y + ymove; // whole way.  
        xmove = ymove = 0; // We are done moving  
    }  
  
    if (!P_TryMove (mo, ptryx, ptryy)) {  
        // blocked move  
        if (mo->player) {  
            // try to slide along it  
            P_SlideMove (mo);  
        }  
        else  
            mo->momx = mo->momy = 0;  
    }  
} while (xmove || ymove);
```

The “Wall Run” visualized

- The closer you are to the wall and the
 - The more like Sonic the Hedgehog you become.



Here I am at the end...
Ruining my slides...

I can't believe this is 10 years old.

VERY Unintended Behavior

CLOSING REMARKS

“I have not failed. I've just found 10,000 ways that won't work.”

— An elephant murderer talking about other people's work

Are we DOOMed to fail?

- In the end, I want to pass off some key knowledge nuggets:
 - Perfect code is an illusion used to sell textbooks.
- We have gained more from these mistakes than if they weren't there: art, culture, and enjoyment.
 - The speedrunning community finds art in our mistakes.
 - Fixing them does not improve the art, just hints at our vanity.
 - The art culture around failure is not about judgement, but exploration.
- Do not come out of this course thinking perfection is the goal.
 - Mistakes in C can be costly for kernels, etc... sure.
 - However, in your day-to-day life, know that often these small mistakes are certainly common at all levels of skill. They can be fixed. They can be fun.
- **So, have fun writing and reading code!**