SAT Solving with Conflict Driven Clause Learning

William Schultz

CS 7240 Final Project

April 27, 2022

Overview and Project Goals

- Satisfiability is the canonical NP-complete problem.
- Much work has been devoted to building efficient SAT solvers over last decades.
- Project Goal: Implement a basic SAT solver based on conflict driven clause learning (CDCL), the dominant core technique used in modern solvers.
 - Gain a deeper understanding of the DPLL and CDCL based algorithms for SAT solving
 - Use as a platform for potentially exploring new SAT solving techniques
 - E.g. learning heuristics using a data-driven approach, extending methods of CrystalBall [SKM19]

The SAT problem:

Given a boolean formula in conjunctive normal form, determine whether there exists an assignment to the variables of the formula that makes the overall formula true.

The SAT problem:

Given a boolean formula in conjunctive normal form, determine whether there exists an assignment to the variables of the formula that makes the overall formula true.

e.g.

$$(x_1 \vee x_2) \wedge (\neg x_3 \vee \neg x_1)$$

The SAT problem:

Given a boolean formula in conjunctive normal form, determine whether there exists an assignment to the variables of the formula that makes the overall formula true.

e.g.

$$(x_1 \lor x_2) \land (\neg x_3 \lor \neg x_1)$$

SAT, with
$$\{x_1 = 1, x_2 = 0, x_3 = 0\}$$
.

The SAT problem:

Given a boolean formula in conjunctive normal form, determine whether there exists an assignment to the variables of the formula that makes the overall formula true.

e.g.

$$(x_1 \vee x_2) \wedge (\neg x_3 \vee \neg x_1)$$

SAT, with
$$\{x_1 = 1, x_2 = 0, x_3 = 0\}$$
.

CNF notation:

$$\{\{x_1,x_2\},\{\neg x_3,\neg x_1\}\}$$



DPLL: SAT as Search

- A basic approach to solving SAT is to view it as a search problem over possible assignments.
- This is the basis of the Davis-Putnam-Logemann-Loveland (DPLL) algorithm [DLL62]
- Basic idea of DPLL is to do a depth first, brute force search with backtracking along with some basic formula simplification as you go.
 - Also employs the unit propagation rule

 Core simplification rule employed in DPLL, and also in CDCL as we will see later.

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A *unit clause* is a clause that contains exactly one literal.

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}\$$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}\$$

 $\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}\$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\} \\
 \{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\} \\
 \{\{\neg c\}, \{c, \neg d\}\} \\
 \{\{\neg c\}, \{c, \neg d\}\} \\
 \{\{\neg d\}\}$$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg d\}\}$$

- Core simplification rule employed in DPLL, and also in CDCL as we will see later.
- A unit clause is a clause that contains exactly one literal.
- If a CNF formula contains a unit clause then we can apply unit propagation i.e. set that literal to the appropriate truth value to satisfy its clause e.g.

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{b\}, \{\neg b, \neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg c\}, \{c, \neg d\}\}$$

$$\{\{\neg d\}\}$$


$$\{\{\neg d\}\}$$

$$\{\}$$

$$\{SAT)$$


DPLL: Example

$$\{\neg a, b\}
\{\neg b, \neg c\}
\{\neg c, \neg d\}$$




DPLL: Example

$$\{\neg a, b\}
\{\neg b, \neg c\}
\{\neg c, \neg d\}$$



DPLL: Example

$$\{\neg a, b\}
\{\neg b, \neg c\}
\{\neg c, \neg d\}$$



• DPLL is a rather naive algorithm

- DPLL is a rather naive algorithm
- An extension to this basic framework is to learn from conflicts


- DPLL is a rather naive algorithm
- An extension to this basic framework is to learn from conflicts
- When you encounter a conflict in the search tree, *learn* a clause that prevents you from making the similar mistakes again

- DPLL is a rather naive algorithm
- An extension to this basic framework is to learn from conflicts
- When you encounter a conflict in the search tree, *learn* a clause that prevents you from making the similar mistakes again
- This fundamental approch is known as conflict-driven clause learning (CDCL) and started being employed in SAT solvers around the late 90s and early 2000s.

- DPLL is a rather naive algorithm
- An extension to this basic framework is to learn from conflicts
- When you encounter a conflict in the search tree, learn a clause that prevents you from making the similar mistakes again
- This fundamental approach is known as conflict-driven clause learning (CDCL) and started being employed in SAT solvers around the late 90s and early 2000s.
- In addition, employ non-chronological backtracking

CDCL

- When using CDCL, if a conflict is encountered, we not only backtrack to the previous level, as in DPLL
- We try to learn a *conflict clause* along with a *backjump* level, which determines how far back in the search tree to unwind to.







Figure: Termination tree using standard DPLL.

9/15







Figure: Termination tree using standard DPLL.

9/15






Figure: Termination tree using standard DPLL.

9/15

- ullet From basic DPLL traversal we can see that there is no satisfying assignment where a=1
- But, we could have learned earlier on that this was an unfruitful section of the search space
- Idea is to analyze the conflict the occurred from partial assignment $\{a=1,b=1,c=1,x=1\}$

CDCL: Implication Graph

- Can represent the propagation of variable assignments in an implication graph
- Nodes of this graph represent variable assignments made in the current search path
- Edges correspond to dependencies between these assignments.

SAT Solver Implementation

- Iimplementing my own CDCL SAT solver as a framework for exploring future potential SAT enhancements
- Around 1500 lines of C++, tested on a variety of easy to medium SAT benchmark problems
- https://github.com/will62794/mysat

Evaluation

 Some performance results of my SAT solver against a performant, modern solver.

Future Extensions

- Resolution proofs
- Variable ordering heuristics
- Learning heuristics
- Learning end to end SAT solver (neuroSAT)

Questions?

Martin Davis, George Logemann, and Donald Loveland.

A machine program for theorem-proving.

Commun. ACM, 5(7):394–397, jul 1962.

Mate Soos, Raghav Kulkarni, and Kuldeep S. Meel. CrystalBall: Gazing in the Black Box of SAT Solving.

In Mikoláš Janota and Inês Lynce, editors, *Theory and Applications of Satisfiability Testing – SAT 2019*, pages 371–387, Cham, 2019. Springer International Publishing.