Buoy 62091 - 2024 Quality Control Report

Generated: 2025-08-19 23:48:23

Generated: 2025-08-19 23:48:23

Data Overview

• Station ID: 62091 • Year: 2024

• Total Records: 14,468

• Time Range: 2024-01-01 00:00:00 to 2024-10-30 23:00:00

• Duration: 303 days • Sensors/Loggers: 4 active

- 12105_CR6: 5,944 records (41.1%) - 7577_CR6: 5,943 records (41.1%) - 347_Wavesense: 1,292 records (8.9%)

- 8704_CR6: 1,289 records (8.9%)

Quality Control Results

Record-Level QC Status

- **QC complete:** 11,301 records (78.1%) - **No QC performed:** 3,167 records (21.9%)

Parameter-Level QC Results

Parameter	Total	Missing	Range Fail	Spike Fail	Flat Line Fail	Passed	Pass Rate
airpressure	14,468	0	0	1	17	14,450	99.9%
airtemp	14,468	0	0	0	392	14,076	97.3%
humidity	14,468	0	0	3	220	14,245	98.5%
windsp	14,468	0	0	0	30	14,438	99.8%
winddir	14,468	0	0	225	12	14,231	98.4%
hm0	14,468	0	0	0	2,806	11,662	80.6%
hmax	14,468	0	0	0	1,294	13,174	91.1%
tp	14,468	0	0	74	155	14,239	98.4%
mdir	14,468	0	0	352	6	14,110	97.5%
seatemp_aa	14,468	0	0	0	82	14,386	99.4%

Issues Identified

- airpressure: 1 spike values (>10.0 change)

- airpressure: 17 flat line values (5+ consecutive identical) - airtemp: 392 flat line values (5+ consecutive identical)

- humidity: 3 spike values (>20.0 change)

- humidity: 220 flat line values (5+ consecutive identical) - windsp: 30 flat line values (5+ consecutive identical)

- winddir: 225 spike values (>180.0 change)

- winddir: 12 flat line values (5+ consecutive identical)
- hm0: 2806 flat line values (5+ consecutive identical)
- hmax: 1294 flat line values (5+ consecutive identical)
- tp: 74 spike values (>10.0 change)
- tp: 155 flat line values (5+ consecutive identical)
- mdir: 352 spike values (>180.0 change)
- mdir: 6 flat line values (5+ consecutive identical)
- seatemp_aa: 82 flat line values (5+ consecutive identical)

QC Limits Applied

Station-specific QC limits used for this analysis:

Parameter	Min Value	Max Value	Spike Threshold	Notes
airpressure	950.0	1050.0	10.0	Default
airtemp	-20.0	40.0	5.0	Default
humidity	0.0	100.0	20.0	Default
windsp	0.0	60.0	20.0	Station-specific
winddir	0.0	360.0	180.0	Default
hm0	0.0	18.0	4.0	Station-specific
hmax	0.0	30.0	6.0	Station-specific
tp	1.0	25.0	10.0	Default
mdir	0.0	360.0	180.0	Default
seatemp_aa	4.0	18.0	2.0	Station-specific

Data Visualization

QC Failure Color Coding

The visualization uses different colors to distinguish QC failure types:

- **Blue dots**: Good data (passed all QC tests)
- **Red dots**: Range failures (values outside physical limits)
- **Orange dots**: Spike failures (unrealistic sudden changes)
- **Purple dots**: Flat line failures (sensor stuck/malfunctioning)

The bottom-right panel shows a stacked bar chart with the percentage breakdown of each QC result type per parameter.

Recommendations

Manual QC Actions Needed

- 1. **Review flagged extreme values** validate against weather events
- 2. **Investigate sensor failures** replace/repair faulty sensors
- 3. **Cross-validate between loggers** compare duplicate measurements
- 4. **Apply sensor hierarchy** prioritize Wavesense for hm0, Datawell for hmax
- 5. **Transfer to production** move QC'd data to irish_buoys_fugro table

Next Steps

- 1. Execute parameter-level QC SQL commands from readme.md
- 2. Perform individual value corrections for flagged data
- 3. Complete record-level QC marking
- 4. Transfer approved data to production table

Data Visualization



QC Failure Color Coding

- Blue dots: Good data (passed all QC tests)
- Red dots: Range failures (values outside physical limits)
- Orange dots: Spike failures (unrealistic sudden changes)
- Purple dots: Flat line failures (sensor stuck/malfunctioning)

The bottom-right panel shows a stacked bar chart with percentage breakdown of each QC result type per parameter.