



Select a definition

V2 Transaction API

V2 Transaction API

v2-transaction OAS 2.0

/swagger/v2-transaction/swagger.json

This is version V2 of the Intuiflow Scheduling Transaction WebApi.

The main goal of this API is to transact orders.

Have a need or an idea for us? If there is an API you need that isn't available in the customer-facing V2 interface, please contact us at [Demand Driven Tech Support](#) with a description of your integration needs.

Authorize



Transactions



GET

/api/v2/scheduling/orders/{schedulingOrderId}/transactions

Gets all transactions for the scheduling order specified by schedulingOrderId



POST

/api/v2/scheduling/orders/{schedulingOrderId}/transactions
/{operationSequenceNumber}/complete

Posts a complete transaction entry to a scheduling order specified by schedulingOrderId



POST

/api/v2/scheduling/orders/{schedulingOrderId}/transactions
/{operationSequenceNumber}/receive

Posts a receive transaction entry to a scheduling order specified by schedulingOrderId



POST

/api/v2/scheduling/orders/{schedulingOrderId}/transactions
/{operationSequenceNumber}/start

Posts a start transaction entry to a scheduling order specified by schedulingOrderId



POST

/api/v2/scheduling/orders/{schedulingOrderId}/transactions/voidall

Marks all transactions for a scheduling order by schedulingOrderId void or not void. This action is taken only if the order is not closed, otherwise the request is ignored.



GET

/api/v2/scheduling/orders/transactions

Gets all transactions for the scheduling order specified by orderNumber, partNumber, revision and location



Parameters

Try it out

Name	Description
orderNumber * required string (query)	An existing scheduling order number orderNumber
partNumber * required string (query)	The part number of the scheduling order partNumber
location * required string (query)	The location of the scheduling order location
revision string (query)	The revision of the part number revision
withRoot boolean (query)	Add a root element when mime type is 'application/json' <i>Default value</i> : false false

Responses

Response content type

application/json

Code	Description
200	OK
	Example Value Model <pre>[{ "Id": 0, "OrderNumber": "string", "ScheduleOrderId": 0, "OperationSequenceNumber": 0, "EntryDate": "2026-02-14T17:56:04.664Z", "EntryType": "string", "Quantity": 0, "IsLastBatch": true, "Notes": "string", "Voided": true, "PartNumber": "string", "Revision": "string", "Location": "string", "Resource": "string" }]</pre>

POST

/api/v2/scheduling/orders/transactions/{operationSequenceNumber}/complete
Posts a complete transaction entry to a scheduling order specified by orderNumber, partNumber, revision and location.



Parameters

Try it out

Name

Description

operationSequenceNumber * required

integer(\$int32)
(path)

An operation sequence number in the rope of the scheduling order, use MAXINT for the final buffer operation

operationSequenceNumber

orderNumber * required

string
(query)

An existing scheduling order number

orderNumber

partNumber * required

string
(query)

The part number of the scheduling order

partNumber

location * required

string
(query)

The location of the scheduling order

location

revision

string
(query)

The revision of the part number

revision

body * required

object
(body)

Example Value Model

```
{
  "Quantity": 0,
  "IsLastBatch": true,
  "DoBackFill": true,
  "Notes": "string"
}
```

Parameter content type

application/json

Responses

Response content type

application/json

Code	Description
200	OK Example Value Model <pre>{ "EntityID": "string", "ValidationErrors": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": ["string"] }, "ValidationWarnings": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": ["string"] }, "IsNewEntity": true, "IsValid": true}</pre>
POST	/api/v2/scheduling/orders/transactions/{operationSequenceNumber}/receive Posts a receive transaction entry to a scheduling order specified by orderNumber, partNumber, revision and location 
Parameters Try it out	
Name	Description
operationSequenceNumber * required integer(\$int32) (path)	An operation sequence number in the rope of the scheduling order, use MAXINT for the final buffer operation operationSequenceNumber
orderNumber * required string (query)	An existing scheduling order number orderNumber
partNumber * required string (query)	The part number of the scheduling order partNumber

Name		Description
location * required string (query)		The location of the scheduling order location
revision string (query)		The revision of the part number revision
body * required object (body)		Example Value Model <pre>{ "Quantity": 0, "IsLastBatch": true, "DoBackFill": true, "Notes": "string", "ReasonCode": "string" }</pre> Parameter content type application/json
Responses		Response content type application/json
Code	Description	
200	OK	
	Example Value Model <pre>{ "EntityID": "string", "ValidationErrors": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": ["string"] }, "ValidationWarnings": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": [</pre>	

Code

Description

```
        "string"
      ]
    },
    "IsNewEntity": true,
    "IsValid": true
  }
}
```

POST

/api/v2/scheduling/orders/transactions/{operationSequenceNumber}/start

Posts a start transaction entry to a scheduling order specified by orderNumber, partNumber, revision and location.

Parameters

Try it out

Name	Description
operationSequenceNumber * required integer(\$int32) (path)	An operation sequence number in the rope of the scheduling order, use MAXINT for the final buffer operation operationSequenceNumber
orderNumber * required string (query)	An existing scheduling order number orderNumber
partNumber * required string (query)	The part number of the scheduling order partNumber
location * required string (query)	The location of the scheduling order location
revision string (query)	The revision of the part number revision
body * required object (body)	Example Value Model <pre>{ "Quantity": 0, "IsLastBatch": true, "DoBackFill": true, "Notes": "string" }</pre> Parameter content type application/json

Responses

Response content type

application/json

Code	Description
200	OK Example Value Model <pre>{ "EntityID": "string", "ValidationErrors": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": ["string"] }, "ValidationWarnings": { "additionalProp1": ["string"], "additionalProp2": ["string"], "additionalProp3": ["string"] }, "IsNewEntity": true, "IsValid": true}</pre>

POST

/api/v2/scheduling/orders/transactions/voidall

Marks all transactions for one or more scheduling orders by schedulingOrderIds void or not void. This action is taken only if the order is not closed, otherwise the request is ignored.

🔒

▼

POST

/api/v2/scheduling/orders/transactions/voidallbykey

Marks all transactions for a scheduling order by orderNumber, partNumber, revision and location void or not void. This action is taken only if the order is not closed, otherwise the request is ignored.

🔒

^

Parameters

Try it out

Name	Description
orderNumber string (query) * required	An existing scheduling order number orderNumber

Name

Description

partNumber * requiredstring
(query)

The part number of the scheduling order

location * requiredstring
(query)

The location of the scheduling order

revision

string
(query)

The revision of the part number

void
boolean
(query)A boolean value indicating if the rope item register entry should be marked voided or not
Default value : true

Responses

Response content type

Code

Description

200

OK

Example Value Model

true

GET

/api/v2/scheduling/transactions/{location}

Gets all transactions for all scheduling orders for the specified location with optional date ranges beforeEntryDate and afterEntryDate



Parameters

[Try it out](#)

Name

Description

location * requiredstring
(path)

A location to filter for scheduling orders

beforeEntryDate

A filter for orders with an entry date on or before this value

Name	Description
------	-------------

string(\$date-time) (query)	
--------------------------------	--

	beforeEntryDate
--	----------------------------

afterEntryDate string(\$date-time) (query)	
--	--

	A filter for orders with an entry date on or after this value
--	---

	afterEntryDate
--	---------------------------

withRoot boolean (query)	
--------------------------------	--

	Add a root element when mime type is 'application/json' <i>Default value</i> : false
--	---

	false
--	------------------

Responses	
-----------	--

	Response content type
--	-----------------------

	application/json
--	-----------------------------

Code	Description
------	-------------

200	
-----	--

	OK
--	----

	Example Value Model
--	------------------------

	<pre>[{ "Id": 0, "OrderNumber": "string", "ScheduleOrderId": 0, "OperationSequenceNumber": 0, "EntryDate": "2026-02-14T17:56:04.683Z", "EntryType": "string", "Quantity": 0, "IsLastBatch": true, "Notes": "string", "Voided": true, "PartNumber": "string", "Revision": "string", "Location": "string", "Resource": "string" }]</pre>
--	--

POST	
------	--

	/api/v2/scheduling/transactions/void
--	--------------------------------------

	Sets or removes a void to one or more transactions by schedulingRopeItemRegisterIds (aka rope item register item identifier)
--	---



Parameters	
------------	--

	Try it out
--	-----------------------

Name	Description
------	-------------

void	
------	--

	A boolean value indicating if the rope item register entry should be marked voided or not
--	---

Name**Description**

boolean
(*query*)

Default value : true

true

body * required

array<integer>
(*body*)

Example Value Model

[
 0
]

Parameter content type

application/json

Responses

Response content type

application/json

Code**Description**

200

OK