

Interoperation for Lazy and Eager Evaluation

William Faught

October 19, 2010

Abstract

Programmers forgo existing solutions to problems in other programming languages where interoperation proves too cumbersome; they remake solutions, rather than reuse them. To unburden programmers to facilitate reuse, interoperation must resolve incompatible programming language features transparently at the boundaries between languages. To address part of this problem, this paper presents a model of computation that resolves lazy and eager evaluation strategies. Unforced values act as thunks that are used and forced where appropriate by the languages themselves and do not require programmer forethought.

1 Introduction

The complexities of software interoperation in part engender the proverbial reinvention of the wheel. Programmers forgo existing solutions to problems in other programming languages where interoperation proves too cumbersome; they remake solutions, rather than reuse them. To unburden programmers to facilitate reuse, interoperation must resolve incompatible programming language features transparently at the boundaries between languages. To address part of this problem, this paper presents a model of computation that resolves lazy and eager evaluation strategies.

The systems of interoperation presented by Matthews and Findler [2] used call-by-value evaluation strategies that eagerly evaluate expressions. Were a language introduced to their systems that uses a call-by-name evaluation strategy that lazily evaluates expressions, interoperation would change the meaning of values converted between the lazy language and the eager ones. For example, since the application of a converted function involves applications in both the outer and inner languages, the argument is subject to both the outer and inner evaluation strategies. If the outer

language is lazy and the inner language is eager, then the argument may be evaluated by the inner language but not the outer language, thereby violating assumptions made by the outer language about the order of evaluation and thus changing the meaning of the original function. Furthermore, the conversion of composite types like lists from lazy languages to eager ones may diverge or cause an error because eager evaluation will convert the entire value, which may be of infinite size or contain expressions assumed by lazy languages not to be immediately evaluated.

Lazy and eager evaluation take opposite approaches: lazy evaluation evaluates expressions as needed, and eager evaluation evaluates all expressions. As such, for common expressions, lazy evaluation evaluates a proper subset of the expressions that eager evaluation does. In other words, the set of lazy evaluation strictness points is a proper subset of that of eager evaluation. The difference between these two sets is the set of incompatible strictness points that may change the meaning of values converted from eager languages to lazy ones or may cause a divergence or an error for values converted from lazy languages to eager ones. Where guarded expressions of lazy languages occur at these points, the original lazy evaluation strategy must be followed, and the guards not evaluated. This requires introducing a dual notion of values where *forced* values force the evaluation of guarded expressions of lazy languages and *unforced* values prevent their evaluation.

2 Model of Computation

The model of computation extends the model presented by Kinghorn [1] with a third language identical to the ML model except it uses lazy evaluation, and as such is named after Haskell, to which it is more similar. Hereafter, the names Haskell, ML, and Scheme refer to their corresponding models in this paper. Lists are added to all three languages. Being lazy, Haskell does not evaluate function arguments or list construction operands. These three points constitute the set of incompatible strictness points between Haskell and ML and Haskell and Scheme. Haskell guards in ML and Scheme must not be evaluated where they occur at these points, but they can be evaluated at all other points.

Haskell guards are considered a special kind of value called an unforced value. Unforced values include both Haskell guards and traditional values called forced values. Haskell guards that are forced to evaluate become forced values through the conversion of the Haskell value to an ML or Scheme value. As such, all ML and Scheme expressions either reduce to unforced values, cause errors, or diverge. ML and Scheme reduction rules and evaluation contexts use unforced values at the incompatible strictness points to match against Haskell guards, and their evaluation

$$\begin{aligned}
& zeroes = \mathbf{fix} (\lambda x_H : \{\mathbf{N}\}. \mathbf{cons} \bar{0} x_H) \\
& (\mathbf{hs} (\{\mathbf{N}\} \rightarrow \{\mathbf{N}\}) (\lambda x_S. x_S)) zeroes \quad \rightarrow \\
& (\lambda x'_H : \{\mathbf{N}\}. \mathbf{hs} \{\mathbf{N}\} ((\lambda x_S. x_S) (\mathbf{sh} \{\mathbf{N}\} x'_H))) zeroes \quad \rightarrow \\
& \mathbf{hs} \{\mathbf{N}\} ((\lambda x_S. x_S) (\mathbf{sh} \{\mathbf{N}\} zeroes)) \quad \rightarrow \\
& \mathbf{hs} \{\mathbf{N}\} (\mathbf{sh} \{\mathbf{N}\} zeroes) \quad \rightarrow \\
& \mathbf{hs} \{\mathbf{N}\} (\mathbf{sh} \{\mathbf{N}\} (\mathbf{cons} \bar{0} zeroes)) \quad \rightarrow \\
& \mathbf{hs} \{\mathbf{N}\} (\mathbf{cons} (\mathbf{sh} \mathbf{N} \bar{0}) (\mathbf{sh} \{\mathbf{N}\} zeroes)) \quad \rightarrow \\
& \mathbf{hs} \{\mathbf{N}\} (\mathbf{cons} \bar{0} (\mathbf{sh} \{\mathbf{N}\} zeroes)) \quad \rightarrow \\
& \mathbf{cons} (\mathbf{hs} \mathbf{N} \bar{0}) (\mathbf{hs} \{\mathbf{N}\} (\mathbf{sh} \{\mathbf{N}\} zeroes))
\end{aligned}$$

Figure 1: Haskell argument and list conversions.

contexts prevent evaluation within Haskell guards at those points.

Figure 1 illustrates forced and unforced values at work for the cases explained in the introduction. The reductions for lines 1-4 show that the outer Haskell argument *zeroes* is not forced by the application of the inner Scheme function. The reductions for lines 4-8 show that the conversion of *zeroes* from Haskell to Scheme did not diverge, despite *zeroes* being a list of infinite size.

The interoperation of Haskell and ML posed another problem: the conversion of type abstractions. The application of a converted type abstraction cannot substitute the type argument into the inner language directly, since the inner language has no notion of the types of the outer language. Instead, conversion substitutes lumps in a guard's inner type. The application of a converted type abstraction substitutes the type argument in the guard's outer type. Since the natural embedding [2] requires the guard's outer and inner types to be equal, a new equality relation called lump equality is used here that allows lumps within the guard's inner type to match any corresponding type in the guard's outer type.

The proof of correctness of this model would be similar to that of Kinghorn [1], *mutatis mutandis*.

Haskell is presented in figures 2, 3, 4, 5, and 6; ML is presented in figures 7, 8, 9, 10, and 11; Scheme is presented in figures 12, 13, 14, 15, and 16; the unbrand function is presented in figure 17; the lump equality relation is presented in figure 18; and legends of symbol and syntax names are presented in figures 19, 20, and 21.

$$\begin{aligned}
e_H &= x_H \mid v_H \mid e_H e_H \mid e_H \langle t_H \rangle \mid \mathbf{fix} \, e_H \mid o \, e_H e_H \mid \mathbf{if0} \, e_H e_H e_H \mid f \, e_H \\
&\quad \mathbf{null?} \, e_H \mid \mathbf{wrong} \, t_H \, string \mid \mathbf{hm} \, t_H \, t_M \, e_M \mid \mathbf{hs} \, k_H \, e_S \\
v_H &= \lambda x_H : t_H . e_H \mid \Lambda u_H . e_H \mid \bar{n} \mid \mathbf{nil} \, t_H \mid \mathbf{cons} \, e_H e_H \mid \mathbf{hm} \, L \, t_M \, w_M \\
&\quad \mathbf{hs} \, L \, w_S \\
t_H &= L \mid N \mid u_H \mid \{t_H\} \mid t_H \rightarrow t_H \mid \forall u_H . t_H \\
k_H &= L \mid N \mid u_H \mid \{k_H\} \mid k_H \rightarrow k_H \mid \forall u_H . k_H \mid b \diamond t_H \\
o &= + \mid - \\
f &= \mathbf{hd} \mid \mathbf{tl} \\
E_H &= []_H \mid E_H e_H \mid E_H \langle t_H \rangle \mid \mathbf{fix} \, E_H \mid o \, E_H e_H \mid o \, v_H \, E_H \\
&\quad \mathbf{if0} \, E_H e_H e_H \mid f \, E_H \mid \mathbf{null?} \, E_H \mid \mathbf{hm} \, t_H \, t_M \, E_M \mid \mathbf{hs} \, k_H \, E_S
\end{aligned}$$

Figure 2: Haskell syntax and evaluation contexts

$$\begin{array}{c}
\overline{\vdash_H \mathbf{L}} \quad \overline{\vdash_H \mathbf{N}} \quad \overline{\Gamma, u_H \vdash_H u_H} \\
\frac{\Gamma \vdash_H t_H}{\Gamma \vdash_H \{t_H\}} \quad \frac{\Gamma \vdash_H t_H \quad \Gamma \vdash_H t'_H}{\Gamma \vdash_H t_H \rightarrow t'_H} \quad \frac{\Gamma, u_H \vdash_H t_H}{\Gamma \vdash_H \forall u_H. t_H} \\
\\
\frac{\Gamma \vdash_H t_H \quad \Gamma, x_H : t_H \vdash_H e_H : t'_H}{\Gamma \vdash_H (\lambda x_H : t_H. e_H) : t_H \rightarrow t'_H} \quad \frac{\Gamma, u_H \vdash_H e_H : t_H}{\Gamma \vdash_H \Lambda u_H. e_H : \forall u_H. t_H} \quad \overline{\vdash_H \overline{n} : \mathbf{N}} \\
\frac{\Gamma \vdash_H t_H : \quad \Gamma \vdash_H e_H : t_H \quad \Gamma \vdash_H e'_H : \{t_H\}}{\Gamma \vdash_H \mathbf{nil} \ t_H : \{t_H\}} \quad \frac{\Gamma \vdash_H e_H : t_H \quad \Gamma \vdash_H e'_H : \{t_H\}}{\Gamma \vdash_H \mathbf{cons} \ e_H \ e'_H : \{t_H\}} \quad \frac{\Gamma, x_H : t_H \vdash_H x_H : t_H}{\Gamma \vdash_H \mathbf{cons} \ e_H \ e'_H : \{t_H\}} \\
\frac{\Gamma \vdash_H e_H : t_H \rightarrow t'_H \quad \Gamma \vdash_H e'_H : t_H}{\Gamma \vdash_H e_H \ e'_H : t'_H} \quad \frac{\Gamma \vdash_H e_H : t_H \rightarrow t_H}{\Gamma \vdash_H \mathbf{fix} \ e_H : t_H} \\
\frac{\Gamma \vdash_H t_H \quad \Gamma \vdash_H e_H : \forall u_H. t'_H}{\Gamma \vdash_H e_H \langle t_H \rangle : t'_H[t_H/u_H]} \quad \frac{\Gamma \vdash_H e_H : \{t_H\}}{\Gamma \vdash_H \mathbf{hd} \ e_H : t_H} \quad \frac{\Gamma \vdash_H e_H : \{t_H\}}{\Gamma \vdash_H \mathbf{tl} \ e_H : \{t_H\}} \\
\frac{\Gamma \vdash_H e_H : \mathbf{N} \quad \Gamma \vdash_H e'_H : \mathbf{N}}{\Gamma \vdash_H o \ e_H \ e'_H : \mathbf{N}} \quad \frac{\Gamma \vdash_H e_H : \{t_H\}}{\Gamma \vdash_H \mathbf{null?} \ e_H : \mathbf{N}} \quad \frac{\Gamma \vdash_H [k_H] \quad \Gamma \vdash_S e_S : \mathbf{TST}}{\Gamma \vdash_H \mathbf{hs} \ k_H \ e_S : [k_H]} \\
\frac{\Gamma \vdash_H e_H : \mathbf{N} \quad \Gamma \vdash_H e'_H : t_H \quad \Gamma \vdash_H e''_H : t_H}{\Gamma \vdash_H \mathbf{if0} \ e_H \ e'_H \ e''_H : t_H} \quad \frac{\Gamma \vdash_H t_H}{\Gamma \vdash_H \mathbf{wrong} \ t_H \ string : t_H} \\
\frac{\Gamma \vdash_H t_H \quad \Gamma \vdash_M t_M \quad \Gamma \vdash_M e_M : t'_M \quad t_H \doteq t_M \quad t_M = t'_M}{\Gamma \vdash_H \mathbf{hm} \ t_H \ t_M \ e_M : t_H}
\end{array}$$

Figure 3: Haskell typing rules

$$\begin{aligned}
& \mathcal{E}[(\lambda x_H : t_H.e_H) e'_H]_H \rightarrow \mathcal{E}[e_H[e'_H/x_H]] \\
& \mathcal{E}[(\Lambda u_H.e_H)(t_H)]_H \rightarrow \mathcal{E}[e_H[b \diamond t_H/u_H]] \\
& \mathcal{E}[\mathbf{fix} (\lambda x_H : t_H.e_H)]_H \rightarrow \mathcal{E}[e_H[\mathbf{fix} (\lambda x_H : t_H.e_H)/x_H]] \\
& \mathcal{E}[+ \bar{n} \bar{n'}]_H \rightarrow \mathcal{E}[\overline{n + n'}] \\
& \mathcal{E}[- \bar{n} \bar{n'}]_H \rightarrow \mathcal{E}[\overline{\max(n - n', 0)}] \\
& \mathcal{E}[\mathbf{if0} \bar{0} e_H e'_H]_H \rightarrow \mathcal{E}[e_H] \\
& \mathcal{E}[\mathbf{if0} \bar{n} e_H e'_H]_H \rightarrow \mathcal{E}[e'_H] \ (n \neq 0) \\
& \mathcal{E}[\mathbf{hd} (\mathbf{nil} t_H)]_H \rightarrow \mathcal{E}[\mathbf{wrong} t_H \text{ “Empty list”}] \\
& \mathcal{E}[\mathbf{tl} (\mathbf{nil} t_H)]_H \rightarrow \mathcal{E}[\mathbf{wrong} \{t_H\} \text{ “Empty list”}] \\
& \mathcal{E}[\mathbf{hd} (\mathbf{cons} e_H e'_H)]_H \rightarrow \mathcal{E}[e_H] \\
& \mathcal{E}[\mathbf{tl} (\mathbf{cons} e_H e'_H)]_H \rightarrow \mathcal{E}[e'_H] \\
& \mathcal{E}[\mathbf{null?} (\mathbf{nil} t_H)]_H \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{null?} (\mathbf{cons} e_H e'_H)]_H \rightarrow \mathcal{E}[\bar{1}] \\
& \mathcal{E}[\mathbf{wrong} t_H \text{ string}]_H \rightarrow \mathbf{Error: string}
\end{aligned}$$

Figure 4: Haskell operational semantics

$$\begin{aligned}
& \mathcal{E}[\mathbf{hm} \ t_H \ \mathbf{L} \ (\mathbf{mh} \ \mathbf{L} \ t'_H \ e_H)]_H \rightarrow \mathcal{E}[e_H] \quad (t_H = t'_H \text{ and } t_H \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{hm} \ t_H \ \mathbf{L} \ (\mathbf{mh} \ \mathbf{L} \ t'_H \ e_H)]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ t_H \ \text{“Type mismatch”}] \\
& \quad (t_H \neq t'_H \text{ and } t_H \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{hm} \ t_H \ \mathbf{L} \ (\mathbf{ms} \ \mathbf{L} \ w_S)]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ t_H \ \text{“Bad value”}] \quad (t_H \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{hm} \ \mathbf{N} \ \mathbf{N} \ \bar{n}]_H \rightarrow \mathcal{E}[\bar{n}] \\
& \mathcal{E}[\mathbf{hm} \ \{t_H\} \ \{t_M\} \ (\mathbf{nil} \ t'_M)]_H \rightarrow \mathcal{E}[\mathbf{nil} \ t_H] \\
& \mathcal{E}[\mathbf{hm} \ \{t_H\} \ \{t_M\} \ (\mathbf{cons} \ v_M \ v'_M)]_H \rightarrow \\
& \quad \mathcal{E}[\mathbf{cons} \ (\mathbf{hm} \ t_H \ t_M \ v_M) \ (\mathbf{hm} \ \{t_H\} \ \{t_M\} \ v'_M)] \\
& \mathcal{E}[\mathbf{hm} \ (t_H \rightarrow t'_H) \ (t_M \rightarrow t'_M) \ (\lambda x_M : t''_M . e_M)]_H \rightarrow \\
& \quad \mathcal{E}[\lambda x_H : t_H . \mathbf{hm} \ t'_H \ t'_M \ ((\lambda x_M : t''_M . e_M) \ (\mathbf{mh} \ t_M \ t_H \ x_H))] \\
& \mathcal{E}[\mathbf{hm} \ (\forall u_H . t_H) \ (\forall u_M . t_M) \ (\Lambda u'_M . e_M)]_H \rightarrow \mathcal{E}[\Lambda u_H . \mathbf{hm} \ t_H \ t_M [\mathbf{L}/u_M] \ e_M [\mathbf{L}/u'_M]]
\end{aligned}$$

Figure 5: Haskell-ML operational semantics

$$\begin{aligned}
& \mathcal{E}[\mathbf{hs} \ N \ \bar{n}]_H \rightarrow \mathcal{E}[\bar{n}] \\
& \mathcal{E}[\mathbf{hs} \ N \ w_S]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ N \ \text{“Not a number”}] \ (w_S \neq \bar{n}) \\
& \mathcal{E}[\mathbf{hs} \ \{k_H\} \ \mathbf{nil}]_H \rightarrow \mathcal{E}[\mathbf{nil} \ [k_H]] \\
& \mathcal{E}[\mathbf{hs} \ \{k_H\} \ (\mathbf{cons} \ v_S \ v'_S)]_H \rightarrow \mathcal{E}[\mathbf{cons} \ (\mathbf{hs} \ k_H \ v_S) \ (\mathbf{hs} \ \{k_H\} \ v'_S)] \\
& \mathcal{E}[\mathbf{hs} \ \{k_H\} \ w_S]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ [\{k_H\}] \ \text{“Not a list”}] \\
& \quad (w_S \neq \mathbf{nil} \text{ and } w_S \neq \mathbf{cons} \ v_S \ v'_S) \\
& \mathcal{E}[\mathbf{hs} \ (b \diamond t_H) \ (\mathbf{sh} \ (b \diamond t_H) \ e_H)]_H \rightarrow \mathcal{E}[e_H] \\
& \mathcal{E}[\mathbf{hs} \ (b \diamond t_H) \ w_S]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ t_H \ \text{“Brand mismatch”}] \ (w_S \neq \mathbf{sh} \ (b \diamond t_H) \ e_H) \\
& \mathcal{E}[\mathbf{hs} \ (k_H \rightarrow k'_H) \ (\lambda x_S. e_S)]_H \rightarrow \mathcal{E}[\lambda x_H : [k_H]. \mathbf{hs} \ k'_H \ ((\lambda x_S. e_S) \ (\mathbf{sh} \ k_H \ x_H))] \\
& \mathcal{E}[\mathbf{hs} \ (k_H \rightarrow k'_H) \ w_S]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ [k_H \rightarrow k'_H] \ \text{“Not a function”}] \\
& \quad (w_S \neq \lambda x_S. e_S) \\
& \mathcal{E}[\mathbf{hs} \ (\forall u_H. k_H) \ w_S]_H \rightarrow \mathcal{E}[\Lambda u_H. \mathbf{hs} \ k_H \ w_S]
\end{aligned}$$

Figure 6: Haskell-Scheme operational semantics

$$\begin{aligned}
e_M &= x_M \mid v_M \mid e_M e_M \mid e_M \langle t_M \rangle \mid \mathbf{fix} \ e_M \mid o \ e_M \ e_M \mid \mathbf{if0} \ e_M \ e_M \ e_M \\
&\quad \mathbf{cons} \ e_M \ e_M \mid f \ e_M \mid \mathbf{null?} \ e_M \mid \mathbf{wrong} \ t_M \ \mathit{string} \mid \mathbf{ms} \ k_M \ e_S \\
v_M &= w_M \mid \mathbf{mh} \ t_M \ t_H \ e_H \\
w_M &= \lambda x_M : t_M . e_M \mid \Lambda u_M . e_M \mid \bar{n} \mid \mathbf{nil} \ t_M \mid \mathbf{cons} \ v_M \ v_M \mid \mathbf{mh} \ L \ t_H \ e_H \\
&\quad \mathbf{ms} \ L \ w_S \\
t_M &= L \mid N \mid u_M \mid \{t_M\} \mid t_M \rightarrow t_M \mid \forall u_M . t_M \\
k_M &= L \mid N \mid u_M \mid \{k_M\} \mid k_M \rightarrow k_M \mid \forall u_M . k_M \mid b \diamond t_M \\
o &= + \mid - \\
f &= \mathbf{hd} \mid \mathbf{tl} \\
E_M &= U_M \mid \mathbf{mh} \ t_M \ t_H \ E_H \\
U_M &= []_M \mid E_M \ e_M \mid w_M \ U_M \mid E_M \langle t_M \rangle \mid \mathbf{fix} \ E_M \mid o \ E_M \ e_M \mid o \ w_M \ E_M \\
&\quad \mathbf{if0} \ E_M \ e_M \ e_M \mid \mathbf{cons} \ U_M \ e_M \mid \mathbf{cons} \ v_M \ U_M \mid f \ E_M \mid \mathbf{null?} \ E_M \\
&\quad \mathbf{ms} \ k_M \ E_S
\end{aligned}$$

Figure 7: ML syntax and evaluation contexts

$$\begin{array}{c}
\overline{\vdash_M \mathbf{L}} \quad \overline{\vdash_M \mathbf{N}} \quad \overline{\Gamma, u_M \vdash_M u_M} \\
\frac{\Gamma \vdash_M t_M}{\Gamma \vdash_M \{t_M\}} \quad \frac{\Gamma \vdash_M t_M \quad \Gamma \vdash_M t'_M}{\Gamma \vdash_M t_M \rightarrow t'_M} \quad \frac{\Gamma, u_M \vdash_M t_M}{\Gamma \vdash_M \forall u_M. t_M} \\
\\
\frac{\Gamma \vdash_M t_M \quad \Gamma, x_M : t_M \vdash_M e_M : t'_M}{\Gamma \vdash_M (\lambda x_M : t_M. e_M) : t_M \rightarrow t'_M} \quad \frac{\Gamma, u_M \vdash_M e_M : t_M}{\Gamma \vdash_M \Lambda u_M. e_M : \forall u_M. t_M} \quad \overline{\vdash_M \bar{n} : \mathbf{N}} \\
\\
\frac{\Gamma \vdash_M t_M}{\Gamma \vdash_M \mathbf{nil} \ t_M : \{t_M\}} \quad \frac{\Gamma \vdash_M e_M : t_M \quad \Gamma \vdash_M e'_M : \{t_M\}}{\Gamma \vdash_M \mathbf{cons} \ e_M \ e'_M : \{t_M\}} \quad \frac{}{\Gamma, x_M : t_M \vdash_M x_M : t_M} \\
\\
\frac{\Gamma \vdash_M e_M : t_M \rightarrow t'_M \quad \Gamma \vdash_M e'_M : t_M}{\Gamma \vdash_H e_M \ e'_M : t'_M} \quad \frac{\Gamma \vdash_M e_M : t_M \rightarrow t_M}{\Gamma \vdash_M \mathbf{fix} \ e_M : t_M} \\
\\
\frac{\Gamma \vdash_M t_M \quad \Gamma \vdash_M e_M : \forall u_M. t'_M}{\Gamma \vdash_M e_M \langle t_M \rangle : t'_M[t_M/u_M]} \quad \frac{\Gamma \vdash_M e_M : \{t_M\}}{\Gamma \vdash_M \mathbf{hd} \ e_M : t_M} \quad \frac{\Gamma \vdash_M e_M : \{t_M\}}{\Gamma \vdash_M \mathbf{tl} \ e_M : \{t_M\}} \\
\\
\frac{\Gamma \vdash_M e_M : \mathbf{N} \quad \Gamma \vdash_M e'_M : \mathbf{N}}{\Gamma \vdash_M o \ e_M \ e'_M : \mathbf{N}} \quad \frac{\Gamma \vdash_M e_M : \{t_M\}}{\Gamma \vdash_M \mathbf{null?} \ e_M : \mathbf{N}} \quad \frac{\Gamma \vdash_M \lfloor k_M \rfloor \quad \Gamma \vdash_S e_S : \mathbf{TST}}{\Gamma \vdash_M \mathbf{ms} \ k_M \ e_S : \lfloor k_M \rfloor} \\
\\
\frac{\Gamma \vdash_M e_M : \mathbf{N} \quad \Gamma \vdash_M e'_M : t_M \quad \Gamma \vdash_M e''_M : t_M}{\Gamma \vdash_M \mathbf{if0} \ e_M \ e'_M \ e''_M : t_M} \quad \frac{\Gamma \vdash_M t_M}{\Gamma \vdash_M \mathbf{wrong} \ t_M \ string : t_M} \\
\\
\frac{\Gamma \vdash_M t_M \quad \Gamma \vdash_H t_H \quad \Gamma \vdash_H e_H : t'_H \quad t_M \doteq t_H \quad t_H = t'_H}{\Gamma \vdash_M \mathbf{mh} \ t_M \ t_H \ e_H : t_M}
\end{array}$$

Figure 8: ML typing rules

$$\begin{aligned}
& \mathcal{E}[(\lambda x_M : t_M.e_M) v_M]_M \rightarrow \mathcal{E}[e_M[v_M/x_M]] \\
& \mathcal{E}[(\Lambda u_M.e_M)\langle t_M \rangle]_M \rightarrow \mathcal{E}[e_M[b \diamond t_M/u_M]] \\
& \mathcal{E}[\mathbf{fix} (\lambda x_M : t_M.e_M)]_M \rightarrow \mathcal{E}[e_M[\mathbf{fix} (\lambda x_M : t_M.e_M)/x_M]] \\
& \mathcal{E}[+ \bar{n} \bar{n}']_M \rightarrow \mathcal{E}[\overline{n + n'}] \\
& \mathcal{E}[- \bar{n} \bar{n}']_M \rightarrow \mathcal{E}[\overline{\max(n - n', 0)}] \\
& \mathcal{E}[\mathbf{if0} \bar{0} e_M e'_M]_M \rightarrow \mathcal{E}[e_M] \\
& \mathcal{E}[\mathbf{if0} \bar{n} e_M e'_M]_M \rightarrow \mathcal{E}[e'_M] \ (n \neq 0) \\
& \mathcal{E}[\mathbf{hd} (\mathbf{nil} t_M)]_M \rightarrow \mathcal{E}[\mathbf{wrong} t_M \text{ “Empty list”}] \\
& \mathcal{E}[\mathbf{tl} (\mathbf{nil} t_M)]_M \rightarrow \mathcal{E}[\mathbf{wrong} \{t_M\} \text{ “Empty list”}] \\
& \mathcal{E}[\mathbf{hd} (\mathbf{cons} v_M v'_M)]_M \rightarrow \mathcal{E}[v_M] \\
& \mathcal{E}[\mathbf{tl} (\mathbf{cons} v_M v'_M)]_M \rightarrow \mathcal{E}[v'_M] \\
& \mathcal{E}[\mathbf{null?} (\mathbf{nil} t_M)]_M \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{null?} (\mathbf{cons} v_M v'_M)]_M \rightarrow \mathcal{E}[\bar{1}] \\
& \mathcal{E}[\mathbf{wrong} t_M \text{ string}]_H \rightarrow \mathbf{Error: string}
\end{aligned}$$

Figure 9: ML operational semantics

$$\begin{aligned}
& \mathcal{E}[\mathbf{mh} \ t_M \ \mathbf{L} \ (\mathbf{hm} \ \mathbf{L} \ t'_M \ w_M)]_M \rightarrow \mathcal{E}[w_M] \ (t_M = t'_M \text{ and } t_M \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{mh} \ t_M \ \mathbf{L} \ (\mathbf{hm} \ \mathbf{L} \ t'_M \ w_M)]_M \rightarrow \mathcal{E}[\mathbf{wrong} \ t_M \ \text{“Type mismatch”}] \ (t_M \neq t'_M \text{ and } t_M \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{mh} \ t_M \ \mathbf{L} \ (\mathbf{hs} \ \mathbf{L} \ w_S)]_H \rightarrow \mathcal{E}[\mathbf{wrong} \ t_M \ \text{“Bad value”}] \ (t_M \neq \mathbf{L}) \\
& \mathcal{E}[\mathbf{mh} \ \mathbf{N} \ \mathbf{N} \ \bar{n}]_M \rightarrow \mathcal{E}[\bar{n}] \\
& \mathcal{E}[\mathbf{mh} \ \{t_M\} \ \{t_H\} \ (\mathbf{nil} \ t'_H)]_M \rightarrow \mathcal{E}[\mathbf{nil} \ t_M] \\
& \mathcal{E}[\mathbf{mh} \ \{t_M\} \ \{t_H\} \ (\mathbf{cons} \ e_H \ e'_H)]_M \rightarrow \mathcal{E}[\mathbf{cons} \ (\mathbf{mh} \ t_M \ t_H \ e_H) \ (\mathbf{mh} \ \{t_M\} \ \{t_H\} \ e'_H)] \\
& \mathcal{E}[\mathbf{mh} \ (t_M \rightarrow t'_M) \ (t_H \rightarrow t'_H) \ (\lambda x_H : t''_H . e_H)]_M \rightarrow \\
& \quad \mathcal{E}[\lambda x_M : t_M . \mathbf{mh} \ t'_M \ t'_H \ ((\lambda x_H : t''_H . e_H) \ (\mathbf{hm} \ t_H \ t_M \ x_M))] \\
& \mathcal{E}[\mathbf{mh} \ (\forall u_M . t_M) \ (\forall u_H . t_H) \ (\Lambda u'_H . e_H)]_M \rightarrow \mathcal{E}[\Lambda u_M . \mathbf{mh} \ t_M \ t_H [\mathbf{L}/u_H] \ e_H [\mathbf{L}/u'_H]]
\end{aligned}$$

Figure 10: ML-Haskell operational semantics

$$\begin{aligned}
& \mathcal{E}[\mathbf{ms} \ \mathbf{N} \ \bar{n}]_M \rightarrow \mathcal{E}[\bar{n}] \\
& \mathcal{E}[\mathbf{ms} \ \mathbf{N} \ w_S]_M \rightarrow \mathcal{E}[\mathbf{wrong} \ \mathbf{N} \ \text{“Not a number”}] \ (w_S \neq \bar{n}) \\
& \mathcal{E}[\mathbf{ms} \ \{k_M\} \ \mathbf{nil}]_M \rightarrow \mathcal{E}[\mathbf{nil} \ [k_M]] \\
& \mathcal{E}[\mathbf{ms} \ \{k_M\} \ (\mathbf{cons} \ v_S \ v'_S)]_M \rightarrow \mathcal{E}[\mathbf{cons} \ (\mathbf{ms} \ k_M \ v_S) \ (\mathbf{ms} \ \{k_M\} \ v'_S)] \\
& \mathcal{E}[\mathbf{ms} \ \{k_M\} \ w_S]_M \rightarrow \mathcal{E}[\mathbf{wrong} \ [\{k_M\}] \ \text{“Not a list”}] \\
& \quad (w_S \neq \mathbf{nil} \text{ and } w_S \neq \mathbf{cons} \ v_S \ v'_S) \\
& \mathcal{E}[\mathbf{ms} \ (b \diamond t_M) \ (\mathbf{sm} \ (b \diamond t_M) \ v_M)]_M \rightarrow \mathcal{E}[v_M] \\
& \mathcal{E}[\mathbf{ms} \ (b \diamond t_M) \ w_S]_M \rightarrow \mathcal{E}[\mathbf{wrong} \ [b \diamond t_M] \ \text{“Brand mismatch”}] \\
& \quad (w_S \neq \mathbf{sm} \ (b \diamond t_M) \ e_M) \\
& \mathcal{E}[\mathbf{ms} \ (k_M \rightarrow k'_M) \ (\lambda x_S. e_S)]_M \rightarrow \\
& \quad \mathcal{E}[\lambda x_M : [k_M]. \mathbf{ms} \ k'_M \ ((\lambda x_S. e_S) \ (\mathbf{sm} \ k_M \ x_M))] \\
& \mathcal{E}[\mathbf{ms} \ (k_M \rightarrow k'_M) \ w_S]_M \rightarrow \mathcal{E}[\mathbf{wrong} \ [k_M \rightarrow k'_M] \ \text{“Not a function”}] \\
& \quad (w_S \neq \lambda x_S. e_S) \\
& \mathcal{E}[\mathbf{ms} \ (\forall u_M. k_M) \ w_S]_M \rightarrow \mathcal{E}[\Lambda u_M. \mathbf{ms} \ k_M \ w_S]
\end{aligned}$$

Figure 11: ML-Scheme operational semantics

$$\begin{aligned}
e_S &= x_S \mid v_S \mid e_S e_S \mid o e_S e_S \mid p e_S \mid \text{if0 } e_S e_S e_S \mid \text{cons } e_S e_S \mid f e_S \\
&\quad \text{wrong } string \mid \text{sm } k_M e_M \\
v_S &= w_S \mid \text{sh } k_H e_H \\
w_S &= \lambda x_S. e_S \mid \bar{n} \mid \text{nil} \mid \text{cons } v_S v_S \mid \text{sh } (b \diamond t_H) e_H \mid \text{sm } (b \diamond t_M) w_M \\
o &= + \mid - \\
f &= \text{hd} \mid \text{tl} \\
p &= \text{fun?} \mid \text{list?} \mid \text{null?} \mid \text{num?} \\
E_S &= U_S \mid \text{sh } k_H E_H \\
U_S &= []_S \mid E_S e_S \mid w_S U_S \mid o E_S e_S \mid o w_S E_S \mid p E_S \mid \text{if0 } E_S e_S e_S \\
&\quad \text{cons } U_S e_S \mid \text{cons } v_S U_S \mid f E_S \mid \text{sm } k_M E_M
\end{aligned}$$

Figure 12: Scheme syntax and evaluation contexts

$$\begin{array}{c}
\overline{\vdash_S \text{TST}} \\
\\
\frac{\Gamma, x_S : \text{TST} \vdash_S e_S : \text{TST}}{\Gamma \vdash_S \lambda x_S. e_S : \text{TST}} \quad \overline{\vdash_S \bar{n} : \text{TST}} \quad \overline{\vdash_S \text{nil} : \text{TST}} \\
\frac{\Gamma \vdash_S e_S : \text{TST} \quad \Gamma \vdash_S e'_S : \text{TST}}{\Gamma \vdash_S \text{cons } e_S e'_S : \text{TST}} \quad \overline{\Gamma, x_S : \text{TST} \vdash_S x_S : \text{TST}} \\
\frac{\Gamma \vdash_S e_S : \text{TST} \quad \Gamma \vdash_S e'_S : \text{TST}}{\Gamma \vdash_H e_S e'_S : \text{TST}} \quad \frac{\Gamma \vdash_S e_S : \text{TST}}{\Gamma \vdash_S f e_S : \text{TST}} \\
\frac{\Gamma \vdash_S e_S : \text{TST} \quad \Gamma \vdash_S e'_S : \text{TST}}{\Gamma \vdash_S o e_S e'_S : \text{TST}} \quad \frac{\Gamma \vdash_S e_S : \text{TST}}{\Gamma \vdash_S p e_S : \text{TST}} \\
\frac{\Gamma \vdash_S e_S : \text{TST} \quad \Gamma \vdash_S e'_S : \text{TST} \quad \Gamma \vdash_S e''_S : \text{TST}}{\Gamma \vdash_S \text{if0 } e_S e'_S e''_S : \text{TST}} \quad \overline{\vdash_S \text{wrong string} : \text{TST}} \\
\frac{\Gamma \vdash_H [k_H] \quad \Gamma \vdash_H e_H : t_H \quad [k_H] = t_H}{\Gamma \vdash_S \text{sh } k_H e_H : \text{TST}} \quad \frac{\Gamma \vdash_M [k_M] \quad \Gamma \vdash_M e_M : t_M \quad [k_M] = t_M}{\Gamma \vdash_S \text{sm } k_M e_M : \text{TST}}
\end{array}$$

Figure 13: Scheme typing rules

$$\begin{aligned}
& \mathcal{E}[(\lambda x_S. e_S) v_S]_S \rightarrow \mathcal{E}[e_S[v_S/x_S]] \\
& \mathcal{E}[w_S v_S]_S \rightarrow \mathcal{E}[\mathbf{wrong} \text{ “Not a function”}] \ (w_S \neq \lambda x_S. e_S) \\
& \mathcal{E}[+ \bar{n} \bar{n}']_S \rightarrow \mathcal{E}[\overline{n + n'}] \\
& \mathcal{E}[- \bar{n} \bar{n}']_S \rightarrow \mathcal{E}[\overline{\max(n - n', 0)}] \\
& \mathcal{E}[o w_S w'_S]_S \rightarrow \mathcal{E}[\mathbf{wrong} \text{ “Not a number”}] \ (w_S \neq \bar{n} \text{ or } w'_S \neq \bar{n}) \\
& \mathcal{E}[\mathbf{if0} \bar{0} e_S e'_S]_S \rightarrow \mathcal{E}[e_S] \\
& \mathcal{E}[\mathbf{if0} \bar{n} e_S e'_S]_S \rightarrow \mathcal{E}[e'_S] \ (n \neq 0) \\
& \mathcal{E}[\mathbf{if0} w_S e_S e'_S]_S \rightarrow \mathcal{E}[\mathbf{wrong} \text{ “Not a number”}] \ (w_S \neq \bar{n}) \\
& \mathcal{E}[f \mathbf{nil}]_S \rightarrow \mathcal{E}[\mathbf{wrong} \text{ “Empty list”}] \\
& \mathcal{E}[\mathbf{hd} (\mathbf{cons} v_S v'_S)]_S \rightarrow \mathcal{E}[v_S] \\
& \mathcal{E}[\mathbf{tl} (\mathbf{cons} v_S v'_S)]_S \rightarrow \mathcal{E}[v'_S] \\
& \mathcal{E}[f w_S]_S \rightarrow \mathcal{E}[\mathbf{wrong} \text{ “Not a list”}] \ (w_S \neq \mathbf{nil} \text{ and } w_S \neq \mathbf{cons} v_S v'_S) \\
& \mathcal{E}[\mathbf{fun?} (\lambda x_S. e_S)]_S \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{fun?} w_S]_S \rightarrow \mathcal{E}[\bar{1}] \ (w_S \neq \lambda x_S. e_S) \\
& \mathcal{E}[\mathbf{list?} \mathbf{nil}]_S \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{list?} (\mathbf{cons} v_S v'_S)]_S \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{list?} w_S]_S \rightarrow \mathcal{E}[\bar{1}] \ (w_S \neq \mathbf{nil} \text{ and } w_S \neq \mathbf{cons} v_S v'_S) \\
& \mathcal{E}[\mathbf{null?} \mathbf{nil}]_S \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{null?} w_S]_S \rightarrow \mathcal{E}[\bar{1}] \ (w_S \neq \mathbf{nil}) \\
& \mathcal{E}[\mathbf{num?} \bar{n}]_S \rightarrow \mathcal{E}[\bar{0}] \\
& \mathcal{E}[\mathbf{num?} w_S]_S \rightarrow \mathcal{E}[\bar{1}] \ (w_S \neq \bar{n}) \\
& \mathcal{E}[\mathbf{wrong} \text{ string}]_S \rightarrow \mathbf{Error: string}
\end{aligned}$$

Figure 14: Scheme operational semantics

$$\begin{aligned}
& \mathcal{E}[\mathbf{sh\ L\ (hm\ L\ } k_M\ w_M)]_S \rightarrow \mathcal{E}[\mathbf{wrong\ “Bad\ value”}] \\
& \mathcal{E}[\mathbf{sh\ L\ (hs\ L\ } w_S)]_S \rightarrow \mathcal{E}[w_S] \\
& \mathcal{E}[\mathbf{sh\ N\ } \bar{n}]_S \rightarrow \mathcal{E}[\bar{n}] \\
& \mathcal{E}[\mathbf{sh\ \{k_H\}\ (nil\ } t_H)]_S \rightarrow \mathcal{E}[\mathbf{nil}] \\
& \mathcal{E}[\mathbf{sh\ \{k_H\}\ (cons\ } e_H\ e'_H)]_S \rightarrow \mathcal{E}[\mathbf{cons\ (sh\ } k_H\ e_H)\ (\mathbf{sh\ \{k_H\}\ } e'_H)] \\
& \mathcal{E}[\mathbf{sh\ (k_H\ } \rightarrow k'_H)\ (\lambda x_H : t_H.e_H)]_S \rightarrow \\
& \quad \mathcal{E}[\lambda x_S.\mathbf{sh\ } k'_H\ ((\lambda x_H : t_H.e_H)\ (\mathbf{hs\ } k_H\ x_S))] \\
& \mathcal{E}[\mathbf{sh\ (\forall u_H.k_H)\ (\Lambda u'_H.e_H)}]_S \rightarrow \mathcal{E}[\mathbf{sh\ } k_H[\mathbf{L}/u_H]\ e_H[\mathbf{L}/u'_H]]
\end{aligned}$$

Figure 15: Scheme-Haskell operational semantics

$$\begin{aligned}
\mathcal{E}[\mathbf{sm} \ L \ (\mathbf{mh} \ L \ k_H \ e_H)]_S &\rightarrow \mathcal{E}[\mathbf{wrong} \ \text{“Bad value”}] \\
\mathcal{E}[\mathbf{sm} \ L \ (\mathbf{ms} \ L \ w_S)]_S &\rightarrow \mathcal{E}[w_S] \\
\mathcal{E}[\mathbf{sm} \ N \ \bar{n}]_S &\rightarrow \mathcal{E}[\bar{n}] \\
\mathcal{E}[\mathbf{sm} \ \{k_M\} \ (\mathbf{nil} \ t_M)]_S &\rightarrow \mathcal{E}[\mathbf{nil}] \\
\mathcal{E}[\mathbf{sm} \ \{k_M\} \ (\mathbf{cons} \ v_M \ v'_M)]_S &\rightarrow \mathcal{E}[\mathbf{cons} \ (\mathbf{sm} \ k_M \ v_M) \ (\mathbf{sm} \ \{k_M\} \ v'_M)] \\
\mathcal{E}[\mathbf{sm} \ (k_M \rightarrow k'_M) \ (\lambda x_M : t_M. e_M)]_S &\rightarrow \\
&\quad \mathcal{E}[\lambda x_S. \mathbf{sm} \ k'_M \ ((\lambda x_M : t_M. e_M) \ (\mathbf{ms} \ k_M \ x_S))] \\
\mathcal{E}[\mathbf{sm} \ (\forall u_M. k_M) \ (\Lambda u'_M. e_M)]_S &\rightarrow \mathcal{E}[\mathbf{sm} \ k_M[L/u_M] \ e_M[L/u'_M]]
\end{aligned}$$

Figure 16: Scheme-ML operational semantics

$$\begin{aligned}
\lfloor \mathbf{L} \rfloor &= \mathbf{L} \\
\lfloor \mathbf{N} \rfloor &= \mathbf{N} \\
\lfloor u_H \rfloor &= u_H \\
\lfloor u_M \rfloor &= u_M \\
\lfloor \{k_H\} \rfloor &= \{\lfloor k_H \rfloor\} \\
\lfloor \{k_M\} \rfloor &= \{\lfloor k_M \rfloor\} \\
\lfloor k_H \rightarrow k_H \rfloor &= \lfloor k_H \rfloor \rightarrow \lfloor k_H \rfloor \\
\lfloor k_M \rightarrow k_M \rfloor &= \lfloor k_M \rfloor \rightarrow \lfloor k_M \rfloor \\
\lfloor \forall u_H. k_H \rfloor &= \forall u_H. \lfloor k_H \rfloor \\
\lfloor \forall u_M. k_M \rfloor &= \forall u_M. \lfloor k_M \rfloor \\
\lfloor b \diamond t_H \rfloor &= t_H \\
\lfloor b \diamond t_M \rfloor &= t_M
\end{aligned}$$

Figure 17: Unbrand function

$$\begin{aligned}
& x \dot{=} x \\
& x \dot{=} y \Rightarrow y \dot{=} x \\
& x \dot{=} y \text{ and } y \dot{=} z \Rightarrow x \dot{=} z \\
& t_H \dot{=} L \\
& t_M \dot{=} L \\
& t_H = t_M \Rightarrow t_H \dot{=} t_M
\end{aligned}$$

Figure 18: Lump equality relation

Symbol	Name
b	Brand
k	Conversion scheme
e	Expression
E	Forced evaluation context
w	Forced value
L	Lump
\doteq	Lump equality relation
\mathcal{E}	Meta evaluation context
\bar{n}	Natural number
\mathbb{N}	Natural number
\rightarrow	Reduction relation
t	Type
u	Type variable
Γ	Typing environment
\vdash	Typing relation
U	Unforced evaluation context
v	Unforced value
x	Variable

Figure 19: Symbol names

Syntax	Name
$+ e e$	Addition
<code>if0 $e e e$</code>	Condition
<code>nil t</code>	Empty list
<code>nil</code>	Empty list
<code>wrong $t string$</code>	Error
<code>wrong $string$</code>	Error
<code>fix e</code>	Fixed-point operation
$\lambda x : t. e$	Function abstraction
$\lambda x_S. e_S$	Function abstraction
$e e$	Function application
<code>hm $t_H t_M e_M$</code>	Haskell-ML guard
<code>hs $k_H e_S$</code>	Haskell-Scheme guard
<code>cons $e e$</code>	List construction
<code>hd e</code>	List head
<code>tl e</code>	List tail
<code>mh $t_M t_H e_H$</code>	ML-Haskell guard
<code>ms $k_M e_S$</code>	ML-Scheme guard
<code>sh $k_H e_H$</code>	Scheme-Haskell guard
<code>sm $k_M e_M$</code>	Scheme-ML guard
$- e e$	Subtraction
$\Lambda u. e$	Type abstraction
$e \langle t \rangle$	Type application
<code>fun? e_S</code>	Value predicate
<code>list? e_S</code>	Value predicate
<code>null? e</code>	Value predicate
<code>num? e_S</code>	Value predicate

Figure 20: Syntax names

Syntax	Name
$b \diamond t$	Branded type
$\forall u.t$	Forall
$\forall u.k$	Forall
$t \rightarrow t$	Function abstraction
$k \rightarrow k$	Function abstraction
$\{t\}$	List
$\{k\}$	List

Figure 21: Syntax names

3 Conclusion

Lazy and eager evaluation can be resolved transparently for common expressions at the boundaries between languages with unforced and forced values. This is more convenient than an explicit force operator that programmers must use manually by anticipating which expressions must be forced.

The approach this paper used for interoperation between three languages is not scalable. Values from each language can be directly converted to values of the other two languages and back. n languages require $n*(n-1)$ conversion mappings between them. As the number of languages increases, the number of conversion mappings grows geometrically, which is unmaintainable. A better approach would be to make only two conversion mappings per language and chain them together to form a single path between any two languages, which would require only $n-1$ conversion mappings and grow linearly. Were this done for this model, the number of conversion mappings would be four instead of six.

References

- [1] David L. Kinghorn. Preserving parametricity while sharing higher-order, polymorphic functions between scheme and ml. Master's thesis, California Polytechnic State University, San Luis Obispo, June 2007.
- [2] Jacob Matthews and Robert Bruce Findler. Operational semantics for multi-language programs. *SIGPLAN Not.*, 42(1):3–10, 2007.