Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.

Texecom Premier Elite 24

Intruder alarm control panel - Installation manual

Revision QA-025-A. Installed variant: Premier Elite 24.

This synthetic document tests local text extraction, identification and page citations.

It is not an equipment instruction and supplies no verified manufacturer limits.

System category: Intruder. Equipment type: panel.

Supported model range for this fixture: Premier Elite 24 only.

Zone resistance fault - read-only records

Record the exact zone fault message and whether it is present, intermittent or cleared.

Record the panel time and any offset from the engineer's clock.

Identify the affected input, detector and expander, and the actual configured wiring profile.

If the expander cannot be reached, record the access restriction and return-visit needs.

A resistance value alone does not identify the installed wiring profile or a cable fault.

Do not reset or clear history merely to obtain a healthy display.

Measurement context and return visit

A reading record needs exact measurement points, reference, instrument and units.

Record whether the load is connected and the operating condition at the measurement time.

Record unavailable, unknown, unstable, OL and zero as different observations.

Resistance measurements require a suitable verified isolated span and known remote ends.

An external power supply requires its own applicable manual and installed model confirmation.

Retain the original entry when a reading is corrected; record why it changed.