



Engineers  
Planners  
Surveyors  
Landscape Architects  
Environmental Scientists

**Corporate Headquarters**  
331 Newman Springs Road, Suite 203  
Red Bank, NJ 07701  
T: 732.383.1950  
F: 732.383.1984  
[www.maserconsulting.com](http://www.maserconsulting.com)

### SD# 7 - Quadex Structure Guard

- ☒ NO EXCEPTION TAKEN  
☐ EXCEPTION TAKEN AS NOTED  
☐ NOTE EXCEPTIONS AND CONFIRM IN WRITING  
☐ NO REPLY REQUIRED UNLESS CHECKED BELOW  
☐ REVISE AND RESUBMIT  
☐ REJECTED - SEE REMARKS


CHECKING IS ONLY FOR CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND COMPLIANCE WITH THE INFORMATION GIVEN IN THE CONTRACT DOCUMENTS. CONTRACTOR IS RESPONSIBLE FOR DIMENSIONS TO BE CONFIRMED AND CORRELATED AT THE JOB SITE FOR INFORMATION THAT PERTAINS SOLELY TO THE FABRICATION PROCESSES OR TO TECHNIQUES TO CONSTRUCTION; AND FOR COORDINATION OF THE WORK OF ALL TRADES.

### COMMENTS

Name: \_\_\_\_\_

Date: Friday, June 24, 2016

*with reh.*




**EPOXY COATING SUBI**  
**FEATURING STRUCTU**

**PRODUCTS**

**SYSTEMS**





---

Epoxy C

1. Company History
2. Structure Guard Technical Data Sheet
3. Specification Structure Destruction

### 3. Specification: Structure Restoration & Epoxy Materials Installation

### 4. Material Safety Data Sheet

- > Structure Guard

### 5. Ancillary Water Stop Products

- > Quad Plug (TDS and MSDS)

- > Hyperform (TDS and MSDS)

### 6. Before & After Installations Photos

Epoxy C

---



REPAIR  
MATERIAL

*COMPANY HISTORY*

---

**2016**

---

**4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | qua**

---

**Epoxy C****CORPORATE PROFILE****Quadex LLC****ADDRESS**

4801 Crystal Hill Road  
North Little Rock, AR 72118  
501-758-8628 Office  
501-758-3814 Fax

**WEBSITE**

quadexonline.com

**EXPERIENCE**

Over 20 years in the sewer and pipe rehat  
business with over 75,000,000 lbs. of mat

**CUSTOMERS**

Washington Suburban Sanitary Commissi  
Metropolitan Sewer District of St. Louis  
City of Austin  
City of Hot Springs  
City of Melbourne

City of Pinellas Park  
Little Rock Wastewater Utility  
City of Memphis  
City of Boston  
City of Fort Worth  
City of Huntsville  
Miami-Dade Water & Sewer

---

4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | que

---

Epoxy C

OUR BUSINESS

## OUR BUSINESS

Quadex LLC was founded in 1991 and is one of the most respected names in the protective coatings and linings sector of the wastewater rehabilitation industry. We began by manufacturing a complete line of cementitious products and continue to refine our existing products as well as develop new products that keep Quadex at the forefront of the infrastructure protection and restoration industry. Our staff and team of "Certified Applicators" are dedicated to providing only the highest quality products and equipment utilized to rehabilitate aging, damaged wastewater structures. Quadex products and equipment, as well as our network of "Certified Applicators" that use them, work to protect and restore the structural integrity of water related structures including large diameter pipe, manholes, wetwells, pump stations, headworks and other severe duty wastewater structures.

Quadex products are formed with advanced technology and are known for their ease of successful installation, long-term corrosion resistance, superior impermeability, application service workability. Our products provide a permanent seal against corrosion and support an installation that ensures the performance of each structure. Quadex conducts in-house studies through the American Society for Testing and Materials (ASTM) to ensure



---

4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | qua

---

Epoxy C

---



REPAIR  
MATERIA

# STRUCTURE GUARD TECHNICAL

---

4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | qua

---

Epoxy C

## STRUCTURE GUARD CORROSION RESISTANT EPOXY PROTEC

### Description

Structure Guard is a 100% solids high build epoxy coating formulated to provide long term corrosion protection and structural enhancement for manholes, pump stations, treatment plants or any wastewater infrastructure subject to high levels

### Chemical Resistance

- Acetic Acid 10%
- Brine Water
- Diesel Fuel
- Gasoline

plastic or dry. Structure Guard is designed to resist corrosion of corrosion and/or abrasion. Structure Guard sets fast for a quick return-to-service in the most aggressive and turbulent environments. It finishes smooth and slick to enhance flow and can also be used as an interior or exterior pipe lining.

### Features and Benefits

- 100% Solids, No VOC's
- Spray applied at 200 mils in a single pass
- Excellent corrosion and abrasion resistance

### Typical Performance Data

Color	Light Bluegreen
Finish	Very Smooth (Manning Coefficient: .009)
Flash Point	> 250°F (121°C)
Specific Gravity Resin	1.45 Hardener: 0.97
Dry Service	30°F – 250°F (121°C)
Spill/Splash	190°F (87.7°C)
Immersion Service	150°F (65.5°C)

### Application Systems

- Heated Plural Airless Spray Units
- Minimum Output 5000 psi
- Product Hose: Min. - Optimum I.D. 0.375 - 0.5 inch

### Cure Time (at 70°F or 21°C)

Re-coat Window	8 hours
Light Loading	6 – 12 hours
Immersion (Aqueous) Service	6 - 12 hours
Full Chemical Cure	7 days

### Pot Life

- 40°F (4°C) 1 hour
- 75°F (24°C) 35 minutes
- 92°F (33°C) 20 minutes

### Substrate

- Mineral Spirits
- Crude Oil
- Ethylene Glycol
- Sodium Hydroxide 50%
- Sewage (Hydrogen Sulfide)
- Fresh and non-potable water
- Ethanol

Structure Guard passes requirements.

### Multiple Coats

Good coating practice typically requires 2 coats to attain finished thickness. Structure Guard may be applied before the previous coat is fully cured, typically 8 hours @ 70°F. This will shorten this window. Surface must be brush blast before applying. Surface must be clean and dry surface that has not been including amine blush or abrased by sanding or wire brushing.

The same requirements apply to adjacent coating sections. If the coating surface is not to be brush blasted, use a non-flammable solvent or sanding to create adequate surface profile.

### Packaging

Structure Guard is available in 5 gallon and 10 gallon pails.

### Yield

Structure Guard will yield approximately 1 gallon @ 80 mils thickness on substrate porosity and suggest application of two coats. A film thickness gauge may be used to determine thickness.

Epoxy C

### Surface Preparation

Coating performance is largely determined by the degree of surface preparation... More is Better.

CONCRETE & MASONRY substrates must be prepared in a manner that provides a uniform, sound, clean, neutralized surface with sufficient profile suitable for the specified coating. The substrate must be free of all contaminants, such as oil, grease, rust, scale or deposits and have a surface profile equivalent to a CSP2 to CSP5 in accordance with ICRI Technical Guideline No. 03732. This can generally be achieved by abrasive blasting, shot blasting, high pressure water cleaning, water jetting, acid etch, hot water/steam cleaning or a combination of methods.

STEEL surfaces may require "Solvent Cleaning" (SSPC-SP 1) to remove oil, grease and other soluble contaminants. Chemical contaminants may be removed according to SSPC-SP 12/ NACE No. 5. Identification of the contaminants along with their concentrations may be obtained from laboratory and field

tests as described in SSP and Analysis of Soluble S coated should then be p NACE No.1 "White Blast SSPC-SP 10/NACE No. 2 other service. In certain sit be to use high (>5,000 psi water cleaning or water resulting anchor profile sh the coating thickness spec

### Warranty

Quadex warrants its product and workmanship. Within one year of installation, if the product is proven defective, Quadex will refund its purchase price, and its obligation shall be limited to the purchase price. There are no other warranties. There is no warranty if Quadex's written directions

### Physical Properties

Gel Time, 150 grams at 25°C	ASTMD2471	18
Tensile Strength	ASTM D638	7,
Elongation	ASTM D638	1.
Flexural Strength	ASTM D790	44

Flexural Strength	ASTM D790	11
Flexural Modulus	ASTM D790	53
Compressive Strength	ASTM D695	13
Shore D Hardness	ASTM D2240	85
Taber Abrasion, CS 17 Wheel	ASTM D4060	<
Adhesion to Concrete	ASTM D4541	>
Adhesion to Blasted Steel	ASTM D4541	>
Water Vapor Transmission	ASTM D1651	3.
Water Absorption	ASTM D570	0.
Volatile Organic Content	ASTM D2580	N.


Physical properties were evaluated on compounds cured for 5 days at 25°C / 50% relative hu

---

4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | qua

---

Epoxy C



QUADEX

REPAIR  
MATERIAL

*SPECIFICATION: STRUCTURE RES  
PROTECTION EPOXY MATERIALS*

---

4801 Crystal Hill Road | North Little Rock, AR 72118 | 501.758.8628 | qua