



William Ting <williamdjting@gmail.com>

FW: Reap Children

1 message

William Ting <william_ting_2@sfu.ca>
To: "williamdjting@gmail.com" <williamdjting@gmail.com>

Thu, Jul 20, 2023 at 6:10 AM

From: Daily Byte**Sent:** Thursday, July 20, 2023 6:10:19 AM (UTC-08:00) Pacific Time (US & Canada)**To:** William Ting**Subject:** Reap Children

The Daily Byte

Good morning,

Need help with yesterday's problem? [Start getting solutions.](#)

Today's Byte

You are given two lists of integers and an integer representing a process id to kill. One of the lists represents a list of process ids and the other represents a list of each of the processes' corresponding (by index) parent ids. When a process is killed, all of its children should also be killed. Return a list of all the process ids that are killed as a result of killing the requested process.


Ex: Given the following...

```
pid = [2, 4, 3, 7]
```

```
ppid = [0, 2, 2, 3]
```

```
kill = 3
```

the tree of processes can be represented as follows:



```
return [3, 7] as killing process 3 will also require killing  
its child (i.e. process 7).
```

Thanks,
The Daily Byte

Need help negotiating your offer? Chat with former tech recruiters who'll guide you on exactly what to say to get you paid more. Get negotiation help from [levels.fyi](#).

Want to take a break? [snooze](#) or [unsubscribe](#)

© 2023 The Daily Byte. All rights reserved.