

443. String Compression

[Description \(/problems/string-compression/description/\)](/problems/string-compression/description/)[Hints \(/problems/string-compression/hints/\)](/problems/string-compression/hints/)[Submissions \(/problems/string-compr](/problems/string-compr)[🎲 Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)

Given an array of characters, compress it **in-place** (https://en.wikipedia.org/wiki/In-place_algorithm).

The length after compression must always be smaller than or equal to the original array.

Every element of the array should be a **character** (not int) of length 1.

After you are done **modifying the input array in-place** (https://en.wikipedia.org/wiki/In-place_algorithm), return the new length of the array.

Follow up:

Could you solve it using only O(1) extra space?

Example 1:**Input:**

```
["a","a","b","b","c","c","c"]
```

Output:

Return 6, and the first 6 characters of the input array should be: ["a","2","b","2","c","3"]

Explanation:

"aa" is replaced by "a2". "bb" is replaced by "b2". "ccc" is replaced by "c3".

Example 2:**Input:**

```
["a"]
```

Output:

Return 1, and the first 1 characters of the input array should be: ["a"]

Explanation:

Nothing is replaced.

Example 3:**Input:**

```
["a","b","b","b","b","b","b","b","b","b","b","b","b"]
```

Output:

Return 4, and the first 4 characters of the input array should be: ["a","b","1","2"].

Explanation:

Since the character "a" does not repeat, it is not compressed. "bbbbbbbbbbbb" is replaced by "b12". Notice each digit has it's own entry in the array.

Note:

1. All characters have an ASCII value in [35, 126] .
2. $1 \leq \text{len}(\text{chars}) \leq 1000$.

Seen this question in a real interview before? ☐ Yes ☐ No



🔗 C++

Difficulty: Easy**Total Accepted:** 28.9K**Total Submissions:** 80.9K**Contributor:** Grain_In_Ear (/grain_in_ear/)**Companies** ⓘ ▼**Related Topics** ▼**Similar Questions** ▼[📝 Notes](#)