

Nested sampling: powering next-generation inference and machine learning tools for astrophysics, cosmology, particle physics and beyond

Will Handley

wh260@cam.ac.uk

Royal Society University Research Fellow
Astrophysics Group, Cavendish Laboratory, University of Cambridge
Kavli Institute for Cosmology, Cambridge
Gonville & Caius College
willhandley.co.uk/talks

30th August 2024



UNIVERSITY OF
CAMBRIDGE




LBI: Likelihood-based inference

The standard approach if you are fortunate enough to have a likelihood function $P(D|\theta)$:

$$P(\theta|D) = \frac{P(D|\theta)P(\theta)}{P(D)}$$

1. Define prior $\pi(\theta)$
 - ▶ spend some time being philosophical
2. Sample posterior $P(\theta|D)$
 - ▶ use out-of-the-box MCMC tools such as emcee or MultiNest
 - ▶ make some triangle plots
3. Optionally compute evidence $\mathcal{Z}(D)$
 - ▶ e.g. nested sampling or parallel tempering
 - ▶ do some model comparison (i.e. science)
 - ▶ talk about tensions



LBI: Likelihood-based inference


The standard approach if you are fortunate enough to have a likelihood function $P(D|\theta)$:

$$P(\theta|D) = \frac{P(D|\theta)P(\theta)}{P(D)}$$

$$\text{Posterior} = \frac{\text{Likelihood} \times \text{Prior}}{\text{Evidence}}$$

1. Define prior $\pi(\theta)$
 - ▶ spend some time being philosophical
2. Sample posterior $P(\theta|D)$
 - ▶ use out-of-the-box MCMC tools such as emcee or MultiNest
 - ▶ make some triangle plots
3. Optionally compute evidence $\mathcal{Z}(D)$
 - ▶ e.g. nested sampling or parallel tempering
 - ▶ do some model comparison (i.e. science)
 - ▶ talk about tensions

DES Y5 SN Ia
[2401.02929]



LBI: Likelihood-based inference




The standard approach if you are fortunate enough to have a likelihood function $\mathcal{L}(D|\theta)$:

$$\mathcal{P}(\theta|D) = \frac{\mathcal{L}(D|\theta)\pi(\theta)}{\mathcal{Z}(D)}$$

$$\text{Posterior} = \frac{\text{Likelihood} \times \text{Prior}}{\text{Evidence}}$$

1. Define prior $\pi(\theta)$
 - ▶ spend some time being philosophical
2. Sample posterior $\mathcal{P}(\theta|D)$
 - ▶ use out-of-the-box MCMC tools such as emcee or MultiNest
 - ▶ make some triangle plots
3. Optionally compute evidence $\mathcal{Z}(D)$
 - ▶ e.g. nested sampling or parallel tempering
 - ▶ do some model comparison (i.e. science)
 - ▶ talk about tensions

DES Y5 SN Ia
[2401.02929]




LBI: Likelihood-based inference

The standard approach if you are fortunate enough to have a likelihood function $\mathcal{L}(D|\theta)$:

$$P(\theta|D)P(D) = P(\theta, D) = P(D|\theta)P(\theta),$$

1. Define prior $\pi(\theta)$
 - ▶ spend some time being philosophical
2. Sample posterior $P(\theta|D)$
 - ▶ use out-of-the-box MCMC tools such as emcee or MultiNest
 - ▶ make some triangle plots
3. Optionally compute evidence $\mathcal{Z}(D)$
 - ▶ e.g. nested sampling or parallel tempering
 - ▶ do some model comparison (i.e. science)
 - ▶ talk about tensions




LBI: Likelihood-based inference

The standard approach if you are fortunate enough to have a likelihood function $\mathcal{L}(D|\theta)$:

$$\mathcal{P} \times \mathcal{Z} = \mathcal{J} = \mathcal{L} \times \pi, \quad \text{Joint} = \mathcal{J} = P(\theta, D)$$

1. Define prior $\pi(\theta)$
 - ▶ spend some time being philosophical
2. Sample posterior $P(\theta|D)$
 - ▶ use out-of-the-box MCMC tools such as emcee or MultiNest
 - ▶ make some triangle plots
3. Optionally compute evidence $\mathcal{Z}(D)$
 - ▶ e.g. nested sampling or parallel tempering
 - ▶ do some model comparison (i.e. science)
 - ▶ talk about tensions



The three pillars of Bayesian inference

Parameter estimation

What do the data tell us about the parameters of a model?
e.g. the size or age of a Λ CDM universe

$$P(\theta|D, M) = \frac{P(D|\theta, M)P(\theta|M)}{P(D|M)}$$

$$\mathcal{P} = \frac{\mathcal{L} \times \pi}{\mathcal{Z}}$$

$$\text{Posterior} = \frac{\text{Likelihood} \times \text{Prior}}{\text{Evidence}}$$

Model comparison

How much does the data support a particular model?
e.g. Λ CDM vs a dynamic dark energy cosmology

$$P(M|D) = \frac{P(D|M)P(M)}{P(D)}$$

$$\frac{\mathcal{Z}_M \Pi_M}{\sum_m \mathcal{Z}_m \Pi_m}$$

$$\text{Posterior} = \frac{\text{Evidence} \times \text{Prior}}{\text{Normalisation}}$$

Tension quantification

Do different datasets make consistent predictions from the same model? e.g. CMB vs Type IA supernovae data

$$\mathcal{R} = \frac{\mathcal{Z}_{AB}}{\mathcal{Z}_A \mathcal{Z}_B}$$

$$\begin{aligned} \log \mathcal{S} &= \langle \log \mathcal{L}_{AB} \rangle_{\mathcal{P}_{AB}} \\ &\quad - \langle \log \mathcal{L}_A \rangle_{\mathcal{P}_A} \\ &\quad - \langle \log \mathcal{L}_B \rangle_{\mathcal{P}_B} \end{aligned}$$


Model comparison $\mathcal{Z} = P(D|M)$

- ▶ Bayesian model comparison allows mathematical derivation of key philosophical principles.

Viewed from data-space D :

Popper's falsificationism

- ▶ Prefer models that make bold predictions.
- ▶ if proven true, model more likely correct.



- ▶ Falsificationism comes from normalisation

Viewed from parameter-space θ :

Occam's razor

- ▶ Models should be as simple as possible
- ▶ ... but no simpler

- ▶ Occam's razor equation:

$$\log \mathcal{Z} = \langle \log \mathcal{L} \rangle_{\mathcal{P}} - \mathcal{D}_{KL}$$

- ▶ “Occam penalty”: KL divergence between prior π and posterior \mathcal{P} .

$$\mathcal{D}_{KL} \sim \log \frac{\text{Prior volume}}{\text{Posterior volume}}$$


Model comparison $\mathcal{Z} = P(D|M)$

- ▶ Bayesian model comparison allows mathematical derivation of key philosophical principles.

Viewed from data-space D :

Popper's falsificationism

- ▶ Prefer models that make bold predictions.
- ▶ if proven true, model more likely correct.



- ▶ Falsificationism comes from normalisation

Viewed from parameter-space θ :

Occam's razor

- ▶ Models should be as simple as possible
- ▶ ... but no simpler

- ▶ Occam's razor equation:

$$\log \mathcal{Z} = \langle \log \mathcal{L} \rangle_{\mathcal{P}} - \mathcal{D}_{\text{KL}}$$

- ▶ “Occam penalty”: KL divergence between prior π and posterior \mathcal{P} .

$$\mathcal{D}_{\text{KL}} \sim \log \frac{\text{Prior volume}}{\text{Posterior volume}}$$


Model comparison $\mathcal{Z} = P(D|M)$

- ▶ Bayesian model comparison allows mathematical derivation of key philosophical principles.

Viewed from data-space D :

Popper's falsificationism

- ▶ Prefer models that make bold predictions.
- ▶ if proven true, model more likely correct.



- ▶ Falsificationism comes from normalisation

Viewed from parameter-space θ :

Occam's razor

- ▶ Models should be as simple as possible
- ▶ ... but no simpler

- ▶ Occam's razor equation:

$$\log \mathcal{Z} = \langle \log \mathcal{L} \rangle_{\mathcal{P}} - \mathcal{D}_{\text{KL}}$$

- ▶ “Occam penalty”: KL divergence between prior π and posterior \mathcal{P} .


$$\mathcal{D}_{\text{KL}} \sim \log \frac{\text{Prior volume}}{\text{Posterior volume}}$$

What is Nested Sampling?

- ▶ Nested sampling is a radical, multi-purpose numerical tool.
- ▶ Given a (scalar) function f with a vector of parameters θ , it can be used for:


Optimisation

$$\theta_{\max} = \max_{\theta} f(\theta)$$




Exploration

draw/sample $\theta \sim f$




Integration

$$\int f(\theta) dV$$



Where is Nested Sampling?

- ▶ For many purposes, in your Neural Net you should group Nested Sampling with (MCMC) techniques such as:
 - ▶ Metropolis-Hastings (PyMC, MontePython)
 - ▶ Hamiltonian Monte Carlo (Stan, blackjax)
 - ▶ Ensemble sampling (emcee, zeus).
 - ▶ Variational Inference (Pyro)
 - ▶ Sequential Monte Carlo
 - ▶ Thermodynamic integration
 - ▶ Genetic algorithms
- ▶ You may have heard of it branded form:
 - ▶ MultiNest
 - ▶ PolyChord
 - ▶ dynesty
 - ▶ ultranest



Integration in Physics

- ▶ Integration is a fundamental concept in physics, statistics and data science:

Partition functions

$$Z(\beta) = \int e^{-\beta H(q,p)} dq dp$$

Path integrals


$$\Psi = \int e^{iS} \mathcal{D}x$$

Bayesian marginals


$$\mathcal{Z}(D) = \int \mathcal{L}(D|\theta) \pi(\theta) d\theta$$


- ▶ Need numerical tools if analytic solution unavailable.
- ▶ High-dimensional numerical integration is hard.
- ▶ Riemannian strategy estimates volumes geometrically:


$$\int f(x) d^n x \approx \sum_i f(x_i) \Delta V_i \sim \mathcal{O}(e^n)$$





- ▶ Curse of dimensionality \Rightarrow exponential scaling.

















MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling




MCMC




Nested sampling



MCMC




Nested sampling




MCMC

- ▶ Single “walker”
- ▶ Explores posterior
- ▶ Fast, if proposal matrix is tuned
- ▶ Parameter estimation, suspiciousness calculation
- ▶ Channel capacity optimised for generating posterior samples



Nested sampling


- ▶ Ensemble of “live points”
- ▶ Scans from prior to peak of likelihood
- ▶ Slower, no tuning required
- ▶ Parameter estimation, model comparison, tension quantification
- ▶ Channel capacity optimised for computing partition function



The nested sampling meta-algorithm: live points

- ▶ Start with n random samples over the space.
- ▶ Delete outermost sample, and replace with a new random one at higher integrand value.
- ▶ The “live points” steadily contract around the peak(s) of the function.
- ▶ We can use this evolution to estimate volume *probabilistically*.
- ▶ At each iteration, the contours contract by $\sim \frac{1}{n}$ of their volume.
- ▶ This is an exponential contraction, so


$$\int f(x)dV \approx \sum_i f(x_i)\Delta V_i, \quad V_i = V_0 e^{-i/n}$$



The nested sampling meta-algorithm: live points

- ▶ Start with n random samples over the space.
- ▶ Delete outermost sample, and replace with a new random one at higher integrand value.
- ▶ The “live points” steadily contract around the peak(s) of the function.
- ▶ We can use this evolution to estimate volume *probabilistically*.
- ▶ At each iteration, the contours contract by $\sim \frac{1}{n}$ of their volume.
- ▶ This is an exponential contraction, so


$$\int f(x)dV \approx \sum_i f(x_i)\Delta V_i, \quad V_i = V_0 e^{-i/n}$$



The nested sampling meta-algorithm: live points

- ▶ Start with n random samples over the space.
- ▶ Delete outermost sample, and replace with a new random one at higher integrand value.
- ▶ The “live points” steadily contract around the peak(s) of the function.
- ▶ We can use this evolution to estimate volume *probabilistically*.
- ▶ At each iteration, the contours contract by $\sim \frac{1}{n}$ of their volume.
- ▶ This is an exponential contraction, so


$$\int f(x)dV \approx \sum_i f(x_i)\Delta V_i, \quad V_i = V_0 e^{-i/n}$$



The nested sampling meta-algorithm: live points

- ▶ Start with n random samples over the space.
- ▶ Delete outermost sample, and replace with a new random one at higher integrand value.
- ▶ The “live points” steadily contract around the peak(s) of the function.
- ▶ We can use this evolution to estimate volume *probabilistically*.
- ▶ At each iteration, the contours contract by $\sim \frac{1}{n}$ of their volume.
- ▶ This is an exponential contraction, so


$$\int f(x)dV \approx \sum_i f(x_i)\Delta V_i, \quad V_i = V_0 e^{-i/n}$$




The nested sampling meta-algorithm: live points

- ▶ Start with n random samples over the space.
- ▶ Delete outermost sample, and replace with a new random one at higher integrand value.
- ▶ The “live points” steadily contract around the peak(s) of the function.
- ▶ We can use this evolution to estimate volume *probabilistically*.
- ▶ At each iteration, the contours contract by $\sim \frac{1}{n} \pm \frac{1}{n}$ of their volume.
- ▶ This is an exponential contraction, so

$$\int f(x)dV \approx \sum_i f(x_i)\Delta V_i, \quad V_i = V_0 e^{-(i \pm \sqrt{i})/n}$$



The nested sampling meta-algorithm: dead points




- ▶ At the end, one is left with a set of discarded “dead” points.
- ▶ Dead points have a unique scale-invariant distribution $\propto \frac{dV}{V}$.
- ▶ Uniform over original region, exponentially concentrating on region of interest (until termination volume).
- ▶ Good for training emulators (HERA [[2108.07282](#)]).

Applications


- ▶ training emulators.
- ▶ gridding simulations
- ▶ beta flows
- ▶ “dead measure”

Implementations of Nested Sampling [2205.15570](NatReview)


MultiNest [0809.3437]




PolyChord [1506.00171]




DNest [1606.03757]




ProxNest [2106.03646]



UltraNest [2101.09604]



NeuralNest [1903.10860]



nessai [2102.11056]

nora [2305.19267]

jaxnest [2012.15286]

nautilus [2306.16923]

<wh260@cam.ac.uk>

willhandley.co.uk/talks

dynesty [1904.02180]

Types of nested sampler

- ▶ Broadly, most nested samplers can be split into how they create new live points.
- ▶ i.e. how they sample from the hard likelihood constraint $\{\theta \sim \pi : \mathcal{L}(\theta) > \mathcal{L}_*\}$.

Rejection samplers

- ▶ e.g. MultiNest, UltraNest.
- ▶ Constructs bounding region and draws many invalid points until $\mathcal{L}(\theta) > \mathcal{L}_*$.
- ▶ Efficient in low dimensions, exponentially inefficient $\sim \mathcal{O}(e^{d/d_0})$ in high $d > d_0 \sim 10$.

- ▶ Nested samplers usually come with:

- ▶ *resolution* parameter n_{live} (which improve results as $\sim \mathcal{O}(n_{\text{live}}^{-1/2})$).
- ▶ set of *reliability* parameters [2101.04525], which don't improve results if set arbitrarily high, but introduce systematic errors if set too low.
- ▶ e.g. Multinest efficiency eff or PolyChord chain length n_{repeats} .

Chain-based samplers

- ▶ e.g. PolyChord, ProxNest.
- ▶ Run Markov chain starting at a live point, generating many valid (correlated) points.
- ▶ Linear $\sim \mathcal{O}(d)$ penalty in decorrelating new live point from the original seed point.

Applications of nested sampling


Adam Ormondroyd



PhD

Cosmology

- ▶ Battle-tested in Bayesian cosmology on
 - ▶ Parameter estimation: multimodal alternative to MCMC samplers.
 - ▶ Model comparison: using integration to compute the Bayesian evidence
 - ▶ Tension quantification: using deep tail sampling and suspiciousness computations.
- ▶ Plays a critical role in major cosmology pipelines: Planck, DES, KiDS, BAO, SNe.
- ▶ The default Λ CDM cosmology is well-tuned to have Gaussian-like posteriors for CMB data.
- ▶ Less true for alternative cosmologies/models and orthogonal datasets, so nested sampling crucial.



1

Applications of nested sampling



Metha Prathaban

PhD



Astrophysics

- ▶ In exoplanets [1806.00518]
 - ▶ Parameter estimation: determining properties of planets.
 - ▶ Model comparison: how many planets? Stellar modelling [2007.07278].
 - ▶ exoplanet problems regularly have posterior phase transitions [2102.03387]
- ▶ In gravitational waves
 - ▶ Parameter estimation: Binary merger properties
 - ▶ Model comparison: Modified theories of gravity, selecting phenomenological parameterisations [1803.10210]
 - ▶ Likelihood reweighting: fast slow properties




Applications of nested sampling

Particle physics

- ▶ Nested sampling for cross section computation/event generation $\sigma = \int_{\Omega} d\Phi |\mathcal{M}|^2$.
- ▶ Nested sampling can explore the phase space Ω and compute integral blind with comparable efficiency to HAAG/RAMBO [2205.02030].
- ▶ Bayesian sparse reconstruction [1809.04598] applied to bump hunting allows evidence-based detection of signals in phenomenological backgrounds [2211.10391].
- ▶ Fine tuning quantification
- ▶ Fast estimation of small p -values [2106.02056](PRL), just make switch:
 $X \leftrightarrow p, \mathcal{L} \leftrightarrow \lambda, \theta \leftrightarrow x.$

David Yallup

PDRA




Applications of nested sampling

Lattice field theory

- Consider standard field theory Lagrangian:

$$Z(\beta) = \int D\phi e^{-\beta S(\phi)}, \quad S(\phi) = \int dx^\mu \mathcal{L}(\phi)$$

- Discretize onto spacetime grid.
- Compute partition function
- NS unique traits:
 - Get full partition function for free
 - allows for critical tuning
 - avoids critical slowing down
- Applications in lattice gravity, QCD, condensed matter physics






Applications of nested sampling

Machine learning

- ▶ Machine learning requires:
 - ▶ Training to find weights
 - ▶ Choice of architecture/topology/hyperparameters
- ▶ Bayesian NNs treat training as a model fitting problem
- ▶ Compute posterior of weights (parameter estimation), rather than optimisation (gradient descent)
- ▶ Use evidence to determine best architecture (model comparison), correlates with out-of-sample performance!
- ▶ Solving the full “shallow learning” problem without compromise [2004.12211][2211.10391].
 - ▶ Promising work ongoing to extend this to transfer learning and deep nets.
- ▶ More generally, dead points are optimally spaced for training traditional ML approaches e.g. [2309.05697]



Applications of nested sampling


And beyond...

Catherine Watkinson

Senior Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling


And beyond...

Catherine Watkinson

Senior Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling


And beyond...

Catherine Watkinson

Senior Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling


And beyond...

- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Catherine Watkinson

Senior Data Scientist



Applications of nested sampling

And beyond...

Thomas Mcaloone

PhD → Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling

And beyond...

Thomas Mcaloone

PhD → Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling

And beyond...

Thomas Mcaloone

PhD → Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.



Applications of nested sampling


And beyond...

Thomas Mcaloone

PhD → Data Scientist



- ▶ Techniques have been spun-out (PolyChord Ltd) to:
- ▶ Protein folding
 - ▶ Navigating free energy surface.
 - ▶ Computing misfolds.
 - ▶ Thermal motion.
- ▶ Nuclear fusion reactor optimisation
 - ▶ multi-objective.
 - ▶ uncertainty propagation.
- ▶ Telecoms & DSTL research (MIDAS)
 - ▶ Optimising placement of transmitters/sensors.
 - ▶ Maximum information data acquisition strategies.





REACH: Global 21cm cosmology [2210.07409](NatAstro)

Ian Roque

PhD



- ▶ Imaging the universal dark ages using CMB backlight.
- ▶ 21cm hyperfine line emission from neutral hydrogen.
- ▶ Global experiments measure monopole across frequency.
- ▶ Challenge: science hidden in foregrounds $\sim 10^4 \times$ signal.
- ▶ Lead data analysis team (REACH first light in January)
- ▶ Nested sampling woven in from the ground up (calibrator, beam modelling, signal fitting, likelihood selection).
- ▶ All treated as parameterised model comparison problems.



GAMBIT

Interdisciplinary case studies

- ▶ GAMBIT is an interdisciplinary community and software framework.
- ▶ Like CosmoMC/Cobaya/Bilby, an organiser of data, likelihoods & theory, including:
 - ▶ Collider data (e.g. LHC)
 - ▶ Direct detections (e.g. XENON1T)
 - ▶ Cosmology (MontePython)
 - ▶ Astrophysics (e.g. Bullet Cluster, Supernovae)
 - ▶ Pulsar timing
 - ▶ ... & much more
- ▶ GravBit and LowEnergyBit arising from GAMBIT@KICC workshop



GAMBIT: sub-GeV Dark matter constraints

Interdisciplinary case studies

Felix Kahlhoefer et al

GAMBIT cosmo/DM working group




- ▶ Physical model of sub-GeV thermal dark matter with a dark photon mediator A :

$$\mathcal{L}_{\text{int}} = -\frac{1}{2} m_{A'}^2 A'^{\mu} A'_{\mu} - \frac{1}{4} A'^{\mu\nu} A'_{\mu\nu} - \kappa e A'^{\mu} \sum_f q_f \bar{f} \gamma_{\mu} f ,$$

- ▶ Constrain using cosmological, astrophysical, accelerator & direct detection data.
- ▶ Bayesian Model comparison of Fermion ψ vs scalar Φ models (scalar preferred).


$$\mathcal{L}_{\psi} = \bar{\psi} (i\cancel{\partial} - m_{\text{DM}}) \psi + g_{\text{DM}} A'^{\mu} \bar{\psi} \gamma_{\mu} \psi ,$$

$$\begin{aligned} \mathcal{L}_{\Phi} = & |\partial_{\mu} \Phi|^2 - m_{\text{DM}}^2 |\Phi|^2 - g_{\text{DM}}^2 A'_{\mu} A'^{\mu} |\Phi|^2 \\ & + i g_{\text{DM}} A'^{\mu} [\Phi^* (\partial_{\mu} \Phi) - (\partial_{\mu} \Phi^*) \Phi] , \end{aligned}$$




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from
joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and
learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using
machine learning (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to remove machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to remove machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “*probability of everything*”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$
and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to remove machine learning github.com/handley-lab/lsbi.




SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.



SBI: Simulation-based inference

- ▶ What do you do if you don't know $\mathcal{L}(D|\theta)$?
- ▶ If you have a simulator/forward model
 $\theta \rightarrow D$ defines an *implicit likelihood* \mathcal{L} .
- ▶ Simulator generates samples from $\mathcal{L}(\cdot|\theta)$.
- ▶ With a prior $\pi(\theta)$ can generate samples from joint distribution $\mathcal{J}(\theta, D) = \mathcal{L}(D|\theta)\pi(\theta)$
the “probability of everything”.
- ▶ Task of SBI is take joint \mathcal{J} samples and learn posterior $\mathcal{P}(\theta|D)$ and evidence $\mathcal{Z}(D)$ and possibly likelihood $\mathcal{L}(D|\theta)$.
- ▶ Present state of the art achieves this using *machine learning* (neural networks).
 - ▶ My group's research tries to removes machine learning github.com/handley-lab/lsbi.



Why SBI?

SBI is useful because:

1. If you don't have a likelihood, you can still do inference
 - ▶ This is the usual case beyond CMB cosmology
2. Faster than LBI
 - ▶ emulation – also applies to LBI in principle
3. No need to pragmatically encode fiducial cosmologies
 - ▶ Covariance computation implicitly encoded in simulations
 - ▶ Highly relevant for disentangling tensions & systematics
4. Equips AI/ML with Bayesian interpretability
5. Lower barrier to entry than LBI
 - ▶ Much easier to forward model a systematic
 - ▶ Emerging set of plug-and-play packages
 - ▶ For this reason alone, it will come to dominate scientific inference



github.com/sbi-dev



github.com/undark-lab/swyft



github.com/florent-leclercq/pyselfi



github.com/justinalsing/pydelfi

SBI in cosmology

- ▶ 2024 has been the year it has started to be applied to real data.
- ▶ Mostly for weak lensing
- ▶ However: SBI requires mock data generation code
- ▶ Most data analysis codes were built before the generative paradigm.
- ▶ It's still a lot of work to upgrade cosmological likelihoods to be able to do this (e.g. plik & camspec).

Investigating the turbulent hot gas in X-COP galaxy clusters

S. Dupourqué¹, N. Clerc¹, E. Pointecouteau¹, D. Eckert², S. Ettori³, and F. Vazza^{4,5,6}

Dark Energy Survey Year 3 results: simulation-based cosmological inference with wavelet harmonics, scattering transforms, and moments of weak lensing mass maps II. Cosmological results

M. Gatti,^{1,*} G. Campailla,² N. Jeffrey,³ L. Whitney,³ A. Paredes,⁴ J. Prat,⁵ J. Williamson,³ M. Ravera,² B.

Neural Posterior Estimation with guaranteed exact coverage: the ringdown of GW150914

Marco Crisostomi^{1,2}, Kallol Dey³, Enrico Barausse^{1,2}, Roberto Trotta^{1,2,4,5}

Applying Simulation-Based Inference to Spectral and Spatial Information from the Galactic Center Gamma-Ray Excess

Katharena Christy,^a Eric J. Baxter,^b Jason Kumar^a

KIDS-1000 and DES-Y1 combined: Cosmology from peak count statistics

Joachim Harnois-Déraps^{1*}, Sven Heydenreich², Benjamin Giblin³, Nicolas Martinet⁴,
Tilman Tröster⁵, Marika Asgari^{1,6,7}, Pierre Burger^{8,9,10}, Tiago Castro^{1,12,13,14},
Klaus Dolag¹⁵, Catherine Heymans^{3,16}, Hendrik Hildebrandt¹⁶, Benjamin Joachimi¹⁷ &
Angus H. Wright¹⁶

KiDS-SBI: Simulation-Based Inference Analysis of KiDS-1000 Cosmic Shear

Maximilian von Wietersheim-Kramsta^{1,2,3}, Kiyam Lin⁴, Nicolas Tessore¹, Benjamin Joachimi¹, Arthur Loureiro^{4,5},
Robert Reischke^{6,7}, and Angus H. Wright¹

Simulation-based inference of deep fields: galaxy population model and redshift distributions

Beatrice Moser,^{a,1} Tomasz Kacprzak,^{a,b} Silvan Fischbacher,^a
Alexandre Refregier,^a Dominic Grimm,^a Luca Tortorelli^c

SmBIG: Cosmological Constraints using Simulation-Based Inference of Galaxy Clustering with Marked Power Spectra

ELENA MASSARA  ^{1,2,*}, CHANGHOON HAN  ², MICHAEL EICKENBERG ², SHERELY HO ³, JIAMIN HOU ²,
PABLO LEMOS ^{4,5}, CHIRAG MODI ^{4,6}, AZADEH MORADNEZHAD DEHGHAN  ^{7,8,11}, LIAM PARKER ^{5,12} AND
BENOÎT RÉGALDO-SAINT BLANCARD 

Conclusions

github.com/handley-lab



- ▶ Nested sampling is a multi-purpose numerical tool for:
 - ▶ Numerical integration $\int f(x) dV$,
 - ▶ Exploring/scanning/optimising *a priori* unknown functions,
 - ▶ Performing Bayesian inference and model comparison.
- ▶ It is applied widely across cosmology & particle physics.
- ▶ It's unique traits as the only numerical Lebesgue integrator mean with compute it will continue to grow in importance.
- ▶ SBI represents the future of inference beyond LBI.

