

Crafters Market

Google Ads API Integration — Design Documentation

Prepared: May 27, 2026 · Production URL: <https://craftersmarket.org> · Developer-token holder MCC: 783-002-9964

1. Tool Overview

Crafters Market is a US-based multi-vendor marketplace for independent CNC, plasma, and laser fabricators. The Google Ads API integration described in this document is a strictly **read-only**, internal-use tool that pulls daily campaign-level performance metrics from our own MCC into the platform's admin analytics dashboard. It powers no ad-buying automation, no bid changes, no campaign creation. Its sole purpose is to give the operator a single-pane view of channel ROI alongside our other marketing channels (Meta Ads, Google Analytics).

The integration is one of seven internal data sources that feed the same admin dashboard: Stripe payments, Shippo shipping, Mailgun email metrics, Google Analytics 4, Meta Ads, Buffer social engagement, and Google Ads. It does not expose the Google Ads data to any external user, third party, or buyer.

2. Business Model

Crafters Market is a multi-vendor marketplace platform. Independent makers (sole proprietors and small workshops) list custom-made physical products — wall art, signs, furniture, address numbers — on craftersmarket.org. We handle the entire buyer-facing flow: product discovery, checkout via Stripe Connect, shipping label generation via Shippo, transactional email via Mailgun, and customer service. Makers fulfill orders from their own workshops and ship direct to buyers.

Revenue streams: (1) a 5% platform fee on each completed transaction; (2) a \$0.20 listing fee per item after a free 10-listing quota per maker; (3) optional weekly promotion credits at \$5/listing; (4) Plus membership at \$12/month for high-volume makers (15 free listings + reduced 4% platform fee).

Marketing usage of Google Ads: we run Search and Performance Max campaigns against our own MCC to drive qualified buyer traffic to product detail pages on craftersmarket.org. The Google Ads API integration is purely for measuring the return on this spend — not for managing the campaigns themselves, which we configure manually inside the Google Ads UI.

3. Data Flow

The integration is implemented as a backend module in our FastAPI Python application (file: **`routers/google_ads.py`**). It exposes four admin-only endpoints, all gated behind a JWT bound to a single super-admin role:

Endpoint	Purpose
GET /api/admin/integrations/google-ads/status	Returns connection state, last sync timestamp, row count, and any error.

GET /api/admin/integrations/google-ads/oauth/start	Mints a CSRF state token and returns Google's consent URL.
GET /api/admin/integrations/google-ads/oauth/callback	Exchanges the authorization code for a refresh token and persists it.
POST /api/admin/integrations/google-ads/sync	Manual trigger for the daily metrics sync; reuses the same code path as cron.
POST /api/admin/integrations/google-ads/disconnect	Deletes the locally stored refresh token.

Daily sync job: a scheduled task runs at 03:30 UTC every 24 hours. It calls a single GAQL query against the customer's MCC, fetches the previous calendar day's campaign-level metrics, and upserts them into our internal **ad_spend** MongoDB collection keyed on (platform, campaign_id, date). The admin dashboard reads from this collection — it never queries the Google Ads API at request time.

The exact GAQL query used:

```
SELECT campaign.id, campaign.name, segments.date, metrics.cost_micros,
metrics.clicks, metrics.impressions, metrics.conversions FROM campaign WHERE
segments.date = 'YYYY-MM-DD' ORDER BY campaign.id
```

Six fields, one day at a time, one customer (our own MCC). No writes, no batch jobs, no bulk historical pulls.

4. OAuth Scopes & Access Pattern

Requested scope: `https://www.googleapis.com/auth/adwords` (single scope, read intent only — we never call any mutate or create services from the SDK).

OAuth client type: Web application. Authorized redirect URIs are restricted to two callbacks:

- `https://craftersmarket.org/api/admin/integrations/google-ads/oauth/callback` (production)
- `https://active-project-4.preview.emergentagent.com/api/admin/integrations/google-ads/oauth/callback` (staging)

Token storage: the refresh token returned by Google's token endpoint is persisted in our managed MongoDB instance under the **integration_credentials** collection (`_id = "google_ads"`), one document total. The access token is fetched on-demand from the refresh token at sync time — never persisted, never logged.

CSRF protection: the OAuth start endpoint generates a 32-byte random state token and persists it to the **integration_oauth_states** collection with a 10-minute TTL. The callback validates and single-use-deletes the state before exchanging the code.

Access pattern: exactly one customer ID (our own MCC) — operations against sub-accounts route through `login_customer_id = 7830029964` as required by the Google Ads SDK.

5. Expected API Usage

Quantified usage profile (well within the 15,000 ops/day Basic Access ceiling):

Metric	Value
Customers queried	1 (our own MCC: 783-002-9964)
Daily scheduled sync calls	1 <code>search_stream</code> per day at 03:30 UTC
Manual sync calls	≤ 5/day (admin debug only)
Mutate / write operations	0 (never)
Estimated daily operations	< 50
Estimated daily API quota usage	< 1% of Basic Access ceiling

6. Security & Compliance

- **Transport:** all OAuth and Ads API traffic uses TLS 1.3 via the official Google Ads Python SDK (`google-ads ≥ 14`, `use_proto_plus=True`).
- **Credential isolation:** the developer token, OAuth client secret, and persisted refresh token are stored in environment variables (in production) and a MongoDB collection (refresh token only). None are exposed to the frontend or returned in any admin API response.
- **Access control:** all five admin endpoints listed in Section 3 require a valid admin JWT. Buyer and maker JWTs are rejected. There is exactly one super-admin user (`williams342@gmail.com`).

- **Audit trail:** every sync attempt writes a row to **integration_sync_log** with `started_at`, `finished_at`, `status`, `rows_synced`, and `error` (if any). The admin dashboard surfaces the last sync timestamp and the last error message so the operator can diagnose failures without leaving the UI.
- **Token revocation:** the operator can disconnect at any time via the admin UI, which deletes the persisted refresh token. Full revocation at the Google account level is the operator's responsibility via <https://myaccount.google.com/permissions>.
- **No third-party sharing:** the Google Ads data fetched is stored only in our internal MongoDB and is displayed only to the super-admin. It is not re-exported, sold, shared with third-party analytics services, or used to train any model.

*This document covers the entire Google Ads API surface area used by Crafters Market as of the date above. The integration is implemented in our open-source-stack FastAPI backend; the source file (**routers/google_ads.py**) can be made available to Google's review team on request.*