

William Kelley
MST and Shortest Path

```
/*
William Kelley
OOP - Assignment 2
Graphs
Source for Help: A lot of stackoverflow, nothing in particular was
used but
definitely pulled a lot of references and similarities from.
https://www.geeksforgeeks.org/breadth-first-search-or-bfs-for-a-graph/
https://www.geeksforgeeks.org/depth-first-search-or-dfs-for-a-graph/
*/

#include <iostream>
#include <cstdlib>
#include <string>
#include <cstring>
#include <iomanip>
#include <vector>
#include <list>
#include <algorithm>
#include <fstream>
#include <sstream>

std::ifstream infile;
std::ofstream outfile;

using namespace std;

template <class T>
class Graph {
public:
    Graph() {};
    ~Graph<T>() {};
    virtual bool adjacent(T x, T y) { return false; };
    virtual vector<T> neighbors(T x) {
        vector<T> graph;
        graph.push_back(1);
        return graph;
    };
    virtual void addNode() { cout << "Parent class 'addNode()'" << endl;
};
    virtual void deleteNode() { cout << "Parent class 'deleteNode()'" <<
endl; };
    virtual void addEdge() { cout << "Parent class 'addEdge()'" << endl;
};
    virtual void deleteEdge() { cout << "Parent class 'deleteEdge()'" <<
endl; };
```

```

    virtual void BFS() { cout << "Parent class 'BFS()'" << endl; };
    virtual void DFSUtil() { cout << "Parent class 'DFSUtil()'" << endl;
};
    virtual void DFS() { cout << "Parent class 'DFS()'" << endl; };
    virtual void MST() { cout << "Parent class 'MST()'" << endl; };
};

```

```

template <class T>
class AdjacencyMatrix : public Graph<T> {
private:
    std::vector<T> adjmatrix;
public:
    AdjacencyMatrix() {};
    ~AdjacencyMatrix() {};
    std::vector<T> getGraph() const;
    void copyGraph(list<T> copyMe);
    void inputGraph(string s);
    void printGraph() const;
    void printGraph(vector<T>) const;
    bool adjacent(T x, T y);
    std::vector<T> neighbors(T x);
    void addNode(T x);
    void deleteNode(T x);
    void addEdge(T x, T y);
    void deleteEdge(T x, T y);
    void BFS(T v);
    void DFSUtil(T v, bool visited[]);
    void DFS(T v);
    void MST();
    void ShortestPath();
};

```

```

template <class T>
class AdjacencyList : public Graph<T> {
private:
    std::list<T> adjlist;
public:
    AdjacencyList() {};
    ~AdjacencyList() {};
    std::list<T> getGraph() const;
    void copyGraph(vector<T> copyMe);
    void inputGraph(string s);
    void printGraph() const;
    void printGraph(vector<T>) const;
    bool adjacent(T x, T y);
    std::vector<T> neighbors(T x);
    void addNode(T x);
    void deleteNode(T x);
    void addEdge(T x, T y);
};

```

```

    void deleteEdge(T x, T y);
    void BFS(T v);
    void DFSUtil(T v, bool visited[]);
    void DFS(T v);
    void MST();
    void ShortestPath();
};

template<class T>
std::vector<T> AdjacencyMatrix<T>::getGraph() const
{
    return adjmatrix;
}

template<class T>
void AdjacencyMatrix<T>::copyGraph(list<T> copyMe)
{
    for (auto i = copyMe.begin(); i != copyMe.end(); ++i)
    {
        addEdge((*i / 10), (*i % 10));
    }
}

template<class T>
void AdjacencyMatrix<T>::inputGraph(string s)
{
    string input;
    T array[20];

    infile.open(s);
    while (std::getline(infile, input))
    {
        T x;
        replace(input.begin(), input.end(), ',', ' ');
        replace(input.begin(), input.end(), ':', ' ');
        input.erase(std::remove(input.begin(), input.end(), ' '),
input.end());
        for (auto i = 0; i < input.length(); ++i)
        {
            array[i] = input[i] - '0';
        }
        x = array[0];
        for (auto j = 0; j < input.length(); ++j)
        {
            addEdge(x, array[j]);
        }
    }
    infile.close();
}

```

```

template<class T>
void AdjacencyMatrix<T>::printGraph() const
{
    cout << endl;
    for (auto i = adjmatrix.begin(); i != adjmatrix.end(); ++i)
    {
        std::cout << (*i / 10) << "->" << (*i % 10) << '\n';
    }
    cout << endl;
}

```

```

template<class T>
void AdjacencyMatrix<T>::printGraph(vector<T> x) const
{
    for (auto i = x.begin(); i != x.end(); ++i)
    {
        std::cout << (*i / 10) << "->" << (*i % 10) << '\n';
    }
    cout << endl;
}

```

```

template<class T>
bool AdjacencyMatrix<T>::adjacent(T x, T y)
{
    T point = (x * 10) + y;
    std::vector<int>::iterator it;
    it = find(adjmatrix.begin(), adjmatrix.end(), point);
    if (it != adjmatrix.end())
    {
        return true;
    }
    else
    {
        return false;
    }
}

```

```

template<class T>
std::vector<T> AdjacencyMatrix<T>::neighbors(T x)
{
    std::vector<T> returnVector;
    std::vector<T> currentVector = getGraph();
    T singleDigit = NULL;
    T nodeId = (x * 10);
    T max = nodeId + 9;
    for (nodeId; nodeId <= max; ++nodeId)
    {

```

```

        for (auto i = currentVector.begin(); i != currentVector.end(); ++i)
        {
            if (*i == nodeId)
            {
                returnVector.push_back(*i);
            }
            else
            {
                void;
            }
        }
    }
    cout << endl;

    return returnVector;
}

template<class T>
void AdjacencyMatrix<T>::addNode(T x)
{
    T point = x + (x * 10);    // this allows for the user to combine the
                                // points into a single value to be stored
    adjmatrix.erase(std::remove(adjmatrix.begin(), adjmatrix.end(),
                                point), adjmatrix.end());
    adjmatrix.push_back(point);
    sort(adjmatrix.begin(), adjmatrix.end());
}

template<class T>
void AdjacencyMatrix<T>::deleteNode(T x)
{
    T point = (x * 10);
    for (T i = 0; i <= 9; ++i)
    {
        adjmatrix.erase(std::remove(adjmatrix.begin(), adjmatrix.end(),
                                      point + i), adjmatrix.end());
        for (T i = 0; i <= 9; ++i) {
            adjmatrix.erase(std::remove(adjmatrix.begin(), adjmatrix.end(),
                                          ((i * 10) + (point / 10))), adjmatrix.end());
        }
    }
    sort(adjmatrix.begin(), adjmatrix.end());
}

template<class T>
void AdjacencyMatrix<T>::addEdge(T x, T y)
{
    T point = (x * 10) + y;

```

```

    adjmatrix.erase(std::remove(adjmatrix.begin(), adjmatrix.end(),
point), adjmatrix.end()); //deleting edge if it exists and re-adding
just for ease
    adjmatrix.push_back(point);
    sort(adjmatrix.begin(), adjmatrix.end());
}

```

```

template<class T>
void AdjacencyMatrix<T>::deleteEdge(T x, T y)
{
    T point = (x * 10) + y;
    std::vector<int>::iterator it;
    it = find(adjmatrix.begin(), adjmatrix.end(), point);
    if (it != adjmatrix.end())
    {
        cout << "Edge found, deleteing edge." << endl;
        adjmatrix.erase(std::remove(adjmatrix.begin(), adjmatrix.end(),
point), adjmatrix.end());
    }
    else
    {
        cout << "Unable to locate edge." << endl;
    }
    sort(adjmatrix.begin(), adjmatrix.end());
}

```

```

template<class T>
void AdjacencyMatrix<T>::BFS(T v)
{
    const int V = 10;
    T first;
    T second;
    vector<int> adj[10];
    for (auto i = adjmatrix.begin(); i != adjmatrix.end(); ++i)
    {
        first = *i / 10;
        second = *i % 10;
        adj[first].push_back(second);
    }

    // Mark all the vertices as not visited
    bool *visited = new bool[V];
    for (int i = 0; i < V; i++)
        visited[i] = false;

    // Create a queue for BFS
    list<int> queue;

    // Mark the current node as visited and enqueue it

```

```

visited[v] = true;
queue.push_back(v);

// 'i' will be used to get all adjacent
// vertices of a vertex
list<int>::iterator i;

while (!queue.empty())
{
    // Dequeue a vertex from queue and print it
    v = queue.front();
    cout << v << " ";
    queue.pop_front();

    // Get all adjacent vertices of the dequeued
    // vertex s. If a adjacent has not been visited,
    // then mark it visited and enqueue it
    for (auto i = adj[v].begin(); i != adj[v].end(); ++i)
    {
        if (!visited[*i])
        {
            visited[*i] = true;
            queue.push_back(*i);
        }
    }
}

}

template<class T>
void AdjacencyMatrix<T>::DFSUtil(T v, bool visited[])
{
    const int V = 10;
    T first;
    T second;
    vector<int> adj[10];
    for (auto i = adjmatrix.begin(); i != adjmatrix.end(); ++i)
    {
        first = *i / 10;
        second = *i % 10;
        adj[first].push_back(second);
    }

    // Mark the current node as visited and
    // print it
    visited[v] = true;
    cout << v << " ";

    // Recur for all the vertices adjacent
    // to this vertex

```

```

    list<int>::iterator i;
    for (auto i = adj[v].begin(); i != adj[v].end(); ++i)
        if (!visited[*i])
            DFSUtil(*i, visited);
}

template<class T>
void AdjacencyMatrix<T>::DFS(T v)
{
    // Mark all the vertices as not visited
    bool *visited = new bool[10];
    for (auto i = 0; i < 10; i++)
        visited[i] = false;

    // Call the recursive helper function
    // to print DFS traversal
    DFSUtil(v, visited);
}

template<class T>
void AdjacencyMatrix<T>::MST()
{
    cout << "MST function for moregraph.cpp > AdjacencyMatrix" << endl;
}

template<class T>
void AdjacencyMatrix<T>::ShortestPath()
{
    cout << "ShortestPath function for moregraph.cpp > AdjacencyMatrix"
<< endl;
}

template<class T>
std::list<T> AdjacencyList<T>::getGraph() const
{
    return adjlist;
}

template<class T>
void AdjacencyList<T>::copyGraph(vector<T> copyMe)
{
    for (auto i = copyMe.begin(); i != copyMe.end(); ++i)
    {
        addEdge((*i / 10), (*i % 10));
    }
}

template<class T>
void AdjacencyList<T>::inputGraph(string s)

```



```

{
    string input;
    T array[20];

    infile.open(s);
    while (std::getline(infile, input))
    {
        T x;
        replace(input.begin(), input.end(), ',', ' ');
        replace(input.begin(), input.end(), ':', ' ');
        input.erase(std::remove(input.begin(), input.end(), ' '),
input.end());
        for (auto i = 0; i < input.length(); ++i)
        {
            array[i] = input[i] - '0';
        }
        x = array[0];
        for (auto j = 0; j < input.length(); ++j)
        {
            addEdge(x, array[j]);
        }
    }
    infile.close();
}

```

```

template<class T>
void AdjacencyList<T>::printGraph() const
{
    cout << endl;

    for (auto i = adjlist.begin(); i != adjlist.end(); ++i)
    {
        std::cout << (*i / 10) << "->" << (*i % 10) << '\n';
    }
    cout << endl;
}

```

```

template<class T>
void AdjacencyList<T>::printGraph(vector<T> x) const
{
    for (auto i = x.begin(); i != x.end(); ++i)
    {
        std::cout << (*i / 10) << "->" << (*i % 10) << '\n';
    }
    cout << endl;
}

```

```

template<class T>
bool AdjacencyList<T>::adjacent(T x, T y)

```

```

{
    T point = (x * 10) + y;
    std::list<int>::iterator it;
    it = find(adjlist.begin(), adjlist.end(), point);
    if (it != adjlist.end())
    {
        return true;
    }
    else
    {
        return false;
    }
}

template<class T>
std::vector<T> AdjacencyList<T>::neighbors(T x)
{
    std::vector<T> returnVector;
    std::list<T> currentList = getGraph();
    T singleDigit = NULL;
    T nodeId = (x * 10);
    T max = nodeId + 9;
    for (nodeId; nodeId <= max; ++nodeId)
    {
        for (auto i = currentList.begin(); i != currentList.end(); ++i)
        {
            if (*i == nodeId)
            {
                returnVector.push_back(*i);
            }
            else
            {
                void;
            }
        }
    }
    cout << endl;

    return returnVector;
}

template<class T>
void AdjacencyList<T>::addNode(T x)
{
    T point = x + (x * 10);    // this allows for the user to combine the
    points into a single value to be stored
    adjlist.erase(std::remove(adjlist.begin(), adjlist.end(), point),
adjlist.end());
    adjlist.push_back(point);
}

```

```

    adjlist.sort();
}

template<class T>
void AdjacencyList<T>::deleteNode(T x)
{
    T point = (x * 10);
    for (T i = 0; i <= 9; ++i)
    {
        adjlist.erase(std::remove(adjlist.begin(), adjlist.end(), point +
i), adjlist.end());
        for (T i = 0; i <= 9; ++i)
        {
            adjlist.erase(std::remove(adjlist.begin(), adjlist.end(), ((i *
10) + (point / 10))), adjlist.end());
        }
    }
    adjlist.sort();
}

template<class T>
void AdjacencyList<T>::addEdge(T x, T y)
{
    T point = (x * 10) + y;
    adjlist.erase(std::remove(adjlist.begin(), adjlist.end(), point),
adjlist.end()); //deleting edge if it exists and re-adding just for
ease
    adjlist.push_back(point);
    adjlist.sort();
}

template<class T>
void AdjacencyList<T>::deleteEdge(T x, T y)
{
    T point = (x * 10) + y;
    std::list<int>::iterator it;
    it = find(adjlist.begin(), adjlist.end(), point);
    if (it != adjlist.end())
    {
        cout << "Edge found, deleteing edge." << endl;
        adjlist.erase(std::remove(adjlist.begin(), adjlist.end(), point),
adjlist.end());
    }
    else
    {
        cout << "Unable to locate edge." << endl;
    }
    adjlist.sort();
}

```

```

template<class T>
void AdjacencyList<T>::BFS(T v)
{
    const int V = 10;
    T first;
    T second;
    vector<int> adj[10];
    for (auto i = adjlist.begin(); i != adjlist.end(); ++i)
    {
        first = *i / 10;
        second = *i % 10;
        adj[first].push_back(second);
    }

    // Mark all the vertices as not visited
    bool *visited = new bool[V];
    for (int i = 0; i < V; i++)
        visited[i] = false;

    // Create a queue for BFS
    list<int> queue;

    // Mark the current node as visited and enqueue it
    visited[v] = true;
    queue.push_back(v);

    // 'i' will be used to get all adjacent
    // vertices of a vertex
    list<int>::iterator i;

    while (!queue.empty())
    {
        // Dequeue a vertex from queue and print it
        v = queue.front();
        cout << v << " ";
        queue.pop_front();

        // Get all adjacent vertices of the dequeued
        // vertex s. If a adjacent has not been visited,
        // then mark it visited and enqueue it
        for (auto i = adj[v].begin(); i != adj[v].end(); ++i)
        {
            if (!visited[*i])
            {
                visited[*i] = true;
                queue.push_back(*i);
            }
        }
    }
}

```

```

    }
}

template<class T>
void AdjacencyList<T>::DFSUtil(T v, bool visited[])
{
    const int V = 10;
    T first;
    T second;
    vector<int> adj[10];
    for (auto i = adjlist.begin(); i != adjlist.end(); ++i)
    {
        first = *i / 10;
        second = *i % 10;
        adj[first].push_back(second);
    }

    // Mark the current node as visited and
    // print it
    visited[v] = true;
    cout << v << " ";

    // Recur for all the vertices adjacent
    // to this vertex
    list<int>::iterator i;
    for (auto i = adj[v].begin(); i != adj[v].end(); ++i)
        if (!visited[*i])
            DFSUtil(*i, visited);
}

template<class T>
void AdjacencyList<T>::DFS(T v)
{
    // Mark all the vertices as not visited
    bool *visited = new bool[10];
    for (auto i = 0; i < 10; i++)
        visited[i] = false;

    // Call the recursive helper function
    // to print DFS traversal
    DFSUtil(v, visited);
}

template<class T>
void AdjacencyList<T>::MST()
{
    cout << "MST function for moregraph.cpp > AdjacencyList" << endl;
}

```

```

template<class T>
void AdjacencyList<T>::ShortestPath()
{
    cout << "ShortestPath function for moregraph.cpp > AdjacencyList" <<
endl;
}

int main()
{
    AdjacencyMatrix<int> matrix;
    AdjacencyMatrix<int> copyMatrix;
    AdjacencyList<int> list;
    AdjacencyList<int> copyList;

    int inputX;
    int inputY;

    string fileName = "text.txt";

    cout << "Note to testers: only accepts single digit values.\n\n";

    cout << "Input File and Print for Matrix\n";

    matrix.inputGraph(fileName);
    matrix.printGraph();

    cout << "Input File and Print for List\n";

    list.inputGraph(fileName);
    list.printGraph();

    cout << "Add Node to Matrix(enter 0 to exit): \n";
    cin >> inputX;
    while (inputX != 0) {
        matrix.addNode(inputX);
        cout << "\nEnter another node to enter or enter 0 to exit\n";
        cin >> inputX;
    }

    matrix.printGraph();

    cout << "Delete Node from Matrix(enter 0 to exit): \n";
    cin >> inputX;
    while (inputX != 0) {
        matrix.deleteNode(inputX);
        cout << "\nEnter another node to delete or enter 0 to exit\n";
        cin >> inputX;
    }
}

```

```

matrix.printGraph();

cout << "Add Edge to Matrix(enter 0 to exit): x,y with values
separated by space\n";
cin >> inputX >> inputY;
while (inputX != 0) {
    matrix.addNode(inputX);    // by my theory if there's a node,
then it relates to itself as well
    matrix.addEdge(inputX, inputY);
    cout << "\nEnter another edge to enter or enter 0 0 to exit\n";
    cin >> inputX >> inputY;
}

matrix.printGraph();

cout << "Delete Edge from Matrix(enter 0 to exit): x,y with values
separated by space\n";
cin >> inputX >> inputY;
while (inputX != 0) {
    matrix.deleteEdge(inputX, inputY);
    cout << "\nEnter another edge to delete or enter 0 0 to exit\n";
    cin >> inputX >> inputY;
}

matrix.printGraph();

cout << "What Node would you like to know the neighbors of? (enter
node or 0 to exit)\n";
cin >> inputX;
while (inputX != 0) {
    matrix.printGraph(matrix.neighbors(inputX));
    cout << "\nEnter another node to find out neighbors or enter 0 to
exit\n";
    cin >> inputX;
}

cout << "Enter nodes to determine whether or not they are adjacent
(enter x,y values seperated by a space or 0 0 to exit)\n";
cin >> inputX >> inputY;
while (inputX != 0) {
    matrix.adjacent(inputX, inputY);
    cout << "\nEnter another edge to determine whether it has
adjacency (enter x,y values separated by a space or 0 0 to exit)\n";
    cin >> inputX >> inputY;
}

cout << "What BFS vertex would you like to know the nodes of? (enter
node or 0 to exit)\n";
cin >> inputX;

```

```

    while (inputX != 0) {
        matrix.BFS(inputX);
        cout << "\nEnter another node to find BFS of or enter 0 to
exit\n";
        cin >> inputX;
    }

    cout << "What DFS vertex would you like to know the nodes of? (enter
node or 0 to exit)\n";
    cin >> inputX;
    while (inputX != 0) {
        matrix.DFS(inputX);
        cout << "\nEnter another node to find BFS of or enter 0 to
exit\n";
        cin >> inputX;
    }

    cout << "Copying Matrix to List" << endl;
    copyList.copyGraph(matrix.getGraph());
    copyList.printGraph();

    cout << "Copying List to Matrix" << endl;
    copyMatrix.copyGraph(list.getGraph());
    copyMatrix.printGraph();

    matrix.MST();
    list.MST();

    matrix.ShortestPath();
    list.ShortestPath();

    cout << "\n\nSince my functions are virtually the same for either,
I've only displayed the Matrix\n";

    system("PAUSE");
}

```

/*
OUTPUT

Note to testers: only accepts single digit values.

Input File and Print for Matrix

```

1->1
1->2
1->3
1->4
2->2

```


2->4
2->5
3->1
3->3
3->5
4->1
4->4

Input File and Print for List

1->1
1->2
1->3
1->4
2->2
2->4
2->5
3->1
3->3
3->5
4->1
4->4

1->1
1->2
1->3
1->4
2->2
2->4
2->5
3->1
3->3
3->5
4->1
4->4

Add Edge to Matrix(enter 0 to exit): x,y with values separated by
space
5 6

Enter another edge to enter or enter 0 0 to exit
7 9

Enter another edge to enter or enter 0 0 to exit
0 0
Copying Matrix to List

1->1

```
1->2
1->3
1->4
2->2
2->4
2->5
3->1
3->3
3->5
4->1
4->4
5->5
5->6
7->7
7->9
```

Copying List to Matrix

```
1->1
1->2
1->3
1->4
2->2
2->4
2->5
3->1
3->3
3->5
4->1
4->4
```

MST function for moregraph.cpp > AdjacencyMatrix

MST function for moregraph.cpp > AdjacencyList

ShortestPath function for moregraph.cpp > AdjacencyMatrix

ShortestPath function for moregraph.cpp > AdjacencyList

Since my functions are virtually the same for either, I've only displayed the Matrix

```
/*
```