

Package ‘daRt’

August 21, 2019

Type Package

Title Read DART Model Outputs

Version 0.5.0

Author William T. J. Morrison

Maintainer William T. J. Morrison <willmorrison661@gmail.com>

Description For reading outputs from the Discrete Anisotropic Radiative Transfer (DART) model, formatted in a ``long" dplyr-ready format suitable for efficient analysis.

Github <https://github.com/willmorrison1/daRt>

License GPL-3

Encoding UTF-8

RoxygenNote 6.1.1

R topics documented:

accessors	2
as.data.frame,SimulationData-method	2
Directions-class	3
getData	3
getFiles	3
Images-class	3
imagesToDirectionsDF	4
plot.directions	4
RB3D-class	5
SimulationData-class	5
SimulationFiles-class	5
simulationFilter	6
SimulationFilter-class	6
Index	8

accessors

Access object information

Description

Generic functions to access information from the objects with classes defined in this package

Usage`product(x)``simname(x)``files(x)``bands(x)``iters(x)``variables(x)``variablesRB3D(x)``typeNums(x)``imageType(x)``imageNo(x)`

`as.data.frame, SimulationData-method`*as.data.frame*

Description`as.data.frame`**Usage**

```
## S4 method for signature 'SimulationData'
as.data.frame(x, as.tibble = TRUE)
```

Arguments

x	SimulationData.
---	-----------------

Directions-class	<i>Directions data class</i>
------------------	------------------------------

Description

Directions data class that extends [SimulationData-class](#) class.

getData	<i>Main function: get DART data</i>
---------	-------------------------------------

Description

Main function to get data from DART simulation outputs in a friendly 'long' data format that is part of an object that extends a [SimulationData-class](#) type object

Usage

```
getData(x, sF, ...)
```

Arguments

x	simulation directory or directories (character) or SimulationFiles-class object
sF	SimulationFilter-class if x = character

getFiles	<i>Get DART output filenames</i>
----------	----------------------------------

Description

Get DART output filenames

Usage

```
getFiles(x = "character", sF = "SimulationFilter")
```

Arguments

x	simulation directory or directories (character)
sF	SimulationFilter-class object
...	Optional arguments of: nCores: number of cores to use when loading data.

Images-class	<i>Images data class</i>
--------------	--------------------------

Description

Image data class extends [SimulationData-class](#) class.

imagesToDirectionsDF	<i>imagesToDirectionsDF</i>
----------------------	-----------------------------

Description

Convert an Images-class object to a Directions-class object

Usage

```
imagesToDirectionsDF(x, fun)
```

Arguments

x	Images-class object
fun	Function to apply across each image.

Details

Aggregate images to single values

plot.directions	<i>plot.directions</i>
-----------------	------------------------

Description

Plot directions data as polar plot.

Usage

```
## S3 method for class 'directions'
plot(azimuth, zenith, value, azimuthOffsetVal = 0,
     outerRadius = max(zenith) + max(zenith) * 0.01, zenithLabPch = 20,
     zenithLabCol = "darkgrey", zenithLabCex = 1, brks = seq(min(value),
     max(value), length.out = 10), cols = c("dark grey",
     colorRampPalette(c("purple", "blue3", "yellow", "red"))(length(brks) -
     3), "firebrick4"), ...)
```

Arguments

azimuth	Numeric. Azimuth angle with DART conventions
zenith	Numeric. Zenith angle with DART conventions
value	Numeric. Values associated with the given azimuth and zenith angles
azimuthOffsetVal	Numeric. Scene offset (degrees) as shown in the DART GUI.
outerRadius	Numeric. Maximum radius (degrees) of polar plot
zenithLabPch	Numeric. Pch for zenith label.
zenithLabCol	Character. Colour for zenith label.

zenithLabCex	Numeric. Cex for zenith label.
brks	Numeric. Breaks for colour palette e.g. seq(0, 1, by = 0.1). Optional.
cols	Character. Colours for given breaks. Optional.
...	Additional options passed to points() when drawing directions points.

RB3D-class

RB3D class

Description

RB3D (Radiative Budget 3D) class that extends [SimulationData-class](#) class.

SimulationData-class

Generic SimulationData class

Description

Generic SimulationData class that extends to data classes for specific DART products

Slots

data data.frame.

See Also

[Images-class](#) [Directions-class](#) [RB3D-class](#)

SimulationFiles-class

SimulationFiles class

Description

An S4 class to represent the files within a simulation or simulations. Created using the [getFiles](#) method. Specific files within the class are modified by the object with class [SimulationFilter-class](#)

Usage

simdir(x)

Slots

simulationFilter contains [SimulationFilter-class](#) object

files a data.frame, with each row describing the file

sequenceInfoList a list, with each list element showing the variable permutation(s) within this specific simulation sequence.

simulationFilter Create [SimulationFilter](#) class

Description

Function for creating the [SimulationFilter](#) class

Usage

```
simulationFilter(product = "character", ...)
```

Arguments

product One of "directions", "rb3D", "images".
...

See Also

[SimulationFilter-class](#)

SimulationFilter-class
SimulationFilter class.

Description

SimulationFilter class.

Usage

```
product(x) <- value  
iters(x) <- value  
bands(x) <- value  
variablesRB3D(x) <- value  
variables(x) <- value  
typeNums(x) <- value  
imageType(x) <- value  
imageNo(x) <- value
```

Slots

bands character.
variables character.
iters character.
variablesRB3D character.
typeNums character.
imageType character.
imageNo numeric.
product character.

See Also

[simulationFilter](#)

Index

accessors, [2](#)
as.data.frame, SimulationData-method, [2](#)

bands (accessors), [2](#)
bands<- (SimulationFilter-class), [6](#)

Directions-class, [3](#), [5](#)

files (accessors), [2](#)

getData, [3](#)
getFiles, [3](#), [5](#)

imageNo (accessors), [2](#)
imageNo<- (SimulationFilter-class), [6](#)
Images-class, [3](#), [4](#), [5](#)
imagesToDirectionsDF, [4](#)
imageType (accessors), [2](#)
imageType<- (SimulationFilter-class), [6](#)
iters (accessors), [2](#)
iters<- (SimulationFilter-class), [6](#)

plot.directions, [4](#)
product (accessors), [2](#)
product<- (SimulationFilter-class), [6](#)

RB3D-class, [5](#), [5](#)

simdir (SimulationFiles-class), [5](#)
simname (accessors), [2](#)
SimulationData-class, [3](#), [5](#), [5](#)
SimulationFiles-class, [3](#), [5](#)
SimulationFilter, [6](#)
simulationFilter, [6](#), [7](#)
SimulationFilter-class, [3](#), [5](#), [6](#)

typeNums (accessors), [2](#)
typeNums<- (SimulationFilter-class), [6](#)

variables (accessors), [2](#)
variables<- (SimulationFilter-class), [6](#)
variablesRB3D (accessors), [2](#)
variablesRB3D<-
 (SimulationFilter-class), [6](#)