我的sandbox 样例:

[oracle@demo oracle]\$ pwd
/app/oracle

驱动位置

[oracle@demo oracle]\$ find . -name ARmysql27.so

- ./biee/bi/common/ODBC/Merant/7.1.2/lib/ARmysql27.so
- ./biee/bi/common/ODBC/Merant/7.1.4/lib/ARmysql27.so

配置文件中驱动位置参考

[oracle@demo oracle]\$ cat ./biee/bi/common/ODBC/Merant/7.1.4/odbc.ini|grep Driver=<install_location>/lib/ARmysql27.so

odbc.ini 位置:

[oracle@demo oracle]\$ find . -name "odbc.ini"

- ./biee/bi/common/ODBC/Merant/7.1.2/odbc.ini
- ./biee/bi/common/ODBC/Merant/7.0.1/odbc.ini
- ./biee/bi/common/ODBC/Merant/7.1.4/odbc.ini
- ./biee/bi/common/ODBC/Merant/5.3/odbc.ini
- ./biee/user_projects/domains/bi2/config/fmwconfig/bienv/core/odbc.ini
- ./biee/user_projects/domains/bi/config/fmwconfig/bienv/core/odbc.ini

根据官方文档说明:

https://docs.oracle.com/middleware/1221/biee/BIEMG/deploy_rpd.htm#BIEMG1197

应该是这个:

./biee/user_projects/domains/bi/config/fmwconfig/bienv/core/odbc.ini

定下了配置文件,就可以配置了,参考配置如下:

参考配置:

########[oracle@demo oracle]\$ cat ./biee/bi/common/ODBC/Merant/7.1.4/odbc.ini

[MySQL Wire Protocol]

Driver=/lib/ARmysql27.so

Description=DataDirect 7.1 MySQL Wire Protocol

AlternateServers=

ApplicationUsingThreads=1

ConnectionReset=0

ConnectionRetryCount=0

ConnectionRetryDelay=3

Database=

DefaultLongDataBuffLen=1024

EnableDescribeParam=0

EncryptionMethod=0

FailoverGranularity=0

FailoverMode=0

FailoverPreconnect=0

HostName=

HostNameInCertificate=

InteractiveClient=0

LicenseNotice=You must purchase commercially licensed MySQL database software or a

MySQL Enterprise subscription in order to use the DataDirect Connect for ODBC for MySQL

Enterprise driver with MySQL software.

KeyStore=

KeyStorePassword=

LoadBalanceTimeout=0

LoadBalancing=0

LogonID=

LoginTimeout=15

MaxPoolSize=100

MinPoolSize=0

Password=

Pooling=0

PortNumber=
QueryTimeout=0
ReportCodepageConversionErrors=0
TreatBinaryAsChar=0
TrustStore=
TrustStorePassword=

ValidateServerCertificate=1