

VLAN ID	VLAN Name	Subnet	CIDR (Subnet Mask)	Inni-A1	Inni-A2	Inni-A3	Inni-D1	Inni-D2	Inni-R1	Inni-R2
99	SHUT									
12	PENNA Trode	131.31.12.0	/24 (255.255.255.0)				.4	.5	.2	.3
16	Inni Tek	131.31.16.0	/24 (255.255.255.0)				.4	.5	.2	.3
31	Lumberg	200.20.31.128	/26 (255.255.255.192)				.132	.133	.130	.131
61	channel 5	200.20.61.192	/26 (255.255.255.192)				.196	.197	.194	.195
80	The Bobs	222.1.80.48	/28 (255.255.255.240)				.52	.53	.50	.51
90	Inni Server	222.1.90.16	/28 (255.255.255.240)				.20	.21	.18	.19
1	Management	198.34.203.64	/27 (255.255.255.224)	.80	.81	.82	.70	.71	.66	.67
	PTP	81.33.41.16	/30 (255.255.255.252)						.17	.18
	ISP	92.23.11.248	/30 (255.255.255.252)						.249	
	ISP	92.23.11.252	/30 (255.255.255.252)							.253

	Inni-A1	Inni-A2	Inni-A3	Inni-D1	Inni-D2	Inni-R1	Inni-R2
VTP Mode	Client	Client	Client	Server	Client		
EIGRP ASN						44	44
Spanning Tree Root Primary				12, 16, 31	61, 80, 90		
Spanning Tree Root Secondary				61, 80, 90	12, 16, 31		

Console Password	static		
VTP Domain	flingers.com		
VTP Password	MinimumFlair		
Enable Secret	shock		
IP Domain	officespace.com		
ISP Management	98.87.44.111		
Username	michael.bolton	Secret	aZclown

Access Control List(s)	
LIST #	(APPLY TO ALL VTY LINES)
98	Permit the ISP Management host.
98	Permit the Management subnet.
LIST #	(APPLY TO ALL ISP FACING INTERFACES)
123	Permit SSH from the ISP Management host.
123	Deny SSH from all other sources.
123	Permit all traffic from all other sources

Dynamic Routing	
EIGRP	Enable the PTP and ISP interfaces on the router(s) Turn off auto-summary