

VLAN ID	VLAN Name	Subnet	CIDR (Subnet Mask)	b1002-f1-2960	b1002-f2-2960	b1002-f3-2960	b1002-f1-3560	b1002-f2-3560	b1002-f1-2911	b1002-f2-2911
5	shutdown	-	-	-	-	-	-	-	-	-
11	sfs-users	200.195.1.224	/28 (255.255.255.240)	-	-	-	.228	.229	.226	.227
12	cons-users	200.195.1.192	/27 (255.255.255.224)	-	-	-	.196	.197	.194	.195
16	cyber-users	200.195.1.160	/27 (255.255.255.224)	-	-	-	.164	.165	.162	.163
27	pa-users	200.195.1.128	/27 (255.255.255.224)	-	-	-	.132	.133	.130	.131
50	ce-users	200.195.1.0	/26 (255.255.255.192)	-	-	-	.4	.5	.2	.3
31	fss-users	200.195.1.64	/26 (255.255.255.192)	-	-	-	.68	.69	.66	.67
1	Management	10.200.233.0	/24 (255.255.255.0)	.10	.11	.12	.20	.21	.30	.31
-	PTP	132.25.10.252	/30 (255.255.255.252)	-	-	-	-	-	.253	.254
-	ISP	200.195.1.248	/30 (255.255.255.252)	-	-	-	-	-	.249	-
-	ISP	200.195.1.252	/30 (255.255.255.252)	-	-	-	-	-	-	.253

	b1002-f1-2960	b1002-f2-2960	b1002-f3-2960	b1002-f1-3560	b1002-f2-3560	b1002-f1-2911	b1002-f2-2911
<b>VTP Mode</b>	Client	Client	Client	Server	Client	-	-
<b>EIGRP ASN</b>	-	-	-	-	-	81	81
<b>Spanning Tree Root Primary</b>	-	-	-	11, 12, 16	27, 50, 31	-	-
<b>Spanning Tree Root Secondary</b>	-	-	-	27, 50, 31	11, 12, 16	-	-

<b>VTP Domain</b>	bldg1002.us.af.mil		
<b>VTP Password</b>	samurai		
<b>Enable Secret</b>	warrior		
<b>IP Domain</b>	us.af.mil		
<b>ISP Management</b>	8.8.8.8		
<b>Console Password</b>	cyber		
<b>Username</b>	uct.ninja	<b>Secret</b>	cyber

Access Control List(s)	
LIST #	(APPLY TO ALL VTY LINES)
10	Permit the ISP Management host
10	Permit the management subnet
LIST #	(APPLY TO ALL ISP FACING INTERFACES)
101	Permit SSH from the ISP Management host
101	Deny SSH from all other sources
101	Permit all traffic from all other sources

Dynamic Routing	
EIGRP	Enable the PTP and ISP interfaces on the router(s) Turn off auto-summary