

## GT-Type Side/Cross Trench Grating Covers (std length ~995 mm)

Load Grade: T-2=2000kg | T-6=6000kg | T-14=14000kg | T-20=20000kg | T-25=25000kg  
 Dimensions: mm | Weight: kg/unit

### Load Grade: T-2+pedestrian

| Trench Width (mm) | Model           | Cover Dim. b×a×h (mm) | Weight (kg/unit) | Seat Angle |
|-------------------|-----------------|-----------------------|------------------|------------|
| 100               | <b>GT100-20</b> | 995×160×20            | 4.0              | L40×25×5   |
| 120               | <b>GT120-20</b> | 995×180×20            | 4.4              | L40×25×5   |
| 150               | <b>GT150-20</b> | 995×210×20            | 5.2              | L40×25×5   |
| 180               | <b>GT180-20</b> | 995×240×20            | 5.7              | L40×25×5   |
| 200               | <b>GT200-20</b> | 995×260×20            | 6.0              | L40×25×5   |
| 240               | <b>GT240-25</b> | 995×304×25            | 13.4             | L40×28×3   |
| 300               | <b>GT300-25</b> | 995×364×25            | 15.9             | L40×28×3   |
| 360               | <b>GT360-25</b> | 995×424×25            | 18.3             | L40×28×3   |
| 400               | <b>GT400-25</b> | 995×464×25            | 19.7             | L40×28×3   |
| 450               | <b>GT450-32</b> | 995×544×32            | 28.8             | L56×36×4   |
| 500               | <b>GT500-45</b> | 995×580×45            | 42.2             | L50×50×5   |
| 600               | <b>GT600-50</b> | 995×690×50            | 54.8             | L56×56×6   |

### Load Grade: T-6

| Trench Width (mm) | Model           | Cover Dim. b×a×h (mm) | Weight (kg/unit) | Seat Angle |
|-------------------|-----------------|-----------------------|------------------|------------|
| 100               | <b>GT100-25</b> | 995×164×25            | 8.2              | L40×28×3   |
| 120               | <b>GT120-25</b> | 995×184×25            | 9.2              | L40×28×3   |
| 150               | <b>GT150-25</b> | 995×214×25            | 10.2             | L40×28×3   |
| 180               | <b>GT180-25</b> | 995×244×25            | 11.3             | L40×28×3   |
| 200               | <b>GT200-32</b> | 995×294×32            | 16.6             | L56×36×4   |
| 240               | <b>GT240-32</b> | 995×334×32            | 18.7             | L56×36×4   |
| 300               | <b>GT300-38</b> | 995×416×38            | 26.7             | L70×45×7   |
| 360               | <b>GT360-45</b> | 995×440×45            | 33.0             | L50×50×5   |

|     |                 |            |      |          |
|-----|-----------------|------------|------|----------|
| 400 | <b>GT400-50</b> | 995×490×50 | 40.0 | L56×56×6 |
| 450 | <b>GT450-50</b> | 995×540×50 | 43.4 | L56×56×6 |
| 500 | <b>GT500-50</b> | 995×590×50 | 47.4 | L56×56×6 |
| 600 | <b>GT600-50</b> | 995×700×55 | 60.8 | L60×60×5 |

| Load Grade: T-14     |                 |                          |                     |            |
|----------------------|-----------------|--------------------------|---------------------|------------|
| Trench Width<br>(mm) | Model           | Cover Dim. b×a×h<br>(mm) | Weight<br>(kg/unit) | Seat Angle |
| 100                  | <b>GT100-25</b> | 995×164×25               | 8.2                 | L40×28×3   |
| 120                  | <b>GT120-25</b> | 995×184×25               | 9.2                 | L40×28×3   |
| 150                  | <b>GT150-25</b> | 995×214×25               | 10.2                | L40×28×3   |
| 180                  | <b>GT180-32</b> | 995×274×32               | 15.7                | L56×36×4   |
| 200                  | <b>GT200-32</b> | 995×294×32               | 16.6                | L56×36×4   |
| 240                  | <b>GT240-38</b> | 995×356×38               | 23.2                | L70×45×7   |
| 300                  | <b>GT300-45</b> | 995×380×45               | 28.8                | L50×50×5   |
| 360                  | <b>GT360-50</b> | 995×440×50               | 36.5                | L56×56×6   |
| 400                  | <b>GT400-50</b> | 995×480×50               | 39.3                | L56×56×6   |
| 450                  | <b>GT450-55</b> | 995×550×55               | 48.9                | L60×60×5   |
| 500                  | <b>GT500-60</b> | 995×610×60               | 58.6                | L65×65×5   |
| 600                  | <b>GT600-75</b> | 995×750×75               | 87.9                | L80×80×5   |

| Load Grade: T-20     |                 |                          |                     |            |
|----------------------|-----------------|--------------------------|---------------------|------------|
| Trench Width<br>(mm) | Model           | Cover Dim. b×a×h<br>(mm) | Weight<br>(kg/unit) | Seat Angle |
| 100                  | <b>GT100-25</b> | 995×164×25               | 8.2                 | L40×28×3   |
| 120                  | <b>GT120-25</b> | 995×214×32               | 12.9                | L56×36×4   |
| 150                  | <b>GT150-32</b> | 995×244×32               | 14.3                | L56×36×4   |
| 180                  | <b>GT180-38</b> | 995×296×38               | 19.7                | L70×45×7   |
| 200                  | <b>GT200-38</b> | 995×316×38               | 21.1                | L70×45×7   |
| 240                  | <b>GT240-45</b> | 995×320×45               | 25.0                | L50×50×5   |

|     |                 |            |      |          |
|-----|-----------------|------------|------|----------|
| 300 | <b>GT300-50</b> | 995×390×50 | 32.6 | L56×56×6 |
| 360 | <b>GT360-55</b> | 995×400×55 | 41.6 | L60×60×5 |
| 400 | <b>GT400-55</b> | 995×500×55 | 44.7 | L60×60×5 |
| 450 | <b>GT450-65</b> | 995×590×65 | 59.3 | L70×70×5 |
| 500 | <b>GT500-75</b> | 995×640×75 | 75.9 | L80×80×5 |

| Load Grade: T-25     |                 |                          |                     |            |
|----------------------|-----------------|--------------------------|---------------------|------------|
| Trench Width<br>(mm) | Model           | Cover Dim. b×a×h<br>(mm) | Weight<br>(kg/unit) | Seat Angle |
| 100                  | <b>GT100-32</b> | 995×194×32               | 11.4                | L56×36×4   |
| 120                  | <b>GT120-32</b> | 995×214×32               | 12.9                | L56×36×4   |
| 150                  | <b>GT150-38</b> | 995×266×38               | 18.1                | L70×45×7   |
| 180                  | <b>GT180-45</b> | 955×260×45               | 20.9                | L50×50×5   |
| 200                  | <b>GT200-45</b> | 955×280×45               | 22.2                | L50×50×5   |
| 240                  | <b>GT240-45</b> | 955×320×45               | 25.0                | L50×50×5   |
| 300                  | <b>GT300-50</b> | 955×390×50               | 32.6                | L56×56×6   |
| 360                  | <b>GT360-55</b> | 955×460×55               | 41.6                | L60×60×5   |
| 400                  | <b>GT400-65</b> | 955×520×65               | 54.7                | L70×70×5   |
| 450                  | <b>GT450-75</b> | 995×590×75               | 70.3                | L80×80×5   |

## GU-Type U-Channel Grating Covers (std length 995 mm)

Suitable for plain concrete U-channels without side openings  
Dimensions in mm, Weights in kg/unit

### Load Grade: T-2+pedestrian

| Trench Width(m) | Model           | Cover Dim.<br>mm | Edge Angle | Weight (kg/unit) |
|-----------------|-----------------|------------------|------------|------------------|
| 100             | <b>GU100-20</b> | 995×90×20        | L30×3      | 4.4              |
| 120             | <b>GU120-20</b> | 995×110×20       | L30×3      | 5.0              |
| 150             | <b>GU150-20</b> | 995×140×20       | L30×3      | 5.5              |
| 180             | <b>GU180-20</b> | 995×170×20       | L30×3      | 6.0              |
| 200             | <b>GU200-25</b> | 995×190×25       | L40×5      | 12.2             |
| 240             | <b>GU240-25</b> | 995×230×25       | L40×5      | 13.9             |
| 300             | <b>GU300-25</b> | 995×290×25       | L40×5      | 16.0             |
| 360             | <b>GU360-25</b> | 995×350×25       | L40×5      | 18.4             |
| 400             | <b>GU400-32</b> | 995×390×32       | L40×5      | 23.7             |
| 450             | <b>GU450-32</b> | 995×443×32       | L40×5      | 26.3             |
| 500             | <b>GU500-45</b> | 995×488×45       | L50×6      | 41.7             |
| 600             | <b>GU600-50</b> | 995×588×50       | L56×6      | 53.8             |

### Load Grade: T-6

| Trench Width(m) | Model           | Cover Dim.<br>mm | Edge Angle | Weight (kg/unit) |
|-----------------|-----------------|------------------|------------|------------------|
| 100             | <b>GU100-25</b> | 995×90×25        | L40×5      | 8.3              |
| 120             | <b>GU120-25</b> | 995×110×25       | L40×5      | 9.3              |
| 150             | <b>GU150-25</b> | 995×140×25       | L40×5      | 10.4             |
| 180             | <b>GU180-25</b> | 995×170×25       | L40×5      | 11.4             |
| 200             | <b>GU200-25</b> | 995×190×25       | L40×5      | 12.2             |
| 240             | <b>GU240-32</b> | 995×230×32       | L40×5      | 16.1             |
| 300             | <b>GU300-38</b> | 995×290×38       | L40×5      | 21.3             |
| 360             | <b>GU360-45</b> | 995×350×45       | L50×6      | 32.5             |

|     |                 |                |       |      |
|-----|-----------------|----------------|-------|------|
| 400 | <b>GU400-45</b> | 995×390×<br>45 | L50×6 | 35.1 |
| 450 | <b>GU450-50</b> | 995×440×<br>50 | L50×6 | 41.6 |
| 500 | <b>GU500-50</b> | 995×490×<br>50 | L50×6 | 45.2 |
| 600 | <b>GU600-55</b> | 995×590×<br>55 | L63×6 | 59.4 |

| Load Grade: T-14 |                 |                     |            |                  |
|------------------|-----------------|---------------------|------------|------------------|
| Trench Width(m)  | Model           | Cover Dim.<br>LxWxH | Edge Angle | Weight (kg/unit) |
| 100              | <b>GU100-25</b> | 995×90×25           | L40×5      | 8.3              |
| 120              | <b>GU120-25</b> | 995×110×25          | L40×5      | 9.3              |
| 150              | <b>GU150-25</b> | 995×140×25          | L40×5      | 10.4             |
| 180              | <b>GU180-25</b> | 995×170×25          | L40×5      | 11.4             |
| 200              | <b>GU200-32</b> | 995×190×32          | L40×5      | 14.0             |
| 240              | <b>GU240-32</b> | 995×230×32          | L40×5      | 16.1             |
| 300              | <b>GU300-45</b> | 995×290×45          | L50×6      | 28.4             |
| 360              | <b>GU360-50</b> | 995×350×45          | L50×6      | 32.5             |
| 400              | <b>GU400-50</b> | 995×390×50          | L50×6      | 37.8             |
| 450              | <b>GU450-55</b> | 995×440×55          | L63×6      | 47.4             |



## GM-Type Wellhole / Manhole Grating Covers

Municipal rainwater / sedimentation / sewage manholes Dimensions: mm Weight: kg/set

### Load Grade: T-25

| Wellhole<br>W×H<br>(mm) | Model          | Grating<br>h×a×b | Grating<br>Wt (kg) | Frame<br>B×A×H | Seat<br>Angle | Frame<br>Wt (kg) |
|-------------------------|----------------|------------------|--------------------|----------------|---------------|------------------|
| 300×400                 | <b>GM34-55</b> | 305×500×<br>55   | 14.2               | 335×520×<br>60 | L60×5         | 7.6              |
| 400×400                 | <b>GM44-55</b> | 395×500×<br>55   | 18.3               | 425×520×<br>60 | L60×5         | 8.5              |
| 500×400                 | <b>GM54-55</b> | 485×500×<br>55   | 22.5               | 515×520×<br>60 | L60×5         | 9.3              |
| 300×500                 | <b>GM35-65</b> | 305×620×<br>65   | 22.8               | 335×640×<br>70 | L70×5         | 9.4              |
| 400×500                 | <b>GM45-65</b> | 395×620×<br>65   | 29.5               | 425×640×<br>70 | L70×5         | 10.4             |
| 500×500                 | <b>GM55-65</b> | 485×620×<br>65   | 36.2               | 515×640×<br>70 | L70×5         | 11.4             |
| 300×600                 | <b>GM36-75</b> | 305×740×<br>75   | 28.6               | 335×760×<br>80 | L80×5         | 11.5             |
| 400×600                 | <b>GM46-75</b> | 395×740×<br>75   | 36.4               | 425×760×<br>80 | L80×5         | 12.6             |
| 500×600                 | <b>GM56-75</b> | 485×740×<br>75   | 44.3               | 515×760×<br>80 | L80×5         | 13.7             |
| 500×700                 | <b>GM57-75</b> | 485×840×<br>75   | 49.9               | 515×860×<br>80 | L80×5         | 14.5             |
| 700×700                 | <b>GM77-75</b> | 695×840×<br>75   | 70.6               | 725×860×<br>80 | L80×5         | 17.1             |

### Load Grade: T-20

| Wellhole<br>W×H | Model          | Grating<br>h×a×b | Grating<br>Wt (kg) | Frame<br>B×A×H | Seat<br>Angle | Frame<br>Wt (kg) |
|-----------------|----------------|------------------|--------------------|----------------|---------------|------------------|
| 300×400         | <b>GM34-50</b> | 305×490×<br>50   | 12.8               | 335×510×<br>56 | L56×6         | 7.7              |
| 400×400         | <b>GM44-50</b> | 395×490×<br>50   | 16.5               | 425×510×<br>56 | L56×6         | 8.6              |
| 500×400         | <b>GM54-50</b> | 485×490×<br>50   | 20.3               | 515×510×<br>56 | L56×6         | 9.5              |
| 300×500         | <b>GM35-55</b> | 305×600×<br>55   | 16.7               | 335×620×<br>60 | L60×5         | 8.2              |
| 400×500         | <b>GM45-55</b> | 395×600×<br>55   | 21.7               | 425×620×<br>60 | L60×5         | 9.0              |
| 300×600         | <b>GM36-55</b> | 485×600×<br>55   | 26.6               | 515×620×<br>60 | L60×5         | 9.8              |
| 400×600         | <b>GM46-65</b> | 305×720×<br>65   | 26.2               | 335×740×<br>70 | L70×5         | 10.8             |
| 500×600         | <b>GM56-65</b> | 485×720×<br>65   | 41.6               | 515×740×<br>70 | L70×5         | 13.1             |
| 600×600         | <b>GM66-65</b> | 605×720×<br>65   | 51.9               | 635×740×<br>70 | L70×5         | 14.6             |

|         |                |                |      |                |       |      |
|---------|----------------|----------------|------|----------------|-------|------|
| 500×700 | <b>GM57-75</b> | 485×840×<br>75 | 49.9 | 515×860×<br>80 | L80×5 | 14.5 |
| 700×700 | <b>GM77-75</b> | 695×840×<br>75 | 68.0 | 725×860×<br>80 | L80×5 | 17.1 |

#### Load Grade: T-14/T-6

| Wellhole<br>W×H | Model          | Grating<br>h×a×b | Grating<br>Wt (kg) | Frame<br>B×A×H | Seat<br>Angle | Frame<br>Wt (kg) |
|-----------------|----------------|------------------|--------------------|----------------|---------------|------------------|
| 300×400         | <b>GM34-45</b> | 305×480×<br>45   | 11.3               | 335×500×<br>50 | L50×5         | 6.5              |
| 400×400         | <b>GM44-45</b> | 395×480×<br>45   | 14.7               | 425×500×<br>50 | L50×5         | 7.2              |
| 500×400         | <b>GM54-45</b> | 485×480×<br>45   | 18.0               | 515×500×<br>50 | L50×5         | 7.8              |
| 300×500         | <b>GM35-50</b> | 305×590×<br>50   | 15.1               | 335×610×<br>56 | L56×6         | 8.2              |
| 400×500         | <b>GM45-50</b> | 395×590×<br>50   | 19.5               | 425×610×<br>56 | L56×6         | 9.2              |
| 500×500         | <b>GM55-50</b> | 485×590×<br>50   | 24.0               | 515×610×<br>56 | L56×6         | 10.1             |
| 300×600         | <b>GM36-55</b> | 305×700×<br>55   | 19.3               | 335×720×<br>60 | L60×5         | 8.7              |
| 400×600         | <b>GM46-55</b> | 395×700×<br>55   | 25.0               | 425×720×<br>60 | L60×5         | 9.6              |
| 500×600         | <b>GM56-55</b> | 485×700×<br>55   | 34.6               | 515×720×<br>60 | L60×5         | 10.4             |
| 600×600         | <b>GM66-55</b> | 605×700×<br>55   | 38.2               | 635×720×<br>60 | L60×5         | 11.5             |
| 500×700         | <b>GM57-60</b> | 485×810×<br>60   | 38.1               | 515×830×<br>65 | L65×5         | 12.7             |
| 700×700         | <b>GM77-60</b> | 695×810×<br>60   | 54.6               | 725×830×<br>65 | L65×5         | 15.2             |

#### Load Grade: T-2+pedestrian

| Wellhole<br>W×H | Model          | Grating<br>h×a×b | Grating<br>Wt (kg) | Frame<br>B×A×H | Seat<br>Angle | Frame<br>Wt (kg) |
|-----------------|----------------|------------------|--------------------|----------------|---------------|------------------|
| 300×400         | <b>GM34-32</b> | 305×454×<br>32   | 7.9                | 335×472×<br>36 | L36×4         | 4.4              |
| 400×400         | <b>GM44-32</b> | 395×454×<br>32   | 10.3               | 425×472×<br>36 | L36×4         | 4.8              |
| 500×400         | <b>GM54-32</b> | 485×454×<br>32   | 12.6               | 485×472×<br>36 | L36×4         | 5.0              |
| 300×500         | <b>GM35-40</b> | 305×570×<br>40   | 11.9               | 335×590×<br>45 | L45×5         | 5.9              |
| 400×500         | <b>GM45-40</b> | 395×570×<br>40   | 15.4               | 425×590×<br>45 | L45×5         | 6.5              |
| 500×500         | <b>GM55-40</b> | 485×570×<br>40   | 18.9               | 515×590×<br>45 | L45×5         | 7.2              |
| 300×600         | <b>GM36-40</b> | 305×670×<br>40   | 13.8               | 335×690×<br>45 | L45×5         | 6.3              |
| 400×600         | <b>GM46-40</b> | 395×670×<br>40   | 17.9               | 425×690×<br>45 | L45×5         | 6.9              |



|         |                |                |      |                |       |      |
|---------|----------------|----------------|------|----------------|-------|------|
| 500×600 | <b>GM56-40</b> | 485×670×<br>40 | 21.9 | 515×690×<br>45 | L45×5 | 7.5  |
| 600×600 | <b>GM66-40</b> | 605×670×<br>40 | 27.4 | 635×690×<br>45 | L45×5 | 8.3  |
| 500×700 | <b>GM57-45</b> | 485×780×<br>45 | 28.2 | 515×800×<br>50 | L50×5 | 8.6  |
| 700×700 | <b>GM77-45</b> | 695×780×<br>45 | 40.4 | 725×800×<br>50 | L50×5 | 10.2 |