

Contents

1 Basic	1	3.18 SCC	9
1.1 Default	1	3.19 SPFA	9
1.2 Pragma	1	3.202-SAT	10
1.3 FastIO	1		
2 Geometry	1	4 Math	10
2.1 Minimum Enclosing Circle	1	4.1 Big Integer	10
2.2 Convex Hull	2	4.2 Mod Int	11
2.3 Polar Angle Vector	2	4.3 Fraction	11
2.4 In Convex Hull	2	4.4 FWT	11
2.5 Intersections	2	4.5 FFT	12
2.6 Minkowski	2	4.6 NTT	12
2.7 Point	2	4.7 Polynomial	12
2.8 Polar Angle Sort	3	4.8 Miller Rabin	13
2.9 Rotation Sweep Line	3	4.9 Pollard's Rho	13
		4.10 Discrete Log	13
		4.11 Exgcd/CRT	13
		4.12 Semi-Euclid	13
		4.13 Theorem	14
3 Graph	3	5 String	14
3.1 Block Cut	3	5.1 AC auto	14
3.2 Vertex BCC	3	5.2 SA	15
3.3 Edge BCC	4	5.3 KMP	15
3.4 Centroid Decomp	4	5.4 Z	15
3.5 C3	4	5.5 Manacher	15
3.6 C4	4	5.6 SAM	15
3.7 Directed MST	5		
3.8 Dominator Tree	5	6 Data Structure	16
3.9 Eulerian Path	6	6.1 Li-Chao	16
3.10 Gomory-Hu Tree	6	6.2 Treap	16
3.11 HVL Decomp	6	6.3 Link Cut Tree	16
3.12 Hopcroft-Karp	6	6.4 Ultimate Segment Tree	17
3.13 KM	7		
3.14 Matching	7	7 Misc	18
3.15 Max Clique	8	7.1 Total Binary Search	18
3.16 Max Flow	8	7.2 CDQ	18
3.17 MCMF	9		

1 Basic

```
se rnu nu ai ts=4 sw=4 mouse=vi incsearch
sy on
ino ( )<Esc>i
ino ' '<Esc>i
ino " "<Esc>i
ino [ ]<Esc>i
ino { }<Esc>i
ino {<CR> {<CR><Tab><CR>}<Esc>hxka
vno ( c)<Esc>P
vno [ c]<Esc>P
vno { c}<Esc>P
ino jj <Esc>
ino jk <Esc>
map <F5> :w<CR>:!
g++ -g -fsanitize=undefined,address -Wall -Wextra
-Wshadow %:r.cpp &&echo "Compiled" && ./a.out<CR>
map <F6> :w<CR>:!g++ -g -fsanitize=undefined,
address -Wall -Wextra -Wshadow %:r.cpp -o %:r <CR>
map <F7> :!./a.out<CR>
```

1.1 Default [055771]

```
#include <bits/stdc++.h>
using namespace std;
#define pb emplace_back
#define iter(x) (x).begin(), (x).end()
#define size(x) (int)(x).size()
#define INF 0x3f3f3f3f
#define lowbit(x) ((x) & -(x))
#define tmin(a, b) (a) = min((a), (b))
#define tmax(a, b) (a) = max((a), (b))
typedef long long ll;
typedef pair<int, int> pii;

void db() { cerr << endl; }
template<class T, class... U>
void db(T a, U... b) { cerr << a << " ", db(b...); }

signed main() {
    cin.tie(0) -> sync_with_stdio(0);

    setxkbmap -option caps:swapescape #caps to esc
    cpp file.cpp -dD -P -fpreprocessed |
    tr -d '[:space:]' | md5sum | cut -c-6 #hash command
```

```
#!/usr/bin/bash
for ((i=0;;i++))
do
python gen.py > case.in
./A < case.in > aout
./B < case.in > bout

if ! (cmp -s aout bout);
then
cat case.in
fi
done

1.2 Pragma [0ca2dd]

#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
__builtin_ia32_ldmxcsr(__builtin_ia32_stmxcsr()|0x8040)

1.3 FastIO [11a75d]

inline char gc() {
    const static int SZ = 1 << 16;
    static char buf[SZ], *p1, *p2;
    if (p1 == p2 && (p2 =
        buf + fread(buf = buf, 1, SZ, stdin), p1 == p2))
        return -1;
    return *p1++;
}

void rd() {}
template<typename T, typename... U>
void rd(T &x, U &...y) {
    x = 0;
    bool f = 0;
    char c = gc();
    while (!isdigit(c))
        f ^= !(c ^ 45), c = gc();
    while (isdigit(c))
        x = (x << 1) + (x << 3) + (c ^ 48), c = gc();
    f && (x = -x), rd(y...);
}

template<typename T>
void prt(T x) {
    if (x < 0)
        putchar('-'), x = -x;
    if (x > 9)
        prt(x / 10);
    putchar((x % 10) ^ 48);
}
```

2 Geometry

2.1 Minimum Enclosing Circle [1f681e]

```
P perp(const P &a) {
    return P(-a.y, a.x);
}

struct Circle {
    P o;
    double r;
    inline bool in(const P
        &a) const { return (a - o).lth() <= r + eps; }
};

Circle getcircle(const P &a, const P &b) {
    return Circle{(a + b) / 2, (a - b).lth() / 2};
}

Circle getcircle(const P &a, const P &b, const P &c) {
    const P p1 = (a + b) / 2, p2 = (a + c) / 2;
    Circle res;
    res.o = intersection
        (p1, p1 + perp(a - b), p2, p2 + perp(a - c));
    res.r = (res.o - a).lth();
    return res;
}

Circle findcircle(vector<P> &ar) {
    int n = size(ar);
```

```

shuffle(iter(ar), mt19937(time(NULL)));
Circle res = {ar[0], 0};
for (int i = 0; i < n; i++) {
    if (res.in(ar[i]))
        continue;
    res = {ar[i], 0};
    for (int j = 0; j < i; j++) {
        if (res.in(ar[j]))
            continue;
        res = getcircle(ar[i], ar[j]);
        for (int k = 0; k < j; k++) {
            if (res.in(ar[k]))
                continue;
            res = getcircle(ar[i], ar[j], ar[k]);
        }
    }
}
return res;
}

```

2.2 Convex Hull [61610f]

```

void fdhl(vector<P> &ar, vector<P> &hl) {
    sort(iter(ar));
    for (int i = 0; i < 2; i++) {
        int prln = size(hl);
        for (int j = 0; j < size(ar); j++) {
            while
                (size(hl) - prln > 1 && ori(hl[size(hl) - 1], hl[size(hl) - 2], ar[j]) >= 0)
                hl.pop_back();
            hl.push_back(ar[j]);
        }
        if (size(hl) > 1)
            hl.pop_back();
        reverse(ar.begin(), ar.end());
    }
    if (size(hl) > 1 && hl.front() == hl.back())
        hl.pop_back();
}

```

2.3 Polar Angle Vector [56401e]

```

P BASE(0, 0), BASEV(1, 0);
inline bool updown(const P &a) {
    int tmp = ori(BASE, BASE + BASEV, a);
    if (!tmp)
        return BASEV * (a - BASE) > 0;
    return tmp > 0;
}
bool cmp(const P &a, const P &b) {
    bool ba = updown(a), bb = updown(b);
    if (ba ^ bb)
        return ba;
    return ori(BASE, a, b) > 0;
}

```

2.4 In Convex Hull [513844]

```

bool in(const P &a, const vector<P> &hl) {
    int ln = size(hl);
    if (ln == 1)
        return a == hl[0];
    if (ln == 2) {
        return !ori(hl[0], hl[1], a) && within(a, hl[0], hl[1]);
    }
    int l = 1, r = ln - 1, m;
    while (l < r - 1) {
        m = (l + r) >> 1;
        if (ori(hl[0], a, hl[m]) < 0)
            l = m;
        else
            r = m;
    }
    return ori(hl[0], hl[l], a) >= 0 && ori(hl[l], hl[r], a) >= 0 && ori(hl[r], hl[0], a) >= 0;
}

```

2.5 Intersections [c5adb9]

```

inline
bool within(const P &a, const P &b, const P &c) {
    return (b - a) * (c - a) < eps;
}
bool intersects
    (const P &a, const P &b, const P &c, const P &d) {
    int abc = ori(a, b, c);
    int abd = ori(a, b, d);
    int cda = ori(c, d, a);
    int cdb = ori(c, d, b);
    if (!abc && !abd)
        return within(a, c, d) || within(b, c, d) ||
            within(c, a, b) || within(d, a, b);
    return abc * abd <= 0 && cda * cdb <= 0;
}
P intersection
    (const P &a, const P &b, const P &c, const P &d) {
    double abc = (b - a) ^ (c - a);
    double abd = (b - a) ^ (d - a);
    return (d * abc - c * abd) / (abc - abd);
}

```

2.6 Minkowski [542fed]

```

//need Geometry template
void reorder_polygon(vector<P> &pt){
    int pos = 0;
    for(int i = 1; i < size(pt); i++){
        if(pt[i].y < pt[pos].y || (pt[i].y == pt[pos].y && pt[i].x < pt[pos].x))
            pos = i;
    }
    rotate(pt.begin(), pt.begin() + pos, pt.end());
}
vector<P> minkowski(vector<P> A, vector<P> B){
    reorder_polygon(A);
    reorder_polygon(B);
    A.push_back(A[0]); A.push_back(A[1]);
    B.push_back(B[0]); B.push_back(B[1]);
    vector<P> result;
    int i = 0, j = 0;
    while(i < size(A) - 2 || j < size(B) - 2){
        result.push_back(A[i] + B[j]);
        auto cross
            = (A[i + 1] - A[i]) ^ (B[j + 1] - B[j]);
        if(cross >= 0 && i < size(A) - 2)
            ++i;
        if(cross <= 0 && j < size(B) - 2)
            ++j;
    }
    return result;
}

```

2.7 Point [4a7f8a]

```

struct P {
#define eps 1e-9
    double x, y;
    P() { x = y = 0; }
    P(double x, double y) : x(x), y(y) {}
    friend bool operator<(const P &a, const P &b)
        { return a.x == b.x ? a.y < b.y : a.x < b.x; }
    friend bool operator<=(const P &a, const P &b) {
        return a.x == b.x ? a.y <= b.y : a.x <= b.x; }
    friend bool operator==(const P &a, const P &b) { return a.x == b.x && a.y == b.y; }
    friend bool operator!=(const P &a, const P &b) { return a.x != b.x || a.y != b.y; }
    P operator+(const P &b) const { return P(x + b.x, y + b.y); }
    void operator+=(const P &b) { x += b.x, y += b.y; }
    P operator-(const P &b) const { return P(x - b.x, y - b.y); }
    void operator-=(const P &b) { x -= b.x, y -= b.y; }
    P operator
        *(double b) const { return P(x * b, y * b); }
}

```

```

void operator*=(double b) { x *= b, y *= b; }
P operator
/(double b) const { return P(x / b, y / b); }
void operator/=(double b) { x /= b, y /= b; }
double operator*(
    const P &b) const { return x * b.x + y * b.y; }
double operator^(
    const P &b) const { return x * b.y - y * b.x; }
double lth() const { return sqrt(x * x + y * y); }
double lth2() const { return x * x + y * y; }
inline void print
() { cout << '(' << x << ' ' << y << ')'; }
friend istream &operator>>(
    istream &is, P &a) { return is >> a.x >> a.y; }
friend ostream &operator<<(ostream &os,
    const P &a) { return os << a.x << ' ' << a.y; }
};

int ori(const P &a, const P &b, const P &c) {
    double k = (b - a) ^ (c - a);
    if (fabs(k) < eps)
        return 0;
    return k > 0 ? 1 : -1;
}

```

2.8 Polar Angle Sort [05fa80]

```

P BASE(0, 0);
inline bool updown(const P &a) {
    if (fabs(a.y) < eps)
        return a.x > eps;
    return a.y > eps;
}

bool cmp(const P &a, const P &b) {
    bool ba = updown(a - BASE), bb = updown(b - BASE);
    if (ba ^ bb)
        return ba;
    return ori(BASE, a, b) > 0;
}

```

2.9 Rotation Sweep Line [9fd768]

```

void sweep(int n, vector<P> ar) {
    static const int N = 2005;
    static int id[N], po[N];
    static pii lr[N * N];
    int m = 0;
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            if (i != j)
                lr[m++] = pii(i, j);
    sort(lr, lr + m, [&](const pii
        &a, const pii &b) { return cmp(ar[a.first] -
            ar[a.second], ar[b.first] - ar[b.second]); });
    iota(id, id + n, 0);
    sort(id, id +
        n, [&](int a, int b) { return ar[a].y == ar[b].
            y ? ar[a].x < ar[b].x : ar[a].y < ar[b].y; });
    for (int i = 0; i < n; i++)
        po[id[i]] = i;
    for (int i = 0; i < m; i++) {
        swap(id[po[lr[i].first]], id[po[lr[i].second]]);
        swap(po[lr[i].first], po[lr[i].second]);
    }
}

```

3 Graph

3.1 Block Cut [ac5ea2]

```

struct BCT {
    static const int N = 1e6 + 5; // change
    vector<int> e1[N], e2[N], sk; // e2 is the new tree
    int low[N], dfn[N], ctd = 0, ctn = 0;
    bool vs[N];
    void dfs(int u, int fa) {
        dfn[u] = low[u] = ++ctd;
        sk.pb(u), vs[u] = 1;
        for (int v : e1[u]) {

```

```

            if (v == fa)
                continue;
            if (dfn[v]) {
                if (vs[v])
                    tmin(low[u], dfn[v]);
                continue;
            }
            dfs(v, u), tmin(low[u], low[v]);
            if (low[v] >= dfn[u]) {
                e2[u].pb(++ctn);
                int x;
                do {
                    x = sk.back();
                    sk.pop_back();
                    e2[ctn].pb(x);
                } while (x != v);
            }
            vs[u] = 0;
        }
    }

    inline void addedge
        (int x, int y) { e1[x].pb(y), e1[y].pb(x); }
    inline void ini(int n, int rt) {
        for (int i = 1; i <= ctn; i++)
            e1[i].clear(), e2[i].clear();
        ctn = n, ctd = 0;
        memset(dfn + 1, 0, n << 2);
        memset(vs + 1, 0, n);
        sk.clear();
        dfs(rt, -1);
    }
};

```

3.2 Vertex BCC [3faed3]

```

struct VertexBCC { // !simple affect BCCofE
    int n, m, dft, nbcc;
    vector<int> low, dfn, bln, is_ap, st1, st2, BCCofE;
    vector<vector<pii>> G;
    vector<vector<int>> bcc, nG;
    void dfs(int u, int f) {
        int child = 0;
        low[u] = dfn[u] = ++dft, st1.pb(u);
        for (auto [v, id] : G[u])
            if (!dfn[v]) {
                st2.pb(id);
                dfs(v, u), ++child;
                tmin(low[u], low[v]);
                if (dfn[u] <= low[v]) {
                    is_ap[u] = 1, bln[u] = bln[v] = nbcc++;
                    bcc.pb(vector<int>(1, u)), bcc.back().pb(v);
                    for (; st1.back() != v; st1.pop_back())
                        bcc[bln[u]].pb
                            (st1.back()), bln[st1.back()] = bln[u];
                    st1.pop_back();
                    while (st2.back() != id)
                        BCCofE
                            [st2.back()] = bln[u], st2.pop_back();
                    BCCofE[id] = bln[u], st2.pop_back();
                }
            }
            else if (v != f) {
                tmin(low[u], dfn[v]);
                if (dfn[v] < dfn[u])
                    st2.pb(id);
            }
        if (f == -1 && child < 2)
            is_ap[u] = 0;
        if (f == -1 && child == 2)
            bcc.pb(vector<int>(1, u)), bln[u] = nbcc++;
    }
};

VertexBCC
    (int _n) : n(_n), m(0), low(n), bln(n), G(n) {}
void add_edge(int u, int v) {
    G[u].pb(v), G[v].pb(u, m++);
}

void slv() {

```

```

    is_ap.assign(n, 0), dfn = is_ap, dft = nbcc = 0;
    st1.clear(), st2.clear(), BCCofE.assign(m, -1);
    for (int i = 0; i < n; ++i)
        if (!dfn[i])
            dfs(i, -1);
}
void block_cut_tree() {
    int tmp = nbcc;
    for (int i = 0; i < n; ++i)
        if (is_ap[i])
            bln[i] = tmp++;
    nG.assign(tmp, vector<int>(0));
    for (int i = 0; i < nbcc; ++i)
        for (int j : bcc[i])
            if (is_ap[j])
                nG[i].pb(bln[j]), nG[bln[j]].pb(i);
} // up to 2 * n - 2 nodes!! bln[i] for id
};

```

3.3 Edge BCC [353c57]

```

struct EdgeBCC {
    int n, m, dft, necc;
    vector<int> low, dfn, bln, is_bridge, stk;
    vector<vector<pii>> G;
    void dfs(int u, int f) {
        dfn[u] = low[u] = ++dft, stk.pb(u);
        for (auto [v, id] : G[u])
            if (!dfn[v])
                dfs(v, id), tmin(low[u], low[v]);
            else if (id != f)
                tmin(low[u], dfn[v]);
        if (low[u] == dfn[u]) {
            if (f != -1) is_bridge[f] = 1;
            for (; stk.back() != u; stk.pop_back())
                bln[stk.back()] = necc;
            bln[u] = necc++, stk.pop_back();
        }
    }
    EdgeBCC(int _n): n(_n), m(0), low(n), bln(n), G(n) {}
    void add_edge(int u, int v) {
        G[u].pb(v, m), G[v].pb(u, m++);
    }
    void slv() {
        is_bridge.assign(m, 0), stk.clear();
        dfn.assign(n, 0), dft = necc = 0;
        for (int i = 0; i < n; ++i)
            if (!dfn[i]) dfs(i, -1);
    }
}; // ecc_id(i): bln[i]

```

3.4 Centroid Decomp [314317]

```

struct CentroidDecomposition {
    vector<vector<int>> g;
    vector<int> sub;
    vector<bool> v;
    vector<vector<int>> tree;
    int root;
    void add_edge(int a, int b) {
        g[a].push_back(b);
        g[b].push_back(a);
    }
    CentroidDecomposition(const vector<vector<int>> &g_, int isbuild = true) : g(g_) {
        sub.resize(size(g), 0);
        v.resize(size(g), false);
        if (isbuild) build();
    }
    void build() {
        tree.resize(size(g));
        root = build_dfs(0);
    }
    int get_size(int cur, int par) {
        sub[cur] = 1;

```

```

        for (auto &dst : g[cur]) {
            if (dst == par || v[dst]) continue;
            sub[cur] += get_size(dst, cur);
        }
        return sub[cur];
    }
    int get_centroid(int cur, int par, int mid) {
        for (auto &dst : g[cur]) {
            if (dst == par || v[dst]) continue;
            if (sub[dst] > mid
                ) return get_centroid(dst, cur, mid);
        }
        return cur;
    }
    int build_dfs(int cur) {
        int centroid = get_centroid
            (cur, -1, get_size(cur, -1) / 2);
        v[centroid] = true;
        for (auto &dst : g[centroid]) {
            if (!v[dst]) {
                int nxt = build_dfs(dst);
                if (centroid != nxt
                    ) tree[centroid].emplace_back(nxt);
            }
        }
        v[centroid] = false;
        return centroid;
    }
};

```

3.5 C3 [e348b4]

```

namespace C3 {
    const int N = 1e5 + 5; // change
    vector<int> eg[N], to[N];
    int pl[N], ln, pd[N], id[N], cnt[N];
    ll ans;
    inline void addedge(int x, int y) {
        eg[x].pb(y), eg[y].pb(x);
    }
    ll blt(int n) {
        priority_queue<pii> pq;
        for (int i = 1; i <= n; i++)
            pq.push(pii(pd[i] = -size(eg[i]), i));
        while (!pq.empty()) {
            pii tp = pq.top();
            pq.pop();
            if (id[tp.second])
                continue;
            pl[++ln] = tp.second;
            id[tp.second] = ln;
            for (int v : eg[tp.second])
                if (!id[v])
                    to[v].pb(tp.second
                        ), pq.push(pii(++pd[v], v));
        }
        ans = 0;
        for (int p = 1; p <= n; p++) {
            for (int u : to[pl[p]])
                cnt[u]++;
            for (int u : to[pl[p]])
                for (int v : to[u])
                    ans += cnt[v];
            for (int u : to[pl[p]])
                cnt[u] = 0;
        }
        return ans;
    }
}

```

3.6 C4 [f966c6]

```

namespace C4 {
    const int N = 1e5 + 5; // change
    vector<int> eg[N], to[N];
    int pl[N], ln, pd[N], id[N], cnt[N];

```

```

ll ans;
inline void addedge(int x, int y) {
    eg[x].pb(y), eg[y].pb(x);
}
ll blt(int n) {
    priority_queue<pii> pq;
    for (int i = 1; i <= n; i++)
        pq.push(pii(pd[i] = -size(eg[i]), i));
    while (!pq.empty()) {
        pii tp = pq.top();
        pq.pop();
        if (id[tp.second])
            continue;
        pl[++ln] = tp.second;
        id[tp.second] = ln;
        for (int v : eg[tp.second])
            if (!id[v])
                to[v].pb(tp.second
                    ), pq.push(pii(++pd[v], v));
    }
    ans = 0;
    for (int p = 1; p <= n; p++) {
        for (int u : to[pl[p]])
            for (int v : eg[u])
                if (id[v] < p)
                    ans += cnt[v]++;
        for (int u : to[pl[p]])
            for (int v : eg[u])
                cnt[v] = 0;
    }
    return ans;
}
}

```

3.7 Directed MST [de79a2]

```

struct DirectedMST { // O(m+n lgn)
    struct edge {
        int u, v;
        ll w;
    };
    int n;
    vector<edge> e;
    DirectedMST(int _n) : n(_n), e(0) {}
    void add_edge
        (int u, int v, ll w) { e.pb(edge{u, v, w}); }
    vector<int>
        slv(int root) { // 0-based, return idx of edges
            using T = pair<ll, int>;
            using PQ = pair<priority_queue
                <T, vector<T>, greater<T>>, ll>;
            auto push = [](PQ &pq, T v) {
                pq.first.
                    emplace(v.first - pq.second, v.second);
            };
            auto top = [](const PQ &pq) -> T {
                auto r = pq.first.top();
                return {r.first + pq.second, r.second};
            };
            auto join = [&push, &top](PQ &a, PQ &b) {
                if (size(a.first) < size(b.first))
                    swap(a, b);
                while (!b.first.empty())
                    push(a, top(b)), b.first.pop();
            };
            vector<PQ> h(n * 2);
            for (int i = 0; i < size(e); ++i)
                push(h[e[i].v], {e[i].w, i});
            vector<int> a(n *
                2), v(n * 2, -1), pa(n * 2, -1), r(n * 2);
            iota(iter(a), 0);
            auto o = [&](int x) {
                int y;
                for (y = x; a[y] != y; y = a[y])
                    ;
                for (int ox = x; x != y; ox = x)
                    x = a[x], a[ox] = y;
            };
        }
    };
}

```

```

        return y;
    };
    v[root] = n + 1;
    int pc = n;
    for (int i = 0; i < n; ++i)
        if (v[i] == -1) {
            for (int p = i; v[p] == -1
                || v[p] == i; p = o(e[r[p]].u)) {
                if (v[p] == i) {
                    int q = p;
                    p = pc++;
                    do {
                        h[q].second = -
                            h[q].first.top().first;
                        join(h[pa
                            ], q) = a[q] = p, h[q]);
                    } while
                        ((q = o(e[r[q]].u)) != p);
                }
                v[p] = i;
                while (!h[p].first.empty() &&
                    o(e[top(h[p]).second].u) == p)
                    h[p].first.pop();
                r[p] = top(h[p]).second;
            }
        }
    vector<int> ans;
    for (int i = pc - 1; i >= 0; i--)
        if (i != root && v[i] != n) {
            for (int f = e[r[i]].
                v; f != -1 && v[f] != n; f = pa[f])
                v[f] = n;
            ans.pb(r[i]);
        }
    return ans;
}
}

```

3.8 Dominator Tree [602345]

```

struct DOT {
    static const int N = 2e5 + 5; // change
    int dfn
        [N], id[N], dfc, fa[N], idm[N], sdm[N], bst[N];
    vector<int> G[N], rG[N];
    void ini(int n) { // remember to initialize
        for (int i = 1; i <= n; i++)
            G[i].clear(), rG[i].clear();
        fill(dfn, dfn + n + 1, 0);
    }
    inline void addedge
        (int u, int v) { G[u].pb(v), rG[v].pb(u); }
    int f(int x, int lm) {
        if (x <= lm)
            return x;
        int cr = f(fa[x], lm);
        if (sdm[bst[fa[x]]] < sdm[bst[x]])
            bst[x] = bst[fa[x]];
        return fa[x] = cr;
    }
    void dfs(int u) {
        id[dfn[u] = ++dfc] = u;
        for (int v : G[u])
            if (!dfn[v])
                dfs(v), fa[dfn[v]] = dfn[u];
    }
    void tar(vector<int> *eg, int rt) {
        dfc = 0, dfs(rt);
        for (int i = 1; i <= dfc; i++)
            sdm[i] = bst[i] = i;
        for (int i = dfc; i > 1; i--) {
            int u = id[i];
            for (int v : rG[u])
                if ((v = dfn[v]))
                    f(v, i), tmin(sdm[i], sdm[bst[v]]);
            eg[sdm[i]].pb(i), u = fa[i];
        }
    }
}

```

```

        for (int v : eg[u])
            f(v, u), idm[v]
            = (sdm[bst[v]] == u ? u : bst[v]);
        eg[u].clear();
    }
    for (int i = 2; i <= dfc; i++) {
        if (sdm[i] != idm[i])
            idm[i] = idm[idm[i]];
        eg[id[idm[i]]].pb(id[i]);
    }
}
};

```

3.9 Eulerian Path [1628e1]

```

struct EulerianPath {
    int n, m;
    vector<vector<pii>> adj;
    vector<int> cur, vst;
    vector<pii> ans;
    EulerianPath
        (int _n) : n(_n), m(0), adj(n, vector<pii>(0)) {}
    void add_edge(int a, int b) { adj[a].pb(b, m++); }
    void dfs(int u) {
        for (; cur[u] < size(adj[u]); ++cur[u]) {
            auto [v, id] = adj[u][cur[u]];
            if (vst[id]) continue;
            vst[id] = 1, dfs(v);
            ans.pb(u, v);
        }
    }
    bool go() {
        vector<int> in(n, 0), out(n, 0);
        for (int i = 0; i < n; ++i) {
            out[i] = size(adj[i]);
            for (auto [j, id] : adj[i])
                ++in[j];
        }
        int s = -1, t = -1, ss = -1;
        for (int i = 0; i < n; ++i) {
            if (out[i]) ss = i;
            if (in[i] == out[i]) continue;
            if (in[i] + 1 == out[i]) {
                if (s != -1) return 0;
                s = i;
                continue;
            }
            if (in[i] - 1 == out[i]) {
                if (t != -1) return 0;
                t = i;
                continue;
            }
        }
        return 0;
    }
    if (s == -1) s = ss;
    cur.assign(n, 0), vst.assign(m, 0), ans.clear();
    dfs(s), reverse(iter(ans));
    return accumulate(iter(vst), 0) == m;
}
};

```

3.10 Gomory-Hu Tree [ba0b07]

```

struct edge{
    int u,v,w;
};
vector<edge> result;
vector<edge> ed;
void GomoryHu(int N){
    vector<int> par(N,0);
    for(int i=1;i<N;i++){
        FLOW din;
        for(const auto &[u,v,c]:ed){
            din.addedge(u,v,c,c);
        }
        din.s = i;
        din.t = par[i];
        result.push_back({i,par[i],din.getflow()});
    }
}

```

```

for(int j=i+1;j<N;++j){
    if(par[j]==par[i] && din.dp[j]<INF) par[j]=i;
}
}
}

```

3.11 HVL Decomp [5f618c]

```

namespace HLD {
    int in[N], ou[N], dfc, top[N], sz[N], fa[N], ch[N];
    vector<int> eg[N];
    inline void addedge(int u, int v) {
        eg[u].pb(v), eg[v].pb(u);
    }
    inline void ini(int n) { // after using
        for (int i = 1; i <= n; i++)
            eg[i].clear();
        memset(ch + 1, 0, n << 2), dfc = 0;
    }
    void dsz(int u) {
        sz[u] = 1;
        for (int v : eg[u]) {
            if (v == fa[u])
                continue;
            fa[v] = u, dsz(v), sz[u] += sz[v];
            if (sz[v] > sz[ch[u]])
                ch[u] = v;
        }
    }
    void dfs(int u) {
        in[u] = ++dfc;
        if (ch[u])
            top[ch[u]] = top[u], dfs(ch[u]);
        for (int v : eg[u])
            if (v != fa[u] && v != ch[u])
                top[v] = v, dfs(v);
        ou[u] = dfc;
    }
    inline void blt(int rt) {
        fa[rt] = 0, dsz(rt), top[rt] = rt, dfs(rt);
    }
    void slv(int u, int v) {
        while (top[u] != top[v]) {
            if (in[top[u]] < in[top[v]])
                swap(u, v);
            // [ in[top[u]], in[u] ];
            u = fa[top[u]];
        }
        if (in[u] > in[v])
            swap(u, v);
        // [ in[u], in[v] ];
    }
}

```

3.12 Hopcroft-Karp [f6d745]

```

struct HK {
    static const
        int N = 1e5 + 5, M = N * 2; // change, 1-base
    int fr[N], pr[N], hd[N], m1
        [N], m2[N], to[M], nxt[M], ct = 1, n1, n2, ans;
    inline void ini(int _n1, int _n2) {
        n1 = _n1, n2 = _n2, ct = 1;
        memset(m1 + 1, 0, n1 << 2);
        memset(m2 + 1, 0, n2 << 2);
        memset(hd + 1, 0, n1 << 2);
    }
    inline void addedge(int u, int v) {
        to[ct] = v, nxt[ct] = hd[u], hd[u] = ct++;
    }
    int getmatch() {
        ans = 0;
        for (bool ok = 1; ok;) {
            ok = 0, memset(fr + 1, 0, n1 << 2);
            queue<int> q;
            for (int i = 1; i <= n1; i++)
                if (!m1[i])

```



```

        q.push(fr[i] = i);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        if (m1[fr[u]])
            continue;
        for (int i = hd[u]; i; i = nxt[i]) {
            int v = to[i];
            if (!m2[v]) {
                while (v)
                    m2[v] = u, swap
                    (m1[u], v), u = pr[u];
                ok = 1, ans++;
                break;
            } else if (!fr[m2[v]])
                q.push(v = m2[v]),
                fr[v] = fr[u], pr[v] = u;
        }
    }
    return ans;
}
};

```

3.13 KM [6aefd7]

```

struct KM {
    static const int N = 505;
    int pr[N], eg[N][N], m1[N], m2[N], n;
    ll lx[N], ly[N], sl[N];
    bool vy[N];
    ll ans;
    inline void ini(int _n) {
        n = _n;
        memset(lx + 1, ~INF, n << 3);
        memset(ly + 1, 0, n << 3);
        memset(m1 + 1, 0, n << 2);
        memset(m2 + 1, 0, n << 2);
        for (int i = 1; i <= n; i++)
            memset(eg[i] + 1, ~INF, n << 2);
    }
    inline void addedge(int u, int v, int w) {
        tmax(eg[u][v], w), tmax(lx[u], (ll)w);
    }
    ll getmatch() {
        ans = 0;
        for (int p = 1, u, v; p <= n; p++) {
            memset(sl + 1, INF, n << 3);
            memset(vy + 1, 0, n);
            for (u = p; u = m2[v], vy[v] = 1) {
                ll mn = 1ll << 60;
                for (int i = 1; i <= n; i++) {
                    if (vy[i])
                        continue;
                    if (eg[u][i] != ~INF && lx
                        [u] + ly[i] - eg[u][i] < sl[i])
                        sl[i] = lx[u] + ly
                        [i] - eg[u][i], pr[i] = u;
                    if (sl[i] < mn)
                        mn = sl[i], v = i;
                }
                for (int i = 1; i <= n; i++) {
                    if (vy[i])
                        ly[i] += mn, lx[m2[i]] -= mn;
                    else
                        sl[i] -= mn;
                }
                lx[p] -= mn;
                if (!m2[v])
                    break;
            }
            while (v)
                u = pr[v], m2[v] = u, swap(v, m1[u]);
        }
        for (int i = 1; i <= n; i++)
            ans += eg[i][m1[i]];
        return ans;
    }
};

```

```

    }
};

```

3.14 Matching [becd87]

```

struct Matching {
    static const int maxn
        = 505, p = (int)1e9 + 7; // change this, 1-base
    int sizen = 0;
    int sub_n = 0;
    int id[maxn], vertices[maxn], matches[maxn];
    bool row_marked
        [maxn] = {false}, col_marked[maxn] = {false};
    int A[maxn][maxn], B[maxn][maxn], t[maxn][maxn];
    vector<pair<int, int>> sidearr;
    void init(int _n) {
        sizen = _n;
        sub_n = 0;
        fill(id, id + _n + 1, 0);
        fill(vertices, vertices + _n + 1, 0);
        fill(matches, matches + _n + 1, 0);
        fill(row_marked, row_marked + _n + 1, 0);
        fill(col_marked, col_marked + _n + 1, 0);
        for (int i = 0; i <= _n; i++) {
            fill(A[i], A[i] + _n + 1, 0);
            fill(B[i], B[i] + _n + 1, 0);
            fill(t[i], t[i] + _n + 1, 0);
        }
        sidearr.clear();
    }
    Matching(int _n) {
        init(_n);
    }
    int qpow(int a, int b) {
        int ans = 1;
        while (b) {
            if (b & 1) ans = (long long)ans * a % p;
            a = (long long)a * a % p;
            b >>= 1;
        }
        return ans;
    }
    void Gauss(int A[][maxn], int B[][maxn], int n) {
        if (B) {
            memset(B, 0, sizeof(t));
            for (int i = 1; i <= n; i++) B[i][i] = 1;
        }
        for (int i = 1; i <= n; i++) {
            if (!A[i][i]) {
                for (int j = i + 1; j <= n; j++) {
                    if (A[j][i]) {
                        swap(id[i], id[j]);
                        for (int k = i; k <= n; k++)
                            swap(A[i][k], A[j][k]);
                        if (B
                            ) for (int k = 1; k <= n; k++)
                            swap(B[i][k], B[j][k]);
                        break;
                    }
                }
                if (!A[i][i]) continue;
            }
            int inv = qpow(A[i][i], p - 2);
            for (int j = 1; j <= n; j++) {
                if (i != j && A[j][i]) {
                    int t
                        = (long long)A[j][i] * inv % p;
                    for (int k = i; k <= n; k++)
                        if (A[i][k]) A[j][k] = (
                            A[j][k] - (ll)t * A[i][k]) % p;
                    if (B) {
                        for (int k = 1; k <= n; k++) if
                            (B[i][k]) B[j][k] = (B[j][
                            k] - (ll)t * B[i][k]) % p;
                    }
                }
            }
        }
    }
};

```

```

    }
    if (B) {
        for (int i = 1; i <= n; i++) {
            int inv = qpow(A[i][i], p - 2);
            for (int j = 1; j <= n; j++) {
                if (B[i][j]) B[i][j]
                    = (long long)B[i][j] * inv % p;
            }
        }
    }
}

void eliminate(int r, int c) {
    row_marked[r] = col_marked[c] = true;
    int inv = qpow(B[r][c], p - 2);
    for (int i = 1; i <= sub_n; i++) {
        if (!row_marked[i] && B[i][c]) {
            int t = (long long)B[i][c] * inv % p;

            for (int j = 1; j <= sub_n; j++)
                if (!col_marked[j] && B[r][j])
                    B[i][j] = (B[i][j] - (
                        long long)t * B[r][j]) % p;
        }
    }
}

void add_edge(int a, int b) {
    sidearr.pb(min(a, b), max(a, b));
}

void build_matching() {
    auto rng = mt19937(chrono::steady_clock
        ::now().time_since_epoch().count());
    for (auto e : sidearr) {
        int x = e.first;
        int y = e.second;
        A[x][y] = rng() % p;
        A[y][x] = -A[x][y];
    }
    for (int i = 1; i <= size_n; i++) id[i] = i;
    memcpy(t, A, sizeof(t));
    Gauss(A, nullptr, size_n);
    for (int i = 1; i <= size_n; i++) {
        if (A[id[i]][id[i]]) vertices[++sub_n] = i;
    }
    for (int i = 1; i <= sub_n; i++) {
        for (int j = 1; j <= sub_n; j++)
            A[i][j] = t[vertices[i]][vertices[j]];
    }
    Gauss(A, B, sub_n);
    for (int i = 1; i <= sub_n; i++) {
        if (!matches[vertices[i]]) {
            for (int j = i + 1; j <= sub_n; j++) {
                if (!matches
                    [vertices[j]] && t[vertices
                        [i]][vertices[j]] && B[j][i]) {
                    matches[
                        vertices[i]] = vertices[j];
                    matches[
                        vertices[j]] = vertices[i];
                    eliminate(i, j);
                    eliminate(j, i);
                    break;
                }
            }
        }
    }
}

int matched(int x) {
    return matches[x];
}
};

```

3.15 Max Clique [2b1496]

```

struct MaxClique { // fast
    when N <= 100, 0-base, output sol[N] to get node;
    static const int N = 105;

```

```

    bitset<N> G[N], cs[N];
    int ans, sol[N], q, cur[N], d[N], n;
    MaxClique(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) G[i].reset();
    }
    void add_edge(int u, int v) {
        G[u][v] = G[v][u] = 1;
    }
    void pre_dfs(vector<int> &r, int l, bitset<N> mask) {
        if (l < 4) {
            for (int i : r) d[i] = (G[i] & mask).count();
            sort(r.begin(), r.end(),
                [&](int x, int y) { return d[x] > d[y]; });
        }
        vector<int> c(size(r));
        int lft = max(ans - q + 1, 1), rgt = 1, tp = 0;
        cs[1].reset(), cs[2].reset();
        for (int p : r) {
            int k = 1;
            while ((cs[k] & G[p]).any()) ++k;
            if (k > rgt) cs[++rgt + 1].reset();
            cs[k][p] = 1;
            if (k < lft) r[tp++] = p;
        }
        for (int k = lft; k <= rgt; ++k)
            for (int p = cs[k]._Find_first
                (); p < N; p = cs[k]._Find_next(p))
                r[tp] = p, c[tp] = k, ++tp;
        dfs(r, c, l + 1, mask);
    }
    void dfs(vector<
        int> &r, vector<int> &c, int l, bitset<N> mask) {
        while (!r.empty()) {
            int p = r.back();
            r.pop_back(), mask[p] = 0;
            if (q + c.back() <= ans) return;
            cur[q++] = p;
            vector<int> nr;
            for (int i : r) if (G[p][i]) nr.pb(i);
            if (!nr.empty()) pre_dfs(nr, l, mask & G[p]);
            else if (q > ans) ans = q, copy_n(cur, q, sol);
            c.pop_back(), --q;
        }
    }
    int solve() {
        vector<int> r(n);
        ans = q = 0, iota(r.begin(), r.end(), 0);
        pre_dfs(r, 0, bitset<N>(string(n, '1')));
        return ans;
    }
};

```

3.16 Max Flow [f1e191]

```

struct FLOW {
    static const int N = 1e3 + 5, M = N * 10; // change
    int dp[N]
        ], cr[N], hd[N], ct = 2, s = 0, t = 1, n, flow;
    inline void ini(int _n) { n = _n; }
    struct E {
        int to, cap, nxt;
    } eg[M];
    inline void addedge(int u, int v, int w, int d=0) {
        eg[ct] = {v, w, hd[u]};
        hd[u] = ct++;
        eg[ct] = {u, d, hd[v]};
        hd[v] = ct++;
    }
    bool bfs() {
        memset(dp, INF, (n + 1) << 2);
        queue<int> q;
        q.push(s), dp[s] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop();

```



```

        for (int i = hd[u]; i; i = eg[i].nxt) {
            const int v = eg[i].to;
            if (!eg[i].cap || dp[u] + 1 >= dp[v])
                continue;
            dp[v] = dp[u] + 1, q.push(v);
        }
    }
    return dp[t] != INF;
}

int dfs(int u, int fl) {
    if (u == t)
        return fl;
    int sm = 0;
    for (int &i = cr[u]; i; i = eg[i].nxt) {
        int v = eg[i].to, &w = eg[i].cap;
        if (!w || dp[u] + 1 != dp[v])
            continue;
        int tp = dfs(v, min(w, fl - sm));
        w -= tp, sm += tp, eg[i ^ 1].cap += tp;
        if (sm == fl)
            return fl;
    }
    return sm;
}

int getflow() {
    flow = 0;
    while (bfs())
        memcpy(cr,
            hd, (n + 1) << 2), flow += dfs(s, INF);
    return flow;
}
};

```

3.17 MCMF [5190af]

```

struct MCMF {
    static const int N = 5005, M = N * 20;
    struct E {
        int to, cap, co, nxt;
    } eg[M];
    int dp[N], hd[
        N], cr[N], ct = 2, s = 0, t = 1, n, flow, cost;
    bool vd[N];
    inline void ini(int _n) { n = _n; }
    inline void addedge(int u, int v, int w, int c) {
        eg[ct] = {v, w, c, hd[u]};
        hd[u] = ct++;
        eg[ct] = {u, 0, -c, hd[v]};
        hd[v] = ct++;
    }
    bool spfa() {
        queue<int> q;
        memset(dp, INF, (n + 1) << 2);
        q.push(s), vd[s] = 1, dp[s] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop(), vd[u] = 0;
            for (int i = hd[u]; i; i = eg[i].nxt) {
                const int v = eg[i].to, c = eg[i].co;
                if (!eg[i].cap || dp[u] + c >= dp[v])
                    continue;
                dp[v] = dp[u] + c;
                if (!vd[v])
                    vd[v] = 1, q.push(v);
            }
        }
        return dp[t] != INF;
    }
    int dfs(int u, int fl) {
        if (u == t)
            return fl;
        int sm = 0;
        vd[u] = 1;
        for (int &i = cr[u]; i; i = eg[i].nxt) {
            int &w =
                eg[i].cap, v = eg[i].to, c = eg[i].co;
            if (!w || vd[v] || dp[u] + c != dp[v])

```

```

                continue;
            int tp = dfs(v, min(fl - sm, w));
            w -= tp, eg[i ^
                1].cap += tp, sm += tp, cost += tp * c;
        }
        vd[u] = 0;
        return sm;
    }
    pii getflow() {
        flow = cost = 0;
        while (spfa())
            memcpy(cr,
                hd, (n + 1) << 2), flow += dfs(s, INF);
        return pii(flow, cost);
    }
};

```

3.18 SCC [ff24f9]

```

struct SCC {
    int n, dft, nsc;
    vector<int> low, dfn, bln, instk, stk;
    vector<vector<int>> G;
    void dfs(int u) {
        low[u] = dfn[u] = ++dft;
        instk[u] = 1, stk.pb(u);
        for (int v : G[u])
            if (!dfn[v])
                dfs(v), tmin(low[u], low[v]);
            else if (instk[v] && dfn[v] < dfn[u])
                tmin(low[u], dfn[v]);
        if (low[u] == dfn[u]) {
            for (; stk.back() != u; stk.pop_back())
                bln[stk.back()] = nsc, instk[stk.back()] = 0;
            instk[u] = 0, bln[u] = nsc++, stk.pop_back();
        }
    }
    SCC(int _n): n(_n), low(n), bln(n), G(n) {}
    void add_edge(int u, int v) { G[u].pb(v); }
    void slv() {
        dfn.assign(n, 0), instk = dfn, dft = nsc = 0;
        for (int i = 0; i < n; ++i)
            if (!dfn[i]) dfs(i);
    }
}; // scc_id(i): bln[i]

```

3.19 SPFA [0ad2fd]

```

struct SPFA {
    int n;
    vector<ll> d;
    vector<vector<pair<int, ll>>> adj;
    SPFA(int _n
        ): n(_n), adj(_n, vector<pair<int, ll>>(0)) {}
    void add_edge
        (int u, int v, ll w) { adj[u].pb(v, w); }
    bool go(int s) {
        vector<int> cnt(n, 0), inq(n, 0);
        queue<int> q;
        d.assign(n, LONG_LONG_MAX);
        d[s] = 0, inq[s] = 1, q.emplace(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop(), inq[u] = 0;
            for (auto [v, w] : adj[u]) {
                if (d[v] > d[u] + w) {
                    if (++cnt[v] >= n)
                        return 0; // negative cycle
                    d[v] = d[u] + w;
                    if (!inq[v])
                        q.emplace(v), inq[v] = 1;
                }
            }
        }
        return 1;
    }
};

```

3.20 2-SAT [710518]

```
struct TwoSAT { // SCC needed
    int n;
    vector<bool> istrue;
    SCC scc;
    TwoSAT(int _n) : n(_n), scc(n + n) {}
    int rv(int a) { return a >= n ? a - n : a + n; }
    void add_clause(int a, int b) {
        scc.add_edge(rv(a), b);
        scc.add_edge(rv(b), a);
    }
    bool slv() {
        scc.slv(), istrue.assign(n + n, 0);
        for (int i = 0; i < n; ++i) {
            if (scc.bln[i] == scc.bln[i + n]) return 0;
            istrue[i] = scc.bln[i] < scc.bln[i + n];
            istrue[i + n] = !istrue[i];
        }
        return 1;
    }
};
```

4 Math

4.1 Big Integer [4347d6]

```
#undef size
template<typename T>
inline string to_string(const T& x){
    stringstream ss;
    return ss<<x,ss.str();
}
struct bigN:vector<ll>{
    const static int base=1000000000,width=log10(base);
    bool negative;
    bigN(const_iterator
        a,const_iterator b):vector<ll>(a,b){}
    bigN(string s){
        if(s.empty())return;
        if(s[0]=='-')negative=1,s=s.substr(1);
        else negative=0;
        for(int i=int(s.size())-1;i>=0;i-=width){
            ll t=0;
            for(int j=max(0,i-width+1);j<=i;++j)
                t=t*10+s[j]-'0';
            push_back(t);
        }
        trim();
    }
    template<typename T>
    bigN(const T &x):bigN(to_string(x)){}
    bigN():negative(0){}
    void trim(){
        while(size()&&!back())pop_back();
        if(empty())negative=0;
    }
    void carry(int _base=base){
        for(size_t i=0;i<size();++i){
            if(at(i)>=_base&&at(i)<_base)continue;
            if(i+1==size())push_back(0);
            int r=at(i)%_base;
            if(r<0)r+=_base;
            at(i+1)+=(at(i)-r)/_base,at(i)=r;
        }
    }
    int abscmp(const bigN &b)const{
        if(size()>b.size())return 1;
        if(size()<b.size())return -1;
        for(int i=int(size())-1;i>=0;--i){
            if(at(i)>b[i])return 1;
            if(at(i)<b[i])return -1;
        }
        return 0;
    }
    int cmp(const bigN &b)const{
        if(negative!=b.negative)return negative?-1:1;
        return negative?-abscmp(b):abscmp(b);
    }
};
```

```

    }
    bool operator<(const bigN&b)const{return cmp(b)<0;}
    bool operator>(const bigN&b)const{return cmp(b)>0;}
    bool operator<=(const bigN&b)const{return cmp(b)<=0;}
    bool operator>=(const bigN&b)const{return cmp(b)>=0;}
    bool operator==(const bigN&b)const{return !cmp(b);}
    bool operator!=(const bigN&b)const{return cmp(b)!=0;}
    bigN abs()const{
        bigN res=*this;
        return res.negative=0, res;
    }
    bigN operator-()const{
        bigN res=*this;
        return res.negative=!negative,res.trim(),res;
    }
    bigN operator+(const bigN &b)const{
        if(negative)return -(-(*this)+(-b));
        if(b.negative)return *this-(-b);
        bigN res=*this;
        if(b.size()>size())res.resize(b.size());
        for(size_t i=0;i<b.size();++i)res[i]+=b[i];
        return res.carry(),res.trim(),res;
    }
    bigN operator-(const bigN &b)const{
        if(negative)return -(-(*this)-(-b));
        if(b.negative)return *this+(-b);
        if(abscmp(b)<0)return -(b-(*this));
        bigN res=*this;
        if(b.size()>size())res.resize(b.size());
        for(size_t i=0;i<b.size();++i)res[i]-=b[i];
        return res.carry(),res.trim(),res;
    }
    bigN operator*(const bigN &b)const{
        bigN res;
        res.negative=negative!=b.negative;
        res.resize(size()+b.size());
        for(size_t i=0;i<size();++i)
            for(size_t j=0;j<b.size();++j)
                if((res[i+j]+at(i)*b[j])>=base){
                    res[i+j+1]+=res[i+j]/base;
                    res[i+j]%=base;
                }
        return res.trim(),res;
    }
    bigN operator/(const bigN &b)const{
        int norm=base/(b.back()+1);
        bigN x=abs()*norm;
        bigN y=b.abs()*norm;
        bigN q,r;
        q.resize(x.size());
        for(int i=int(x.size())-1;i>=0;--i){
            r=r*base+x[i];
            int s1=r.size()<=y.size()?0:r[y.size()];
            int s2=r.size()<y.size()?0:r[y.size()-1];
            int d=(ll(base)*s1+s2)/y.back();
            r=r-y*d;
            while(r.negative)r=r+y,--d;
            q[i]=d;
        }
        q.negative=negative!=b.negative;
        return q.trim(),q;
    }
    bigN operator%(const bigN &b)const{
        return *this-(*this/b)*b;
    }
    friend istream& operator>>(istream &ss, bigN &b){
        string s;
        return ss>>s, b=s, ss;
    }
    friend
        ostream& operator<<(ostream &ss, const bigN &b){
            if(b.negative)ss<<'-'<<endl;
            ss<<(b.empty()?0:b.back());
            for(int i=int(b.size())-2;i>=0;--i)
                ss<<setw(width)<<setfill('0')<<b[i];
            return ss;
        }
};
```

```

}
template<typename T>
operator T(){
    stringstream ss;
    ss<<*this;
    T res;
    return ss>>res,res;
}
};
#define size(x) (int)(x).size()

```

4.2 Mod Int [c34f76]

```

template <unsigned P>
struct mint { // P not prime break /=
    unsigned v;
    mint(ll v = 0) : v((v%P+P) % P) {}
    mint &operator+=(mint const &o) {
        v = (v += o.v) >= P ? v - P : v;
        return *this;
    }
    mint &operator-=(mint const &o) {
        v = (v < o.v) ? v + P - o.v : v - o.v;
        return *this;
    }
    mint &operator*=(mint const &o) {
        v = 1ll * v * o.v % P;
        return *this;
    }
    friend
    mint operator+(mint const &a, mint const &b) {
        return mint(a) += b;
    }
    friend
    mint operator-(mint const &a, mint const &b) {
        return mint(a) -= b;
    }
    friend
    mint operator*(mint const &a, mint const &b) {
        return mint(a) *= b;
    }
    inline mint pow(ll n) const {
        mint r(1);
        mint a = v;
        for (; n; a *= a, n >>= 1)
            r *= (n & 1) ? (a) : (mint(1));
        return r;
    }
    mint &operator/=(mint const &o) {
        *this *= o.pow(P - 2);
        return *this;
    }
    friend
    mint operator/(mint const &a, mint const &b) {
        return mint(a) /= b;
    }
    friend ostream
    &operator<<(ostream &os, mint const &m) {
        return os << m.v;
    }
    friend istream &operator>>(istream &is, mint &m) {
        return is >> m.v;
    }
};

```

4.3 Fraction [9c92bf]

```

struct frac {
    ll n, d;
    frac(const
        ll &n = 0, const ll &d = 1) : n(_n), d(_d) {
        ll t = __gcd(n, d);
        n /= t, d /= t;
        if (d < 0)
            n = -n, d = -d;
    }
    frac operator-() const {
        return frac(-n, d);
    }
};

```

```

}
frac operator+(const frac &b) const {
    return frac(n * b.d + b.n * d, d * b.d);
}
void operator+=(const frac &b) {
    *this = frac(n * b.d + b.n * d, d * b.d);
}
frac operator-(const frac &b) const {
    return frac(n * b.d - b.n * d, d * b.d);
}
void operator-=(const frac &b) {
    *this = frac(n * b.d - b.n * d, d * b.d);
}
frac operator*(const frac &b) const {
    return frac(n * b.n, d * b.d);
}
void operator*=(const frac &b) {
    *this = frac(n * b.n, d * b.d);
}
frac operator/(const frac &b) const {
    return frac(n * b.d, d * b.n);
}
void operator/=(const frac &b) {
    *this = frac(n * b.d, d * b.n);
}
friend ostream
&operator<<(ostream &os, frac const &f) {
    if (f.d == 1)
        return os << f.n;
    return os << f.n << '/' << f.d;
}
friend istream &operator>>(istream &is, frac &f) {
    istream &tp = is >> f.n >> f.d;
    f = frac(f.n, f.d);
    return tp;
}
};

```

4.4 FWT [02d887]

```

struct Fast_Walsh_Transform { // Modint needed
    string op; // and, or, xor
    void fwt(vector<mint> &v, bool ifwt) {
        int n = __lg(size(v));
        mint iv2 = mint(1) / 2;
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < 1 << n; ++j)
                if (op == "and" && (~j >> i & 1) || op == "or" && (j >> i & 1)) {
                    if (!ifwt)
                        v[j] += v[j ^ (1 << i)];
                    else
                        v[j] -= v[j ^ (1 << i)];
                } else if (op == "xor" && (j >> i & 1)) {
                    mint x = v[j ^ (1 << i)], y = v[j];
                    if (!ifwt)
                        v[j ^ (1 << i)] = x + y, v[j] = x - y;
                    else
                        v[j ^ (1 << i)] = (x + y) *
                            iv2, v[j] = (x - y) * iv2;
                }
    }
    vector<mint> v1, v2; // size(v1) = size(v2) = 2^k
    Fast_Walsh_Transform(const vector
        <mint> &_v1, const vector<mint> &_v2, const
        string &_op) : v1(_v1), v2(_v2), op(_op) {}
    vector<mint> solve
    () { // ans_k = \sum_{i op j = k} a_i * b_j
        fwt(v1, 0), fwt(v2, 0);
        for (int i = 0; i < size(v1); ++i)
            v1[i] *= v2[i];
        fwt(v1, 1);
        return v1;
    }
};

```

4.5 FFT [c93f4dc]

```
typedef complex<double> cd;
struct FFT {
#define M_PI 3.14159265358979323846264338327950288
    static const int K = 19, N = 1 << K; // change
    cd pL[N];
    int rv[N];
    void dft(vector<cd> &ar) {
        int n = size(ar), k = log2(n);
        if (n <= 1)
            return;
        for (int i = 1; i < n; i++)
            if (i < rv[i] >> (K - k))
                swap(ar[i], ar[rv[i] >> (K - k)]);
        cd a, b;
        for (int l = 1; l < n; l <= 1) {
            for (int i = 0; i < n; i += l << 1) {
                for (int j = 0; j < l; j++) {
                    a = ar[i + j],
                    b = ar[i + j + l] * pL[j + l];
                    ar[i + j] = a + b;
                    ar[i + j + l] = a - b;
                }
            }
        }
    }
    void idft(vector<cd> &ar) {
        double n = size(ar);
        reverse(ar.begin() + 1, ar.end());
        for (cd &i : ar)
            i /= n;
        dft(ar);
    }
    vector<cd> pmul(vector<cd> a, vector<cd> b) {
        int n = size(a) + size(b) - 1;
        while (n & (n - 1))
            n += lowbit(n);
        a.resize(n), b.resize(n);
        dft(a), dft(b);
        for (int i = 0; i < n; i++)
            a[i] *= b[i];
        idft(a), a.resize(n);
        return a;
    }
    FFT() {
        pL[1] = polar(1.0, 0.0);
        for (int k = 2; k < N; k <= 1)
            for (int i = k; i < k << 1; i++)
                pL[i] = polar(1.0,
                    2.0 * M_PI * (i - k) / (k * 2.0));
        for (int i = 1, hb = -1; i < N; i++) {
            if (!(i & (i - 1)))
                hb++;
            rv[i] =
                rv[i ^ (1 << hb)] | 1 << (K - 1 - hb);
        }
    }
};
```

4.6 NTT [5af390]

```
const int M = 998244353;
typedef mint<M> mi;
struct NTT {
    static const int K = 20, N = 1 << K;
    mi pL[N];
    int rv[N];
    void dft(vector<mi> &ar) {
        static int n, k;
        n = size(ar), k = log2(n);
        if (n <= 1)
            return;
        for (int i = 1; i < n; i++)
            if (i < rv[i] >> (K - k))
                swap(ar[i], ar[rv[i] >> (K - k)]);
        static mi a, b;
```

```
        for (int l = 1; l < n; l <= 1) {
            for (int i = 0; i < n; i += l << 1) {
                for (int j = 0; j < l; j++) {
                    a = ar[i + j],
                    b = ar[i + j + l] * pL[j + l];
                    ar[i + j] = a + b;
                    ar[i + j + l] = a - b;
                }
            }
        }
    }
    void idft(vector<mi> &ar) {
        static mi invn;
        invn.v = 1, invn /= size(ar);
        reverse(ar.begin() + 1, ar.end());
        for (mi &i : ar)
            i *= invn;
        dft(ar);
    }
    template<typename T>
    T pmul(T a, T b) {
        static int n;
        n = size(a) + size(b) - 1;
        while (n & (n - 1))
            n += lowbit(n);
        a.resize(n), b.resize(n);
        dft(a), dft(b);
        for (int i = 0; i < n; i++)
            a[i] *= b[i];
        idft(a), a.resize(n);
        return a;
    }
    NTT() {
        pL[1] = 1;
        for (int k = 1; k < K; k++) {
            mi omega = mi(3).pow((M - 1) >> (k + 1));
            for (int i = 1 << (k - 1); i < 1 << k; i++)
                pL[i * 2] = pL
                    [i], pL[i * 2 + 1] = pL[i] * omega;
        }
        for (int i = 1, hb = -1; i < N; i++) {
            if (!(i & (i - 1)))
                hb++;
            rv[i] =
                rv[i ^ (1 << hb)] | 1 << (K - 1 - hb);
        }
    }
};
```

4.7 Polynomial [048b32]

```
template<typename T>
struct Poly:vector<T>{
    using vector<T>::vector;
    static NTT con;
    Poly(const Poly &p, int m): vector<T>(m){
        copy_n(p.data(), min(size(p), m), this->data());
    }
    Poly& isz(int m) { return this->resize(m), *this; }
    Poly operator+(T const &b){
        Poly ret = Poly(*this, size(*this));
        ret[0] += b;
        return ret;
    }
    Poly operator*(T const &b){
        Poly ret = Poly(*this, size(*this));
        for (int i = 0; i < size(ret); i++) ret[i] += b;
        return ret;
    }
    Poly operator+(Poly &b){
        Poly ret = Poly(*this, max(size(b), size(*this)));
        for (int i = 0; i < size(ret); i++) ret[i] += b[i];
        return ret;
    }
    Poly operator*(Poly b){
        return con.pmul(*this, b);
    }
};
```

```

}
Poly dx() {
    Poly ret(size(*this)-1);
    for(int i
        =0;i<size(ret);i++) ret[i]=T(i+1)*(*this)[i+1];
    ret.resize(max(1,size(ret)));
    return ret;
}
Poly ix() {
    Poly ret(size(*this) + 1);
    for(int i=1;i<size
        (ret);i++) ret[i] = T(1)/T(i) * (*this)[i-1];
    return ret;
}
Poly inv() {
    int n = size(*this);
    if(n==1) return {T(1)/(*this)[0]};
    int m = n<<1;
    while(m^lowbit(m)) m+=lowbit(m);
    Poly xi = Poly(*this,(n+1)/2).inv().isz(m);
    Poly yi(*this,m);
    con.dft(xi);con.dft(yi);
    for(int i=0;i<m;i++){
        xi[i] = xi[i]*(mi(2)-yi[i]*xi[i]);
    }
    con.idft(xi);
    return xi.isz(n);
}
Poly ln(){
    int n = size(*this);
    Poly ret = (*this).dx();
    Poly inv = (*this).inv();
    ret = ret*inv;
    ret.resize(n);
    return ret.ix().isz(n);
}
Poly exp(){
    int n = size(*this);
    if(n==1) return {T(1)};
    Poly xi = Poly(*this,(n+1)/2).exp().isz(n);
    Poly yi = xi.ln();yi[0]=T(-1);
    for(int i=0;i<n;i++) yi[i] = (*this)[i]-yi[i];
    return (xi*yi).isz(n);
}
Poly pow(T k){
    Poly d = (*this).ln();
    d = d*k;
    d = d.exp();
    return d;
}
};
template<typename T>
NTT Poly<T>::con;

```

4.8 Miller Rabin [67a711]

```

bool isPrime(const uint64_t n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    uint64_t A[] = {2,
        325, 9375, 28178, 450775, 9780504, 1795265022},
    s = __builtin_ctzll(n-1), D = n >> s;
    for (auto a : A) {
        uint64_t p = 1, g=a%n, i=s, d=D;
        for (;d;g=__int128
            (g)*g%n,d/=2) if(d&1) p = __int128(p)*g%n;
        while (p != 1 && p
            != n - 1 && a % n && i--) p = __int128(p)*p%n;
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}

```

4.9 Pollard' s Rho [8252e7]

```

ll PollardRho(
    ll x) { // get a factor of x(not prime) in O(x^0.25)
    ll s = 0, t = 0;
    ll c = (ll)rand() % (x - 1) + 1;

```

```

    int step = 0, g = 1;
    ll val = 1;
    for (g = 1;; g <= 1, s = t, val = 1) {
        for (step = 1; step <= g; ++step) {
            t = (__int128(t)*t+c)%x;
            val = __int128(val) * abs(t - s) % x;
            if ((step % 127) == 0) {
                ll d = __gcd(val, x);
                if (d > 1) return d;
            }
        }
        ll d = __gcd(val, x);
        if (d > 1) return d;
    }
}

```

4.10 Discrete Log [78c47f]

```

int mod_log(int a, int b, int m) {
    if(b==1%m) return 0;
    int n = int(ceil(sqrt(m)));
    int e = 0;
    int k = 1;
    for (int g; (g = gcd(a, m)) != 1;) {
        if (b % g != 0) return -1;
        b /= g; m /= g;
        e++;
    }
    k = (1LL*k*(a/g))%m;
    if (b == k) return e;
}
int x = 1;
unordered_map<int, int> map_;
for (int q = 0; q < n; q++, x = (1LL*x*a)%m) {
    map_[(1LL*x*b)%m] = q;
}
int y = x;
for (int p = 1; p <= n; p++, y = (1LL*y*x)%m) {
    if (auto it =
        map_.find((1LL*y*k)%m); it != end(map_)) {
        return int(p) * n - it->second + e;
    }
}
return -1;
}

```

4.11 Exgcd/CRT [f45f4d]

```

// find x,y such that ax+by=gcd(a,b)
ll exgcd(ll a, ll b, ll &x, ll &y) {
    if (!b) return x = 1, y = 0, a;
    ll d = exgcd(b, a % b, y, x);
    return y -= a/b * x, d;
}
ll CRT(int k, ll* a, ll* r) {
    ll n = 1, ans = 0;
    for (int i = 1; i <= k; i++) n = n * r[i];
    for (int i = 1; i <= k; i++) {
        ll m = n / r[i], b, y;
        exgcd(m, r[i], b, y); // b * m mod r[i] = 1
        ans = (ans + a[i] * m * b % n) % n;
    }
    return (ans % n + n) % n;
}
// not coprime
: x = m1p+a1 = m2q+a2 => m1p-m2q = a2-a1, use exgcd

```

4.12 Semi-Euclid [e7979f]

```

//0~(n-1)!!!! sum floor((ax+b)/m)
ll semiEuclid(ll a,ll b,ll m,ll n){
    if(a==0) return (b/m)*(n);
    if(a >= m or b >= m) return n*(
        n-1)/2*(a/m) + n*(b/m) + semiEuclid(a%m,b%m,m,n);
    ll l = (a*(n-1)+b)/m;
    return l*(n-1) - semiEuclid(m,m-b-1,a,l);
}

```

4.13 Theorem

- LTE Lemma $\nu_p(x^n - y^n) = \nu_p(x - y) + \nu_p(n)$, if $p|x - y$.
 $\nu_2(x^n - y^n) = \nu_2(x - y) + \nu_2(n)$, if $4|x - y$. $\nu_2(x^n - y^n) = \nu_2(x - y) + \nu_2(x + y) + \nu_2(n) - 1$, if $2|x - y$ and n is even.
 $\nu_p(x^n + y^n) = \nu_p(x + y) + \nu_p(n)$, if $p|x + y$ and n is odd. $\nu_2(x^n + y^n) = 1$, if $2|x + y$ and n is even. $\nu_2(x^n + y^n) = \nu_2(x + y)$ if $2|x + y$ and n is odd.
- Cramer's rule

$$\begin{aligned} ax + by &= e \\ cx + dy &= f \end{aligned} \Rightarrow \begin{aligned} x &= \frac{ed - bf}{ad - bc} \\ y &= \frac{af - ec}{ad - bc} \end{aligned}$$

- Vandermonde's Identity

$$C(n+m, k) = \sum_{i=0}^k C(n, i) C(m, k-i)$$

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.
- Tutte's Matrix
 Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .
- Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are $\frac{(n-2)!}{(d_1-1)!(d_2-1)! \dots (d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős-Gallai theorem

A sequence of nonnegative integers $d_1 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only

if $d_1 + \dots + d_n$ is even and $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$ holds for

every $1 \leq k \leq n$.

- Gale-Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n

is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Fulkerson-Chen-Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and

$\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Pick's theorem

For simple polygon, when points are all integer, we have $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$.

- Möbius inversion formula

$$\begin{aligned} f(n) &= \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f\left(\frac{n}{d}\right) \\ f(n) &= \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu\left(\frac{d}{n}\right) f(d) \end{aligned}$$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume $= \pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos\theta)(1 - \cos\theta)^2/3$.
- Area $= 2\pi r h = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos\theta)$.

- Lagrange multiplier

- Optimize $f(x_1, \dots, x_n)$ when k constraints $g_i(x_1, \dots, x_n) = 0$.
- Lagrangian function $\mathcal{L}(x_1, \dots, x_n, \lambda_1, \dots, \lambda_k) = f(x_1, \dots, x_n) - \sum_{i=1}^k \lambda_i g_i(x_1, \dots, x_n)$.
- The solution corresponding to the original constrained optimization is always a saddle point of the Lagrangian function.

- Nearest points of two skew lines

- Line 1: $v_1 = p_1 + t_1 d_1$
- Line 2: $v_2 = p_2 + t_2 d_2$
- $n = d_1 \times d_2$
- $n_1 = d_1 \times n$
- $n_2 = d_2 \times n$
- $c_1 = p_1 + \frac{(p_2 - p_1) \cdot n_2}{d_1 \cdot n_2} d_1$
- $c_2 = p_2 + \frac{(p_1 - p_2) \cdot n_1}{d_2 \cdot n_1} d_2$

- Derivatives/Integrals

$$\begin{aligned} \text{Integration by parts: } \int_a^b f(x)g(x)dx &= [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx \\ \left| \frac{d}{dx} \sin^{-1} x &= \frac{1}{\sqrt{1-x^2}} \right| \quad \left| \frac{d}{dx} \cos^{-1} x = -\frac{1}{\sqrt{1-x^2}} \right| \quad \left| \frac{d}{dx} \tan^{-1} x = \frac{1}{1+x^2} \right| \\ \left| \frac{d}{dx} \tan x &= 1 + \tan^2 x \right| \quad \left| \int \tan ax = -\frac{\ln|\cos ax|}{a} \right| \\ \left| \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \text{erf}(x) \right| \quad \left| \int x e^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1) \right| \\ \left| \int \sqrt{a^2 + x^2} &= \frac{1}{2} \left(x\sqrt{a^2 + x^2} + a^2 \text{asinh}(x/a) \right) \right| \end{aligned}$$

- Spherical Coordinate

$$(x, y, z) = (r \sin\theta \cos\phi, r \sin\theta \sin\phi, r \cos\theta)$$

$$(r, \theta, \phi) = (\sqrt{x^2 + y^2 + z^2}, \arccos(z/\sqrt{x^2 + y^2 + z^2}), \text{atan2}(y, x))$$

- Rotation Matrix

$$M(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}, R_x(\theta_x) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\theta_x & -\sin\theta_x \\ 0 & \sin\theta & \cos\theta \end{bmatrix}$$

- Pell's equation $x^2 - ny^2 = 1 \Rightarrow$ let x_1, y_1 be the smallest solution: the other solution has the form $x_i + y_i \sqrt{n} = (x_1 + y_1 \sqrt{n})^i$ (x_1, y_1 can be found by continuous fraction expansion of \sqrt{n})
- Lucas' Theorem

$$\binom{n}{i} \equiv \prod_{j=0}^m \binom{n_j}{i_j} \pmod{p}$$

where a_j is a 's representation in p -base

- Cipolla's algorithm find $a \Rightarrow \left(\frac{a^2-n}{p}\right) = -1$ (legendre symbol) and calculate $(a + \sqrt{a^2-n})^{(p+1)/2}$ in the field $(F)_p(\sqrt{a^2-n})$, that will be a solution. (note: $p=2$ need to be separate out)

5 String

5.1 AC auto [9b275b]

```
struct ACauto {
    const static int N = 2e5 + 5; // change
    int tr
        [26][N], fail[N], ctn = 1, cnt[N], endat[N], n;
    vector<int> top; // fail tree topological order
    inline void clr(int p) {
        fail[p] = cnt[p] = 0;
        for (int i = 0; i < 26; i++)
            tr[i][p] = 0;
    }
    inline int add(const string &s) {
        int cr = 1;
        string tmp;
        for (int c : s) {
            tmp += c;
            c -= 'a';
            if (!tr[c][cr])
                clr(tr[c][cr] = ++ctn);
            cr = tr[c][cr];
        }
        return cr;
    }
    void bld(const vector<string> &ar) {
        for (int i = 0; i < 26; i++)
            tr[i][0] = 1;
        clr(ctn = 1, n = size(ar));
        for (int i = 0; i < n; i++)
            endat[i] = add(ar[i]);
        queue<int> q;
        q.push(1);
        while (!q.empty()) {
            int pr = q.front();
            q.pop();
            top.pb(pr);
            for (int i = 0; i < 26; i++) {
                int &cr = tr[i][pr];
                if (cr)
                    fail[cr]
                        = tr[i][fail[pr]], q.push(cr);
            }
            else
                cr = tr[i][fail[pr]];
        }
    }
};
```



```

    }
    reverse(iter(top));
}
void qry(const string &s) {
    int cr = 1;
    for (char c : s) // ways to walk
        cr = tr[c - 'a'][cr], cnt[cr]++;
    for (int i : top)
        cnt[fail[i]] += cnt[i];
}
};

```

5.2 SA [58db4a]

```

struct SA {
    static const int N = 5e5 + 5; // change
    int sa[N], rk[N], cnt[N], lcp[N], tmp[N], n;
    void blt(const string &s) {
        n = s.length();
        int m = 128;
        memset(cnt + 1, 0, m << 2);
        for (int i = 0; i < n; i++)
            cnt[rk[i] = s[i]]++;
        for (int i = 1; i <= m; i++)
            cnt[i] += cnt[i - 1];
        for (int i = n - 1; i >= 0; i--)
            sa[--cnt[rk[i]]] = i;
        for (int k = 1; k <= 1) {
            int ln = 0;
            for (int i = n - k; i < n; i++)
                tmp[ln++] = i;
            for (int i = 0; i < n; i++)
                if (sa[i] >= k)
                    tmp[ln++] = sa[i] - k;
            memset(cnt + 1, 0, m << 2);
            for (int i = 0; i < n; i++)
                cnt[rk[i]]++;
            for (int i = 1; i <= m; i++)
                cnt[i] += cnt[i - 1];
            for (int i = n - 1; i >= 0; i--)
                sa[--cnt[rk[tmp[i]]]] = tmp[i];
            memcpy(tmp, rk, n << 2), rk[sa[0]] = m = 1;
            for (int i = 1; i < n; i++) {
                if (tmp[sa[i]] != tmp[sa[i - 1]] ||
                    tmp[sa[i] + k] != tmp[sa[i - 1] + k])
                    m++;
                rk[sa[i]] = m;
            }
            if (m == n)
                break;
        }
        for (int i = 0, k = 0; i < n; i++, k -= !!k) {
            if (rk[i] == n)
                continue;
            int j = sa[rk[i]];
            while (i + k < n && j + k < n && s[i + k] == s[j + k])
                k++;
            lcp[rk[i]] = k;
        } // lcp[1~n-1], sa[0~n-1]
    }
};

```

5.3 KMP [2b5dca]

```

vector<int> kmp(string &s) {
    int n = size(s);
    vector<int> pi(n, 0);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j])
            j = pi[j - 1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
}

```

```

    }
    return pi;
}

```

5.4 Z [29dad4]

```

vector<int> z_algo(string &s) { // 0-base
    int n = size(s);
    vector<int> z(n, 0);
    for (int i = 1, l = 0, r = 0; i < n; i++) {
        if (i <= r)
            z[i] = min(z[i - l], r - i + 1);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            z[i]++;
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    z[0] = n;
    return z;
}

```

5.5 Manacher [947d5b]

```

vector<int> manacher(string &s) { // pad s with $->$a$b$c....z$, realans = ans-1.
    string t(size(s) * 2 + 1, '$');
    for (int i = 0; i < size(s); i++) t[i * 2 + 1] = s[i];
    int n = size(t), m = 0, r = 0;
    vector<int> p(n);
    for (int i = 0; i < n; i++) {
        p[i] = (r > i ? min(r - i, p[m - (i - m)]) : 1);
        while (i - p[i] >= 0 && i + p[i] < n &&
            t[i - p[i]] == t[i + p[i]]) ++p[i];
        if (i + p[i] > r) m = i, r = i + p[i];
    }
    return p;
}

```

5.6 SAM [96a460]

```

struct SAM {
    static const int N = 2e5 + 6;
    int tr[26][N], len[N], lnk[N], tmp[N], pl[N], ctn, lst;
    inline void ini(int x) {
        for (int i = 0; i < 26; i++)
            tr[i][x] = 0;
    }
    inline void ini() {
        ini(ctn = lst = len[0] = 0), lnk[0] = -1;
        memset(tmp, 0, sizeof(tmp));
    }
    inline void cp(int x, int y) {
        lnk[x] = lnk[y];
        for (int i = 0; i < 26; i++)
            tr[i][x] = tr[i][y];
    }
    void ext(const char cc) {
        static int c, cr, p, q;
        c = cc - 'a', p = lst;
        ini(cr = ++ctn, len[cr] = len[p] + 1);
        while (~p && !tr[c][p])
            tr[c][p] = cr, p = lnk[p];
        if (~p) {
            q = tr[c][p];
            if (len[q] == len[p] + 1)
                lnk[cr] = q;
            else {
                cp(++ctn, q), len[ctn] = len[p] + 1;
                while (~p && tr[c][p] == q)
                    tr[c][p] = ctn, p = lnk[p];
                lnk[cr] = lnk[q] = ctn;
            }
        } else
            lnk[cr] = 0;
        lst = cr;
    }
    void blt(const string &s) {

```

```

ini();
for (const char &c : s)
    ext(c);
for (int i = 0; i <= ctn; i++)
    tmp[len[i]]++;
for (int i = 1; i <= ctn; i++)
    tmp[i] += tmp[i - 1];
for (int i = ctn; i >= 0; i--)
    pl[--tmp[len[i]]] = i;
}
};

```

6 Data Structure

6.1 Li-Chao [f2885c]

```

struct LiChaoMin {
    struct line {
        ll m, k, id;
        line(ll _m = 0, ll _k
            = 0, ll _id = 0) : m(_m), k(_k), id(_id) {}
        ll at(ll x) { return m * x + k; }
    };
    struct node {
        node *l, *r;
        line f;
        node(line v) : f(v), l(NULL), r(NULL) {}
    };
    node *root;
    int sz;
    void insert(node *&x, int l, int r, line &ln) {
        if (!x) {
            x = new node(ln);
            return;
        }
        ll trl = x->f.at(l), trr = x->f.at(r);
        ll vl = ln.at(l), vr = ln.at(r);
        if (trl <= vl && trr <= vr)
            return;
        if (trl > vl && trr > vr) {
            x->f = ln;
            return;
        }
        if (trl > vl)
            swap(x->f, ln);
        int mid = (l + r) >> 1;
        if (x->f.at(mid) < ln.at(mid))
            insert(x->r, mid + 1, r, ln);
        else
            swap(x->f, ln), insert(x->l, l, mid, ln);
    }
    ll query(node *&x, int l, int r, ll idx) {
        if (!x)
            return LONG_LONG_MAX;
        if (l == r)
            return x->f.at(idx);
        int mid = (l + r) >> 1;
        if (mid >= idx)
            return min(x
                ->f.at(idx), query(x->l, l, mid, idx));
        return min(x
            ->f.at(idx), query(x->r, mid + 1, r, idx));
    }
    LiChaoMin(int _sz) : sz(_sz + 1), root(NULL) {}
    void add_line(ll m, ll k, ll id = 0) {
        auto ln = line(m, k, id);
        insert(root, -sz, sz, ln);
    } // -sz <= query_x <= sz
    ll query
        (ll idx) { return query(root, -sz, sz, idx); }
};

```

6.2 Treap [d7ba9f]

```

namespace Treap {
    const int N = 2e5 + 5;
    struct node {
        int ky, sz, mn, mx, ln, rn;

```

```

        ll sum;
        bool tg;
        static node *pl;
        node() { sum = sz = 0, mx = ~INF, mn = INF; }
        inline void ini(int v) { sum = ky
            = mx = mn = v, sz = 1, ln = rn = tg = 0; }
        inline void upd(int v) {
            ky = mx = mn = v;
            sum = 1ll * v * sz;
            tg = 1;
        }
        inline void up() {
            sz = 1 + pl[ln].sz + pl[rn].sz;
            sum = mx = mn = ky;
            sum += pl[ln].sum + pl[rn].sum;
            tmax(mx, max(pl[ln].mx, pl[rn].mx));
            tmin(mn, min(pl[ln].mn, pl[rn].mn));
        }
        inline
            void down() { tg && (ln && (pl[ln].upd(ky)
                , 0), rn && (pl[rn].upd(ky), 0)), tg = 0; }
    } pool[N];
    mt19937 rnd(time(0));
    node *node::pl = pool, *pl = pool;
    int ctp = 0;
    inline int nwnd(int v) {
        pl[++ctp].ini(v);
        return ctp;
    }
    int mg(int a, int b) {
        if (!a || !b)
            return a ? a : b;
        if ((int
            )rnd() % (pl[a].sz + pl[b].sz) < pl[a].sz)
            return pl[a].down(), pl[
                a].rn = mg(pl[a].rn, b), pl[a].up(), a;
        else
            return pl[b].down(), pl[
                b].ln = mg(a, pl[b].ln), pl[b].up(), b;
    }
    void splsz(int rt, int &a, int &b, int k) {
        if (!rt)
            return a = b = 0, void();
        pl[rt].down();
        if (pl[pl[rt].ln].sz < k)
            a = rt, splsz(pl[rt].rn,
                pl[a].rn, b, k - pl[pl[rt].ln].sz - 1);
        else
            b = rt, splsz(pl[rt].ln, a, pl[b].ln, k);
        pl[rt].up();
    }
    void splky(int rt, int &a, int &b, int v) {
        if (!rt)
            return a = b = 0, void();
        pl[rt].down();
        if (pl[rt].ky <= v)
            a = rt, splky(pl[rt].rn, pl[a].rn, b, v);
        else
            b = rt, splky(pl[rt].ln, a, pl[b].ln, v);
        pl[rt].up();
    }
}

```

6.3 Link Cut Tree [49d7e6]

```

struct LCT {
    static const int N = 4e5 + 5; // change
    int fa[N], ch[2][N], sz[N], sv[N];
    #define gch(x) ((x) == ch[1][fa[x]])
    #define nrt(x) ((x) == ch[gch(x)][fa[x]])
    #define up
        (x) sz[x] = sz[ch[0][x]] + sz[ch[1][x]] + sv[x] + 1
    inline void rota(int x) {
        int f = fa[x], ff = fa[f], k = gch(x);
        if (nrt(f))
            ch[gch(f)][ff] = x;
        fa[x] = ff;

```

```

    if (ch[!k][x])
        fa[ch[!k][x]] = f;
    ch[k][f] = ch[!k][x];
    ch[!k][x] = f, fa[f] = x;
    up(f), up(x);
}
inline void splay(int x) {
    for (int f = fa[x]; nrt(x); rota(x), f = fa[x])
        if (nrt(f))
            rota(gch(x) ^ gch(f) ? x : f);
}
inline int acc(int x) {
    int p;
    for (p = 0; x; p = x, x = fa[x])
        splay(x), sv[x] += sz[
            ch[1][x]] - sz[p], ch[1][x] = p, up(x);
    return p;
}
inline int findroot(int x) {
    int cr = acc(x);
    while (ch[0][cr])
        cr = ch[0][cr];
    splay(cr);
    return cr;
}
void link(int x, int y) {
    int rt = findroot(y);
    acc(x), acc(rt);
    acc(y), splay(y);
    sv[y] += sz[x];
    fa[x] = y, up(y);
    acc(rt);
}
void cut(int x, int y) {
    int rt = findroot(y);
    acc(rt);
    acc(y), splay(y), splay(x);
    sv[y] -= sz[x];
    fa[x] = 0, up(y);
    acc(x), acc(rt);
}
};

```

6.4 Ultimate Segment Tree [6e7e86]

```

struct SegBeat {
    int n, n0;
    vector<ll> max_v, smax_v,
        max_c, min_v, smin_v, min_c, sum, len, ladd, lval;
    void update_node_max(int k, ll x) {
        sum[k] += (x - max_v[k]) * max_c[k];
        if (max_v
            [k] == min_v[k]) max_v[k] = min_v[k] = x;
        else if (max_v
            [k] == smin_v[k]) max_v[k] = smin_v[k] = x;
        else max_v[k] = x;
        if (lval[k] != 1e18 && x < lval[k]) lval[k] = x;
    }
    void update_node_min(int k, ll x) {
        sum[k] += (x - min_v[k]) * min_c[k];
        if (max_v
            [k] == min_v[k]) max_v[k] = min_v[k] = x;
        else if (smax_v
            [k] == min_v[k]) min_v[k] = smax_v[k] = x;
        else min_v[k] = x;
        if (lval[k] != 1e18 && lval[k] < x) lval[k] = x;
    }
    void push(int k) {
        if (n0-1 <= k) return;
        if (lval[k] != 1e18) {
            updateall(2*k+1, lval[k]);
            updateall(2*k+2, lval[k]);
            lval[k] = 1e18;
            return;
        }
        if (ladd[k] != 0) {
            addall(2*k+1, ladd[k]);

```

```

            addall(2*k+2, ladd[k]);
            ladd[k] = 0;
        }
        if (max_v[k] < max_v
            [2*k+1]) update_node_max(2*k+1, max_v[k]);
        if (min_v[k] < min_v
            [2*k+1]) update_node_min(2*k+1, min_v[k]);
        if (max_v[k] < max_v
            [2*k+2]) update_node_max(2*k+2, max_v[k]);
        if (min_v[k] < min_v
            [2*k+2]) update_node_min(2*k+2, min_v[k]);
    }
    void update(int k) {
        sum[k] = sum[2*k+1] + sum[2*k+2];
        if (max_v[2*k+1] < max_v[2*k+2]) {
            max_v[k] = max_v[2*k+2];
            max_c[k] = max_c[2*k+2];
            smax_v
                [k] = max(max_v[2*k+1], smax_v[2*k+2]);
        } else if (max_v[2*k+1] > max_v[2*k+2]) {
            max_v[k] = max_v[2*k+1];
            max_c[k] = max_c[2*k+1];
            smax_v
                [k] = max(smax_v[2*k+1], max_v[2*k+2]);
        } else {
            max_v[k] = max_v[2*k+1];
            max_c[k] = max_c[2*k+1] + max_c[2*k+2];
            smax_v
                [k] = max(smax_v[2*k+1], smax_v[2*k+2]);
        }
        if (min_v[2*k+1] < min_v[2*k+2]) {
            min_v[k] = min_v[2*k+1];
            min_c[k] = min_c[2*k+1];
            smin_v
                [k] = min(smin_v[2*k+1], min_v[2*k+2]);
        } else if (min_v[2*k+1] > min_v[2*k+2]) {
            min_v[k] = min_v[2*k+2];
            min_c[k] = min_c[2*k+2];
            smin_v
                [k] = min(min_v[2*k+1], smin_v[2*k+2]);
        } else {
            min_v[k] = min_v[2*k+1];
            min_c[k] = min_c[2*k+1] + min_c[2*k+2];
            smin_v
                [k] = min(smin_v[2*k+1], smin_v[2*k+2]);
        }
    }
    void _chmin
        (ll x, int a, int b, int k, int l, int r) {
        if (b <= l || r <= a || max_v[k] <= x) return;
        if (a <= l && r <= b && smax_v[k] < x) {
            update_node_max(k, x);
            return;
        }
        push(k);
        _chmin(x, a, b, 2*k+1, l, (l+r)/2);
        _chmin(x, a, b, 2*k+2, (l+r)/2, r);
        update(k);
    }
    void _chmax
        (ll x, int a, int b, int k, int l, int r) {
        if (b <= l || r <= a || x <= min_v[k]) return;
        if (a <= l && r <= b && x < smin_v[k]) {
            update_node_min(k, x);
            return;
        }
        push(k);
        _chmax(x, a, b, 2*k+1, l, (l+r)/2);
        _chmax(x, a, b, 2*k+2, (l+r)/2, r);
        update(k);
    }
    void addall(int k, ll x) {
        max_v[k] += x;
        if (smax_v[k] != -1e18) smax_v[k] += x;
        min_v[k] += x;

```

```

    if(smin_v[k] != 1e18) smin_v[k] += x;
    sum[k] += len[k] * x;
    if(lval[k] != 1e18) lval[k] += x;
    else ladd[k] += x;
}
void updateall(int k, ll x) {
    max_v[k] = x;
    smax_v[k] = -1e18;
    min_v[k] = x;
    smin_v[k] = 1e18;
    max_c[k] = min_c[k] = len[k];
    sum[k] = x * len[k];
    lval[k] = x;
    ladd[k] = 0;
}
void _add_val
(ll x, int a, int b, int k, int l, int r) {
    if(b <= l || r <= a) return;
    if(a <= l && r <= b) {
        addall(k, x);
        return;
    }
    push(k);
    _add_val(x, a, b, 2*k+1, l, (l+r)/2);
    _add_val(x, a, b, 2*k+2, (l+r)/2, r);
    update(k);
}
void _update_val
(ll x, int a, int b, int k, int l, int r) {
    if(b <= l || r <= a) return;
    if(a <= l && r <= b) {
        updateall(k, x);
        return;
    }
    push(k);
    _update_val(x, a, b, 2*k+1, l, (l+r)/2);
    _update_val(x, a, b, 2*k+2, (l+r)/2, r);
    update(k);
}
ll _query_max(int a, int b, int k, int l, int r) {
    if(b <= l || r <= a) return -1e18;
    if(a <= l && r <= b) return max_v[k];
    push(k);
    ll lv = _query_max(a, b, 2*k+1, l, (l+r)/2);
    ll rv = _query_max(a, b, 2*k+2, (l+r)/2, r);
    return max(lv, rv);
}
ll _query_min(int a, int b, int k, int l, int r) {
    if(b <= l || r <= a) return 1e18;
    if(a <= l && r <= b) return min_v[k];
    push(k);
    ll lv = _query_min(a, b, 2*k+1, l, (l+r)/2);
    ll rv = _query_min(a, b, 2*k+2, (l+r)/2, r);
    return min(lv, rv);
}
ll _query_sum(int a, int b, int k, int l, int r) {
    if(b <= l || r <= a) return 0;
    if(a <= l && r <= b) return sum[k];
    push(k);
    ll lv = _query_sum(a, b, 2*k+1, l, (l+r)/2);
    ll rv = _query_sum(a, b, 2*k+2, (l+r)/2, r);
    return lv + rv;
}
SegBeat(int _n) : n(_n) {
    max_v.resize(4*_n+4, 0); smax_v.resize
        (4*_n+4, -1e18); max_c.resize(4*_n+4, 1);
    min_v.resize(4*_n+4, 0); smin_v.
        resize(4*_n+4, 1e18); min_c.resize(4*_n+4, 1);
    sum.resize(4*_n+4, 0); len.resize(4*_n+4, 0);
    ladd.resize(4*_n+4, 0); lval.resize(4*_n+4, 1e18);
    n0 = 1;
    while(n0 < n) n0 <= 1;
    len[0] = n0;
    for(int i=0; i<n0-1; ++
        i) len[2*i+1] = len[2*i+2] = (len[i] >> 1);
}

```

```

    for(int i=n; i<n0; ++i) {
        max_v[n0-1+i] = smax_v[n0-1+i] = -1e18;
        min_v[n0-1+i] = smin_v[n0-1+i] = 1e18;
        max_c[n0-1+i] = min_c[n0-1+i] = 0;
    }
    for(int i=n0-2; i>=0; i--) update(i);
}
void chmin(int
    a, int b, ll x) {_chmin(x, a-1, b, 0, 0, n0);}
void chmax(int
    a, int b, ll x) {_chmax(x, a-1, b, 0, 0, n0);}
void add_val(int a
    , int b, ll x) {_add_val(x, a-1, b, 0, 0, n0);}
void update_val(int a, int
    b, ll x) {_update_val(x, a-1, b, 0, 0, n0);}
ll query_max(int a
    , int b) {return _query_max(a-1, b, 0, 0, n0);}
ll query_min(int a
    , int b) {return _query_min(a-1, b, 0, 0, n0);}
ll query_sum(int a
    , int b) {return _query_sum(a-1, b, 0, 0, n0);}
};

```

7 Misc

7.1 Total Binary Search [ac23f3]

```

struct TotalBS {
    int Q;
    vector<int> ans;
    TotalBS(int _Q) {
        Q=_Q;
        ans.resize(Q);
    }
    void split(vector<
        int> &qrys, vector<int> &ok, vector<int> &fail) {
        for(auto i : qrys) {
        }
        vector<int>.swap(qrys);
        return;
    }
    void do_things(int l, int mid) {
        return;
    }
    void undo_things(int l, int mid) {
        return;
    }
    void total_BS(int l, int r, vector<int> &qrys) {
        if (l == r) {
            for(auto i : qrys) {
                ans[i] = l;
            }
        }
        int mid = (l + r) / 2;
        do_things(l, mid);
        vector<int> lft, rgt;
        split(qrys, lft, rgt);
        total_BS(mid + 1, r, rgt);
        undo_things(l, mid);
        total_BS(l, mid, lft);
    }
};

```

7.2 CDQ [11f96f]

```

void CDQ(int l, int r) { // 三維偏序
    if (l == r)
        return;
    int mid = (l + r) / 2;
    CDQ(l, mid);
    CDQ(mid + 1, r);
    sort(arr + l, arr + mid + 1, cmpB);
    sort(arr + mid + 1, arr + r + 1, cmpB);
    int i = l;
    int j = mid + 1;
    while (j <= r) {
        while (i <= mid && ue[i].b <= ue[j].b) {
            BIT.Add(arr[i].c, arr[i].cnt);
        }
    }
}

```

```
        i++;
    }
    ue[j].res += BIT.Ask(arr[j].c);
    j++;
}
for (int k = 1; k < i; k++)
    BIT.Add(arr[k].c, -arr[k].cnt);
return;
}
```