Open WebUI – Quick User Guide

This guide explains how to use our local LLMs through **Open WebUI** and through its **OpenAI-compatible API**.

1. Use the models in Open WebUI

1. Open the Open WebUI https://gentl.torus.ai.
2. Sign in with your credentials.
3. Start a **New Chat**.
4. Select the model you want from the **model selector**.
5. Start chatting.

2. Use the models through the API

Open WebUI exposes an **OpenAI-compatible Chat Completions API**. This means you can use the models from applications, scripts, IDEs, automation tools, or other software that supports OpenAI-compatible APIs. First you need to have your API key:

1. In Open WebUI, open your profile menu.
2. Go to **Settings → Account**.
3. Find **API Keys**.
4. Click **Generate New API Key**.

Treat your API key like a password. Do not share it or commit it to Git. The key has the same permissions as your Open WebUI account.

3. Find the available models

You can query the models available to your account by visiting https://gentl.torus.ai/api/models when you are already signed-in or running

```
curl -H "Authorization: Bearer YOUR_API_KEY" \
  https://gentl.torus.ai/api/models
```

Replace:

- `YOUR_API_KEY` with your personal API key.

The response contains the model IDs that you can use in API requests or in the settings of compatible applications.

4. Using local models in OpenAI-compatible applications

If an application asks for:

Setting	Value
Base URL	`https://gentl.torus.ai/api`
API Key	Your Open WebUI API key
Model	A model ID available in Open WebUI https://gentl.torus.ai/api/models

The exact configuration depends on the application.

> **Important:** Some applications expect the OpenAI `/v1` URL structure while Open WebUI's documented chat endpoint is `/api/chat/completions`. If an application does not work with the configuration above, check its documentation for whether it requires a standard `/v1` OpenAI endpoint.

5. Send a chat request manually

The main endpoint is:

```
https://gentl.torus.ai/api/chat/completions
```

Example with `curl`:

```
curl -X POST "https://gentl.torus.ai/api/chat/completions" \
  -H "Authorization: Bearer YOUR_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "model": "MODEL_ID",
    "messages": [
      {
        "role": "user",
        "content": "Tell me a joke."
      }
    ]
  }'
```

Replace `MODEL_ID` with one of the model IDs available in Open WebUI.

Open WebUI's chat endpoint follows the OpenAI Chat Completions format, so existing OpenAI-compatible applications can generally be configured to use it.

Official documentation

Open WebUI Documentation

API Keys

API Endpoints