Customer(customer_id: Integer, birth_date: Date, first_name: String, last_name: String, passport_number: Integer, visa_number: Integer)

Account(account_id: Integer, email: String, account_password: String)
- customer_id is FK reference to Customer

Airport(airport_id: Integer, airport_name: String, flight_type: String)

Airline(airline_id: Integer, airline_name: String)

Aircraft(aircraft_id: Integer, model: String, capacity: String, airline_id: Integer)
- airline_id is FK reference to Airline

Flight(flight_id: Integer, flight_status: String, departure_time: Time, arrival_time: Time, departure_date: Date, arrival_date: Date, trip_type: String, flight_trip_type: String, arrival_location: String, departure_location: String, airline_id: Integer, aircraft_id: Integer, cost: Decimal)
- airline_id is FK reference to Airline
- aircraft_id is FK reference to Aircraft

Baggage(baggage_id: Integer, customer_id: Integer)
- customer_id is FK to Customer

International_flight(flight_id: Integer)
- flight_id FK to Flight

Domestic_flight(flight_id: Integer)
- flight_id FK to Flight

Seat(seat number: Integer, aircraft_id: Integer, flight_id)
- aircraft_id is FK reference to Aircraft
- flight_id is FK reference to flight
- Seat number is partial key

Ticket(ticket_id: Integer, airline_id: Integer, cost: Decimal, flight_class: String, customer_id: Integer, aircraft_id: Integer, seat_number: Integer, flight_id: Integer)
- customer_id is FK reference to Customer
- airline_id is FK reference to Airline
- aircraft_id is FK reference to Seat
- Seat_number, aircraft is FK reference to Seat(seat_number, aircraft_id)

Credit_Card(card_number: Integer, card_type: String)

Payment_info(transaction_id: Integer, airline_id: Integer, card_number: Integer)

- airline_id is FK reference to Airline

—-Relationship tables—
Books(customer_id: Integer, ticket_id: Integer, airline_id: Integer, flight_id: Integer, checkin_status: String, special_requests: String)

- customer_id is FK reference to Customer
- flight_id is FK reference to Flight
- airline_id, ticket_id FK references Ticket(airline_id, ticket_id)

Recieves(ticket_id: Integer, transaction_id: Integer)

- Ticket receives payment info
- ticket_id is FK reference to Ticket
- transaction_id is FK reference to Payment_info
-

Stationed(airline_id: Integer, aiport_id: Integer)

- Where the airplane is stationed at
- airline_id is FK reference to Airline
- airport_id is FK reference to Airport

BaggageOn(baggage_id: Integer, flight_id: Integer, baggage_status: String)

- Baggage_id is FK reference to Baggage(baggage_id)
- flight_id is FK reference to Flight(flight_id)