

## Discovery kit with STM32C011F6 MCU

### Introduction

The **STM32C0116-DK** Discovery kit helps to discover features of the STM32C0 Series microcontroller in a UFQFPN20 package. This Discovery kit features one UFQFPN20 to DIL20 module designed with the **STM32C011F6** microcontroller and allows the user to develop and share applications. It includes an on-board ST-LINK/V2-1 to debug and program the embedded STM32 microcontroller.

The STM32C0116-DK Discovery kit is operated by plugging it into a PC through a standard USB Type-A or USB Type-C® to Micro-B cable.

Figure 1. STM32C0116-DK top view





Figure 2. STM32C0116-DK bottom view



*Pictures are not contractual.*

## 1 Features

- **STM32C011F6** Arm® Cortex®-M0+ core-based microcontroller with 32 Kbytes of flash memory and 6 Kbytes of RAM, in a UFQFPN20 package
- User LED
- Reset push-button
- 5-way joystick using a single ADC input pin
- Individual STM32 UFQFPN20 to DIL20 module
- Board connectors:
  - USB Micro-B
  - DIL20 socket
  - Dedicated LCD footprint
  - Grove (UART)
  - 2 x 10-pin headers for MCU daughterboard
  - Extension connectors
- On-board ST-LINK/V2-1 debugger/programmer with USB re-enumeration capability: mass storage and debug port
- Comprehensive free software libraries and examples available with the STM32Cube MCU Package
- Support of a wide choice of Integrated Development Environments (IDEs) including IAR Embedded Workbench®, MDK-ARM, and STM32CubeIDE

*Note: Arm is a registered trademark of Arm Limited (or its subsidiaries) in the US and/or elsewhere.*



## 2 Ordering information

To order the STM32C0116-DK Discovery kit, refer to [Table 1](#). Additional information is available from the datasheet and reference manual of the target STM32.

**Table 1. Ordering information**

Order code	Board reference	Target STM32
STM32C0116-DK	MB1684	STM32C011F6U6

### 2.1 Codification

The meaning of the codification is explained in [Table 2](#).

**Table 2. Codification explanation**

STM32C0XXY-DK	Description	Example: STM32C0116-DK
STM32C0	MCU series in STM32 32-bit Arm Cortex MCUs	STM32C0 Series
XX	MCU product line in the series	STM32C0x1 product line
Y	STM32 flash memory size: • 6 for 32 Kbytes	32 Kbytes
DK	Discovery kit	Discovery kit

## 3 Development environment

### 3.1 System requirements

- Multi-OS support: Windows® 10, Linux® 64-bit, or macOS®
- USB Type-A or USB Type-C® to Micro-B cable

*Note:* macOS® is a trademark of Apple Inc., registered in the U.S. and other countries and regions.  
Linux® is a registered trademark of Linus Torvalds.  
All other trademarks are the property of their respective owners.

### 3.2 Development toolchains

- IAR Systems® - IAR Embedded Workbench®<sup>(1)</sup>
- Keil® - MDK-ARM<sup>(1)</sup>
- STMicroelectronics - STM32CubeIDE

1. On Windows® only.

### 3.3 Demonstration software

The demonstration software, included in the STM32Cube MCU Package corresponding to the on-board microcontroller, is preloaded in the STM32 flash memory for easy demonstration of the device peripherals in standalone mode. The latest versions of the demonstration source code and associated documentation can be downloaded from [www.st.com](http://www.st.com).

## 4 Conventions

Table 3 provides the conventions used for the ON and OFF settings in the present document.

**Table 3. ON/OFF convention**

Convention	Definition
Jumper JPx ON	Jumper fitted
Jumper JPx OFF	Jumper not fitted
Jumper JPx [1-2]	Jumper fitted between Pin 1 and Pin 2
Solder bridge SBx ON	SBx connections closed by 0 $\Omega$ resistor
Solder bridge SBx OFF	SBx connections left open
Resistor Rx ON	Resistor soldered
Resistor Rx OFF	Resistor not soldered
Capacitor Cx ON	Capacitor soldered
Capacitor Cx OFF	Capacitor not soldered

## 5 Quick start

Before installing and using the product, accept the Evaluation Product License Agreement from the [www.st.com/epl](http://www.st.com/epl) webpage. For more information on the STM32C0116-DK Discovery kit and demonstration software, visit the [STM32C0116-DK](http://www.st.com/stm32c0116-dk) product webpage.

### 5.1 Getting started

Follow the sequence below to configure the Discovery kit and launch the demonstration application (Refer to [Figure 3](#) for component location):

1. Check the JP1 jumper position on the board (Refer to [Table 4](#)).
2. For the correct identification of the device interfaces from the host PC and before connecting the board, install the ST-LINK/V2-1 USB driver, available on the [www.st.com](http://www.st.com) website.
3. To power the board, connect the Discovery kit to a PC with a Type-A to Micro-B USB cable through the CN3 USB connector of the board.
4. Then, the LD1 COM red LED lights up, and the LD3 green LED blinks.
5. The demonstration software, as well as other software examples for exploring features, are available in [STM32C0116-DK](#) product web page.

**Table 4. Jumper configuration**

Jumper	Definition	Position <sup>(1)</sup>	Comment <sup>(1)</sup>
JP1	IDD	<b>ON</b>	For current measurement

1. Default jumper state is in bold.

## 6 Hardware layout and configuration

Figure 3 and Figure 4 show the location of the STM32C0116-DK features. The mechanical dimensions of the board are shown in Figure 5.

### 6.1 PCB layout

**Figure 3. PCB layout (Top view)**






Figure 4. PCB layout (Bottom view)





## 6.2 Mechanical drawing

Figure 5. Board mechanical drawing (In millimeters)



## 6.3 Embedded ST-LINK/V2-1

The embedded ST-LINK/V2-1 supports only the SWD for STM32 devices.

The ST-LINK/V2-1 programming and debugging tool is integrated into the STM32C0116-DK Discovery kit. For information about debugging and programming features, refer to the user manual *ST-LINK/V2 in-circuit debugger/programmer for STM8 and STM32 (UM1075)*, and the technical note *Overview of ST-LINK derivatives (TN1235)*, which describe in detail all the ST-LINK/V2 features.

The additional features supported on the ST-LINK/V2-1 are:

- USB software re-enumeration
- Mass storage interface on USB
- USB power management request for more than 100 mA power on USB

Known limitation:


- Activating the readout protection on the STM32 target prevents the target application from running afterward. The target readout protection must be kept disabled on ST-LINK/V2-1 boards.

### 6.3.1 Drivers

The ST-LINK/V2-1 requires a dedicated USB driver, which, for Windows 7® and Windows 8®, is found at [www.st.com](http://www.st.com). For Windows 10®, it is not necessary to install the driver, as the ST-LINK is automatically identified. In case the STM32C0116-DK Discovery kit is connected to the PC before the driver is installed, some Discovery board interfaces may be declared as “Unknown” in the PC device manager. In this case, the user must install the dedicated driver files, and update the driver of the connected device from the device manager as shown in Figure 6.

**Note:** Prefer using the “USB Composite Device” handle for a full recovery.

Figure 6. USB composite device



### 6.3.2 ST-LINK/V2-1 firmware upgrade

The ST-LINK/V2-1 embeds a firmware upgrade mechanism for the in-situ upgrade through the USB port. As the firmware may evolve during the lifetime of the ST-LINK/V2-1 product (for example new functionalities, bug fixes, support for new microcontroller families), it is recommended to visit the [www.st.com](http://www.st.com) website before starting to use the STM32C0116-DK Discovery kit and periodically, to stay up-to-date with the latest firmware version.

## 6.4 Power supply

The STM32C0116-DK Discovery kit is designed to be powered using the CN3 ST-LINK/V2-1 USB connector.

## 6.5 Board functions

### 6.5.1 LEDs

#### LD1 ST-LINK COM LED

The LD1 green and red bicolor LED provides information about the ST-LINK communication status. LD1 default color is red. LD1 turns green to indicate that the communication is in progress between the PC and ST-LINK, with the following setup:

- Blinking red: The first USB enumeration with the PC is taking place
- Red LED ON: When the initialization between the PC and ST-LINK is complete
- Blinking red or green: During programming and debugging with target
- Orange ON: Communication failure

#### LD3 user LED

This green LED is connected to the PB6 GPIO of the STM32C011F6 microcontroller. To light this LED, a LOW logic state must be written in the corresponding GPIO.

### 6.5.2 Push-buttons

#### B1 Reset/user button

This push-button is connected to NRST (PF2-NRST) and is used to reset the STM32C0 Series microcontroller or to generate a user event.

#### B2 joystick

This joystick is a 5-way rock switch using a single ADC input pin (PA8). Push-in “Select” can be used as a digital user button and EXTI wakeup interrupt. The joystick position for the ADC value refers to [Table 5](#).

**Table 5. Joystick position versus ADC value**

Joystick position	Measurement ratio	ADC value (In volts)
Select	0	0
Left	0.20	0.67
Down	0.40	1.32
Up	0.61	2.01
Right	0.80	2.65
No key pressed	1.0	3.3

### 6.5.3 IDD current consumption measurement

The IDD-labeled JP1 jumper is used to measure the STM32C0 Series microcontroller consumption by removing the jumper and by connecting an ammeter.

- JP1 ON: The STM32C0 Series microcontroller is powered by 3V3 voltage (Default).
- JP1 OFF: An ammeter must be connected to measure the STM32C0 Series microcontroller current. If there is no ammeter, the microcontroller is not powered.

#### 6.5.4 Solder bridges

The solder bridges are located on the top layer of STM32C0116-DK. Their configuration appears in Table 6.

**Table 6. Solder bridge configuration**

Solder bridge control	Solder bridge (SB)	State <sup>(1)</sup>	Description <sup>1</sup>
ST-LINK reset	SB3	ON	ST-LINK in the Reset state
		<b>OFF</b>	ST-LINK in normal operation
VCP interface	SB1/SB2	<b>ON</b>	VCP connect ST-LINK and MCU on board
		OFF	VCP is used as GPIO
AVDD	SB4	ON	VDD provides power to AVDD
		<b>OFF</b>	VDD does not provide power to AVDD

1. Default solder bridge state is in bold

## 7 Board connectors

### 7.1 CN2 DIL20 socket

An STM32 device mounted on a DIL20 module can be programmed or debugged by plugging it into the CN2 socket. The DIL20 socket pinout is detailed in [Table 7](#).

**Table 7. DIL20 socket pinout**

Connector	Pin number	Pin name	Port
CN2	1	PC15-OSCX_OUT	Not used
	3	VDD	Power supply
	5	GND	Ground
	7	PF2-NRST	RESET or USER button
	9	PA0	Not used
	11	PA1	Not used
	13	PA2	Grove_USART2_TX
	15	PA3	Grove_USART2_RX
	17	PA4	LCD_SPI1_NSS
	19	PA5	LCD_SPI1_SCK
	2	PA6	LCD_SPI1_MISO
	4	PA7	LCD_SPI1_MOSI
	6	PA8	Joystick with ADC
	8	PA11 [PA9]	VCP_USART1_TX remap to PA9
	10	PA12 [PA10]	VCP_USART1_RX remap to PA10
	12	PA13	Serial wire debug I/O
	14	PA14-BOOT0	Serial wire clock
	16	PB6	User LED
	18	PB7	Not used
	20	PC14-OSCX_IN	Not used

### 7.2 CN4 Grove connector

The Grove connector is 4 pins UART connector. It is described in [Table 8](#).

**Table 8. Grove connector pinout**

Connector	Pin number	Pin name	Port
CN4	1	PA3	USART2_RX for receiver
	2	PA2	USART2_TX for transmitter
	3	VDD	3.3 V power supply
	4	GND	Ground

### 7.3 CN1/CN5 extension connectors

The silkscreen morpho extension connectors are available on the STM32C0116-DK Discovery kit to support flexibility in user applications. It is described in [Table 9](#).

Table 9. CN1/CN5 extension connectors

Connector	Pin number	Pin name	Port
CN1	1	VDD	-
	2	GPIO	PA2
	3	NC	-
	4	GND	-
CN5	1	NC	-
	3	NC	-
	5	NC	-
	7	AVDD	-
	9	GND	-
	11	GPIO	PA7
	13	GPIO	PA4
	15	GPIO	PA8
	17	NC	-
	19	GPIO	PC14
	21	GPIO	PA1
	23	GPIO	PA0
	25	NC	-
	27	NC	-
	29	NC	-
	31	NC	-
	33	GPIO	PB6
	35	NC	-
	37	NC	-
	2	GPIO	PC15
	4	GPIO	PB7
	6	GPIO	PA9
	8	5V	-
	10	NC	-
	12	NC	-
	14	NC	-
	16	GPIO	PA6
	18	GPIO	PA3
	20	GND	-
	22	NC	-
	24	NC	-
	26	GPIO	PA5
	28	NC	-
	30	NC	-
	32	GND	-
	34	GPIO	PA10
	36	NC	-
	38	NC	-

## 7.4 U1 LCD connector

The LCD connector is a footprint for the NHD-C0216CZ-FSW-FBW-3V3 LCD. It is described in [Table 10](#).

**Table 10. LCD connector**

Connector	Pin number	Pin name	Port
U1	1	NRST	Reset signal
	2	PA6	LCD_SPI1_MISO for the register select signal
	3	PA4	LCD_SPI1_NSS for the chip select signal
	4	PA5	LCD_SPI1_SCK for the serial clock
	5	PA7	LCD_SPI1_MOSI for the data serial input
	6	GND	Ground
	7	VDD	3.3V power supply
	8	VOUT	DC/DC voltage converter
	9	C1+	Voltage booster circuit
	10	C1-	Voltage booster circuit
	A	A	No connection
	K	K	No connection

## 8 STM32C011F6 I/O assignment

The STM32C011F6 pin-out can be directly transposed to the DIL20 module pin-out, as shown in [Table 11](#).

**Table 11. STM32C011F6 I/O assignment**

Pin number	Pin name	Description
1	PC15-OSCX_OUT	Not used
2	VDD	Power supply
3	VSS	Ground
4	PF2-NRST	RESET or USER button
5	PA0	Not used
6	PA1	Not used
7	PA2	Grove_USART2_TX
8	PA3	Grove_USART2_RX
9	PA4	LCD_SPI1_NSS
10	PA5	LCD_SPI1_SCK
11	PA6	LCD_SPI1_MISO
12	PA7	LCD_SPI1_MOSI
13	PA8	Joystick with ADC
14	PA11 [PA9]	VCP_USART1_TX remap to PA9
15	PA12 [PA10]	VCP_USART1_RX remap to PA10
16	PA13	Serial wire debug I/O
17	PA14-BOOT0	Serial wire clock
18	PB6	User LED
19	PB7	Not used
20	PC14-OSCX_IN	Not used



## 9 STM32C0116-DK board information

### 9.1 Product marking

The stickers located on the top or bottom side of the PCB provide product information:

- Product order code and product identification for the first sticker
- Board reference with revision, and serial number for the second sticker

On the first sticker, the first line provides the product order code, and the second line the product identification.

On the second sticker, the first line has the following format: "MBxxxx-Variant-yyz", where "MBxxxx" is the board reference, "Variant" (optional) identifies the mounting variant when several exist, "y" is the PCB revision and "zz" is the assembly revision, for example B01. The second line shows the board serial number used for traceability.

Evaluation tools marked as "ES" or "E" are not yet qualified and therefore not ready to be used as reference design or in production. Any consequences deriving from such usage will not be at ST charge. In no event, ST will be liable for any customer usage of these engineering sample tools as reference designs or in production.

"E" or "ES" marking examples of location:

- On the targeted STM32 that is soldered on the board (For an illustration of STM32 marking, refer to the STM32 datasheet "Package information" paragraph at the [www.st.com](http://www.st.com) website).
- Next to the evaluation tool ordering part number that is stuck or silk-screen printed on the board.

Some boards feature a specific STM32 device version, which allows the operation of any bundled commercial stack/library available. This STM32 device shows a "U" marking option at the end of the standard part number and is not available for sales.

In order to use the same commercial stack in his application, a developer may need to purchase a part number specific to this stack/library. The price of those part numbers includes the stack/library royalties.

### 9.2 STM32C0116-DK product history

#### 9.2.1 Product identification DK32C0116\$KU1

This product identification is based on the MB1684 revision B-01 board.

It embeds the [STM32C011F6U6](#) microcontroller with revision code "A". The limitations of this revision are detailed in the errata sheet *STM32C011 device errata* ([ES0569](#)).

#### Product limitations

No limitation identified for this product identification.

### 9.3 Board revision history

#### 9.3.1 Board MB1684 revision B-01

The revision B-01 is the initial release of the MB1684 board.

#### Board limitation

No limitation identified for this board revision.

## 10 Federal Communications Commission (FCC) and Innovation, Science and Economic Development Canada (ISED) Compliance Statements

### 10.1 FCC Compliance Statement

#### Part 15.19

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### Part 15.21

Any changes or modifications to this equipment not expressly approved by STMicroelectronics may cause harmful interference and void the user's authority to operate this equipment.

#### Part 15.105

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception which can be determined by turning the equipment off and on, the user is encouraged to try to correct interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

*Note: Use only shielded cables.*

#### Responsible party (in the USA)

Terry Blanchard  
Americas Region Legal | Group Vice President and Regional Legal Counsel, The Americas  
STMicroelectronics, Inc.  
750 Canyon Drive | Suite 300 | Coppel, Texas 75019  
USA  
Telephone: +1 972-466-7845

### 10.2 ISED Compliance Statement

This device complies with FCC and ISED Canada RF radiation exposure limits set forth for general population for mobile application (uncontrolled exposure). This device must not be collocated or operating in conjunction with any other antenna or transmitter.

#### Compliance Statement

Notice: This device complies with ISED Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

ISED Canada ICES-003 Compliance Label: CAN ICES-3 (B) / NMB-3 (B).

**Déclaration de conformité**

Avis: Le présent appareil est conforme aux CNR d'ISDE Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Étiquette de conformité à la NMB-003 d'ISDE Canada : CAN ICES-3 (B) / NMB-3 (B).

## Revision history

**Table 12. Document revision history**

Date	Revision	Changes
16-Feb-2022	1	Initial release.

## Contents

<b>1</b>	<b>Features</b>	<b>2</b>
<b>2</b>	<b>Ordering information</b>	<b>3</b>
2.1	Codification	3
<b>3</b>	<b>Development environment</b>	<b>4</b>
3.1	System requirements	4
3.2	Development toolchains	4
3.3	Demonstration software	4
<b>4</b>	<b>Conventions</b>	<b>5</b>
<b>5</b>	<b>Quick start</b>	<b>6</b>
5.1	Getting started	6
<b>6</b>	<b>Hardware layout and configuration</b>	<b>7</b>
6.1	PCB layout	7
6.2	Mechanical drawing	9
6.3	Embedded ST-LINK/V2-1	10
6.3.1	Drivers	10
6.3.2	ST-LINK/V2-1 firmware upgrade	10
6.4	Power supply	10
6.5	Board functions	11
6.5.1	LEDs	11
6.5.2	Push-buttons	11
6.5.3	IDD current consumption measurement	11
6.5.4	Solder bridges	12
<b>7</b>	<b>Board connectors</b>	<b>13</b>
7.1	CN2 DIL20 socket	13
7.2	CN4 Grove connector	13
7.3	CN1/CN5 extension connectors	13
7.4	U1 LCD connector	15
<b>8</b>	<b>STM32C011F6 I/O assignment</b>	<b>16</b>
<b>9</b>	<b>STM32C0116-DK board information</b>	<b>17</b>
9.1	Product marking	17
9.2	STM32C0116-DK product history	17
9.2.1	Product identification DK32C0116\$KU1	17
9.3	Board revision history	17
9.3.1	Board MB1684 revision B-01	17

---

<b>10</b>	<b>Federal Communications Commission (FCC) and Innovation, Science and Economic Development Canada (ISED) Compliance Statements .....</b>	<b>18</b>
10.1	FCC Compliance Statement .....	18
10.2	ISED Compliance Statement .....	18
<b>Revision history .....</b>		<b>20</b>
<b>List of tables .....</b>		<b>23</b>
<b>List of figures .....</b>		<b>24</b>

## List of tables

<b>Table 1.</b>	Ordering information . . . . .	3
<b>Table 2.</b>	Codification explanation . . . . .	3
<b>Table 3.</b>	ON/OFF convention . . . . .	5
<b>Table 4.</b>	Jumper configuration . . . . .	6
<b>Table 5.</b>	Joystick position versus ADC value . . . . .	11
<b>Table 6.</b>	Solder bridge configuration . . . . .	12
<b>Table 7.</b>	DIL20 socket pinout . . . . .	13
<b>Table 8.</b>	Grove connector pinout . . . . .	13
<b>Table 9.</b>	CN1/CN5 extension connectors . . . . .	14
<b>Table 10.</b>	LCD connector . . . . .	15
<b>Table 11.</b>	STM32C011F6 I/O assignment . . . . .	16
<b>Table 12.</b>	Document revision history . . . . .	20

## List of figures

<b>Figure 1.</b>	STM32C0116-DK top view . . . . .	1
<b>Figure 2.</b>	STM32C0116-DK bottom view . . . . .	1
<b>Figure 3.</b>	PCB layout (Top view) . . . . .	7
<b>Figure 4.</b>	PCB layout (Bottom view) . . . . .	8
<b>Figure 5.</b>	Board mechanical drawing (In millimeters) . . . . .	9
<b>Figure 6.</b>	USB composite device. . . . .	10



**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved