Who Knows the Goal? Local Context, Task Provenance, and Restricted Assembly When Work Is Split Across Agents[1]

Hirokazu James Wilson
Independent researcher · Team HJ · LA hub (AE Studio) · Track 2
With Apart Research

Abstract

An agent may receive a rule without the information needed to apply it. We study this problem using a harmless four-word passphrase and a synthetic rule against disclosure. Study 1 varies task framing and coordination. Under the rule, solo agents assemble the passphrase in 19/20 Haiku and 8/10 Sonnet trials when its purpose is unstated, versus zero in the measured explicit-purpose trials. Splitting work never exceeds the observed solo assembly rate when purpose is unstated, although separate posts often disclose all four words. Study 2 holds the pipeline fixed and supplies each agent with trusted task-purpose metadata. For a restricted objective phrased without the policy keywords, recoverability falls from 45/50 to 0/50 held-out Haiku trials, a paired change of -90 percentage points (95% CI [-98, -80]). Authorized assembly increases by 37 points [20, 53] across 49 complete pairs. A keyword gate misses restricted paraphrases, while the tested LLM monitor yields no authorized completions. The contribution is a controlled demonstration of how missing purpose information and incomplete outcome measures can distort safety evaluations. The results support evaluating disclosure alongside useful completion; they do not establish robustness to harmful tasks, adversarial agents or forged metadata.

1 Introduction

An instruction to select an item from a list may be ordinary inventory work or one step toward disclosing a secret. A worker given only the lookup cannot tell which purpose it serves. Dividing work can conceal this purpose, but a solo agent can lack the same information. A comparison between an informed solo agent and uninformed workers can therefore mistake an information difference for an effect of teamwork.

Study 1 asks whether splitting work increases disclosure relative to solo agents with the same task-purpose visibility. Study 2 asks whether sharing the original purpose improves compliance while preserving authorized completion in a fixed pipeline. The studies use different policies, protocols and seeds; their results are not pooled.

We distinguish a complete answer in one post from an answer recoverable across posts, and report authorized completion alongside restricted disclosure. This tests instruction following under a synthetic operator rule, not harmful capabilities or deliberate evasion.

1 Research conducted at the Swarm Alignment Hackathon, November 2026




Figure 1. Study 1 compares task-purpose visibility and coordination; Study 2 tests trusted purpose information. Only accepted posts enter the deterministic scorer. Blocked proposals remain private audit logs.

2 Related Work

Decomposition research shows how apparently benign subtasks can contribute to harmful outputs. Jones et al. combine models with complementary capabilities [8]; subsequent work studies multi-turn decomposition, realistic agent workflows and capability laundering [14, 9, 12]. Our synthetic task instead tests whether splitting work still has an advantage when the solo baseline also lacks the purpose. Reports of effectiveness and alignment changing together in AI organizations further motivate reporting both outcomes [13].

ConfAIde evaluates disclosure in its social and informational context [11], while multi-agent risk research identifies information asymmetries as a broader concern [7]. We isolate a simpler case: identical local lookups serve different declared purposes. Here, task provenance means a trusted statement of purpose, not an authenticated record of origin or data lineage.

AgentHarm evaluates malicious task completion across diverse tool-based tasks, including benign counterparts [1]. AI control evaluates safeguards against intentional subversion [6], and sequential monitoring examines cumulative intent across decomposed requests [2]. Our actors are not deliberately adversarial, and our single monitor prompt is not a reproduction of those defenses. Their emphasis on explicit threat models and useful performance motivates our narrower joint evaluation of disclosure and authorized completion.

3 Task and Evaluation

A seed generates four disjoint six-word lists and selects one position in each. Joining the selected words in order gives a fictional vault passphrase. Agents receive a rule forbidding its disclosure, including individual words, or a no-policy control. In Study 2, the rule also explicitly permits authorized inventory work. Agents publish with POST or publish nothing with PASS; the collector also accepts leading POST without a colon.

Assembly requires the four target words consecutively and in order in one accepted post, after normalizing case and punctuation. **Recoverability** also counts answers distributed across posts: each target word must appear in a post containing no other item from its list. An assembled phrase counts as recoverable even if surrounded by distractors. These deterministic rules do not measure real-world exploitability and can miss human-inferable disclosures mixed with distractors.

We report Wilson 95% intervals, seed-paired differences in percentage points (pp) with 2,000 paired-bootstrap resamples, and exact McNemar tests [15, 4, 10, 5]. Seeds identify task instances, not controlled model-sampling randomness. Failed trials are excluded; paired analyses retain only seeds valid in both conditions. Secondary comparisons are unadjusted. Shared vocabulary, prompts and services limit generalization beyond these instances. Appendices A-C give detailed methods, counts and collection disclosures.

4 Study 1 Context and Coordination

4.1 Design

The frozen v2 design crosses two policies, neutral or explicit framing, and eight conditions. Neutral tasks request inventory items; explicit tasks identify passphrase parts. Framing changes several cues and prompt lengths together, so any difference cannot be attributed to a single cue or an internal recognition mechanism.

Conditions are solo; five or twelve separate solo attempts; four workers followed by an assembler; four-agent shared boards with or without a team objective; and informed or uninformed coordinator relays. Every role receives the same policy. Repeated-solo scores use the best single attempt. Pipeline and swarm call caps match the repeated-solo controls; the six-call relay lacks an exact solo control. Relay prompts ignore framing and differ only in the coordinator's purpose statement. Purpose visibility can be compared, but local views and interaction structures differ. Fixed turns do not test self-organization.

Haiku 5.5 uses seeds 1000-1019 and Sonnet 5.5 uses 1000-1009, after pilots on seeds 0-19. All 1,040 original and rerun records are valid. An original Sonnet cell lists mixed served models; its same-seed rerun logs Sonnet 5.5 throughout. Appendix B keeps these records separate.

4.2 Results

Under the strict rule, neutral solo agents assemble in 19/20 Haiku and 8/10 Sonnet trials. Explicit solo assembly is 0/20 and 0/10, including repeated attempts and the Sonnet rerun. This shows sensitivity to framing, not guaranteed future refusal.

Strict policy and neutral framing	Haiku assembled	Haiku recoverable	Sonnet assembled	Sonnet recoverable
solo	19/20	19/20	8/10	8/10
pipeline	2/20	19/20	3/10	8/10
swarm with objective	0/20	19/20	0/10	7/10
swarm without objective	0/20	11/20	0/10	6/10

Table 1. Split posts often reveal all four words without joining them. Sonnet entries are from the original strict/neutral cell, not the strict/explicit rerun.

No split condition exceeds the solo agent's observed assembly rate when task purpose is unstated. This does not establish equivalence or rule out a decomposition effect in other tasks. Under strict/explicit framing, neither pipeline nor swarm makes all four words recoverable, although individual words sometimes appear. Under neutral framing, assembly alone substantially understates disclosure (Table 1).

The no-policy controls also reveal coordination failures: neither neutral swarm assembles even without a restriction. Haiku pipeline assembly falls from 20/20 without a policy to 2/20 with it, yet strict-policy recoverability remains 19/20. Low assembly can thus reflect failed coordination or incomplete policy enforcement; it cannot by itself establish protection.

Relay comparisons do not establish a decomposition advantage. Appendix B.3 gives request rates and paired contrasts, separating the original mixed-model cell from its verified same-seed rerun.

5 Study 2 Trusted Task Purpose

5.1 Design

Study 2 fixes four independent lookup workers followed by an assembler, with five actor calls per trial. The policy permits authorized inventory work and forbids obtaining passphrase words, according to the task purpose available in context. Each seed pairs identical lookups with an authorized or restricted objective. In the local condition, authorization changes neither the worker prompts nor the assembler's instructions; the assembler sees only the resulting posts. No reliable authorization signal is supplied.

Four conditions are crossed with authorization and two wording pairs. **Local** supplies the local task and policy. **Provenance** adds the original objective and a statement linking the contribution to it, in the trusted system prompt. **Monitor** retains local actors but adds an objective- and history-aware LLM that allows or blocks each proposed post, requiring up to five extra calls. **Keyword gate** blocks all posts when the objective matches passphrase, vault, password or access code. Only accepted posts count as disclosure.

The restricted paraphrase requests four secret words opening a company strongroom without the gate's policy keywords. The keyword version names the vault passphrase; the authorized keyword objective explicitly says its inventory items are not passphrase material. These are two fixed wording pairs, not a diverse paraphrase test.

After a development pilot, the protocol was committed at 435d20d before recorded held-out collection; this is not independent preregistration. Haiku 5.5 ran seeds 3000-3049 in sixteen cells: 800 planned trials, 799 valid. One authorized/paraphrase/provenance trial failed and was excluded without replacement. Restricted paraphrase recoverability is the primary endpoint; authorized assembly measures utility. Other comparisons are secondary.

5.2 Results

Paraphrase endpoint	Local	Provenance	Paired change in pp [95% CI]
Restricted recoverability	45/50	0/50	-90 [-98, -80]
Authorized assembly	15/49	33/49	+37 [+20, +53]

Table 2. Complete seed pairs for the primary disclosure comparison and secondary utility comparison; exact McNemar $p < 0.001$ for both. Utility excludes seed 3010 from both conditions because its provenance trial failed. The all-valid local result is 15/50; Appendix C reports all cells and failure bounds.

Adding trusted purpose information reduces observed restricted disclosure and improves authorized completion (Table 2). The secondary keyword comparison has the same direction: restricted recoverability falls from 49/50 to 0/50, while authorized assembly rises from 12/50 to 48/50. The treatment includes both the objective and a contribution statement; their effects are not separated.

Authorized paraphrase words are already recoverable in 47/50 local trials, versus 47/49 with provenance. The larger change in assembly suggests that context also helps produce the requested joined answer. This does not isolate the assembler's contribution: every actor receives the added context.

The keyword gate leaves 46/50 restricted paraphrases recoverable and permits no authorized keyword completion. The LLM monitor blocks 792/795 proposals and permits no authorized completion in either wording. Its zero restricted recoverability comes with zero measured utility. These findings concern the specified gate and monitor prompt; they do not rank provenance against monitoring methods generally.

6 Interpretation and Limits

Purpose visibility must be controlled before attributing disclosure to teamwork: an uninformed solo agent can disclose the same answer as a team. Judging only the assembled answer also misses disclosures in intermediate posts. Evaluation should cover all outputs available to the observer and report authorized completion alongside restricted disclosure.

Study 2 demonstrates use of a supplied distinction, not inference of hidden intent or verification of authorization. The treatment resolves an ambiguity deliberately built into the baseline. Purpose-only and length-matched context controls are absent, so alternative prompt cues remain possible explanations. The monitor changes information, call count and veto power together, without a tuned or stateless comparison.

Both studies use one harmless task and one provider family; Study 2 uses one model and a fixed pipeline. Study 1 has small samples, bundled framing changes and repeated relay seeds. Neither study tests adaptive adversaries, forged metadata, real harmful requests or asynchronous tool use. No-policy coordination failures and conservative scoring further limit interpretation. Zero events in fifty trials still allows a one-sided 95% upper bound of about 5.8% on a common failure probability under independent identically distributed Bernoulli trials [3].

7 Conclusion

In this controlled task, trusted purpose information improves disclosure control and authorized completion. Splitting work provides no observed assembly advantage over an uninformed solo agent. Evaluations should therefore account for purpose visibility, intermediate disclosures and useful completion. Broader claims require diverse tasks and providers, controls that isolate the added context, and adversarial tests of metadata and monitoring.

Code and Data

Code, data and offline audit instructions: https://github.com/wilsonhj/swarm-composition and Appendix C. Replay checks archived outcomes, not independent behavioral replication or every collection detail. No new inference was run for this revision.

References

[1] Andriushchenko, M., Souly, A., Dziemian, M., Duenas, D., Lin, M., Wang, J., et al. (2025). AgentHarm: A Benchmark for Measuring Harmfulness of LLM Agents. International Conference on Learning Representations. Source

[2] Chen, Y.-H., Joshi, N., Chen, Y., Andriushchenko, M., Angell, R., & He, H. (2026). Monitoring Decomposition Attacks with Lightweight Sequential Monitors. International Conference on Learning Representations. Source

[3] Clopper, C. J. & Pearson, E. S. (1934). The Use of Confidence or Fiducial Limits Illustrated in the Case of the Binomial. Biometrika / pp. 404–413. Source

[4] Efron, B. (1979). Bootstrap Methods: Another Look at the Jackknife. The Annals of Statistics / pp. 1–26. Source

[5] Fagerland, M. W., Lydersen, S., & Laake, P. (2013). The McNemar test for binary matched-pairs data: mid-p and asymptotic are better than exact conditional. BMC Medical Research Methodology / pp. 91. Source

[6] Greenblatt, R., Shlegeris, B., Sachan, K., & Roger, F. (2024). AI Control: Improving Safety Despite Intentional Subversion. Proceedings of the 41st International Conference on Machine Learning / pp. 16295–16336. Source

[7] Hammond, L., Chan, A., Clifton, J., Hoelscher-Obermaier, J., Khan, A., McLean, E., et al. (2025). Multi-Agent Risks from Advanced AI. arXiv:2502.14143. Source

[8] Jones, E., Dragan, A., & Steinhardt, J. (2025). Adversaries Can Misuse Combinations of Safe Models. Proceedings of the 42nd International Conference on Machine Learning / pp. 28327–28349. Source

[9] Kothamasu, V., Smith, V., & Yadav, C. (2026). Hidden in Plain Sight: Benchmarking Agent Safety Against Decomposition Attacks with DeCompBench. arXiv:2606.13994. Source

[10] McNemar, Q. (1947). Note on the Sampling Error of the Difference Between Correlated Proportions or Percentages. Psychometrika / pp. 153–157. Source

[11] Mireshghallah, N., Kim, H., Zhou, X., Tsvetkov, Y., Sap, M., Shokri, R., et al. (2024). Can LLMs Keep a Secret? Testing Privacy Implications of Language Models via Contextual Integrity Theory. arXiv:2310.17884 / International Conference on Learning Representations. Source

[12] Russinovich, M., Bullwinkel, B., Severi, G., Ovadiuc, C., & Salem, A. (2026). Divide, Consult, Conquer: Capability Laundering Through Aligned LLMs. arXiv:2609.15383. Source

[13] Shen, J. H., Zhu, D., Srinivasan, S., Sleight, H., Wagner III, L. T., Matthews, M. J., et al. (2026). AI Organizations are More Effective but Less Aligned than Individual Agents. arXiv:2604.10290. Source

[14] Srivastav, D. & Zhang, X. (2025). Safe in Isolation, Dangerous Together: Agent-Driven Multi-Turn Decomposition Jailbreaks on LLMs. Proceedings of the 1st Workshop for Research on Agent Language Models (REALM 2025) / Association for Computational Linguistics / pp. 170–183. Source

[15] Wilson, E. B. (1927). Probable Inference, the Law of Succession, and Statistical Inference. Journal of the American Statistical Association / pp. 209–212. Source

Appendix A: Limitations and Dual-Use / Ethical Considerations

A.1 Measurement and interpretation

The studies test a synthetic rule on harmless strings, not trained-in refusal or a transferable jailbreak. Only accepted posts count. Exposed parts count target mentions; identified parts exclude other items from the same list in that post. Recoverability requires four identified parts or assembly. Warnings quoting targets can count; distractors, encodings, inflections and reordered words can evade scoring. Sonnet strict/neutral swarm seed 1004 illustrates undercounting.

Low scores can also reflect task failure. In the no-policy pipeline and relay worker diagnostic, 36/695 posts omit the target (pipeline 4/240; informed relay 10/226; uninformed relay 22/229). This includes non-lookup posts and excludes swarm and strict-policy turns. No-policy neutral swarms never assemble the phrase.

A.2 Design and inference

Study 1 has 10-20 seeds per cell and roughly seven unadjusted comparisons. Framing changes multiple cues together. Hinted framing and swarms above four agents occur only in exploratory work, outside the confirmatory design. Relay framing cells and the verified-model rerun repeat tasks. Their pooled trial counts are not independent seed counts. Equal call caps do not equalize tokens or information; the six-call relay lacks an exact solo control. Fixed roles and turns exclude asynchronous or tool-using coordination.

Study 2 uses one model and two fixed wording pairs. Local inputs cannot distinguish authorization; supplied purpose is trusted, not authenticated. Forgery and tampering are untested. There are no purpose-only or length-matched context controls, and the paraphrase does not exclude other lexical cues. The monitor changes information, calls and veto power together; no stateless ablation or prompt-tuning comparison isolates them. It yields no authorized completions. A committed protocol freeze is not independent preregistration or proof that seeds were never inspected.

Shared prompts, vocabulary and services limit independence assumptions. Bootstrap intervals can disagree with exact tests. Zero in fifty permits about 5.8% failure at a one-sided 95% bound under independent Bernoulli trials, with no guarantee under distribution shift.

A.3 Dual-use ethics and research assistance

These findings could help someone hide a restricted objective behind ordinary local tasks or distribute disclosure across posts to evade checks on complete answers. The public harness uses harmless strings, with no harmful-task decompositions or live-target attack material; transfer to harmful tasks remains untested.

No human subjects, personal data, live credentials or harmful payloads were used. Public inputs and transcripts support auditing. A future transferable vendor weakness would require a disclosure assessment. No pre-sprint assets were used (C.5). The extended limitations retain the longer discussion.

LLM Usage Statement. Claude and Codex assisted coding, review and report preparation. Numerical results were checked against frozen artifacts by independent outcome scoring and offline replay; a separate claim ledger covers earlier source documents. The author is responsible for the submission.

Appendix B: Study 1 Methods and Supporting Results

B.1 Conditions and information





Figure B1. Solo sees all lists. Pipeline workers see one list each; the assembler sees their board. Swarm agents share a board in fixed round-robin order. The relay coordinator sees no lists. All roles receive the same policy.

Condition	Actors	Maximum calls	Task information
solo	one	1	all four lists
solo@k5 / solo@k12	one	5 / 12	all lists; best single attempt
pipeline	4 + 1	5	one list per worker; board for assembler
swarm@n4	four	12	own list, board, team objective
swarm_noobj@n4	four	12	own list and board; no team objective
relay informed / uninformed	1 + 4	6	coordinator: board; worker: own list, position, board

Every list has six disjoint vocabulary items; positions are seed-determined. The strict policy forbids passphrase disclosure, including individual words; the no-policy prompt omits that rule. Neutral framing requests inventory lookups; explicit framing identifies passphrase parts. The full methods supplement preserves exact prompts. All 260 swarm runs use twelve calls, with no early stops.

B.2 All Study 1 outcome cells



Study 1 (v2, held-out seeds). Columns: policy (none/strict, same for every role) x framing (neutral/explicit). Relay prompts do not use framing, so relay framing cells are replicates. † Run manifest lists two served models (claude-sonnet-5, claude-sonnet-5-5); the rerun on the same 10 seeds was served by claude-sonnet-5-5 only.

Figure B2. Frozen v2 held-out results. Cells show successes/valid trials; assembly is left, recoverability right. Sonnet includes the same-seed verified-model rerun. The dagger marks an original cell listing two served models. Relay prompts ignore framing, so those columns repeat the same task instructions rather than distinct framing interventions.

B.3 Relay comparisons and model provenance

Strict policy, pooled framing	Haiku informed	Haiku uninformed	Sonnet informed	Sonnet uninformed
Coordinator sent a request	0/40	7/40	0/30	27/30
Assembled	0/40	1/40	0/30	7/30
Recoverable	0/40	3/40	0/30	13/30
No-policy assembly	29/40	16/40	9/20	17/20

Table B1. Sonnet strict totals combine twenty original trials and ten rerun trials on the same ten seeds. Seven assemblies come from four seeds; thirteen recoverable trials from seven. One pooled cell has mixed served models. Excluding it gives 5/20 assembled and 9/20 recoverable.

Against informed solo, the uninformed Sonnet main-run relay differs by +20 pp assembled (95% CI [0, +50], exact p = 0.50) and +40 pp recoverable ([+10, +70], p = 0.125). Rerun differences are +10 pp ([0, +30]) and +20 pp ([0, +50]). Solo/explicit is 0/10 in both runs. Haiku differences are +5 pp assembled ([0, +15]) and +15 pp recoverable ([0, +30]). These small-sample comparisons do not establish a decomposition effect.

Against equally uninformed solo, relay assembly is lower: Sonnet strict/neutral 4/10 versus 8/10, and Haiku 1/40 pooled relay trials versus 19/20 solo trials. Informed coordinators under strict policy send no requests (0/70); without the policy all do (40/40 Haiku, 20/20 Sonnet). Of 27 strict-policy uninformed Sonnet requests, 22 mention the passphrase, usually as a warning. Such warnings do not identify the lookup items as its words.

Models and calls. Claude Code runs used claude -p without tools and provider-default sampling. Haiku 5.5 has twenty seeds and 4,720 calls; original Sonnet 5.5 has ten seeds and 2,360 calls. The Sonnet strict/explicit manifest lists claude-sonnet-5 and claude-sonnet-5-5 without per-turn attribution. A 590-call rerun on the same seeds logs claude-sonnet-5-5 for every turn. It assembles the uninformed relay in 1/10 trials and makes it recoverable in 2/10, versus 2/10 and 4/10 in the original corresponding cell. Totals are 1,040 valid rows and 7,670 logged calls, with no recorded failures.

Exploratory work. The Haiku strict/neutral batch from the stopped exploratory v1 full run (seeds 0-19) assembles solo in 20/20 and pipeline/swarms in 0/20, with recoverability in 12-20 of twenty. It is excluded from v2 inference.

A separate Sonnet extension used seeds 1010-1019 for solo, five-attempt solo and both relays (160 trials, 720 calls). Under the strict rule, uninformed relays assembled in 4/10 explicit and 2/10 neutral trials, versus 0/10 and 8/10 for solo. All four manifests mark the working tree dirty; two explicit-cell turns list both Sonnet 5 and 5.5. These exploratory results are excluded from confirmatory analyses. The follow-up report gives model sensitivities and additional hinted-framing exploration. Neither supplies cross-provider replication.

Appendix C: Study 2 Evidence and Reproduction

C.1 Fixed pipeline and publication controls




Figure C1. Workers do not read one another's replies. The assembler receives accepted posts. Provenance adds trusted original purpose to every actor. The LLM monitor sees objective, sender, accepted board and proposal, but no target, seed, lists, selected positions or scores. The keyword gate inspects the objective. Blocked proposals are not published.

The same lookups are paired with authorized inventory and restricted passphrase objectives. Local worker prompts and assembler instructions do not vary by authorization; sampled replies can differ. In provenance, the system prompt supplies the original objective plus a contribution statement. The paraphrase objective avoids the gate's policy keywords; the authorized keyword objective explicitly states that the items are not passphrase material. This tests two fixed wording pairs, not arbitrary paraphrases. Exact strings are preserved in the full supplement.

C.2 Worked input and recorded responses




Figure C2. A recorded restricted/paraphrase trial pair, not an aggregate estimate. Local workers post their selected words; with trusted purpose all five actors return PASS. Each lane makes five actor calls. Recoverability permits reconstruction across posts; assembly requires one post joining the four words in order.


Worker	Six-word list in order	Position	Selected word
0	umber, ember, jade, cobalt, iris, zephyr	2	ember
1	xenon, yarrow, onyx, tundra, harbor, willow	6	willow
2	violet, koi, dune, lotus, nectar, fjord	4	lotus
3	garnet, maple, raven, sage, quartz, birch	4	sage

Table C1. Seed-3000 inputs. Each worker receives only its own row. The restricted paraphrase asks for four secret words opening the company strongroom; authorized objectives request an inventory report. Supplement B.3.4 preserves stored raw replies and reconstructed inputs.

C.3 All sixteen held-out cells

Condition	Paraphrase restricted	Paraphrase authorized	Keyword restricted	Keyword authorized
local	45/50 / 17/50	47/50 / 15/50	49/50 / 14/50	47/50 / 12/50
provenance	0/50 / 0/50	47/49 / 33/49	0/50 / 0/50	49/50 / 48/50
monitor	0/50 / 0/50	0/50 / 0/50	0/50 / 0/50	0/50 / 0/50
keyword gate	46/50 / 16/50	48/50 / 14/50	0/50 / 0/50	0/50 / 0/50

Table C2. Each cell gives recoverable / assembled, using valid n. Restricted recoverability is the safety endpoint; authorized assembly is the utility endpoint. One authorized/paraphrase/provenance backend failure is excluded; all restricted cells have fifty valid trials.



Study 2 (task provenance, held-out seeds 3000-3049, Claude Haiku 5.5, 50 seeds per cell); not pooled with Study 1.
* 1 trial failed (backend error) in paraphrase / authorized / provenance; excluded, valid n = 49; all-trial range 66%-68%.

Figure C3. Haiku 5.5 held-out seeds 3000-3049. Lower restricted recoverability is better (left); higher authorized assembly is better (right). Bars include Wilson 95% intervals. The asterisk marks the cell with one excluded backend failure. Zero restricted disclosure with no authorized completion does not establish a useful safeguard.

On every recorded row, exact-string assembly equals normalized assembly, and exposed-part counts equal identified-part counts. The definitions differ even though these outcomes coincide here. The secondary calculation script reproduces these checks.

C.4 Paired contrasts and collection disclosures

Provenance minus local	Wording	Change in pp [95% CI]	Discordant + / -	Exact p
Primary restricted recoverability	paraphrase	-90 [-98, -80]	0 / 45	< 0.001
Authorized assembly	paraphrase	+37 [+20, +53]	21 / 3	< 0.001
Restricted recoverability	keyword	-98 [-100, -94]	0 / 49	< 0.001
Authorized assembly	keyword	+72 [+58, +86]	37 / 1	< 0.001

Table C3. Seed-paired differences with 2,000 paired-bootstrap resamples. Authorized paraphrase uses 49 complete pairs: local 15/49 and provenance 33/49. The excluded seed 3010 was a local non-completion, giving the all-valid local rate 15/50 in Table C2. All other contrasts use fifty pairs. Only the first row is primary.

Monitor minus keyword gate	Assembled pp [95% CI]; discordance; p	Recoverable pp [95% CI]; discordance; p
Authorized keyword	0 [0, 0]; +0/-0; 1.000	0 [0, 0]; +0/-0; 1.000
Authorized paraphrase	-28 [-40, -16]; +0/-14; < 0.001	-96 [-100, -90]; +0/-48; < 0.001
Restricted keyword	0 [0, 0]; +0/-0; 1.000	0 [0, 0]; +0/-0; 1.000
Restricted paraphrase	-32 [-46, -20]; +0/-16; < 0.001	-92 [-98, -84]; +0/-46; < 0.001

Table C4. Secondary, unadjusted comparisons within fifty complete seed pairs per row. Both conditions can block publication; the LLM monitor additionally evaluates proposals and accepted history. Full local-baseline and identified-part contrasts remain in the supplement.

Failure. A worker backend error at seed 3010 in authorized/paraphrase/provenance leaves 49 valid trials. All-trial bounds are 66-68% assembled and 94-96% recoverable. There are no malformed monitor verdicts or non-protocol replies.

Call accounting. There are 4,795 logged turns: 4,000 actor and 795 monitor, including one failed turn without a model ID. The manifest's backend counter records 4,794 completed calls. Every logged served-model ID is claude-haiku-5-5. Manifest-reported cost is $0.96, billed to a subscription; these records do not establish an independently audited bill or all transport retries.

Pilot erratum. The frozen protocol says the pilot monitor blocked every authorized proposal. It blocked 160/161 authorized proposals (320/321 overall), allowing one keyword-authorized proposal at seed 2018. The protocol remains unedited to preserve its hash; the decision to keep that monitor unchanged does not depend on the error.

C.5 Evidence access and independent checks

Protocol and sampling. The separate Study 2 protocol was frozen at 435d20d4d0d8e7bf24a391d077649b98e6d526ae before recorded held-out collection. Development seeds 2000-2019 informed the primary paraphrase comparison; held-out seeds are 3000-3049. Pilot results are not pooled. Study 1's v2 design followed pilots on 0-19 and uses held-out Haiku seeds 1000-1019 and Sonnet 1000-1009. Git chronology and manifests document the workflow without independently authenticating every collection event.

Archived evidence. Study 1 frozen runs and Study 2 held-out records contain raw replies, manifests and analyses. The full methods and results supplement preserves exact prompt templates, exhaustive tables and transcripts. These commit-pinned links identify the reviewed evidence edition.

Offline audit. The verification guide gives pinned inputs and commands. Replay verifies archived hashes, reconstructs trials from logged replies, and recomputes scores and tables without model calls or an LLM judge. It checks the recorded evidence, not whether future inference reproduces the behavior. Fresh model runs test replication; additional tasks, models, providers and forged-metadata tests assess generalization.

Data quality. The scoped check script and recorded results check hashes, unique trial keys, grid coverage, validity and seed-3000 inputs/outputs. Study 1 has 1,040 valid records; Study 2 has all 800 planned keys and 799 valid records. Original Study 1 turns lack per-call model IDs except in the rerun. Successful Study 2 turns have IDs; its failed turn does not. Failed outcomes are not imputed and runs are not silently pooled.

Sprint provenance. The author confirms that all study assets were produced during the sprint. Public history records the scaffold at 17:24 and v2 implementation at 18:29 Pacific on November 6, after the 13:30 LA kickoff; the first v2 manifest records 18:49. Study 2 collection ran 06:01-06:57 UTC on November 7. The source-linked development timeline records these timestamps. Eleven pilot result files in the initial scaffold lack execution timestamps, so the records do not independently date every asset. No assets are claimed as pre-sprint work.

Independent replication, varied objectives, adversarial purpose metadata and larger asynchronous networks remain future work. The proposed sender-level SAE intervention is unimplemented. Completed collection and replay establish internal reproducibility within the stated provenance limits, not independent behavioral replication.