Wiltiana John
Per Scholas
09/3/2026

In this lab, the first thing we did was take a screw driver and unscrew the switch. After that we put the blue light cable to the computer and the back of the catalyst switch then we performed a factory reset so we can clean up the switch. After connecting to the Tera Term,we configured the basic settings, including changing the host name to SW1 and clicking serial. We then created the 5 departments of VLANs 10,20,30,40,50 assigned IP addresses to each VLAN interface and created DHCP pools.

We ran into a few problems while configuring the switch ports. At first, we kept getting % invalid input errors because of small typing mistakes, such as using underscores instead of hyphens, forgetting to type pool. Another challenge was getting the switch to accept the port range command. Command like f0/1 and fa0/1 were not working. After using show ip interface brief, we discovered that our switch was using GigabitEthernet port instead. We had to use the interface range GigabitEthernet 7/0/1 - 4 to configure the ports. We also assigned ports 1-4 to VLAN 20 instead of VLAN 10. I also typed end too early, so we had to go back into configuration mode, correct the port assignments and finish configuring VLAN50. For the final step, we needed to backup the switch configuration to a TFTP server using the I.P address. However the backup address kept failing because the RJ45 wasn't physically plugged into the switch, so we then plugged it in and assigned the laptop an IP address, and turned off the Windows Firewall . After that, the connection didn't really work, so we moved on to the next step and successfully completed the rest of the lab.

Overall, we did this lab to learn how to clear out old switches settings, segment network traffic into separate departments VLANs for better security, give devices IP addresses automatically with DHCP, and save configuration backup disaster.