AMT Training Manual

Intelligence Centre

AMT 8.26



RPMGLOBAL

AMT Data Model Dictionary

List of Available AMT Reporting Data Models and Fields

Prepared by:	RPMGlobal
Date:	2023

Table of Contents

AMT Log Data Model 9
AMTLogProjTaskCount 9
LoginType 9
LongTermPlanningAMTLog 9
MobileCheckInOutLog 10
UserAMTLog 11
Availability and Scheduled Hours Data Model 11
DailyAvailability 11
DailyDowntime 12
DailyScheduledHours 12
ScheduledHours 12
Billing Data Model 13
ProjectionBillingAmounts 13
ProjectionBillings 13
Budgeting Data Model 14
BudgetComment 14
BudgetCost 15
BudgetEquipment 16
BudgetHeader 17
BudgetHistory 18
BudgetLabourHours 18
BudgetOccurrence 18
BudgetPeriod 20
BudgetTask 22
BudgetUsage 22
Budget vs Actual Data Model 23
ActualCost 23
ActualLabourHours 24
BudgetCost 25
BudgetLabourHours 26
Costs Data Model 27
ActualCost 27
Cost 29
FutureCost 30

Customer Data Model 31
Customer 31
Depreciable Asset Data Model 33
CapitalAssetValue 33
DepreciableAssetJournal 33
DepreciableAssetValue 34
Equipment Details Data Model 35
EquipmentDetails 35
EquipmentDetailsUser 37
EquipmentGeolocationHistory 38
EquipmentTechnicalDetails 39
EquipmentUserSecurity 39
ProjectionHeader 39
ProjectionType 40
SiteUserSecurity 40
UserDetails 40
Equipment Statistics Data Model 41
LifeRemaining 41
Projection 41
Functional Location Data Model 41
FunctionalLocation 41
Generic Interface Log Data Model 42
GenericInterfaceDetailLog 42
GenericInterfaceLog 42
Inspection Data Model 43
InspectionDetails 43
Notification Data Model 44
Notification 44
NotificationComment 45
NotificationDailySnapshot / NotificationMonthlySnapshot / NotificationQuarterlySnapshot / NotificationYearlySnapshot 45
Occurrence Data Model 46
ActualOccurrence 46
FutureOccurrence 46
Occurrence 47
Quick Watch Data Model 48

OverdueUsageReadings 48
Quote Data Model 48
QuoteDetails 48
ReportParameters 50
Standard Job Data Model 50
StandardJob 50
StandardJobLogDetails 52
StandardJobOperation 52
StandardJobOperationPart 53
StandardJobOperationLabour 53
StandardJobOperationMisc 54
Stoppages Data Model 55
StoppagesEvent 55
StoppagesWorkorder 56
StoppagesDowntimeAllocation 56
Strategy Task Data Model 57
StrategyTask 57
StrategyTaskJob 59
StrategyTaskOccurrence 60
ComponentLife 60
CostSource 60
PrimaryPart 61
StatutoryCompliance 61
Timesheet Data Model 62
Roster 62
Timesheet 62
TimesheetEntries 63
Utilisation Data Model 64
UtilisationEquipmentActualUsage 64
UtilisationEquipmentInvalidActualUsage 64
UtilisationEquipmentProjectionUOM 65
UtilisationUsageProfile 65
UtilisationUsageProfileUOM 65
Workorder Data Model 66
ChildWorkorderSettlement 66

ParentWorkorderSettlement....66
WorkorderDetails....67
WorkorderOperations....69
System Table Data Model....70
PriceGroup....70
PartType....70
PayType....71
Priority....71
WorkLocation....71
Shutdown....71
GeolocationStatus....72
Responsibility....72
ComponentCode....72
LabourExpenseCode....72
SystemSource....73
AssetStatus....73
Source....73
AMTUser....73
Employee....73
TaskPlannedTime....74
Symptom....74
Cause....74
OccurrenceTypes....75
ChangeoutCategory....75
JobReadyStatus....75
TaskStatus....75
Parts....75
ReportTime....76
Workorder....76
CostCategory....76
ParentWorkorderSettlement....77
SourceOfSupply....77
ModifierCode....77
TaskCounter....77
ApplicationSeverity....78

Region....78
Division....78
ReportDate....78
ReportPeriod....79
EquipmentCriticality....79
EquipmentLocation....80
EquipmentCategory....80
EquipmentClass....80
Manufacturer....80
Model....81
TaskHeader....81
UOM....81
TaskType....82
CostCentre....82
ExpenseElement....82
CostBearer....83
WorkGroup....83
LabourActivity....83
PartClassification....83
PartRating....84
JobCodes....84
MaintenanceType....84
CostResponsibility....84
CostActivity....84
ReportCalendar....85
Branch....85
Currency....85
OperationWorkStatus....85
Usage Profile Data Model....86
UsageProfile....86
UsageStep....86
UsageProfileParentChildRelationship....86
UsageProfileStepAmounts....86
Universal Logging Data Model....87
AuditLogEvent....87

AuditLogEventDetail 87

AMT Log Data Model

The AMT Log Data Model captures logging information to certain AMT instances such as user logins (to AMT and AMT Mobile), changes to Long-term Planning and AMT Mobile check-ins. The respective AMT Log configurations need to be enabled at the database level to allow logging.

AMTLogProjTaskCount

Provides the number of times a strategy task has been rescheduled. It requires the Projected Task entity needs to be enabled in the AMT_LOG_CONFIG table.

Field	Data Type	Field Size	Description
StrategyTaskKey	Integer		Strategy Task Identifier. This field can be used to join this view to the StrategyTaskDataModel.StrategyTask view to get additional strategy task information.
RescheduleCount	Integer		The number of times the strategy task has been rescheduled.

LoginType

A type of system table that provides identifier for a successful or failed login. Its primary use is to provide the login type description to other Login entities using the Login Type key.

Field	Data Type	Field Size	Description
LoginTypeKey	Integer		Login Type identifier.
LoginTypeDescription	Varchar	16	Login Type description (Successful Login or Failed Login).

LongTermPlanningAMTLog

Captures changes made to strategy tasks in the Long-Term Planning screen, including the user who made the changes. It requires the Projected Task entity needs to be enabled in the AMT_LOG_CONFIG table.

Field	Data Type	Field Size	Description
AmtLogRecordKey	Varchar	2000	AMT Log record identifier. This is the Strategy Task key or Projected Task ID.
AmtLogKey	Integer		AMT Log identifier. This identifies the entry in the AMT LOG table.
Comments	Varchar	2000	Long term Planning log comments.
TimeStamp	Date/Time		AMT Log timestamp.
AmtLogConfigKey	Integer		AMT Log Config table identifier.
EntityName	Varchar	100	Entity name in the AMT Log Config table.
EntityNameTable	Varchar	200	Entity name table in the AMT Log Config table.
PrimaryKey	Varchar	1000	AMT Log Config table primary key.
DisplayView	Varchar	1000	AMT Log Config table display view.
DisplayField	Varchar	1000	AMT Log Config table display field.
FieldName	Varchar	100	Field name from AMT Log Config Field table.
FieldNameTable	Varchar	200	Field table name from AMT Log Config Field table.
AmtLogConfigFieldKey	Integer		AMT Log Config Field table identifier.
LogTypeDescription	Varchar	100	AMT Log Type description. This can be “Manual”, “Automatic and Silent” or “Automatic and User Comments”.
OldValue	Varchar	8000	Previous field value (before change).
NewValue	Varchar	8000	New field value (after change).

AmtLogSystemValue	Varchar	100	AMT Log system value. Provides the reason a user entered for the change.
AmtLogSystemValueKey	Integer		AMT Log System Value identifier.
AmtLogSystemFieldKey	Integer		AMT Log System Field identifier. Directly tied to the user entered reason.
FieldDescription	Varchar	100	AMT Log System Field description.
Branch	Nvarchar	100	Strategy Task equipment branch.
Site	Varchar	50	Strategy Task equipment site.
Fleet	Varchar	50	Strategy Task equipment fleet.
Equipment	Nvarchar	100	Strategy Task equipment.
Model	Varchar	20	Strategy Task equipment model.
ComponentCode	Varchar	76	Strategy Task component code.
System	Varchar	50	Component Code system.
SubSystem	Varchar	50	Component Code sub system.
CostType	Varchar	50	Component Code cost type.
SalesResponsibility	Varchar	61	Strategy Task sales responsibility.
StrategyTaskDescription	Varchar	200	Strategy Task description.
StrategyTask	Varchar	314	Strategy Task header.
BranchKey	Integer		Strategy Task branch identifier.
SiteKey	Integer		Strategy Task site identifier.
FleetKey	Integer		Strategy Task fleet identifier.
EquipmentKey	Integer		Strategy Task equipment identifier.
ModelKey	Integer		Strategy Task equipment model identifier.
SalesResponsibilityKey	Integer		Strategy Task sales responsibility identifier.
CostTypeKey	Integer		Component Code cost type identifier.
SubSystemKey	Integer		Component Code sub system identifier.
ComponentCodeKey	Integer		Strategy Task component code identifier.
StrategyTaskDescriptionKey	Integer		Strategy Task Header identifier.
StrategyTaskKey	Integer		Strategy Task identifier.
UserKey	Integer		Identifier of AMT user who made the change.
SystemKey	Integer		Component Code system identifier.
AMTUserName	Varchar	50	Name of AMT user who made the change.
TaskTypeKey	Integer		Strategy Task Task Type identifier.

MobileCheckInOutLog

Captures every check in and check out to AMT Mobile, along with the date, user, IP address, and duration of check in.

Field	Data Type	Field Size	Description
MobileCheckInOutLogKey	Unique Identifier		Unique identifier used to identify the check in or check out action.
UserKey	Integer		AMT User identifier. This can be joined to the SystemTableDataModel.AMTUser view to get additional AMT user information.
DateKey	Integer		Date of check-in or check-out action.
CheckInOutType	Nvarchar	400	Describes if it is a check-in or check-out.
IsSuccessful	Bit		Describes if check-in or check-out was successful or not.
IpAddress	Varchar	39	IP address of device used to check in or out.
Filters	XML		XML string providing user, site and check in/out details.
DurationSeconds	Integer		Duration of check-in or check-out in seconds.
StartDate	Date/Time		Date and time when check-in/out action started.
EndDate	Date/Time		Date and time when check-in/out action ended.

UserAMTLog

Captures every AMT user login, along with the IP address of the device used for the login and time stamps.

Field	Data Type	Field Size	Description
AmtLogkey	Integer		AMT Log identifier. This identifies the entry in the AMT LOG table.
AmtLogConfigKey	Integer		AMT Log Config table identifier.
UserKey	Integer		Identifier of AMT user who made the change.
UserRoleKey	Integer		AMT User role identifier.
AmtLogRecordKey	Varchar	2000	AMT Log record identifier.
ClientDescription	Varchar	22	Describes if the login is from the AMT Windows client or AMT Mobile.
Comments	Varchar	2000	AMT Log comments.
IPAddress	Varchar	8000	IP address of the device used to log in to AMT.
MACAddress	Varchar	8000	MAC address of the device used to log in to AMT.
TimeStamp	Date/Time		Date and time of the AMT login.
LoginTypeKey	Integer		Login Type identifier. This field can be joined to the AmtLogDataModel.LoginType view to retrieve if login was successful or not.

Availability and Scheduled Hours Data Model

Used to build reports focused on equipment availability (physical or mechanical), equipment scheduled hours and downtime. Availability calculations can be made at a daily or period level.

DailyAvailability

Used for reporting on equipment daily availability. Target, good and alert physical and mechanical availability percentages are also available.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
DateKey	Integer		Date identifier (YYYYMMDD)
UOMKey	Integer		UOM identifier
ScheduledHours	Float		Equipment scheduled hours
CumulativeScheduledHours	Integer		Equipment cumulative scheduled hours
TargetDowntime	Float		Equipment target downtime
ActualUsage	Float		Equipment actual usage in selected date
CumulativeActualUsage	Integer		Equipment cumulative actual usage
TargetUsage	Float		Equipment target usage
CumulativeTargetUsage	Integer		Equipment cumulative target usage
TargetMechanicalAvailabilityDowntime	Float		Target mechanical availability percentage (configurable)
GoodMechanicalAvailabilityDowntime	Float		Good mechanical availability percentage (configurable)
AlertMechanicalAvailabilityDowntime	Float		Alert mechanical availability percentage (configurable)
TargetPhysicalAvailabilityDowntime	Float		Target physical availability percentage (configurable)
GoodPhysicalAvailabilityDowntime	Float		Good physical availability percentage (configurable)
AlertPhysicalAvailabilityDowntime	Float		Alert physical availability percentage (configurable)

DailyDowntime

Actual and planned down time hours at date and equipment level.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
TaskTypeKey	Integer		Task Type identifier
ResponsibilityKey	Integer		Downtime responsibility identifier
DateKey	Integer		Date identifier (YYYYMMDD)
ActualDownTimeHours	Float		Actual Downtime hours on selected date
PlannedDownTimeHours	Float		Planned Downtime hours on selected date

DailyScheduledHours

Equipment daily scheduled hours when set in the Scheduled Hours screen.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
DateKey	Integer		Date identifier (YYYYMMDD)
ScheduledHours	Float		Scheduled hours at a daily level

ScheduledHours

Equipment scheduled hours details at a period level. Start and End Usage as well as configured target, good and alert availability percentages are available.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
ReportPeriod	Integer		Report period (month)
PrimaryUOMKey	Integer		Primary UOM identifier
Equipment	Varchar	100	Equipment name
UOM	Varchar	50	Unit of Measure (e.g., Op Hrs)
PeriodStartUsage	Float		Equipment usage at start of period
PeriodEndUsage	Float		Equipment usage at end of period
ScheduledHours	Float		Equipment scheduled hours
TargetPhysicalAvailabilityPercentage	Float		Target physical availability percentage (configurable)
GoodPhysicalAvailabilityPercentage	Float		Good physical availability percentage (configurable)
AlertPhysicalAvailabilityPercentage	Float		Alert physical availability percentage (configurable)
TargetMechanicalAvailabilityPercentage	Float		Target mechanical availability percentage (configurable)
GoodMechanicalAvailabilityPercentage	Float		Good mechanical availability percentage (configurable)
AlertMechanicalAvailabilityPercentage	Float		Alert mechanical availability percentage (configurable)

Billing Data Model

Data model that provides projected billing details for equipment contracts. These views can be used to build reports related to billing projections across a contract term.

ProjectionBillingAmounts

Provides start and end usage and dates, as well as projected billing amounts for each contract billing step.

Field	Data Type	Field Size	Description
ProjectionBillingKey	Integer		Projected Billing identifier
StartUsage	Float		Equipment projection usage at the start of the billing step
EndUsage	Float		Equipment projection usage at the end of the billing step
StartUsageToDay	Float		Same as StartUsage, with the only difference is that the start usage is based on the start date instead of start period if the billing type is set to "Usage rate by Monthly date range".
EndUsageToDay	Float		Same as EndUsage, with the only difference is that the end usage is based on the end date instead of end period if the billing type is set to "Usage rate by Monthly date range".
StartDate	Date/Time		Unless the billing type is set to "Usage rate by usage steps", this is the date the corresponds to the Start Usage.
EndDate	Date/Time		Unless the billing type is set to "Usage rate by usage steps", this is the date the corresponds to the End Usage.
Amount	Float		Projected billing amount per billing step.

ProjectionBillings

Billing Projection details including the equipment projection name and contract details. It can be used in conjunction with the ProjectionBillingAmounts view to retrieve usages, dates, and billing amounts.

Field	Data Type	Field Size	Description
ProjectionBillingKey	Integer		Projected Billing identifier
EquipmentProjectKey	Integer		Equipment Projection identifier
EquipmentProjectName	Varchar	50	Equipment Projection name
Comments	Varchar	5000	Billing Projection comments
ModelKey	Integer		Equipment model identifier
Model	Varchar	20	Equipment model name
ScheduleName	Varchar	200	Projected Billing schedule name
QUOMKey	Integer		Projected Billing UOM identifier
QUOM	Varchar	20	Projected Billing UOM
ExternalKey	Varchar	50	Projected Billing External ID
EscalationAnchorDate	Date/Time		Projected Billing escalation anchor date
ContractReviewFrequency	Float		Projected Billing contract review frequency
ReviewDate	Date/Time		Projected Billing last review date
ReviewPerson	Varchar	100	Projected Billing last review person
Contract	Varchar	50	Billing Contract name
AutoAccrue	Bit		Auto Accrue Billings flag
AutoGenerate	Bit		Auto Generate Billings flag
Tax1Name	Varchar	50	Billing Tax 1 name
PercentTax1	Float		Billing Tax 1 percentage value
Tax2Name	Varchar	50	Billing Tax 2 name
PercentTax2	Float		Billing Tax 2 percentage value

Tax3Name	Varchar	50	Billing Tax 3 name
PercentTax3	Float		Billing Tax 3 percentage value
CurrencyKey	Integer		Projected Billing Currency identifier
Currency	Varchar	3	Projected Billing currency name
NextReviewDate	Date/Time		Billing next review date
StartUsage	Float		Equipment Start Usage
TermUOM	Varchar	20	Equipment Term UOM
EndUsage	Float		Equipment projection end usage
StartDate	Date/Time		Equipment start date
EndDate	Date/Time		Equipment projection end date
ProjectionTypeKey	Integer		Equipment projection type identifier
ProjectionType	Varchar	50	Equipment projection type name
EndQUOMKey	Integer		Equipment projection end UOM identifier
ExRate	Float		Exchange rate
BillingTypeKey	Integer		Projected Billing Type identifier
BillingType	Varchar	50	Projected Billing Type name
EquipmentPlanKey	Integer		Equipment identifier
EquipmentPlan	Nvarchar	100	Equipment name
DefaultSchedule	Bit		Projected Billing Default Schedule flag
BillStart	Float		Projected Billing start usage
BillEnd	Float		Projected Billing end usage

Budgeting Data Model

Used to build reports related to the AMT Budget and Forecast module. Views are provided ranging from details of the budget header level down to the budget costs level.

BudgetComment

Shows Budget Comments entered in the Budget Cost Occurrence Manager.

Field	Data Type	Field Size	Description
BudgetCommentKey	Integer		Budget Comment identifier
BudgetHeaderKey	Integer		Budget Header identifier. Field can be used to join with the BudgetingDataModel.BudgetHeader view to get Budget Header details.
Equipment	Nvarchar	200	Budget equipment name
TaskHeaderKey	Integer		Task Header identifier
CostCentreKey	Integer		Cost Centre identifier for budget cost
CostCategoryKey	Integer		Cost Category identifier for budget cost
CostExpenseKey	Integer		Expense Element identifier for budget cost
CostBearerKey	Integer		Cost Bearer identifier for budget cost
WorkGroupKey	Integer		Work Group identifier for budget cost
Period	Integer		Budget cost period
UserKey	Integer		Identifier for user who added the comment
BudgetStatusKey	Integer		Budget Status identifier
Comments	Nvarchar	Max	Added comments
CreatedDate	Date/Time		Comment's created date
Deleted	Bit		Deleted flag. Used to identify deleted comments.

BudgetCost

Strategy task cost details (at strategy task occurrence level). Cost details are sliced into different dimensions such as cost centre and expense element.

Field	Data Type	Field Size	Description
BudgetCostKey	Integer		Budget Occurrence Cost identifier (PK)
BudgetOccurrenceKey	Integer		Budget Task Occurrence identifier - Used to link Occurrence Cost to Task Occurrence
BudgetTaskKey	Integer		Budget Task identifier - Used to link Occurrence Cost to Budget Task
BudgetEquipmentKey	Integer		Budget Equipment identifier - Used to link Occurrence Cost to Budget Equipment
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Occurrence Cost to Budget Header
CostCategoryKey	Integer		Cost Category identifier - Can be linked to SystemTableDataModel.CostCategory to get Cost Category name
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
EquipmentCategoryKey	Integer		Equipment Category identifier - Can be linked to EquipmentDetailsDataModel.EquipmentDetails to get Equipment Category name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
ManualEdited	Bit		Indicates if the Budget Cost is manually edited
Cost	Float		Occurrence Cost at Cost
Sell	Float		Occurrence Cost at Sell
LastModifiedDate	Date/Time		Last Change Date for Occurrence Cost
CreatedDate	Date/Time		Occurrence cost created date

BudgetCostByReportCalendar

Budget cost details broken down by calendar period rather than at budget task occurrence level.

Field	Data Type	Field Size	Description
BudgetHeaderKey	Integer		Budget Header identifier
BudgetEquipmentKey	Integer		Budget Equipment identifier
BudgetTaskKey	Integer		Budget Task identifier
ReportCalendarKey	Integer		Calendar identifier
CalendarName	Varchar	500	Calendar Name
CalendarPeriod	Varchar	20	Calendar Period
CostCategoryKey	Integer		Cost Category identifier - Can be linked to SystemTableDataModel.CostCategory to get Cost Category name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group details

EquipmentCategoryKey	Integer		Equipment Category identifier - Can be linked to EquipmentDetailsDataModel.EquipmentDetails to get Equipment Category Name
IsDefaultCostBearer	Bit		Indicates if the Cost Bearer used is the default Cost Bearer
DowntimeHours	Float		Downtime hours in period
OccurrenceQuantity	Integer		Number of occurrences in period
Cost	Float		Cost at Cost in period
Sell	Float		Cost at Sell in period

BudgetEquipment

Budget equipment information. Details of each equipment that has been added to a budget scenario.

Field	Data Type	Field Size	Description
BudgetEquipmentKey	Integer		Budget Equipment identifier (PK)
BudgetHeaderKey	Integer		Budget header identifier - Used to link Budget Equipment to the Budget Header
CostResponsibilityKey	Integer		Equipment Cost Responsibility identifier
CostCentreKey	Integer		Equipment Cost Centre identifier
RegionKey	Integer		Equipment Region identifier
DivisionKey	Integer		Equipment Division identifier
EquipmentLocationKey	Integer		Equipment Location identifier
EquipmentCriticalityKey	Integer		Equipment Criticality identifier
EquipmentCategoryKey	Integer		Equipment Category identifier
UOMKey	Integer		Equipment UOM (Unit of Measure) identifier
ModelKey	Integer		Equipment Model identifier
ManufacturerKey	Integer		Equipment Manufacturer identifier
EquipmentClassKey	Integer		Equipment Class identifier
EquipmentGroupKey	Integer		Equipment Group identifier
IndustryGroupKey	Integer		Industry Group identifier
EquipmentType	Varchar	30	Equipment Type (Real, Modelling, Centreline)
Model	Varchar	20	Equipment model
Manufacturer	Varchar	20	Equipment manufacturer (related to model)
Branch	Varchar	50	Branch that the equipment is under
Site	Varchar	50	Site that the equipment is under
Fleet	Varchar	50	Fleet that the equipment is under
EquipmentName	Varchar	50	Equipment name
SerialNumber	Varchar	50	Equipment serial number
ProjectionName	Varchar	50	Equipment projection (e.g., Current, Budget, Alternate)
ParentEquipmentName	Varchar	50	Parent Equipment name
CostResponsibility	Varchar	103	Equipment Cost Responsibility
CostCentre	Varchar	83	Equipment Cost Centre
Region	Varchar	63	Equipment Region name
Division	Varchar	63	Equipment Division name
EquipmentLocation	Varchar	63	Equipment Location name
EquipmentCriticality	Varchar	50	Equipment Criticality
EquipmentCategory	Varchar	50	Equipment Category
UnitOfMeasure	Varchar	20	Equipment Unit of Measure (UOM) for usage-based assets
EquipmentClass	Varchar	103	Equipment Class
EquipmentGroup	Varchar	103	Equipment Group
IndustryGroup	Varchar	50	Industry Group
StartUsage	Float		Equipment Start Usage based on UOM
EndUsage	Float		Equipment End Usage based on UOM

EquipmentStartDate	Date/Time		Equipment AMT Start Date
EndDate	Date/Time		Equipment AMT End Date
OptimalEndDate	Date/Time		Optimal termination period
AvailabilityType	Varchar	55	Equipment Availability Type (Physical or Mechanical)
NewEquipment	Bit		Flag to indicate new equipment
ReplaceEquipmentName	Varchar	50	Equipment name being replaced
ComponentValue	Float		Component value
RVIC	Float		Residual Value in Component in percentage
SchedulingEfficiency	Float		Scheduling efficiency (equipment downtime) in percentage
PurchasePrice	Float		Equipment purchase price
EquipmentSalePrice	Float		Estimated sell price
TotalCost	Float		Total Cost at Cost
TotalSell	Float		Total Cost at Sell
IgnoreCost	Bit		Flag to ignore the budget cost for the equipment
PercentageMarginParts	Float		Equipment parts cost margin
PercentageMarginLabour	Float		Equipment labour cost margin
PercentageMarginMiscellaneous	Float		Equipment miscellaneous cost margin
CalculationStatus	Varchar	50	Budget equipment calculation status
LastModifedDate	Date/Time		Equipment last modified date
CreatedDate	Date/Time		Equipment created date
AssetConditionCode	Varchar	12	Asset condition code
AssetConditionDescription	Varchar	100	Asset condition description
EquipmentCriticalityCode	Varchar	10	Equipment Criticality Code

BudgetHeader

Provides Budget Header information for each budget scenario.

Field	Data Type	Field Size	Description
BudgetHeaderKey	Integer		Budget Header identifier (PK)
BudgetHeader	Nvarchar	165	Budget Header name - Concatenation of scenario name, budget type and year
ScenarioName	Nvarchar	50	Scenario name
VersionNumber	Nvarchar	50	Budget version number
ExtensionScenarioName	Nvarchar	50	External scenario name
ExtensionVersionNumber	Nvarchar	50	External version
BudgetDescription	Nvarchar	1000	Budget notes
StartPeriod	Integer		Budget start period
EndPeriod	Integer		Budget end period
BudgetYear	Integer		Budget year
BudgetTypeDescription	Nvarchar	50	Budget type
BudgetStatusDescription	Nvarchar	50	Budget status
CalculationStatus	Nvarchar	50	Budget calculation status
IsExported	Bit		Flag to indicate if the budget has been exported
EquipmentCostEscalationNotes	Nvarchar	Max	Budget equipment cost update escalation notes
Currency	Nvarchar	3	Currency used for budget
CurrencyDescription	Nvarchar	50	Currency description
Symbol	Nvarchar	3	Currency symbol (e.g., $)
CurrentReportingBudget	Bit		Flag to indicate if this is a current reporting budget
LastModifiedByUserKey	Integer		Identifier of user who last modified the Budget Header
LastModifiedDate	Date/Time		Last change date of Budget Header
CreatedByUserKey	Integer		Identifier of user who created budget scenario
CreatedDate	Date/Time		

MessageGroupKey	Integer		

BudgetHistory

Displays all user changes made to budgets, including the action performed, the user who performed and the details of the change made.

Field	Data Type	Field Size	Description
Timestamp	Date/Time		Time when the change to the budget was made
BudgetHeaderKey	Integer		Budget Header identifier. Used to link the Budget History to the corresponding Budget Header.
ScenarioName	Varchar	50	Budget scenario name
VersionNumber	Varchar	50	Budget scenario version number
User	Varchar	50	User who made the change
Action	Varchar	10	Action taken in one word (e.g., Modify, Delete, Create)
Target	Varchar	20	Record modified (e.g., Equipment, Budget, Task)
BudgetEquipment	Varchar	50	The Budget Equipment modified
BudgetTask	Varchar	200	The Budget Task modified if the change was at the task or lower level
TargetDate	Varchar	60	Target date for the Budget Task modified, where applicable
Changes	Varchar	500	Verbose details of change performed

BudgetLabourHours

Strategy task cost details (at strategy task occurrence level). Cost details are sliced into different dimensions such as cost centre and expense element.

Field	Data Type	Field Size	Description
BudgetLabourHourKey	Integer		Budget Labour Hours record identifier
BudgetOccurrenceKey	Integer		BudgetOccurrence identifier. This field can be used to join to the BudgetingDataModel.BudgetOccurrence view and get the budget occurrence details.
LabourActivityKey	Integer		Labour Activity identifier assigned to the labour hours entry
CostBearerKey	Integer		Cost Bearer identifier
CostCentreKey	Integer		Cost Centre identifier
WorkGroupKey	Integer		Work Group identifier
LabourHours	Float		Labour Hours
ManuallyEdited	Bit		Flag to indicate if labour hours entry was manually edited
BudgetTaskKey	Integer		Budget Task identifier
BudgetEquipmentKey	Integer		Budget Equipment identifier
BudgetHeaderKey	Integer		Budget Header identifier
ExpenseElementKey	Integer		Expense Element identifier
EquipmentCategoryKey	Integer		Equipment Category identifier
LastModifiedDate	Date/Time		Labour Hours entry last change date

BudgetOccurrence

Budget task occurrence details. Generated from strategy task occurrences when strategy tasks are added to a budget.

Field	Data Type	Field Size	Description
BudgetOccurrenceKey	Integer		Budget Task Occurrence identifier (PK)

BudgetTaskKey	Integer		Budget Task identifier - Used to link Budget Task Occurrence to Budget Task
BudgetEquipmentKey	Integer		Budget Equipment identifier - Used to link Budget Task Occurrence to Budget Equipment
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Task Occurrence to Budget Header
IsActualCost	Bit		Indicates if the occurrence is derived from an actual cost (WO settlement)
CostDate	Date/Time		Task occurrence date
OccurrenceUsage	Float		Task occurrence usage reading (based on Task UOM)
OccurrenceQuantity	Integer		Number of occurrences
DowntimeHours	Float		Task downtime hours
ManualEdited	Bit		Indicates if the occurrence is manually edited
LastModifiedDate	Date/Time		Task occurrence last changed date
CreatedDate	Date/Time		Task occurrence created date
ManualEditedDowntime	Bit		Indicates if the downtime is manually edited

BudgetOverhead

Overhead details in budget scenario. Reported at branch, site and fleet level.

Field	Data Type	Field Size	Description
BudgetOverheadKey	Integer		Budget Overhead identifier (PK)
BudgetHeaderKey	Integer		Budget Header identifier
UserAccessLevel	Varchar	50	User Access Level (e.g., Site)
LevelDescirption	Varchar	100	Budget Overhead level (e.g., Site level)
StartCalendarPeriod	Integer		Budget Overhead start period
EndCalendarPeriod	Integer		Budget Overhead end period
LastModifiedDate	Date/Time		Budget Overhead record last changed date
CreatedDate	Date/Time		Budget Overhead record created date
Branch	Varchar	50	Budget Overhead branch
Site	Varchar	50	Budget Overhead site
Fleet	Varchar	50	Budget Overhead fleet
OverheadCostEscalationNotes	Varchar	Max	Overhead Cost Escalation notes

BudgetOverheadCost

Details budget overhead costs per period. Data can be analysed by cost centre and expense element.

Field	Data Type	Field Size	Description
BudgetOverheadCostKey	Integer		Budget Overhead Cost identifier
BudgetOverheadKey	Integer		Budget Overhead identifier. This field is used to link costs with the BudgetingDataModel.BudgetOverhead view to get overhead details.
BudgetHeaderKey	Integer		Budget Header identifier. The field can be used to join this view with the BudgetingDataModel.BudgetHeader view to get Budget Header details.
CostCentreKey	Integer		Cost Centre identifier. This field can be used to link table to the SystemTableDataModel.CostCentre view to get Cost Centre details.
ExpenseElementKey	Integer		Expense Element identifier. This field can be used to link table to the SystemTableDataModel.CostCentre view to get Cost Centre details.
CalenderPeriod	Integer		Calendar Period when budget overhead cost was recorded.
OverheadCost	Varchar	63	Overhead cost code and description.

CostOverhead	Bit		Flag to indicate if this is a Cost of Sales overhead category
Amount	Float		Overhead cost amount
ManualEdited	Bit		Flag to indicate if overhead cost was manually edited
LastModifiedDate	Date/Time		Last change date of budget overhead cost
CreatedDate	Date/Time		Create date of budget overhead cost
IsCapEx	Bit		Flag to indicate if overhead cost is a CAPEX cost

BudgetOverheadCostByReportCalendar

Budget overhead costs broken down by calendar period.

Field	Data Type	Field Size	Description
BudgetOverheadKey	Integer		Budget Overhead identifier
BudgetHeaderKey	Integer		Budget Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
ReportCalendarKey	Integer		Calendar identifier
CalendarName	Varchar	500	Calendar name
Amount	Float		Budget Overhead Cost amount

BudgetPeriod

Budget equipment period details. This data model can be used to report on equipment availability and RVIC inside a budget scenario.

Field	Data Type	Field Size	Description
BudgetPeriodKey	Integer		Budget Period identifier (PK)
BudgetEquipmentKey	Integer		Budget Equipment identifier - Used to link Budget Period to Budget Equipment
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Period to Budget Header
CalendarPeriod	Integer		Calendar period (YYYYMM)
ScheduledHours	Float		Scheduled hours for equipment in given period
BaselineDowntime	Float		Budget scheduled downtime in given period
TaskDowntime	Float		Task downtime in given period
Availability	Float		Projected availability in given period
RVIC	Float		Residual Value in Component in percentage for given period
PeriodStartDate	Date/Time		Period Start Date
ProjectStartDate	Date/Time		Project Start Date (related to Plant Hire?)
PeriodEndDate	Date/Time		Period End Date
LastModifiedDate	Date/Time		Budget Period last changed date
CreatedDate	Date/Time		Budget Period record created date
ManualEdited	Bit		Indicates if the Budget Period record is manually edited

BudgetPlantHireProject

Provides Plant Hire Project details assigned to the Budget Scenario.

Field	Data Type	Field Size	Description
BudgetPlantHireProjectKey	Integer		Budget Plant Hire Project identifier
BudgetEquipmentKey	Integer		Budget Equipment identifier assigned to the plant hire project
BudgetHeaderKey	Integer		Budget Header identifier
PlantHireProjectKey	Integer		Plant Hire Project identifier (not the same as the Budget Plant Hire key)
PlantHireRateKey	Integer		Plant Hire Rate identifier
HireStatusKey	Integer		Hire Status identifier
StartDate	Date/Time		Plant Hire Project start date
EndDate	Date/Time		Plant Hire Project end date
PercentProjectProbability	Float		Percentage of probability for project
HireStatus	Varchar	50	Hire Status (e.g., committed, probable)
StartPeriod	Integer		Plant Hire Project start period
EndPeriod	Integer		Plant Hire Project end period

BudgetPlantHireRevenue

Provides Plant Hire Revenue details assigned to the Budget Scenario.

Field	Data Type	Field Size	Description
BudgetPlantHireRevenueKey	Integer		Budget Plant Hire Revenue identifier
BudgetPlantHireProjectKey	Integer		Budget Plant Hire Project identifier that the revenue amount is assigned to
PlantHireProjectKey	Integer		Plant Hire Project identifier (not the same as the Budget Plant Hire key)
BudgetEquipmentKey	Integer		Budget Equipment identifier assigned to the plant hire project
BudgetHeaderKey	Integer		Budget Header identifier
BudgetPeriodKey	Integer		Budget period identifier when the revenue was recorded
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
Amount	Float		Budget plant hire revenue amount
ManualEdited	Bit		Flag to indicate if revenue amount was manually edited
ActualRevenue	Bit		Flag to indicate if revenue amount is actual revenue or not

BudgetRevenueByReportCalendar

Similar to the BudgetPlantHireRevenue data model. Revenue is split by calendar and calendar period.

Field	Data Type	Field Size	Description
BudgetHeaderKey	Integer		Budget Header identifier
BudgetEquipmentKey	Integer		Budget Equipment identifier assigned to the plant hire project
BudgetPlantHireProjectKey	Integer		Budget Plant Hire Project identifier that the revenue amount is assigned to
BudgetPlantHireRevenueKey	Integer		Budget Plant Hire Revenue identifier
PlantHireProjectKey	Integer		Plant Hire Project identifier (not the same as the Budget Plant Hire key)
BudgetPeriodKey	Integer		Budget period identifier when the revenue was recorded

ReportCalendarKey	Integer		Custom Report Calendar identifier if it is set up
CalendarName	Varchar	500	Custom Report Calendar name if it is set up
CalendarPeriod	Varchar	20	Custom Report Calendar period
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
Amount	Float		Budget Revenue amount

BudgetTask

Strategy task details for equipment added to budget scenarios. These are also referred to as budget tasks.

Field	Data Type	Field Size	Description
BudgetTaskKey	Integer		Budget Task identifier (PK)
BudgetEquipmentKey	Integer		Budget Equipment identifier - Used to link Budget Task to Budget Equipment
TaskHeaderKey	Integer		Strategy Task Header identifier
TaskHeaderDescription	Varchar	200	Strategy Task Header - Concatenation of 4 codes (CC.MC.TT.TC)
UOMKey	Integer		Task UOM identifier
UOM	Varchar	20	Task Unit of Measure
StrategyTaskFirst	Float		Strategy Task first occurrence (based on UOM)
StrategyTaskFrequency	Float		Strategy Task frequency (based on UOM)
StrategyTaskFinal	Float		Strategy Task final occurrence (based on UOM)
Part	Varchar	100	Primary Part Number for the Strategy Task
IsDowntimeTask	Bit		Flag to indicate if the task requires equipment downtime (stoppage)
ManualEdited	Bit		Flag to indicate if the task is manually edited
LastModifiedDate	Date/Time		Task last changed date
CreatedDate	Date/Time		Task created date
StrategyTaskKey	Integer		AMT Strategy Task identifier - this is different to the Budget Task identifier
IsCapEx	Bit		Indicates if the task is a Capital Expense (CAPEX)
OperationalCriticality	Varchar	50	Task Operational Criticality
MOTCode	Varchar	12	Maintenance Order Type code
MOTDescription	Varchar	100	Maintenance Order Type description
PlanningGroupCode	Varchar	20	Planning Group code
PlanningGroupDescription	Varchar	100	Planning Group description
RequireSTO	Bit		Flag to determine if task requires STO
CalculatedRisk	Varchar	304	Calculated Risk percentage
RiskOverride	Varchar	100	Risk Override

BudgetUsage

Usage details for equipment in a budget scenario. Reported at period level.

Field	Data Type	Field Size	Description
BudgetUsageKey	Integer		Budget Usage identifier (per period) (PK)
BudgetPeriodKey	Integer		Budget Period identifier - Used to link Budget Usage to Budget Period

BudgetEquipmentKey	Integer		Budget Equipment identifier - Used to link Budget Usage to Budget Equipment
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Usage to Budget Header
UOMKey	Integer		UOM identifier
UOM	Varchar	20	Unit of Measure used for usage reading
PeriodStartUsage	Float		Start Usage (based on UOM) for period
ProjectStartUsage	Float		Project Start Usage (related to Plant Hire)
PeriodEndUsage	Float		End Usage (based on UOM) for period
PeriodUsage	Float		Period Usage - Equipment usage in given period
ManualEdited	Bit		Indicates if the Budget Usage record is manually edited

Budget vs Actual Data Model

Used to build reports and datasets to compare budget equipment costs and usage readings with actual (live) equipment costs and usage readings. Different budget scenarios can be compared against actual values for different periods.

ActualCost

Used to retrieve equipment actual costs, split into Parts, Labour and Miscellaneous (at Cost and at Sell) to compare to the budget equipment cost equivalent. Costs are defined at the period (month) level.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
CurrencyKey	Integer		Currency identifier - Can be linked to SystemTableDataModel.Currency to get Currency details
TaskHeaderKey	Integer		Strategy Task Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Costs to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier – Can be linked to SystemTableDataModel.MaintenanceOrderType to get the Maintenance Order Type code and description
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedCostKey	Integer		Projected Cost identifier
CostTypeKey	Integer		Cost Type identifier - from Component Code hierarchy
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy

ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PartsCost	Float		Parts Cost at Cost
LabourCost	Float		Labour Cost at Cost
MiscCost	Float		Miscellaneous Cost at Cost
PartsSell	Float		Parts Cost at Sell
LabourSell	Float		Labour Cost at Sell
MiscSell	Float		Miscellaneous Cost at Sell

ActualLabourHours

Used to retrieve equipment actual labour hours, to compare to the budget equipment labour hours equivalent. Labour hours are defined at the period (month) level.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
TaskHeaderKey	Integer		Task Header identifier - Can be linked to SystemTableDataModel.TaskHeader to get Task Header details
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Usages to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedLabourKey	Integer		Projected Cost identifier
LabourActivityKey	Integer		Labour Activity identifier - Can be linked to SystemTableDataModel.LabourActivity to get LabourActivity name
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier
ModifierKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PeriodLabourHours	Number		Actual labours hours in budget period

ActualUsage

Used to retrieve equipment actual usage reading details, for all units of measure to compare to the budget equipment usage equivalent. Usage reading values are defined at the period (month) level.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Actual Usages to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
UnitOfMearsureKey	Integer		Unit of Measure (UPM) identifier
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedUsageKey	Integer		Projected Usage reading identifier
PeriodUsage	Float		Actual usage in given period

BudgetCost

Used to retrieve budget equipment costs, split into Parts, Labour and Miscellaneous (at Cost and at Sell) to compare to the equipment actual cost equivalent. Costs are defined at the period (month) level.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
CurrencyKey	Integer		Currency identifier - Can be linked to SystemTableDataModel.Currency to get Currency details
TaskHeaderKey	Integer		Strategy Task Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Costs to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedCostKey	Integer		Projected Cost identifier
CostTypeKey	Integer		Cost Type identifier - from Component Code hierarchy
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier

ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PartsCost	Float		Parts Cost@Cost
LabourCost	Float		Labour Cost@Cost
MiscCost	Float		Miscellaneous Cost@Cost
PartsSell	Float		Parts Cost@Sell
LabourSell	Float		Labour Cost@Sell
MiscSell	Float		Miscellaneous Cost@Sell
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier – Can be linked to SystemTableDataModel.MaintenanceOrderType to get the Maintenance Order Type code and description

BudgetLabourHours

Used to retrieve labour hours defined in a budget, to compare to the actual equipment labour hours equivalent. Labour hours are defined at the period (month) level.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
TaskHeaderKey	Integer		Task Header identifier - Can be linked to SystemTableDataModel.TaskHeader to get Task Header details
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Budget Usages to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedLabourKey	Integer		Projected Cost identifier
LabourActivityKey	Integer		Labour Activity identifier - Can be linked to SystemTableDataModel.LabourActivity to get LabourActivity name
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier
ModifierKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PeriodLabourHours	Number		Budget labours hours in budget period

BudgetUsage

Used to retrieve budget equipment usage reading details, for all units of measure to compare to the equipment actual usage equivalent, defined by period.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
BudgetHeaderKey	Integer		Budget Header identifier - Used to link Actual Usages to Budget Header
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier - Related to Plant Hire
UnitOfMearsureKey	Integer		Unit of Measure (UPM) identifier
FunctionalLocationKey	Integer		Functional Location identifier
ProjectedUsageKey	Integer		Projected Usage reading identifier
Period_Usage	Float		Budget usage in given period

Costs Data Model

Used to build reports on equipment projection costs (actual and forecasted) split into Parts, Labour and Miscellaneous (at Cost and at Sell) and different dimensions such as component code, task type, cost centre, expense element, etc.

ActualCost

Equipment actual cost details retrieved from work order settlement cost data. Costs are split into Parts, Labour and Miscellaneous categories and different dimensions such as currency, cost centre and expense element. Actual costs can also be retrieved for multiple projection types, not just the current projection.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy Task identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
CurrencyKey	Integer		Currency identifier - Can be linked to SystemTableDataModel.Currency to get Currency details
TaskHeaderKey	Integer		Strategy Task Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
CostResponsibilityKey	Integer		Cost Responsibility identifier - Can be linked to SystemTableDataModel.CostResponsibility to get Cost Responsibility name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name

LabourActivityKey	Integer		Labour Activity identifier - Can be linked to SystemTableDataModel.LabourActivity to get Labour Activity name
EquipmentCategoryKey	Integer		Equipment Category identifier - Can be linked to SystemTableDataModel.EquipmentCategory to get Equipment Category name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
ProjectedCostKey	Integer		Projected Cost identifier
StrategyTaskJobKey	Integer		Strategy Task Job identifier - Used to link Costs to Strategy Task jobs
ParentWorkorderSettlementKey	Integer		Parent Workorder Settlement identifier
SalesHistoryKey	Integer		Sales History identifier
SalesResponsibilityKey	Integer		Sales Responsibility identifier - Can be linked to SystemTableDataModel.SalesResponsibility to get Sales Responsibility name
SalesStatusKey	Integer		Sales Status identifier - Can be linked to SystemTableDataModel.SalesStatus to get Sales Status name
SalesLostReasonKey	Integer		Sales Lost Reason identifier - Can be linked to SystemTableDataModel.SalesLostReason to get Sales Lost Reason details
FunctionalLocationKey	Integer		Functional Location identifier - Can be linked to FunctionalLocationDataModel.FunctionalLocation to get Functional Location details
ImportProjectionHoldingKey	Integer		Import Projection Holding identifier
CostTypeKey	Integer		Cost Type identifier - from Component Code hierarchy
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PartsCost	Float		Parts Cost at Cost
LabourCost	Float		Labour Cost at Cost
MiscCost	Float		Miscellaneous Cost at Cost
PartsSell	Float		Parts Cost at Sell
LabourSell	Float		Labour Cost at Sell
MiscSell	Float		Miscellaneous Cost at Sell
PartsCostEsc	Float		Escalated Parts Cost at Cost
LabourCostEsc	Float		Escalated Labour Cost at Cost
MiscCostEsc	Float		Escalated Miscellaneous Cost at Cost
PartsSellEsc	Float		Escalated Parts Cost at Sell
LabourSellEsc	Float		Escalated Labour Cost at Sell
MiscSellEsc	Float		Escalated Miscellaneous Cost at Sell
LabourHours	Float		Task/WO Duration
Duration	Float		Labour Hours
AnnualizedCost	Float		Annualised cost
JobInstructionCost	Float		Job Instruction cost
StdJobCost	Float		Standard Job cost
TotalJobCost	Float		Total Job cost
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

Cost

Combination of the ActualCost and FutureCost datasets, allowing the view of all costs for all equipment lifecycle periods (actual and forecasted).

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy Task identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
CurrencyKey	Integer		Currency identifier - Can be linked to SystemTableDataModel.Currency to get Currency details
TaskHeaderKey	Integer		Strategy Task Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
CostResponsibilityKey	Integer		Cost Responsibility identifier - Can be linked to SystemTableDataModel.CostResponsibility to get Cost Responsibility name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
LabourActivityKey	Integer		Labour Activity identifier - Can be linked to SystemTableDataModel.LabourActivity to get Labour Activity name
EquipmentCategoryKey	Integer		Equipment Category identifier - Can be linked to SystemTableDataModel.EquipmentCategory to get Equipment Category name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name
ProjectedCostKey	Integer		Projected Cost identifier
StrategyTaskJobKey	Integer		Strategy Task Job identifier - Used to link Costs to Strategy Task jobs
ParentWorkorderSettlementKey	Integer		Parent Workorder Settlement identifier
SalesHistoryKey	Integer		Sales History identifier
SalesResponsibilityKey	Integer		Sales Responsibility identifier - Can be linked to SystemTableDataModel.SalesResponsibility to get Sales Responsibility name
SalesStatusKey	Integer		Sales Status identifier - Can be linked to SystemTableDataModel.SalesStatus to get Sales Status name
SalesLostReasonKey	Integer		Sales Lost Reason identifier - Can be linked to SystemTableDataModel.SalesLostReason to get Sales Lost Reason details
FunctionalLocationKey	Integer		Functional Location identifier - Can be linked to FunctionalLocationDataModel.FunctionalLocation to get Functional Location details
ImportProjectionHoldingKey	Integer		Import Projection Holding identifier
CostTypeKey	Integer		Cost Type identifier - from Component Code hierarchy
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PartsCost	Float		Parts Cost at Cost
LabourCost	Float		Labour Cost at Cost

MiscCost	Float		Miscellaneous Cost at Cost
PartsSell	Float		Parts Cost at Sell
LabourSell	Float		Labour Cost at Sell
MiscSell	Float		Miscellaneous Cost at Sell
PartsCostEsc	Float		Escalated Parts Cost at Cost
LabourCostEsc	Float		Escalated Labour Cost at Cost
MiscCostEsc	Float		Escalated Miscellaneous Cost at Cost
PartsSellEsc	Float		Escalated Parts Cost at Sell
LabourSellEsc	Float		Escalated Labour Cost at Sell
MiscSellEsc	Float		Escalated Miscellaneous Cost at Sell
Duration	Float		Task/WO Duration
LabourHours	Float		Labour Hours
AnnualizedCost	Float		Annualised cost
JobInstructionCost	Float		Job Instruction cost
StdJobCost	Float		Standard Job cost
TotalJobCost	Float		Total Job cost
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

FutureCost

Equipment future cost details retrieved from strategy task cost data. Costs are split into Parts, Labour and Miscellaneous categories and different dimensions such as currency, cost centre and expense element. Forecast costs can also be retrieved for multiple projection types, not only the current projection.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy Task identifier
ReportPeriodKey	Integer		Report Period identifier - Can be linked to SystemTableDataModel.ReportPeriod to get Period details
CostBearerKey	Integer		Cost Bearer identifier - Can be linked to SystemTableDataModel.CostBearer to get Cost Bearer name
CurrencyKey	Integer		Currency identifier - Can be linked to SystemTableDataModel.Currency to get Currency details
TaskHeaderKey	Integer		Strategy Task Header identifier
CostCentreKey	Integer		Cost Centre identifier - Can be linked to SystemTableDataModel.CostCentre to get Cost Centre name
CostActivityKey	Integer		Cost Activity identifier - Can be linked to SystemTableDataModel.CostActivity to get Cost Activity name
CostResponsibilityKey	Integer		Cost Responsibility identifier - Can be linked to SystemTableDataModel.CostResponsibility to get Cost Responsibility name
ExpenseElementKey	Integer		Expense Element identifier - Can be linked to SystemTableDataModel.ExpenseElement to get Expense Element name
LabourActivityKey	Integer		Labour Activity identifier - Can be linked to SystemTableDataModel.LabourActivity to get Labour Activity name
EquipmentCategoryKey	Integer		Equipment Category identifier - Can be linked to SystemTableDataModel.EquipmentCategory to get Equipment Category name
WorkGroupKey	Integer		Work Group identifier - Can be linked to SystemTableDataModel.WorkGroup to get Work Group name

ProjectedCostKey	Integer		Projected Cost identifier
StrategyTaskJobKey	Integer		Strategy Task Job identifier - Used to link Costs to Strategy Task jobs
ParentWorkorderSettlementKey	Integer		Parent Workorder Settlement identifier
FunctionalLocationKey	Integer		Functional Location identifier - Can be linked to FunctionalLocationDataModel.FunctionalLocation to get Functional Location details
ImportProjectionHoldingKey	Integer		Import Projection Holding identifier
CostTypeKey	Integer		Cost Type identifier - from Component Code hierarchy
SystemKey	Integer		System identifier - from Component Code hierarchy
SubSystemKey	Integer		Sub System identifier - from Component Code hierarchy
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
PartsCost	Float		Parts Cost at Cost
LabourCost	Float		Labour Cost at Cost
MiscCost	Float		Miscellaneous Cost at Cost
PartsSell	Float		Parts Cost at Sell
LabourSell	Float		Labour Cost at Sell
MiscSell	Float		Miscellaneous Cost at Sell
PartsCostEsc	Float		Escalated Parts Cost at Cost
LabourCostEsc	Float		Escalated Labour Cost at Cost
MiscCostEsc	Float		Escalated Miscellaneous Cost at Cost
PartsSellEsc	Float		Escalated Parts Cost at Sell
LabourSellEsc	Float		Escalated Labour Cost at Sell
MiscSellEsc	Float		Escalated Miscellaneous Cost at Sell
Duration	Float		Task/WO Duration
LabourHours	Float		Labour Hours
AnnualizedCost	Integer		Annualised cost
JobInstructionCost	Float		Job Instruction cost
StdJobCost	Float		Standard Job cost
TotalJobCost	Float		Total Job cost
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

Customer Data Model

Contains a single Customer view that provides details for customers that operate equipment.

Customer

Used to report on Customer details.

Field	Data Type	Field Size	Description
CustomerKey	Integer		Customer identifier
Customer	Nvarchar	200	Customer name
CustomerNumber	Nvarchar	80	Customer number
StreetAddress	Nvarchar	1000	Customer street address

Suburb	Nvarchar	400	Customer suburb
StateCode	Nvarchar	80	Customer state code
Phone	Nvarchar	200	Customer phone number
Fax	Nvarchar	200	Customer fax number
PostalStreet	Nvarchar	1000	Customer postal street address
PostalSuburb	Nvarchar	200	Customer postal suburb
PostalStateCode	Nvarchar	40	Customer postal code
BusinessName	Nvarchar	200	Customer business name
BusinessPhone	Nvarchar	100	Customer business phone
BusinessFax	Nvarchar	100	Customer business fax number
BusinessEmail	Nvarchar	100	Customer business email address
Notes	Nvarchar	2000	Customer notes
CustomerPostCode	Nvarchar	200	Customer postcode
CustomerCounty	Nvarchar	200	Customer country
CustomerLocation	Nvarchar	200	Customer location
PrimeIndustry	Nvarchar	200	Customer prime industry code
CustomerIndustry	Nvarchar	200	Customer industry name
ParentCustomerNumber	Nvarchar	200	Parent customer number
IsCustomerFlaggedDelete	Bit		Indicates if the customer is flagged for deletion
CustomerStoreNumber	Nvarchar	200	Customer store number
IsCSACustomer	Bit		Flag to indicate if this is a CSA customer
PartsCustomerClass	Nvarchar	200	Customer parts class
PACC	Nvarchar	400	PACC
CustomerInvoicingIndicator	Nvarchar	200	Customer invoicing indicator
IsIncludingPSM	Bit		Flag to indicate if customer is included in PSM
CostBearer	Nvarchar	200	Customer Cost Bearer
CustomerPrimaryDivision	Nvarchar	200	Customer primary division
CustomerSalesZoneL1	Nvarchar	200	Customer sales zone L1
CustomerSalesZoneL2	Nvarchar	200	Customer sales zone L2
CustomerSize	Nvarchar	200	Customer size
CustomerClassification	Nvarchar	200	Customer classification
PurchasingProfile	Nvarchar	200	Customer purchasing profile
CustomerGroupingA	Nvarchar	200	Customer Grouping A
CustomerGroupingB	Nvarchar	200	Customer Grouping B
CustomerGroupingC	Nvarchar	200	Customer Grouping C
CustomerGroupingD	Nvarchar	200	Customer Grouping D
CustomerGroupingE	Nvarchar	200	Customer Grouping E
CustomerAccountManager	Nvarchar	200	Customer account manager name
PrimeProductSalesResponsibility	Nvarchar	200	Prime product sales responsibility
DealerDepartment	Nvarchar	200	Dealer department name
RelationshipProfile	Nvarchar	200	Relationship profile name
GroupCustomer	Nvarchar	200	Group Customer name
HealthRelationship	Nvarchar	200	Health check relationship
CustomerCountry	Nvarchar	200	Customer country
NoSales	Integer		Number of sales

Depreciable Asset Data Model

Enabled as part of the Asset Register model to track the life and depreciation details of capital assets and components. Used to track and report on capital asset depreciation details.

CapitalAssetValue

Used for reporting on Capital Asset details in the Asset Register module.

Field	Data Type	Field Size	Description
CapitalAssetKey	Integer		Capital Asset identifier (PK). Not to be confused by the Equipment identifier.
EquipmentKey	Integer		Equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
AMTReference	Varchar	200	AMT reference
ExternalReference	Varchar	200	External reference
Description	Varchar	1000	Capital Asset description
CapitalPaid	Float		Amount of capital paid
AccumulatedDepreciation	Float		Accumulated depreciation value
ResidualValue	Float		Residual value of capital asset
CapitalisedDate	Date/Time		Capitalised date
Comments	Varchar	1000	Comments
CurrencyKey	Integer		Currency identifier. This field can be used to join to the SystemTableDataModel.Currency view to get Currency details.
SiteKey	Integer		Site identifier. This field can be used to join to the SystemTableDataModel.Site view to get additional Site details.
FleetKey	Integer		Fleet identifier. This field can be used to join to the SystemTableDataModel.Fleet view to get additional Fleet details.

DepreciableAssetJournal

Used for reporting on asset journals to track depreciation details.

Field	Data Type	Field Size	Description
DepreciableAssetJournalKey	Integer		Depreciable Asset Journal identifier (PK)
EquipmentKey	Integer		Equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
CapitalAssetKey	Integer		Capital Asset identifier. This field can be used to join to the DepreciableAssetDataModel.CapitalAssetValue view to get Capital Asset details.
DepreciableAssetKey	Integer		Depreciable Asset identifier. This field can be used to join to the DepreciableAssetDataModel.DepreciableAssetValue view to get Depreciable Asset details.
EDCKey	Integer		EDC identifier. This field can be used to join to the SystemTableDataModel.EDC view to get additional EDC details.
CostCentreKey	Integer		Cost Centre identifier. This field can be used to join to the SystemTableDataModel.CostCentre view to get additional Cost Centre details.
ExpenseElementKey	Integer		Expense Element identifier. This field can be used to join to the SystemTableDataModel.ExpenseElement view to get additional Expense Element details.
StrategyTaskKey	Integer		Associated Strategy Task identifier. This field can be used to join to the StrategyTaskDataModel.StrategyTask view to get additional Strategy Task details.
TransactionDate	Date/Time		Depreciable Asset Journal transaction date
DebitAmount	Float		Debit amount of transaction

CreditAmount	Float		Credit amount of transaction
CurrencyKey	Integer		Currency identifier. This field can be used to join to the SystemTableDataModel.Currency view to get Currency details.
WorkorderSettlementKey	Integer		Associated Work Order Settlement identifier. This field could be used to join to the WorkorderDataModel.ParentWorkorderSettlement or WorkorderDataModel.ChildWorkorderSettlement views to get additional WO Settlement cost and details.
StartUsage	Float		Depreciable Asset start usage
EndUsage	Float		Depreciable Asset end usage
UOMKey	Integer		UOM identifier associated to start and end usage. This field can be used to join to the SystemTableDataModel.UOM view to get additional UOM details.

DepreciableAssetValue

Used for reporting on asset journals to track depreciation details.

Field	Data Type	Field Size	Description
DepreciableAssetKey	Integer		Depreciable Asset identifier (PK)
CapitalAssetKey	Integer		Capital Asset identifier. This field can be used to join to the DepreciableAssetDataModel.CapitalAssetValue view to get Capital Asset details.
AMTReference	Varchar	200	AMT reference
ExternalReference	Varchar	200	External reference
Description	Varchar	1000	Depreciable Asset description
SerialNumber	Varchar	200	Depreciable Asset serial number
CapitalPaid	Float		Capital amount paid
AccumulatedDepreciation	Float		Accumulated depreciation for asset
ResidualValue	Float		Residual value of asset
CapitalisedDate	Date/Time		Capitalised date
Comments	Varchar	1000	Depreciable Asset comments
AuthorisedBy	Varchar	1000	Authorised by user
AssetClassification1	Varchar	1000	Asset Classification 1
AssetClassification2	Varchar	1000	Asset Classification 2
Status	Varchar	100	Depreciable asset status
CurrencyKey	Integer		Currency identifier. This field can be used to join to the SystemTableDataModel.Currency view to get Currency details.
SiteKey	Integer		Site identifier. This field can be used to join to the SystemTableDataModel.Site view to get additional Site details.
FleetKey	Integer		Fleet identifier. This field can be used to join to the SystemTableDataModel.Fleet view to get additional Fleet details.
DepreciableAssetType	Varchar	22	Depreciable Asset type

Equipment Details Data Model

Used to report on equipment details. This is an essential data model that ties to most of the other data models to retrieve equipment information such as equipment names, branches, sites, fleets, models, as well as equipment projection details.

EquipmentDetails

Used for reporting on equipment details. Heavily used in reports to get equipment hierarchy information and other equipment characteristics.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
Equipment	Varchar	100	Equipment name
EquipmentTypeKey	Integer		Equipment type identifier
EquipmentTypeName	Varchar	30	Equipment type (Real, Modelling, Centreline)
OrganisationKey	Integer		Organisation identifier
Organisation	Varchar	100	Organisation name
BranchKey	Integer		Branch identifier
Branch	Varchar	100	Branch name
SiteKey	Integer		Site identifier
Site	Varchar	50	Site name
FleetKey	Integer		Fleet identifier
Fleet	Varchar	50	Fleet name
ModelKey	Integer		Model identifier
Model	Varchar	20	Model name
RegionKey	Integer		Region identifier
Region	Varchar	50	Region name
DivisionKey	Integer		Division identifier
Division	Varchar	50	Division name
ParentEquipmentKey	Integer		Parent Equipment identifier
ParentEquipment	Varchar	100	Parent Equipment name
EqpLocationKey	Integer		Equipment Location identifier
EqpLocation	Varchar	50	Equipment Location name
EqpCategoryKey	Integer		Equipment Category identifier
EqpCategory	Varchar	50	Equipment Category name
EqpCostCentreKey	Integer		Equipment Cost Centre identifier
EqpCostCentre	Varchar	83	Equipment Cost Centre name
EqpCCActivity	Varchar	10	Equipment Cost Centre
EqpCCLocation	Varchar	10	Equipment Cost Centre Location
EqpCCResponsibility	Varchar	10	Equipment Cost Centre Responsibility
CostResponsibilityKey	Integer		Cost Responsibility identifier
CostResponsibility	Varchar	50	Cost Responsibility name
EqpClassKey	Integer		Equipment Class identifier
EqpClass	Varchar	50	Equipment Class name
EqpGroupKey	Integer		Equipment Group identifier
EqpGroup	Varchar	50	Equipment Group name
EqpCriticalityKey	Integer		Equipment Criticality identifier
EqpCriticality	Varchar	50	Equipment Criticality name
IndustryGroupKey	Integer		Industry Group identifier
IndustryGroup	Varchar	50	Industry Group name
ManufacturerKey	Integer		Manufacturer identifier
Manufacturer	Varchar	20	Manufacturer name

SerialNumber	Varchar	50	Equipment serial number
EqpYear	Integer		Equipment year
ContractKey	Integer		MARC Contract identifier
Contract	Varchar	50	MARC Contract name
ContractTypeKey	Integer		Contract Type identifier
ContractType	Varchar	50	Contract Type name
EqpDescription	Varchar	50	Equipment description
Terminated	Bit		Equipment terminated flag
StartDate	Date/Time		Equipment Start Date
CommissionDate	Date/Time		Equipment Commission Date
OEMEquipmentType	Varchar	100	OEM Equipment Type
OEMEquipmentDivisonCode	Varchar	100	OEM Equipment Division Code
OEMEquipmentDivisonDesc	Varchar	500	OEM Equipment Division Description
OEMEquipmentIndustryCode	Varchar	100	OEM Equipment Industry Code
OEMEquipmentIndustryDesc	Varchar	500	OEM Equipment Industry Description
ProductTypeCode	Varchar	100	Product Type Code
ProductTypeDesc	Varchar	500	Product Type Description
ApplicationCode	Varchar	100	Application Code
ApplicationCodeDesc	Varchar	500	Application Code Description
ApplicationSeverityKey	Integer		Application Severity identifier
ApplicationSeverity	Varchar	100	Application Severity
SaleIndicator	Varchar	100	Sales Indicator
ExcludeFromSalesForecast	Bit		Exclude from Sales Forecast flag
TerritoryIndicator	Varchar	100	Territory Indicator
EquipmentGroupingA	Varchar	500	User defined Equipment Grouping (used for PSM)
EquipmentGroupingB	Varchar	500	User defined Equipment Grouping (used for PSM)
EquipmentGroupingC	Varchar	500	User defined Equipment Grouping (used for PSM)
EngineMake	Varchar	100	Engine Make
EngineModel	Varchar	100	Engine Model
EngineSerialNumber	Varchar	100	Engine Serial Number
SalesResponsibilityKey	Integer		Sales Responsibility identifier
SalesResponsibility	Varchar	33	Sales Responsibility name
Customer	Varchar	100	Customer
CustomerKey	Integer		Customer identifier
PrimaryUOMKey	Integer		Primary UOM identifier
RegistrationCounter	Varchar	20	Equipment registration counter
EquipmentTermRuleKey	Integer		Equipment Term Rule identifier
EquipmentTermRule	Varchar	50	Equipment Term Rule
EndDate	Date/Time		Equipment End Date
EndUsage	Float		Equipment End Usage
IsMARC	Bit		Flag to indicate if MARC equipment
AssetStatusKey	Integer		Asset Status identifier
AssetConditionKey	Integer		Asset Condition identifier
RequireSTO	Bit		Flag to indicate if equipment requires STO
PriceGroupKey	Integer		Equipment Price Group identifier

EquipmentDetailsUser

Similar data model to the EquipmentDetails data model with the distinct difference of displaying the users that have access to each equipment, based on the equipment restrictions at the AMT user level.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
Equipment	Varchar	100	Equipment name
EquipmentTypeKey	Integer		Equipment type identifier
EquipmentTypeName	Varchar	30	Equipment type (Real, Modelling, Centreline)
OrganisationKey	Integer		Organisation identifier
Organisation	Varchar	100	Organisation name
BranchKey	Integer		Branch identifier
Branch	Varchar	100	Branch name
SiteKey	Integer		Site identifier
Site	Varchar	50	Site name
FleetKey	Integer		Fleet identifier
Fleet	Varchar	50	Fleet name
ModelKey	Integer		Model identifier
Model	Varchar	20	Model name
RegionKey	Integer		Region identifier
Region	Varchar	50	Region name
DivisionKey	Integer		Division identifier
Division	Varchar	50	Division name
ParentEquipmentKey	Integer		Parent Equipment identifier
ParentEquipment	Varchar	100	Parent Equipment name
EqpLocationKey	Integer		Equipment Location identifier
EqpLocation	Varchar	50	Equipment Location name
EqpCategoryKey	Integer		Equipment Category identifier
EqpCategory	Varchar	50	Equipment Category name
EqpCostCentreKey	Integer		Equipment Cost Centre identifier
EqpCostCentre	Varchar	83	Equipment Cost Centre name
EqpCCActivity	Varchar	10	Equipment Cost Centre
EqpCCLocation	Varchar	10	Equipment Cost Centre Location
EqpCCResponsibility	Varchar	10	Equipment Cost Centre Responsibility
CostResponsibilityKey	Integer		Cost Responsibility identifier
CostResponsibility	Varchar	50	Cost Responsibility name
EqpClassKey	Integer		Equipment Class identifier
EqpClass	Varchar	50	Equipment Class name
EqpGroupKey	Integer		Equipment Group identifier
EqpGroup	Varchar	50	Equipment Group name
EqpCriticalityKey	Integer		Equipment Criticality identifier
EqpCriticality	Varchar	50	Equipment Criticality name
IndustryGroupKey	Integer		Industry Group identifier
IndustryGroup	Varchar	50	Industry Group name
ManufacturerKey	Integer		Manufacturer identifier
Manufacturer	Varchar	20	Manufacturer name
SerialNumber	Varchar	50	Equipment serial number
EqpYear	Integer		Equipment year
ContractKey	Integer		MARC Contract identifier
Contract	Varchar	50	MARC Contract name
ContractTypeKey	Integer		Contract Type identifier
ContractType	Varchar	50	Contract Type name

EqpDescription	Varchar	50	Equipment description
Terminated	Bit		Equipment terminated flag
StartDate	Date/Time		Equipment Start Date
CommissionDate	Date/Time		Equipment Commission Date
OEMEquipmentType	Varchar	100	OEM Equipment Type
OEMEquipmentDivisonCode	Varchar	100	OEM Equipment Division Code
OEMEquipmentDivisonDesc	Varchar	500	OEM Equipment Division Description
OEMEquipmentIndustryCode	Varchar	100	OEM Equipment Industry Code
OEMEquipmentIndustryDesc	Varchar	500	OEM Equipment Industry Description
ProductTypeCode	Varchar	100	Product Type Code
ProductTypeDesc	Varchar	500	Product Type Description
ApplicationCode	Varchar	100	Application Code
ApplicationCodeDesc	Varchar	500	Application Code Description
ApplicationSeverityKey	Integer		Application Severity identifier
ApplicationSeverity	Varchar	100	Application Severity
SaleIndicator	Varchar	100	Sales Indicator
ExcludeFromSalesForecast	Bit		Exclude from Sales Forecast flag
TerritoryIndicator	Varchar	100	Territory Indicator
EquipmentGroupingA	Varchar	500	User defined Equipment Grouping (used for PSM)
EquipmentGroupingB	Varchar	500	User defined Equipment Grouping (used for PSM)
EquipmentGroupingC	Varchar	500	User defined Equipment Grouping (used for PSM)
EngineMake	Varchar	100	Engine Make
EngineModel	Varchar	100	Engine Model
EngineSerialNumber	Varchar	100	Engine Serial Number
SalesResponsibilityKey	Integer		Sales Responsibility identifier
SalesResponsibility	Varchar	33	Sales Responsibility name
Customer	Varchar	100	Customer
CustomerKey	Integer		Customer identifier
PrimaryUOMKey	Integer		Primary UOM identifier
RegistrationCounter	Varchar	20	Equipment registration counter
EquipmentTermRuleKey	Integer		Equipment Term Rule identifier
EquipmentTermRule	Varchar	50	Equipment Term Rule
EndDate	Date/Time		Equipment End Date
EndUsage	Float		Equipment End Usage
IsMARC	Bit		Flag to indicate if MARC equipment
AssetStatusKey	Integer		Asset Status identifier
AssetConditionKey	Integer		Asset Condition identifier
RequireSTO	bit		Flag to indicate if equipment requires STO
UserKey	Integer		User Identifier that has access to Equipment
UserLoginName	Varchar	50	User Login Name that has access to Equipment
UserName	Varchar	50	User Name that has access to Equipment
UserEmailAddress	Varchar	300	User email address that has access to Equipment

EquipmentGeolocationHistory

Used for reporting on equipment location details. Geolocation information is provided for map data and visuals.

Field	Data Type	Field Size	Description
EquipmentGeolocationHistoryKey	Unique Identifier	16	Equipment Geolocation History identifier (PK)
GeolocationStatusKey	Integer		Geolocation Status identifier

GeolocationSourceKey	Integer		Geolocation Source identifier
EquipmentKey	Integer		Equipment identifier
TimestampUtc	Date/Time		Timestamp
Location	Geography		Location
LocationDms	Varchar	50	Location DMS
Latitude	Float		Latitude
Longitude	Float		Longitude
Altitude	Float		Altitude
Accuracy	decimal		Accuracy
AltitudeAccuracy	decimal		Altitude accuracy
GeolocationStatus	Varchar	200	Geolocation Status
GeolocationSource	Varchar	200	Geolocation Source

EquipmentTechnicalDetails

The Equipment Technical Details (e.g., License No, Registration No, Tare Weight, etc.) are defined at the Equipment Group level, and they can vary between different client installation. There is no defined set of Equipment technical details other than the Equipment identifier.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.

EquipmentUserSecurity

Data model used to display the equipment each AMT user has access to at a branch, site, and fleet level.

Field	Data Type	Field Size	Description
UserKey	Integer		AMT User identifier
UserLoginName	Varchar	50	AMT User Login Name
UserName	Varchar	50	AMT User Name
UserEmailAddress	Varchar	300	AMT User email address
EquipmentKey	Integer		Equipment identifier user has access to
BranchKey	Integer		Branch identifier for equipment that user has access to
SiteKey	Integer		Site identifier for equipment that user has access to
FleetKey	Integer		Fleet identifier for equipment that user has access to
EqpPlan	Varchar	100	Equipment user has access to
Branch	Varchar	100	Branch for equipment that user has access to
Site	Varchar	50	Site for equipment that user has access to
Fleet	Varchar	50	Fleet for equipment that user has access to

ProjectionHeader

Projection name and term details for each asset in AMT. It also includes the projected end usage and end date.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
EquipmentKey	Integer		Equipment identifier

ProjectionTypeKey	Integer		Projection Type identifier
ProjectionName	Varchar	50	Projection Type name (e.g., Current, Budget, Centreline)
EquipmentTermTypeKey	Integer		Equipment Term Type identifier
EquipmentTermType	Varchar	50	Equipment Term Type
EndUsage	Float		Equipment end usage
EndDate	Date/Time		Equipment end date
UsageProfileKey	Integer		Identifier for usage profile linked to the equipment projection

ProjectionType

Simple data model to display the different projection types. Equipment details can be joined to this view to get the projection type names.

Field	Data Type	Field Size	Description
ProjectionTypeKey	Integer		Projection Type identifier
ProjectionType	Varchar	50	Projection Type name (e.g., Current, Budget, Centreline)

SiteUserSecurity

Simple data model to identify the sites each AMT user has access to. It can be joined to the EquipmentDetails data model to get the site name.

Field	Data Type	Field Size	Description
UserKey	Integer		User identifier
SiteKey	Integer		Site identifier users have access to

UserDetails

Additional AMT user information, displaying the different user roles and the equipment hierarchy they have access to.

Field	Data Type	Field Size	Description
UserKey	Integer		User identifier
UserRoleKey	Integer		User Role identifier
UserRoleName	Varchar	50	User Role
UserRoleDescription	Varchar	1000	User Role description
UserLoginName	Varchar	50	AMT User login name
UserName	Varchar	50	AMT User Name - normally full name
UserEmailAddress	Varchar	300	AMT User email address
BranchKey	Varchar	Max	Branch identifiers the user has access to
SiteKey	Varchar	Max	Site identifiers the user has access to
FleetKey	Varchar	Max	Fleet identifiers the user has access to
Branch	Varchar	Max	Branches the user has access to
Site	Varchar	Max	Sites the user has access to
Fleet	Varchar	Max	Fleets the user has access to

Equipment Statistics Data Model

Contains data models to report on equipment projection start and end usage details for equipment lifecycle data. It also contains a Life Remaining data model to report on term usage and calculated life remaining per equipment.

LifeRemaining

Used to report on equipment total lifecycle cost, total term usage and current life remaining.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy task identifier
EquipmentKey	Integer		Equipment identifier
UOMKey	Integer		Equipment primary UOM identifier
TotalCost	Float		Total equipment cost
TotalCostEsc	Float		Total equipment escalated cost
MaxOccUsage	Float		Usage of last task occurrence
TermUsage	Float		Equipment term usage
LifeRemainingPercent	Float		Life remaining in percentage

Projection

Equipment projection core details, mainly Start and End Usage per unit of measure.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
CurrencyKey	Integer		Site currency identifier
PrimaryUOMKey	Integer		Equipment primary UOM identifier
StartUsagePrimaryUOM	Float		Start usage primary UOM
EndUsagePrimaryUOM	Float		End usage primary UOM
EndUOMKey	Integer		End UOM identifier
StartUsageEndUOM	Float		Start usage UOM identifier
EndUsageEndUOM	Float		End usage UOM identifier

Functional Location Data Model

Used to report on Functional Location details.

FunctionalLocation

Functional Location details, including keys and descriptions.

Field	Data Type	Field Size	Description
FunctionalLocationKey	Integer		Functional location identifier
Name	Varchar	100	Functional location name
Description	Varchar	100	Functional location description
LevelKey	Integer		Functional location level identifier

LevelDescription	Varchar	100	Functional location level description
CategoryKey	Integer		Functional location category identifier
CategoryDescription	Varchar	100	Functional location category description
Terminated	Bit		Functional location terminated flag
ObjectType	Varchar	50	Functional location object type
Model	Varchar	50	Model code
MnfSerialNumber	Varchar	100	Manufacturer serial number
SystemSource	Varchar	10	Functional location system source
ParentFunctionalLocationKey	Integer		Parent functional location identifier

Generic Interface Log Data Model

Contains the Generic Interface Log view to display fields used for the Generic Interface Log report in AMT. The data model can be used to develop a custom Interface Log report.

GenericInterfaceDetailLog

Provides additional interface error log details. Allows further analysis specific to records imported via EPF.

Field	Data Type	Field Size	Description
ImportErrorKey	Integer		Import Error table identifier (PK)
ImportErrorSubKey	Integer		Import Error sub identifier
ErrorDetail	Varchar	5000	Import error description. The reason the record in question failed to process.
LastModifiedDate	Date/Time		Last Modified Date. This indicates the date and time when the record was logged in the Generic Interface Log (i.e., when the error occurred).
ImportErrorSubTypeKey	Integer		Import Error sub-type identifier
ImportErrorSubTypeDescription	Nvarchar	1000	Import Error sub-type description
ImportErrorSubTypeDetailKey	Integer		Import Error Sub Type detail identifier
ImportErrorSubTypeDetailDescription	Nvarchar	2000	Import Error Sub Type Detail description.
AssetKey	Integer		Asset identifier for the record that failed to import
Asset	Nvarchar	100	Asset name for the record that failed to import
SiteKey	Integer		Site identifier for the record that failed to import
Site	Varchar	50	Site name for the record that failed to import

GenericInterfaceLog

Provides Generic Interface Log details including the failed file or message, import record and error descriptions.

Field	Data Type	Field Size	Description
ImportErrorKey	Integer		Import Error table identifier (PK)
ImportFileName	Varchar	1000	The folder path and file name of the interface file for classic integration or the NextGen interface name
ErrorDescription	Varchar	8000	Error description. The reason the record in question failed to process.
LineNo	Integer		Line number from payload or file that failed to process
ImportErrorTypeKey	Integer		Import Error Type description
ImportErrorTypeDescription	Varchar	50	Import Error Type (e.g., Business Rules)

LastModifiedDate	Date/Time		Last Modified Date. This indicates the date and time when the record was logged in the Generic Interface Log (i.e., when the error occurred).
ImportRecord	Varchar	Max	Import Record. For NextGen interface records, this will display the XML payload.
ImportSourceKey	Integer		Import Source identifier
ImportSourceDescription	varchar	100	Import Source description (e.g., file)

Inspection Data Model

Used to report on asset inspection details logged from AMT Mobile.

InspectionDetails

Provides details for each asset inspection performed using AMT Mobile. Provides details of the inspection, type, equipment to which the inspection was performed and employee who made the inspection.

Field	Data Type	Field Size	Description
InspectionTitle	Varchar	100	Equipment inspection title
InspectionTypeKey	Integer		Inspection Type identifier
InspectionType	Varchar	100	Inspection Type name
InspectionStepKey	Integer		Inspection Step identifier
InspectionStepTitle	Varchar	200	Inspection Step Title
SiteKey	Integer		Site identifier. This field can be used to join to the SystemTableDataModel.Site view to get additional Site details.
Site	Varchar	50	Site name
FleetKey	Integer		Fleet identifier. This field can be used to join to the SystemTableDataModel.Fleet view to get additional Fleet details.
Fleet	Varchar	50	Fleet name
EquipmentKey	Integer		Equipment identifier. This field can be linked to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
Equipment	Nvarchar	100	Equipment name
SerialNumber	Varchar	50	Equipment serial number
ModelKey	Integer		Equipment model identifier. This field can be linked to the SystemTableDataModel view to get additional model details.
Model	Varchar	20	Model name
PerformedByEmployeeKey	Integer		Identifier of employee who performed the inspection
PerformedByEmployee	Varchar	61	Name of employee who performed the inspection
DatePerformed	Date/Time		Date when the inspection was performed
InspectionStartDateTime	Date/Time		Date and time when the inspection was started
InspectionEndDateTime	Date/Time		Date and time when the inspection was completed
Duration	Char	8	Duration of the inspection

Notification Data Model

Notifications raised using AMT Mobile. Header and detail views are provided for Notification comments with daily, monthly, quarterly, and yearly snapshots.

Notification

Notification header level view. Provides high level information for notifications such as user, task header, comments and workorder details.

Field	Data Type	Field Size	Description
NotificationKey	Integer		Notification identifier (PK)
EquipmentKey	Integer		Equipment identifier. This field can be linked to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
NotificationAssigneeKey	Integer		Notification Assignee identifier
NotificationStatusKey	Integer		Notification Status identifier
NotificationSourceKey	Integer		Notification Source identifier
NotificationRatingKey	Integer		Notification Rating identifier
TaskHeaderKey	Integer		Task Header identifier. This field can be linked to the SystemTableDataModel.TaskHeader view to get additional Task Header details.
ComponentCodeKey	Integer		Component Code identifier. This field can be linked to the SystemTableDataModel.ComponentCode view to get Component Code details.
ModifierCodeKey	Integer		Modifier Code identifier. This field can be linked to the SystemTableDataModel.ModifierCode view to get Modifier Code details.
TaskTypeKey	Integer		Task Type identifier. This field can be linked to the SystemTableDataModel.TaskType view to get Task Type details.
TaskCounterKey	Integer		Task Counter identifier. This field can be linked to the SystemTableDataModel.TaskCounter view to get Task Counter details.
JobCodeKey	Integer		Job Code identifier. This field can be linked to the SystemTableDataModel.JobCodes view to get Job Code details.
WorkorderKey	Integer		Provides Workorder identifier if one is assigned to the notification
ReviewByKey	Integer		Identifier for user who reviewed the notification
ReviewByAMTUserKey	Integer		Identifier for AMT user who reviewed the notification
CustomerKey	Integer		Customer identifier
Equipment	Nvarchar	100	Equipment name
SerialNumber	Varchar	50	Equipment serial number
Model	Varchar	20	Equipment model name
Site	Varchar	50	Equipment site name
Customer	Varchar	100	Customer name
NotificationNumber	Varchar	100	Notification number
NotificationTitle	Varchar	1000	Notification title
NotificationStatus	Varchar	100	Notification status
NotificationAssignee	Varchar	100	User name to whom the notification is assigned to
NotificationSource	Varchar	100	Notification source (e.g., inspection, CBM, manual)
NotificationRating	Varchar	50	Notification rating (e.g., Ok, Medium Alert, Low Alert)
ComponentCode	Varchar	78	Component Code
ModifierCode	Varchar	103	Modifier Code
TaskType	Varchar	103	Task Type
TaskCounter	Varchar	203	Task Counter
JobCode	Varchar	63	Job Code
EmployeeName	Varchar	61	Employee name
AssignedToPerson	Varchar	100	Name of person notification is assigned to
Counter	Integer		Notification counter

DateRaised	Date/Time		Date when the notification was raised
Age	Integer		Notification age in days
RaisedBy	Varchar	100	Name of AMT user who raised notification
RaisedComments	Varchar	8000	Raised comments
RepairInstructions	Varchar	8000	Repair instructions
LastReviewedByUser	Varchar	50	Name of user who last reviewed notification
ReviewDateTime	Date/Time		Date and time of notification review
WorkorderTitle	Varchar	500	Workorder title if notification is assigned to one
WorkorderNumber	Varchar	150	Workorder number if one is assigned to the notification
WorkorderStatus	Varchar	50	Workorder status if one is assigned to the notification
Measurement	Varchar	41	Associated measurement reading

NotificationComment

Provides Notification comments left by users.

Field	Data Type	Field Size	Description
NotificationCommentKey	Integer		Notification Comment identifier (PK)
NotificationKey	Integer		Notification identifier. This field can be linked to the NotificationDataModel.Notification view to get Notification high level details.
CommentByUserKey	Integer		Identifier of user who posted the notification comment
Comment	Varchar	8000	Notification comment
CommentByUser	Varchar	50	Name of user who posted the notification comment
CommentDateTime	Date/Time		Date and time when comment was published

NotificationDailySnapshot / NotificationMonthlySnapshot / NotificationQuarterlySnapshot / NotificationYearlySnapshot

These views provide snapshots for the state of notification data at different intervals. A view exists for daily, monthly, quarterly (three months) and yearly snapshots. The snapshot views only store record IDs (identifiers) that can be joined to other views to get additional details for each field.

Field	Data Type	Field Size	Description
NotificationKey	Integer		Notification identifier. This field can be used to join to the NotificationDataModel.Notification view to get additional Notification details.
SnapshotDateKey	Integer		Snapshot date in YYYYMMDD format. Monthly, quarterly, and yearly snapshots are taken on the first day of each respected interval.
NotificationRatingKey	Integer		Notification Rating identifier
NotificationStatusKey	Integer		Notification Status identifier
NotificationAssigneeKey	Integer		Notification Assignee identifier
EquipmentKey	Integer		Equipment identifier
CustomerKey	Integer		Customer identifier
NotificationSourceKey	Integer		Notification Source identifier
TaskHeaderKey	Integer		Task Header identifier
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
JobCodeKey	Integer		Job Code identifier
WorkorderKey	Integer		Workorder identifier

ReviewByKey	Integer		Review By identifier
ReviewByAMTUserKey	Integer		Review By AMT User identifier

Occurrence Data Model

Used to report on task occurrences, either actual or forecasted. Useful for producing KPI task compliance reports.

ActualOccurrence

Actual occurrences. Data is mainly based on WO settlements to define when actual occurrences happened and their cost.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
CustomerKey	Integer		Customer identifier
ProjectionKey	Integer		Equipment projection identifier
TaskHeaderKey	Integer		Strategy Task header identifier
StrategyTaskKey	Integer		Strategy Task identifier
PartKey	Integer		Strategy Task Part identifier
CurrencyKey	Integer		Occurrence Cost Currency identifier
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
WorkorderSettlementKey	Integer		Workorder settlement identifier
ParentWorkorderSettlementKey	Integer		Parent workorder settlement identifier
ProjectedOccurrenceKey	Integer		Projected occurrence identifier
OccDate	Integer		Occurrence date
PartsCostEsc	Float		Escalated parts cost at cost
LabourCostEsc	Float		Escalated labour cost at cost
MiscCostEsc	Float		Escalated miscellaneous cost at cost
PartsSellEsc	Float		Escalated parts cost at sell
LabourSellEsc	Float		Escalated labour cost at sell
MiscSellEsc	Float		Escalated miscellaneous cost at sell
Duration	Float		Occurrence task duration
LabourHours	Float		Labour hours
ProjectedCostKey	Integer		Projected cost identifier
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

FutureOccurrence

Future task occurrences. Data is mainly based on Strategy Tasks to define when occurrences are projected to happen and their cost.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
CustomerKey	Integer		Customer identifier
ProjectionKey	Integer		Equipment projection identifier
TaskHeaderKey	Integer		Strategy Task header identifier

StrategyTaskKey	Integer		Strategy Task identifier
PartKey	Integer		Strategy Task Part identifier
CurrencyKey	Integer		Occurrence Cost Currency identifier
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
WorkorderSettlementKey	Integer		Workorder settlement identifier
ParentWorkorderSettlementKey	Integer		Parent workorder settlement identifier
ProjectedOccurrenceKey	Integer		Projected occurrence identifier
OccDate	Integer		Occurrence date
PartsCostEsc	Float		Escalated parts cost@cost
LabourCostEsc	Float		Escalated labour cost@cost
MiscCostEsc	Float		Escalated miscellaneous cost@cost
PartsSellEsc	Float		Escalated parts cost@sell
LabourSellEsc	Float		Escalated labour cost@sell
MiscSellEsc	Float		Escalated miscellaneous cost@sell
Duration	Float		Occurrence task duration
LabourHours	Float		Labour hours
ProjectedCostKey	Integer		Projected cost identifier
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

Occurrence

Combination of the ActualOccurrence and FutureOccurrence datasets, allowing the view of all occurrences for the entire equipment lifecycle (actual and forecasted).

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
CustomerKey	Integer		Customer identifier
ProjectionKey	Integer		Equipment projection identifier
TaskHeaderKey	Integer		Strategy Task header identifier
StrategyTaskKey	Integer		Strategy Task identifier
PartKey	Integer		Strategy Task Part identifier
CurrencyKey	Integer		Occurrence Cost Currency identifier
ShutdownKey	Integer		Shutdown identifier
ProjectCodeKey	Integer		Project Code identifier (related to Plant Hire)
WorkorderSettlementKey	Integer		Workorder settlement identifier
ParentWorkorderSettlementKey	Integer		Parent workorder settlement identifier
ProjectedOccurrenceKey	Integer		Projected occurrence identifier
OccDate	Integer		Occurrence date
PartsCostEsc	Number		Escalated parts cost at cost
LabourCostEsc	Number		Escalated labour cost at cost
MiscCostEsc	Number		Escalated miscellaneous cost at cost
PartsSellEsc	Number		Escalated parts cost at sell
LabourSellEsc	Number		Escalated labour cost at sell
MiscSellEsc	Number		Escalated miscellaneous cost at sell
Duration	Number		Occurrence task duration
LabourHours	Number		Labour hours
ProjectedCostKey	Integer		Projected cost identifier
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier - Can be linked to SystemTableDataModel.MaintenanceOrderType to get Maintenance Order Type details

Quick Watch Data Model

Data Model to retrieve data related to the Quick Watch module in AMT. The Overdue Usage Readings data is provided to report on.

OverdueUsageReadings

Reports on overdue usage readings per equipment, based on the tolerance days for usage reading intervals.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier
LastReadingDateKey	Integer		Last usage reading date identifier
Equipment	Varchar	100	Equipment name
CustomerKey	Integer		Customer identifier
UOMKey	Integer		UOM identifier
ToleranceDays	Float		Tolerance days for usage readings
LastReading	Date / Time		Last usage reading date
Days	Integer		Number of days since last usage reading
DaysOverdue	Float		Number of days overdue since last usage reading

Quote Data Model

Provides high-level and low-level details of quotes created using the AMT Quoter module.

QuoteDetails

Provides low level details of quotes created using the AMT Quoter module. Used to report on details of created sales quotes.

Field	Data Type	Field Size	Description
QuoteKey	Integer		Sales Quote identifier
OrganisationKey	Integer		AMT Organisation identifier
QuoteTypeKey	Integer		Quote Type identifier (e.g., Maintenance Agreement or Service Agreement)
BranchKey	Integer		Equipment branch identifier
ModelKey	Integer		Equipment model identifier
RegisteredEquipmentKey	Integer		Registered equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
ModellingEquipmentKey	Integer		Modelling equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
TemplateCentrelineProjectionKey	Integer		Template Centreline Projection identifier. Used to identify the used Centreline projection.
CustomerKey	Integer		Customer identifier for whom the quote is created for
CreatedByUserKey	Integer		AMT user identifier who created the sales quote
LastModifiedByUserKey	Integer		AMT user identifier who last modified the sales quote
AuthorisedByUserKey	Integer		AMT user identifier who authorised the sales quote
QuoteStatusKey	Integer		Quote Status identifier
PriceGroupKey	Integer		Price Group identifier
BillingMethodKey	Integer		Billing Method identifier

ServicingBranchKey	Integer		Servicing branch identifier
CreatedDateKey	Integer		Create Date in YYYYMMDD format. This can be joined to the SystemTableDataModel.ReportDate view to get different date formats.
LastModifiedDateKey	Integer		Last Modified Date in YYYYMMDD format. This can be joined to the SystemTableDataModel.ReportDate view to get different date formats.
AuthorisationDateKey	Integer		Quote Authorisation Date in YYYYMMDD format. This can be joined to the SystemTableDataModel.ReportDate view to get different date formats.
Quote	Nvarchar	100	Quote name
QuoteType	Varchar	50	Quote Type name
Branch	Nvarchar	100	Branch name
Model	Varchar	20	Model name
RegisteredEquipment	Nvarchar	100	Registered equipment name
Customer	Varchar	100	Customer name
CreatedDate	Date/Time		Quote Create date in standard date/time format
CreatedBy	Varchar	50	Name of AMT user who create the quote
LastModifiedDate	Date/Time		Last Modified date in standard date/time format
LastModifiedBy	Varchar	50	Name of AMT user who last modified the quote
Authorised	Bit		Flag to indicate if quote is authorised or not
AuthorisationDate	Date/Time		Quote authorisation date in standard date/time format
AuthorisedBy	Varchar	50	Name of AMT user who authorised the quote (if authorised)
QuoteStatus	Varchar	100	Quote status
IsAwaitingRegistration	Bit		Flag to indicate if the quote is waiting registration
PriceGroup	Varchar	50	Price Group name
Location	Varchar	100	Location name
CustomerContact	Varchar	100	Customer contact name
IsTravelCostApplied	Bit		Flag to indicate if travel cost is applicable
IsSpecificLabourRatesField	Bit		Flag to indicate if specific labour rates apply
FieldNormalRate	Float		Field normal rate
FieldOvertimeRate	Float		Field overtime rate
FieldOvertimePercentage	Float		Percentage of overtime
IsSpecificLabourRatesShop	Bit		Flag to indicate if this is a specific labour rates shop
ShopNormalRate	Float		Shop normal rate
ShopOvertimeRate	Float		Shop overtime rate
ShopOvertimePercentage	Float		Percentage of shop overtime
DiscountPartsPercentage	Float		Percentage of parts discount
DiscountLabourPercentage	Float		Percentage of labour discount
DiscountMiscPercentage	Float		Percentage of misc. discount
RiskPremiumPercentage	Float		Percentage of risk premium
RiskPremium	Float		Risk premium amount
FreightPercentage	Float		Freight percentage
Notes	Varchar	1000	Quote details notes
AuthorisationComments	Varchar	1000	Authorisation comments. Entered by person who authorised the quote.
AverageTravelHours	Float		Average travel hours
TravelDistance	Float		Travel distance in kms
LabourSharePercentage	Float		Percentage of labour share
SerialNumber	Varchar	50	Serial number
UnitNumber	Varchar	50	Unit number
ContractAmount	Float		Sales contract amount
ContractCost	Float		Contract cost
LubricationCost	Float		Lubrication cost
Age	Integer		Age in days

ReportParameters

Provides high-level quote details used for general reporting of AMT sales quotes.

Field	Data Type	Field Size	Description
QuoteKey	Integer		Quote identifier
EquipmentKey	Integer		Equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails view to get additional equipment details.
Equipment	Nvarchar	100	Equipment name
ProjectionHeaderKey	Integer		Projection header identifier
ModelKey	Integer		Equipment model identifier
Model	Varchar	20	Model name
ModelFamilyKey	Integer		Equipment Group identifier
ModelFamily	Varchar	50	Equipment Group name
FleetKey	Integer		Fleet identifier
Fleet	Varchar	50	Fleet name
SiteKey	Integer		Site identifier
Site	Varchar	50	Site name
BranchKey	Integer		Branch identifier
Branch	Nvarchar	100	Branch name
Dealer	Varchar	50	Dealer name
QuoteTypeKey	Integer		Quote Type identifier
QuoteTypeName	Varchar	50	Quote Type name (e.g., Maintenance Agreement)
EndUsage	Float		Equipment projection end usage
AnnualUsage	Float		Equipment annual usage
EndUOMKey	Integer		Equipment end UOM identifier
EndUOM	Varchar	20	Equipment end unit of measure
DefaultCostBearerKey	Integer		Default Cost Bearer identifier
DefaultCostBearer	Varchar	50	Default Cost Bearer name
Hierarchy	Nvarchar	546	Equipment hierarchy (branch, site, fleet, equipment)
CurrencyKey	Integer		Currency identifier
Currency	Varchar	3	Currency name (e.g., USD).

Standard Job Data Model

Provides views to report on Standard Job details. Views are provided for the Standard Job header, operation, parts, labour, and miscellaneous level.

StandardJob

Provides Standard Job header level information and costs. A Pricing Key field that represents the priced job identifier exists to link the standard job to the corresponding branch and price group.

Field	Data Type	Field Size	Description
StandardJobKey	Integer		Standard Job identifier (primary key field)
ModelKey	Integer		Model identifier. This field can be used to join to the SystemTableDataModel.Model view to get Model details.
ComponentCodeKey	Integer		Component Code identifier. This field can be used to join to the SystemTableDataModel.ComponentCode view to get additional Component Code details.

ModifierCodeKey	Integer		Modifier Code identifier. This field can be used to join to the SystemTableDataModel.ModifierCode view to get additional Modifier Code details.
TaskTypeKey	Integer		Task Type identifier. This field can be used to join to the SystemTableDataModel.TaskType view to get additional Task Type details.
SystemSourceKey	Integer		System Source identifier, which represents the system the Standard Job originated from. This field can be joined to the SystemTableDataModel.SystemSource view to get additional System Source details.
StandardJobBaseCurrencyKey	Integer		Standard Job Currency identifier. This field can be joined to the SystemTableDataModel.Currency view to get additional currency details.
PricingCurrencyKey	Integer		Pricing Job Currency identifier. This is the currency linked to the pricing job.
TaskCounterKey	Integer		Task Counter identifier. This field can be joined to the SystemTableDataModel.TaskCounter view to get additional Task Counter details.
JobCodeKey	Integer		Job Code identifier. This field can be used to join to the SystemTableDataModel.JobCodes view to get additional Job Code details.
MessageGroupKey	Integer		Message Group Identifier. Specifies the Message Group associated to a Standard Job.
PriceGroupKey	Integer		Price Group identifier. This field can be used to join to the SystemTableDataModel.PriceGroup view to get additional Price Group details.
PriceGroup	Varchar	50	Standard Job Price Group name. Based on the Priced Job.
PricingBranchKey	Integer		Pricing Branch identifier. Based on the Priced Job.
PricingBranch	Nvarchar	100	Pricing Branch name. Based on the Priced Job.
PricingKey	Integer		Priced Job identifier. Important field used to identify the Standard Job costs at the pricing branch and price group level.
OrganisationKey	Integer		Organisation identifier. Specifies the organisation that the Standard Job belongs to.
PartPriceStatusKey	Integer		Standard Job Parts Price Status identifier
PartPriceStatus	Varchar	200	Standard Job Parts Price Status name
LabourHours	Float		Standard Job labour hours
TotalCost	Float		Standard Job total cost at the priced job level
DurationHours	Float		Standard Job duration hours
BasePricedJob	Bit		Base Priced Job flag in Standard Job
RequireCalculation	Bit		Flag to indicate if the Priced Job requires calculation
PriceRequired	Bit		Flag to indicate if pricing is required
PriceLastModifiedDate	Date/Time		Indicates the last time the Standard Job price changed
Secured	Bit		Flag to indicate if the Standard Job is secured
AuthorisedGroup	Varchar	50	Authorised Group name
Version	Integer		Standard Job version number
StandardJob	Varchar	500	Standard Job name
DummyJob	Bit		Flag to indicate if the Dummy Job status is enabled
SimulationReference	Varchar	175	Standard Job simulation reference
LastModifiedDate	Date/Time		Standard Job last modified date
StandardJobExternalReference	Varchar	500	Standard Job external reference
OverwriteCosts	Bit		Status of Overwrite All flag
PartsCost	Float		Standard Job parts cost
LabourCost	Float		Standard Job labour cot
MiscCost	Float		Standard Job misc. cost
RequireSTO	Bit		Requires STO flag

StandardJobLogDetails

Tracks changes made to Standard Jobs. The LogEnabled flag needs to be enabled in the AMT_LOG_CONFIG table for the Standard Job entity for AMT to log Standard Job changes.

Field	Data Type	Field Size	Description
LogStandardJobKey	Integer		Standard Job Log identifier
StandardJobKey	Integer		Standard Job identifier. This field can be joined to the StandardJobDataModel.StandardJob to get additional Standard Job details.
StandardJobDescription	Varchar	1000	Standard Job description
StandardJobVersion	Integer		Standard Job version number
Comments	Varchar	1000	Standard Job change log comments
UserName	Varchar	50	AMT user name who made the change to the Standard Job
ModifiedDate	Date/Time		Change date
StandardJobOperationDescription	Varchar	400	Standard Job Operation description
StandardJobOperationType	Varchar	50	Standard Job Operation type
FieldParentId	Integer		Parent field identifier
ParentType	Varchar	50	Standard Job Parent type
FieldParentDescription	Varchar	100	Field parent description
FieldOperationType	Varchar	50	Field operation type
FieldName	Nvarchar	200	Changed field name
OldValue	Nchar	1000	Field's old value (before the change)
NewValue	Nchar	1000	Field's new value (after the change)

StandardJobOperation

Standard Job Operation header details. It also provides the total parts, labour and miscellaneous costs per Standard Job operation.

Field	Data Type	Field Size	Description
StandardJobOperationKey	Integer		Standard Job Operation identifier (PK)
StandardJobKey	Integer		Standard Job identifier. This fields can be used to join to the StandardJobDataModel.StandardJob view to get additional Standard Job details.
PricingKey	Integer		Priced Job identifier
PricingCurrencyKey	Integer		Priced Job Currency identifier
PricingBranchKey	Integer		Priced Job Branch identifier
PricingBranch	Nvarchar	100	Priced Job Branch name
PriceGroupKey	Integer		Price Group identifier
PriceGroup	Varchar	50	Price Group name
OperationComponentCodeKey	Integer		Standard Job Operation Component Code identifier. This field can be used to join to the SystemTableDataModel.ComponentCode view to get additional Component Code details.
OperationJobCodeKey	Integer		Standard Job Operation Job Code identifier. This field can be used to join to the SystemTableDataModel.JobCodes view to get additional Job Code details.
OperationJobLocationKey	Integer		Standard Job Operation Job Location identifier. This field can be used to join to the SystemTableDataModel.JobLocation view to get additional Job Location details.
OperationWorkApplicationKey	Integer		Standard Job Operation Work Application identifier. This field can be used to join to the SystemTableDataModel.WorkApplication view to get the Work Application code.
OperationModifierCodeKey	Integer		Standard Job Operation Modifier Code identifier. This field can be used to join to the SystemTableDataModel.ModifierCode view to get additional Modifier Code details.
OperationJobConditionKey	Integer		Standard Job Operation Job Condition identifier. This field can be used to join to the SystemTableDataModel.JobCondition view to get the Job Condition code.

OperationCabTypeKey	Integer		Standard Job Operation Cab Type identifier.
StandardJobOperationReference	Varchar	50	Standard Job Operation Reference.
StarndardJobOperationDescription	Varchar	500	Standard Job Operation description.
OperationDurationHours	Float		Standard Job Operation duration hours
OperationGroupNo	Varchar	50	Standard Job Operation group number
PartsCost	Float		Standard Job Operation parts cost
LabourCost	Float		Standard Job Operation labour cost
MiscCost	Float		Standard Job Operation misc. cost
Total	Float		Standard Job Operation total cost

StandardJobOperationPart

Standard Job Operation Part details. This view provides labour hours and costs per operation and price job.

Field	Data Type	Field Size	Description
StandardJobOperationPartKey	Integer		Standard Job Operation Part identifier (PK)
StandardJobOperationKey	Integer		Standard Job Operation identifier. This field can be joined to the StandardJobDataModel.StandardJobOperation view to get additional Standard Job Operation details.
PartKey	Integer		Part identifier. This field can be used to join to the SystemTableDataModel.Parts view to get additional Part details.
StandardJobKey	Integer		Standard Job identifier. This fields can be used to join to the StandardJobDataModel.StandardJob view to get additional Standard Job details.
StandardJobOperationPartCostExpenseKey	Integer		Standard Job Operation Part Expense Element identifier. This field can be used to join to the SystemTableDataModel.ExpenseElement view to get additional Expense Element details.
PricingKey	Integer		Priced Job identifier
PricingCurrencyKey	Integer		Priced Job Currency identifier
PriceGroupKey	Integer		Price Group identifier
PriceGroup	Varchar	50	Price Group name
PartPriceKey	Integer		Part Price identifier. Used to get a link to the Part Prices table.
PricingBranchKey	Integer		Priced Job Branch identifier
PricingBranch	Nvarchar	100	Priced Job Branch name
LastModifiedDate	Date/Time		Standard Job Part last modified date
FullCreditFlag	Bit		Specifies full credit type for the part record
Probability	Float		Specifies part usage probability, affecting projected parts costs.
StandardJobOperationPartGroupNo	Varchar	50	Standard Job Operation Part group number
Reference	Varchar	50	Standard Job Part reference
UseCreditPriceFlag	Bit		Flag to indicate whether the credit price is used or not
Quantity	Float		Operation part quantity
PriceStatus	Varchar	13	Part price status
UnitPrice	Float		Part unit price
PartsCost	Float		Total Parts Cost (Unit Price x Quantity)
LastPriceModifiedDate	Date/Time		Last modified date for part price

StandardJobOperationLabour

Standard Job Operation Labour details. This view provides labour hours and costs per operation and price job.

Field	Data Type	Field Size	Description
StandardJobOperationLabourKey	Integer		Standard Job Operation Labour identifier (PK)

StandardJobOperationKey	Integer		Standard Job Operation identifier. This field can be joined to the StandardJobDataModel.StandardJobOperation view to get additional Standard Job Operation details.
LabourActivityKey	Integer		Labour Activity identifier. Used to get the Labour Activity linked to the Labour entry. This field can be used to join to the SystemTableDataModel.LabourActivity view to get additional Labour Activity details.
StandardJobKey	Integer		Standard Job identifier. This field can be used to join to the StandardJobDataModel.StandardJob view to get additional Standard Job details.
PricingKey	Integer		Priced Job identifier.
PricingBranchKey	Integer		Priced Job Branch identifier
PricingBranch	Nvarchar	100	Priced Job Branch name
PricingCurrencyKey	Integer		Priced Job Currency identifier
StandardJobBaseCurrencyKey	Integer		Standard Job base currency identifier
PriceGroupKey	Integer		Price Group identifier. Based on the Priced Job.
PriceGroup	Varchar	50	Price Group name. Based on the Priced Job.
StandardJobOperationLabourCostExpenseKey	Integer		Standard Job Operation Labour Expense Element identifier. This field can be used to join to the SystemTableDataModel.ExpenseElement view to get additional Expense Element details.
Reference	Varchar	50	Standard Job Operation Labour reference
Description	Varchar	50	Standard Job Operation Labour description
LabourHours	Float		Labour hours
LastModifiedDate	Date/Time		Labour hours last changed date
CreateDate	Date/Time		Labour hours created date
LabourRate	Float		Labour rate per hour
LabourCost	Float		Total labour Cost for the operation. Calculated as Labour Hours x Labour Rate per hour

StandardJobOperationMisc

Standard Job Operation Labour details. This view provides labour hours and costs per operation and price job.

Field	Data Type	Field Size	Description
StandardJobMiscKey	Integer		Standard Job Misc Cost identifier (PK)
StandardJobOperationKey	Integer		Standard Job Operation identifier. This field can be joined to the StandardJobDataModel.StandardJobOperation view to get additional Standard Job Operation details.
StandardJobKey	Integer		Standard Job identifier. This field can be used to join to the StandardJobDataModel.StandardJob view to get additional Standard Job details.
MiscCategoryKey	Integer		Misc Category identifier
MiscCategory	Varchar	50	Misc Category name
PricingKey	Integer		Priced Job identifier.
PricingCurrencyKey	Integer		Priced Job Currency identifier
StandardJobBaseCurrencyKey	Integer		Standard Job base currency identifier
PricingBranchKey	Integer		Priced Job Branch identifier
PricingBranch	Nvarchar	100	Priced Job Branch name
PriceGroupKey	Integer		Price Group identifier. Based on the Priced Job.
PriceGroup	Varchar	50	Price Group name. Based on the Priced Job.
StandardJobOperationMiscCostExpenseKey	Integer		Standard Job Operation Misc Expense Element identifier. This field can be used to join to the SystemTableDataModel.ExpenseElement view to get additional Expense Element details.
Description	Varchar	50	Standard Job Misc cost description
Reference	Varchar	50	Standard Job Misc reference
LastModifiedDate	Date/Time		Standard Job Misc entry last modified date

MiscCost	Float		Standard Job Misc cost amount

Stoppages Data Model

Used for reporting on AMT equipment stoppages (events) and downtime. Useful for KPI and equipment availability reports.

StoppagesEvent

Details of AMT events, including event type as well as planned and actual down/up time.

Field	Data Type	Field Size	Description
EventKey	Integer		Event identifier
EquipmentKey	Integer		Equipment identifier. Can be joined to EquipmentDetailsDataModel.EquipmentDetails data model to retrieve additional equipment details.
Description	Varchar	500	Event description
EventStatusKey	Integer		EventStatus identifier. Can be joined to SystemTableDataModel.EventStatus data model to retrieve Event Status code and description.
PriorityKey	Integer		Priority identifier. Can be joined to SystemTableDataModel.Priority data model to get Priority descriptions.
WorkLocationKey	Integer		Work Location identifier. Can be joined to SystemTableDataModel.WorkLocation data model to get Work Location details.
Planned	Bit		Flag to identify if event is planned
BreakDown	Bit		Flag to identify if event is a breakdown
ExpectedUpTime	Date/Time		Event expected up time
Confirmed	Bit		Flag to identify if event is confirmed
EventPreventionKey	Integer		Event Prevention identifier. Can be joined to SystemTableDataModel.EventPrevention to get Event Prevention description.
PlannedDownTime	Date/Time		Event planned down date/time
PlannedDownUsage	Float		Event planned downtime usage reading
PlannedUpTime	Date/Time		Event planned up date/time
PlannedUpUsage	Float		Event planned uptime usage reading
ActualDownTime	Date/Time		Event actual down date/time
ActualDownUsage	Float		Event actual downtime usage reading
ActualUpTime	Date/Time		Event actual up date/time
ActualUpUsage	Float		Event actual uptime usage reading
Notes	Varchar	2500	Event notes
DownDelayNotes	Varchar	1000	Event downtime delay notes
DownDelayHours	Float		Event downtime delay hours
DownDelayId	Integer		Down Delay identifier
EventModeKey	Integer		Event Mode identifier. Can be joined to SystemTableDataModel.EventMode data model to get Event Mode details.
HasDownTime	Bit		Flag to indicate if the event has down time.
NewEvent	Bit		New Event flag
RepairDetails	Varchar	100	Event repair details
UOMKey	Integer		Event UOM identifier. Can be joined to SystemTableDataModel.UOM data model to get UOM details.
ExchangeRateKey	Integer		Exchange Rate identifier

WorkGroupKey	Integer		Work Group identifier. Can be joined to SystemTableDataModel.WorkGroup to get Work Group details.
ShutdownKey	Integer		Shutdown identifier. Can be joined to SystemTableDataModel.Shutdown to get equipment shutdown details.

StoppagesWorkorder

Used to obtain information of workorders that are linked to events.

Field	Data Type	Field Size	Description
EventKey	Integer		Event identifier. Can be joined to StoppagesDataModel.StoppagesEvent to get additional event details.
Redo	Bit		Re-do flag
SourceKey	Integer		Source identifier. Can be joined to SystemTableDataModel.Source to get Source details.
TaskTypeKey	Integer		Task Type identifier. Can be joined to SystemTableDataModel.TaskType to get Workorder Task Type details.
ComponentCodeKey	Integer		Component Code identifier. Can be joined to SystemTableDataModel.ComponentCode to get Workorder Component Code details.
WorkorderKey	Integer		Workorder identifier. This is the identifier of the event workorder. Can be joined to WorkorderDataModel.WorkorderDetails to get additional Workorder details.

StoppagesDowntimeAllocation

Details of event downtime allocations. Mainly used for reporting on downtime responsibilities and metrics associated to them.

Field	Data Type	Field Size	Description
PrimaryDTA	Integer		Flag to indicate if this is the primary downtime allocation
ResponsibilityKey	Integer		Responsibility identifier. Can be joined to SystemTableDataModel.Responsibility to get Responsibility details.
CourseKey	Integer		Identifies task type. Can be joined to SystemTableDataModel.TaskType to get Task Type details.
VarianceCauseKey	Integer		Variance Cause identifier. Can be joined to SystemTableDataModel.VarianceCause to get Variance Cause details.
EventKey	Integer		Event identifier that the Downtime Allocation belongs to.
DowntimeAllocationKey	Integer		Downtime Allocation identifier (PK)
ShutdownKey	Integer		Shutdown identifier. Can be joined to SystemTableDataModel.Shutdown to get equipment shutdown details.
WorkGroupKey	Integer		Work Group identifier. Can be joined to SystemTableDataModel.WorkGroup to get Work Group details.
EquipmentKey	Integer		Equipment identifier. Can be joined to EquipmentDetailsDataModel.EquipmentDetails data model to retrieve additional equipment details.
EventStatusKey	Integer		EventStatus identifier. Can be joined to SystemTableDataModel.EventStatus data model to retrieve Event Status code and description.
PriorityKey	Integer		Priority identifier. Can be joined to SystemTableDataModel.Priority data model to get Priority descriptions.

WorkLocationKey	Integer		Work Location identifier. Can be joined to SystemTableDataModel.WorkLocation data model to get Work Location details.
Planned	Integer		Flag to identify if event is planned
BreakDown	Integer		Flag to identify if event is a breakdown
Confirmed	Integer		Flag to identify if event is confirmed
Redo	Integer		Re-do flag
EventPreventionKey	Integer		Event Prevention identifier. Can be joined to SystemTableDataModel.EventPrevention to get Event Prevention description.
HasDownTime	Integer		Flag to indicate if the event has down time.
NewEvent	Integer		New Event flag
UOMKey	Integer		Event UOM identifier. Can be joined to SystemTableDataModel.UOM data model to get UOM details.
EventModeKey	Integer		Event Mode identifier. Can be joined to SystemTableDataModel.EventMode data model to get Event Mode details.
EventCategoryKey	Integer		Event Category 1 = Planned 2 = Breakdown 3 = Other
Notes	Varchar	500	Event notes
EMIssueReference	Varchar	50	EM Issue reference
EMIssueKey	Integer		EM Issue identifier
SortOrder	Integer		Downtime allocation sort order
SourceKey	Integer		Source identifier. Can be joined to SystemTableDataModel.Source to get Source details.
TaskTypeKey	Integer		Task Type identifier. Can be joined to SystemTableDataModel.TaskType to get Workorder Task Type details.
ComponentCodeKey	Integer		Component Code identifier. Can be joined to SystemTableDataModel.ComponentCode to get Workorder Component Code details.
WorkorderKey	Integer		Workorder identifier. This is the identifier of the event workorder. Can be joined to WorkorderDataModel.WorkorderDetails to get additional Workorder details.
DowntimeDateKey	Integer		Downtime Date in YYYYMMDD format. Can be joined to SystemTableDataModel.ReportDate to get additional date formats.
ActualHours	Float		Actual hours for downtime allocation

Strategy Task Data Model

Used for reporting on AMT Strategy Task details. Views go from strategy task header level to strategy task job to occurrences and cost analysis.

StrategyTask

Details of AMT Strategy Tasks at the header level. Keys and descriptions are provided for some fields to reduce the need for joining with other data models.

Field	Data Type	Field Size	Description
StrategyTaskKey	Integer		Strategy task identifier
EquipmentKey	Integer		Equipment identifier
ProjectionKey	Integer		Equipment projection identifier
TaskHeaderKey	Integer		Strategy Task header identifier

UOMKey	Integer		UOM identifier
UsageOfLastOcc	Float		Usage reading of last occurrence
UsageOfNextOcc	Float		Projected usage reading of next occurrence
ProjectionTypeKey	Integer		Projection Type identifier
DateOfLastOcc	Date/Time		Last occurrence date
DateOfNextOcc	Date/Time		Projected next occurrence date
NextOccurrenceKey	Integer		Next occurrence identifier
CurrentUsage	Float		Equipment current usage reading
LastChangeUsage	Float		Last change usage reading
Unassigned	Integer		Flag to indicate if strategy task is unassigned
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
TaskDescription	Varchar	Max	Strategy Task description
Frequency	Float		Strategy Task frequency
PlanningTask	Bit		Flag to indicate if this is a planned strategy task
PrimaryPartKey	Integer		Primary Part identifier
GroupNumber	Varchar	50	Strategy Task group number
PartClassificationKey	Integer		Part Classification identifier
PartRatingKey	Integer		Part Rating identifier
StrategyTaskDescription	Varchar	100	Strategy Task description
SalesStatusKey	Integer		Sales Status identifier
PurchaseOrderNumber	Varchar	50	Purchase Order number
SalesResponsibility	Varchar	33	Sales Responsibility (employee) name
SalesResponsibilityKey	Integer		Sales Responsibility identifier
OriginalNextOccUsage	Float		Original projected next occurrence usage reading
OriginalNextOcc	Date/Time		Original projected next occurrence date
ReviewStatusKey	Integer		Review Status identifier
ReviewStatus	Varchar	50	Review Status
HealthStatusKey	Integer		Health Status identifier
HealthStatus	Varchar		Health Status
IsOverdue	Bit		Flag to indicate if strategy task is overdue
SuppressionUsageOfLastOcc	Float		Suppression last occurrence usage
SuppressionDateOfLastOcc	Date/Time		Suppression last occurrence date
PurchaseFromDealerPartsProb	Float		Parts purchase from dealer probability in percentage
PurchaseFromDealerLabourProb	Float		Labour purchase from dealer probability in percentage
PurchaseFromDealerMiscsProb	Float		Misc purchase from dealer probability in percentage
NewPurchasePartsProb	Float		New purchase of parts probability
MarketingGrouping	Varchar	603	Marketing Grouping
NotAfter	Float		Strategy Task Final Occurrence (Final Usage or Number of Days depending on UOM-based or Date-based Task)
First	Float		Strategy Task First Occurrence (Usage or Days depending on UOM-based or Date-based Task)
UOM	Varchar	20	Unit of Measure
DefaultLocationForRebuildSiteKey	Integer		Default location for rebuild site identifier
DefaultLocationForRebuildSite	Varchar	50	Default location for rebuild site name
NextLocationForRebuildSiteKey	Integer		Next location for rebuild site identifier
NextLocationForRebuildSite	Varchar	50	Next location for rebuild site name
NextPrimaryPartKey	Integer		Next primary part identifier
NextPartClassificationKey	Integer		Next part classification identifier

ProjTaskModeCode	Varchar	10	Strategy Task mode code
ProjTaskModeDescription	Varchar	50	Strategy Task mode description
IsCapEx	Bit		Indicates if task is a capital expense
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier
MaintenanceOrderType	nvarchar	118	Maintenance Order Type code and description
RequireSTO	Bit		Flag to indicate if STO is required
OperationalCriticalityKey	Integer		Operational Criticality identifier
AssetConditionRating	Integer		Asset Condition Rating
CalculatedRiskRating	Integer		Calculated Risk Rating
EquipmentCriticalityRating	Integer		Equipment Criticality Rating
OverrideRiskGroupKey	Integer		Override Risk Group identifier
RiskGroupKey	Integer		Risk Group identifier
StrategyTaskOperationalCriticalityRating	Integer		Strategy Task Operational Criticality Rating
RiskLastModifiedDate	Date/Time		Risk last changed date
PlanningGroupKey	Integer		Planning Group identifier
PlanningGroup	nvarchar	126	Planning Group code and description
ExternalIdentifier	varchar	100	Strategy Task external identifier
RegulatoryKey	Integer		Regulatory code identifier
RegulatoryCode	nvarchar	20	Regulatory code

StrategyTaskJob

Details of AMT Strategy Tasks job details. Allows the retrieval of cost details, duration, and labour hours for each AMT strategy task.

Field	Data Type	Field Size	Description
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy Task identifier
StrategyTaskJobKey	Integer		Strategy Task Job identifier
StandardJobReference	Text	500	Standard Job reference (allocated to Strategy Task job)
JobCodeKey	Integer		Job Code identifier
PartTypeKey	Integer		Part Type identifier
PricingDate	Integer		Task pricing date
LabourActivityKey	Integer		Labour Activity identifier
ExpenseElementKey	Integer		Expense Element identifier
CostBearerKey	Integer		Cost Bearer identifier
EDCKey	Integer		EDC identifier
CostCentreKey	Integer		Cost Centre identifier
WorkGroupKey	Integer		Work Group identifier
HealthSafetyKey	Integer		Health Safety identifier
TaskHeaderKey	Integer		Strategy Task Header identifier
CostSourceKey	Integer		Cost Source identifier
CurrencyKey	Integer		Job Currency identifier
PartsCostAtCost	Number		Parts cost at cost
LabourCostAtCost	Number		Labour cost at cost
MiscCostAtCost	Number		Miscellaneous cost at cost
PartsCostAtCostEsc	Number		Escalated parts cost at cost
LabourCostAtCostEsc	Number		Escalated labour cost at cost
MiscCostAtCostEsc	Number		Escalated miscellaneous cost at cost
PartsCost	Number		Parts cost at sell
LabourCost	Number		Labour cost at sell

MiscCost	Number		Miscellaneous cost at sell
PartsCostEsc	Number		Escalated Parts cost at sell
LabourCostEsc	Number		Escalated Labour cost at sell
MiscCostEsc	Number		Escalated Miscellaneous cost at sell
LabourHours	Number		Labour hours
Duration	Number		Strategy Task duration
LabourTypeKey	Integer		Labour Type identifier
CostCategoryKey	Integer		Cost Category identifier
CommodityCodeKey	Integer		Commodity Code identifier
BECCodeKey	Integer		BEC Code identifier
SourceOfSupplyKey	Integer		Source of Supply (SOS) identifier

StrategyTaskOccurrence

Details of AMT Strategy Tasks occurrences. Provides the occurrence actual and schedule dates for each strategy task.

Field	Data Type	Field Size	Description
StrategyTaskOccurrenceKey	Integer		Strategy Task Occurrence identifier
EquipmentKey	Integer		Equipment identifier
ProjectionKey	Integer		Equipment projection identifier
StrategyTaskKey	Integer		Strategy Task identifier
OccurrenceDate	Date/Time		Occurrence date
OccurrenceUsage	Float		Occurrence projected usage reading
ScheduledDate	Date/Time		Occurrence scheduled date
ScheduledUsage	Float		Occurrence scheduled usage reading

ComponentLife

Life achieved and life used details for each strategy task. Equivalent fields that use strategy task suppression logic are also provided.

Field	Data Type	Field Size	Description
StrategyTaskKey	Integer		Strategy Task identifier
LastChangeoutSupressionLifeAchived	Float		Last changed component life achieved with suppression logic applied
LastChangeoutLifeAchived	Float		Last changed component life achieved
CurrentSupressionLifeUsed	Float		Component life achieved since last changeout with suppression logic applied
CurrentLifeUsed	Float		Component life achieved since last changeout

CostSource

Provides the list of cost sources for strategy tasks (e.g., standard job, consumables, manual, etc.)

Field	Data Type	Field Size	Description
CostSourceKey	Integer		Strategy Task Cost Source identifier
CostSource	Text	50	Strategy Task cost source (e.g., Cost Allocation, Standard Job).

PrimaryPart

This data model provides detailed information on parts set as primary parts in strategy tasks.

Field	Data Type	Field Size	Description
StrategyTaskKey	Integer		Strategy Task identifier
PartKey	Integer		Strategy Task primary part identifier
Part	Varchar	100	Strategy Task primary part number
PartDescription	Varchar	50	Strategy Task primary part description
PartType	Varchar	10	Strategy Task primary part type
SourceOfSupply	Varchar	50	Primary Part source of supply
PartSuperseded	Bit		Indicates if primary part is superseded
BudgetDeliveryTimeToWorkshop	Float		Projected delivery time to workshop
BudgetTimeWaitingForRebuild	Float		Projected time waiting for rebuild
BudgetRebuildDuration	Float		Projected rebuild duration
BudgetDeliveryTimeToWarehouse	Float		Projected delivery time to warehouse
BudgetTotalTurnTime	Float		Projected total turn time

StatutoryCompliance

This data model provides information on strategy task projected occurrences and when they were performed for compliance requirements.

Field	Data Type	Field Size	Description
StrategyTaskKey	Integer		Strategy Task identifier
Equipment	Varchar	100	Equipment name
EquipmentKey	Integer		Equipment identifier
Fleet	Varchar	50	Fleet name
FleetKey	Integer		Fleet identifier
Site	Varchar	50	Site name
SiteKey	Integer		Site identifier
Branch	Varchar	100	Branch name
BranchKey	Integer		Branch identifier
InspectionTitle	Varchar		Inspection title
ComplianceStatus	Integer		Compliance status based on strategy task last occurrence
LastWorkorderNumber	Varchar	150	Last occurrence workorder number
LastWorkorderKey	Integer		Last occurrence workorder identifier
DateOfNextDue	Date/Time		Strategy Task next due date
DateOfLastPerformed	Date/Time		Strategy Task last performed date
Frequency	Float		Strategy Task frequency
LastPerformed	Float		Strategy Task last performed usage reading
CurrentUsage	Float		Current equipment usage reading
IsOverdue	Bit		Flag to indicate if strategy task is overdue

Timesheet Data Model

Used for reporting on employee rosters and timesheets. This is useful for understanding employee availability and details on their work weeks.

Roster

Employee roster details at the site, work group and employee level. Provides start times and end times for each shift, as well as breaks.

Field	Data Type	Field Size	Description
Employee_Hour_ID	Integer		Employee Hour identifier (PK)
Employee_ID	Integer		Employee identifier. This field can be used to join to the SystemTableDataModel.Employee view to get additional employee details.
From_Time	Date/Time		Start time for an employee shift
To_Time	Date/Time		End time for an employee shift
Break_Start	Date/Time		Time when a shift break starts
Break_Duration	Float		Duration of break in hours
WorkGroup_ID	Integer		Wok Group identifier
Working_Status_ID	Integer		Working Status identifier
Labour_Activity_ID	Integer		Labour Activity identifier
Last_Mod_By_User_ID	Integer		Identifier of AMT user who last modified the roster entry
Last_Mod_Date	Date/Time		Last modified date of roster entry
Create_By_User_ID	Integer		Identifier of AMT user who created the roster entry
Create_Date	Date/Time		Created date of roster entry
Employee_Working_Status	Varchar	50	Working status of employee (e.g., productive, annual leave, sick leave)
SiteKey	Integer		Site identifier of employee
Site	Varchar	50	Site name of employee
WorkGroupCode	Varchar	50	Work Group code
WorkGroupDescription	Varchar	50	Work Group description
LabourActivityCode	Varchar	50	Labour Activity code
LabourActivityDescription	Varchar	50	Labour Activity description

Timesheet

Provides timesheet entries at the work order operation level. This view can be used to report on the employees working on work orders and their associated costs.

Field	Data Type	Field Size	Description
TimesheetKey	Integer		Timesheet identifier (PK)
EmployeeKey	Integer		Employee identifier associated to the timesheet. This field can be used to join to the SystemTableDataModel.Employee view to get additional employee details.
LabourExpenseCodeKey	Integer		Labour Expense Code identifier. This represents the working status such as productive, annual leave, sick leave, etc.
PayTypeKey	Integer		Timesheet pay type identifier. This field can be used to join to the SystemTableDataModel.PayType view to get the Pay Type description (normal, overtime or weekend).
EmployeeConfirmed	Bit		Flag to indicate if the employee has confirmed the timesheet
EmployeeConfirmedTime	Date/Time		Date and time the employee has confirmed the timesheet
SupervisorConfirmed	Bit		Flag to indicate if the employee's supervisor has confirmed the timesheet
SupervisorConfirmedTime	Date/Time		Date and time the employee's supervisor has confirmed the timesheet

SupervisorEmployeeKey	Integer		Employee supervisor identifier. This field can be used to join to the SystemTableDataModel.Employee view to get additional details for the supervisor.
WorkorderKey	Integer		Workorder identifier. Indicates the work order the employee has or will work on.
WorkorderOperationKey	Integer		Work order operation identifier that the employee is allocated to
EventKey	Integer		Event identifier (if one exists) that the work order is assigned to
EquipmentKey	Integer		Equipment identifier for the work order
ParentWorkorderSettlementKey	Integer		Parent WO settlement identifier (if one exists) for the work order the employee is assigned to
DateKey	Integer		Date identifier in YYYYMMDD format. This field can be used to join to the SystemTableDataModel.ReportDate view to get additional date formats.
Hours	Float		Number of hours
LabourRate	Float		Employee labour rate
Cost	Float		Employee labour cost amount
ClockIn	Date/Time		Time when employee clocked in to the job
ClockOut	Date/Time		Time when employee clocked out of the job
PlannedHours	Float		Employee timesheet planned hours
EstimatedEndTime	Date/Time		Timesheet estimated end time

TimesheetEntries

Provides additional timesheet entry details.

Field	Data Type	Field Size	Description
TimesheetKey	Integer		Timesheet identifier (PK)
EmployeeKey	Integer		Employee identifier associated to the timesheet. This field can be used to join to the SystemTableDataModel.Employee view to get additional employee details.
LabourExpenseCodeKey	Integer		Labour Expense Code identifier. This represents the working status such as productive, annual leave, sick leave, etc.
PayTypeKey	Integer		Timesheet pay type identifier. This field can be used to join to the SystemTableDataModel.PayType view to get the Pay Type description (normal, overtime or weekend).
WorkorderKey	Integer		Workorder identifier. Indicates the work order the employee has or will work on.
WorkorderOperationKey	Integer		Work order operation identifier that the employee is allocated to
EventKey	Integer		Event identifier (if one exists) that the work order is assigned to
EquipmentKey	Integer		Equipment identifier for the work order
ParentWorkorderSettlementKey	Integer		Parent WO settlement identifier (if one exists) for the work order the employee is assigned to
DateKey	Integer		Date identifier in YYYYMMDD format. This field can be used to join to the SystemTableDataModel.ReportDate view to get additional date formats.
Hours	Float		Number of hours
LabourRate	Float		Employee labour rate
Cost	Float		Employee labour cost amount
EmployeeConfirmed	Bit		Flag to indicate if the employee has confirmed the timesheet
EmployeeConfirmedTime	Date/Time		Date and time the employee has confirmed the timesheet
SupervisorConfirmed	Bit		Flag to indicate if the employee's supervisor has confirmed the timesheet
SupervisorConfirmedTime	Date/Time		Date and time the employee's supervisor has confirmed the timesheet
TimesheetComments	Varchar	100	User comments added to the timesheet entry
First_Name	Varchar	30	Employee first name
Surname	Varchar	30	Employee surname
Terminated	Bit		Flag to indicate if employee is terminated
Equipment	Nvarchar	144	Equipment name that the timesheet is associated with
EquipmentTypeKey	Integer		Equipment Type identifier

EquipmentTypeName	Varchar	30	Equipment Type name
ParentEquipmentKey	Integer		Parent equipment identifier. This field can be used to join to the EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
ManufacturerKey	Integer		Equipment manufacturer identifier
Manufacturer	Varchar	20	Manufacturer name
SerialNumber	Varchar	50	Serial number
ModelKey	Integer		Equipment model identifier
Model	Varchar	20	Model name
WorkorderSettlementDescription	Varchar	5000	Work Order Settlement description associated to the timesheet entry
OperationDescription	Varchar	200	Work Order Operation description
Description	Varchar	500	Work Order description
WorkorderNumber	Varchar	150	Work Order number
PayType	Varchar	50	Pay Type (normal, overtime, weekend)
LabourExpenseCode	Varchar	50	Labour Expense code. This represents working status such as productive, annual leave, etc.

Utilisation Data Model

Used for reporting on AMT equipment actual and projected utilisation. Useful for finding equipment usage details (valid and invalid) for different units of measures. Equipment Usage Profile details are also provided.

UtilisationEquipmentActualUsage

Equipment actual utilisation. Includes all entered usage readings and reading dates.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can join to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
UOMKey	Integer		UOM identifier. Can join to SystemTableDataModel.UOM to get additional UOM details.
ActualUsageKey	Integer		Actual Usage Reading identifier (PK)
UsageReading	Float		Actual usage reading
ReadingDate	Date/Time		Date of usage reading

UtilisationEquipmentInvalidActualUsage

Invalid usage readings. Includes all entered usage readings marked as invalid by AMT and their corresponding reading dates.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can join to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
UOMKey	Integer		UOM identifier. Can join to SystemTableDataModel.UOM to get additional UOM details.
InvalidUsageKey	Integer		Invalid Usage Reading identifier (PK)
UsageReading	Number		Invalid usage reading value
ReadingDate	Date/Time		Date of usage reading
Model	Text	20	Equipment model code

SerialNumber	Text	50	Equipment serial number

UtilisationEquipmentProjectionUOM

Provides additional equipment utilisation details on top of actual usage readings, such as calculated current usage and forecasted daily utilisation.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can join to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
ProjectionKey	Integer		Equipment projection identifier. Can join to EquipmentDetailsDataModel.ProjectionHeader to get additional equipment projection details.
UOMKey	Integer		UOM identifier. Can join to SystemTableDataModel.UOM to get additional UOM details.
UsageProfileKey	Integer		Usage Profile identifier. Can join to UtilisationDataModel.UtilisationUsageProfile to get additional usage profile details.
StartUsage	Float		Equipment start usage reading
EndUsage	Float		Equipment end usage reading
LastUsageReading	Float		Equipment latest usage reading
LastUsageReadingDate	Date/Time		Equipment latest usage reading date
CalculatedCurrentUsage	Float		Equipment calculated current usage based on usage profile or annual utilisation
QWUsageReadingToleranceDays	Float		Equipment usage reading tolerance days based on Quick Watch. Number of days "tolerated" between usage readings.
CurrentForecastDailyUtilisation	Float		Forecasted daily utilisation based on actual and projected usage readings.
CurrentActualDailyAvgUtilisation90Days	Float		Daily average utilisation based on usage readings entered in the last 90 days.

UtilisationUsageProfile

Usage Profile details. Includes number of equipment projections linked to each usage profile.

Field	Data Type	Field Size	Description
UsageProfileKey	Integer		Usage Profile identifier (PK)
UsageProfile	Varchar	100	Usage Profile name
NumberOfLinkedCurrentProjections	Integer		Number of equipment projections linked to usage profile
CurrentStepEndDate	Date/Time		Specifies the date when the current usage profile step ends.

UtilisationUsageProfileUOM

Provides annualised forecasted usage per equipment and UOM based on current usage profile step.

Field	Data Type	Field Size	Description
UsageProfileKey	Integer		Usage Profile identifier (PK)
UOMKey	Integer		UOM identifier. Can join to SystemTableDataModel.UOM to get additional UOM details.
CurrentStepAnnualisedForecastUsage	Float		Forecasted equipment annual utilisation based on current usage profile step

Workorder Data Model

Used to report on planning workorder details and workorder settlements. WO settlement data models are split into child and parent workorder settlements.

ChildWorkorderSettlement

Workorder settlement details including costs and labour hours. Data model contains both parent and child workorder settlements. Parent WO settlements are identified by the IsParentWorkorderSettlement field.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can join to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
ChildWorkorderSettlementKey	Integer		Child Workorder Settlement identifier
ParentWorkorderSettlementKey	Integer		Parent Workorder Settlement identifier
CostBearerKey	Integer		Cost Bearer identifier
TaskHeaderKey	Integer		Task Header identifier. Can be linked to SystemTableDataModel.TaskHeader to get Task Header details.
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
JobCodeKey	Integer		Job Code identifier
StartDate	Date/Time		Workorder Start Date
WorkorderNumber	Varchar	150	Workorder number
IsParentWorkorderSettlement	Bit		Flag to indicate if WO settlement record is a parent WO settlement
ActualLabourHours	Float		Actual labour hours
ActualDurationHours	Float		Actual duration hours
PartSell	Float		Parts Cost at Sell
LabourSell	Float		Labour Cost at Sell
MiscSell	Float		Miscellaneous Cost at Sell
PartsCostAtCost	Float		Parts Cost at Cost
LabourCostAtCost	Float		Labour Cost at Cost
MiscCostAtCost	Float		Miscellaneous Cost at Cost

ParentWorkorderSettlement

Parent Workorder Settlement details. Parent WO settlements represent actual task occurrences.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can join to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
ParentWorkorderSettlementKey	Integer		Parent WO Settlement identifier
PureWorkorderNumber	Varchar	150	Pure Workorder Number (no suffix)
ParentWorkorderNumber	Varchar	150	Parent Workorder Number
WorkInProgress	Bit		Flag to indicate if workorder is in progress
WorkorderSettlementDescription	Varchar	5000	Workorder Settlement description
TaskHeaderKey	Integer		Task Header identifier. Can be linked to SystemTableDataModel.TaskHeader to get Task Header details
ComponentCodeKey	Integer		Component Code identifier

ModifierCodeKey	Integer		Modifier Code identifier
TaskTypeKey	Integer		Task Type identifier
TaskCounterKey	Integer		Task Counter identifier
JobCodeKey	Integer		Job Code identifier
StartDate	Date / Time		Parent Workorder Start Date
RepairDescription	Varchar	8000	Parent Workorder repair description
UsageAmount	Float		Usage amount at the time when the work order was performed
UOMKey	Integer		Unit of Measure identifier corresponding to the usage amount entered
StatusKey	Integer		WO Settlement status identifier
OccurrenceTypeKey	Integer		Occurrence Type identifier. This field can be joined to the SystemTableDataModel.OccurrenceTypes view to get the Occurrence Type name.
LifeAchieved	Float		Asset life achieved at the time the work order was performed
ExpectedLife	Float		Expected time until the next occurrence. This field is based on the associated strategy task frequency.
MaintenanceOrderTypeKey	Integer		Maintenance Order Type identifier. This field can be joined to the SystemTableDataModel.MaintenanceOrderType view to get Maintenance Order Type details.

WorkorderDetails

Provides details for planning workorders. Most fields in the AMT workorder form can be found in this data model.

Field	Data Type	Field Size	Description
EquipmentKey	Integer		Equipment identifier. Can be joined to EquipmentDetailsDataModel.EquipmentDetails to get additional equipment details.
TaskHeaderKey	Integer		Task Header identifier. Can be joined to SystemTableDataModel.TaskHeader to get additional Task Header details, including 4 codes.
ManufacturerKey	Integer		Manufacturer identifier. Can be joined to SystemTableDataModel.Manufacturer to get Manufacturer code and descriptions.
WorkorderKey	Integer		Workorder identifier (PK)
PriorityKey	Integer		Priority identifier. Can be joined to SystemTableDataModel.Priority to get Priority descriptions.
WorkorderStatusDetailsKey	Integer		WO Status identifier. Can be joined to SystemTableDataModel.TaskStatus to get WO Status descriptions.
WorkorderSourceDetailsKey	Integer		WO Source identifier. Can be joined to SystemTableDataModel.Source to get WO Source details.
DateNotifiedKey	Integer		Workorder date notified in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.
AuthorisedByKey	Integer		Identifier for user who authorised the workorder. Can join to SystemTableDataModel.AMTUser to get user login names.
ActualStartDateKey	Integer		Workorder actual start date in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.
ActualStartDatetimeKey	Integer		Workorder actual start time showing the hour. Can be joined to the SystemTableDataModel.ReportTime data model to get other time formats.
TargetDateKey	Integer		Workorder target date in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.
PerformAtKey	Integer		Workorder Perform at date in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.

WorkgroupKey	Integer		Workgroup identifier. Can be joined to SystemTableDataModel.WorkGroup to get additional work group details.
EmployeeKey	Integer		Employee identifier. Can be joined to SystemTableDataModel.Employee to get employee details.
SettlementDateKey	Integer		Linked WO settlement job date in YYYYMMDD format. Can be linked to WorkorderDataModel.ParentWorkorderSettlement or ChildWorkorderSettlement data models to get WO settlement details.
SymptomKey	Integer		Symptom identifier. Can be joined to SystemTableDataModel.Symptom to get Symptom descriptions.
CauseKey	Integer		Cause identifier. Can be joined to SystemTableDataModel.Cause to get Cause descriptions.
RepairCodeKey	Integer		WO Repair Code identifier.
EMIssueKey	Integer		EM issue identifier. Can be joined to SystemTableDataModel.EMIssue to get EM issue details.
OccurrenceTypeKey	Integer		Occurrence Type identifier Can be joined to SystemTableDataModel.OccurrenceTypes to get Occurrence Type descriptions.
ChangeoutCategorisationCodeKey	Integer		Cahngeout Category Code identifier. Can join to SystemTableDataModel.Changeout Category to get Changeout Category descriptions.
OriginalPartTypeKey	Integer		WO original part type identifier. Can be joined to SystemTableDataModel.PartType to get Part Type details.
WarrantyClaimedByKey	Integer		Warranty Claimed By employee identifier. Can be joined to SystemTableDataModel.Employee to get employee who claimed warranty.
WarrantyClaimedByAMTUserKey	Integer		Warranty Claimed By user identifier. Can be joined to SystemTableDataModel.AMTUser to get user who claimed warranty.
WarrantyClaimDateKey	Integer		Warranty claim date in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.
WarrantyClaimSystemDateKey	Integer		Warranty claim system date in YYYYMMDD format. Can be joined to the SystemTableDataModel.ReportDate data model to get other date formats.
WarrantyClaimStatusKey	Integer		Warranty Claim Status identifier. Can be joined to SystemTableDataModel.ClaimStatus to get Claim Status names.
RebuildPartTypeKey	Integer		WO rebuild part type identifier. Can be joined to SystemTableDataModel.PartType to get Part Type details.
JobReadyStatusKey	Integer		WO Job Ready Status identifier. Can be joined to SystemTableDataModel.JobReadyStatus to get Job Ready Status names.
IsStrategy	Integer		Flag to specify if workorder is linked to a strategy task.
IsConfirmed	Integer		Flag to specify if workorder is confirmed.
PartClassificationKey	Integer		Part Classification identifier. Can be joined to SystemTableDataModel.PartClassification to get Part Classification names.
RebuildPartKey	Integer		WO Rebuild Part identifier. Can be joined to SystemTableDataModel.Parts to get part details.
StrategyPartsSell	Float		Strategy Task Parts cost at sell
StrategyLabourSell	Float		Strategy Task Labour cost at sell
StrategyMiscSell	Float		Strategy Task Misc cost at sell
StrategyLabourHours	Float		Strategy Task Labour hours
PlannedPartsSell	Float		Workorder planned parts cost at sell
PlannedLabourSell	Float		Workorder planned labour cost at sell
PlannedMiscSell	Float		Workorder planned miscellaneous cost at sell
PlannedLabourHours	Float		Workorder planned labour hours
PlannedDuration	Float		Workorder planned duration
ActualPartsSell	Float		Workorder actual parts cost at sell

ActualLabourSell	Float		Workorder actual labour cost at sell
ActualMiscSell	Float		Workorder actual miscellaneous cost at sell
ActualLabourHours	Float		Workorder actual labour hours
ActualDuration	Float		Workorder actual duration
LifeAchieved	Float		Workorder life achieved since last occurrence
UsageAmount	Float		WO usage amount
OverwriteLifeAchieved	Float		WO overwrite life achieved
ReceiptedIntoStock	Bit		Flag to indicate if receipted into stock
DeliveryToWorkshopHours	Float		Delivery to workshop hours
WaitingForRebuildHours	Float		Waiting for rebuild hours
RebuildHours	Float		Rebuild hours
ExpectedLife	Float		Expected life (based on strategy task frequency)
DeliveryToWarehouseHours	Float		Delivery to warehouse hours
EventKey	Integer		Event identifier if WO is linked to an event. Can be joined to StoppagesDataModel.StoppagesEvent to get event details.
StrategyTaskKey	Integer		Strategy Task identifier if workorder is linked to a strategy task. Can be joined to StrategyTaskDataModel.StrategyTask to get strategy task details.
DurabilityIndex	Bit		Durability index.
WorkInProgress	Bit		Flag to indicate if workorder is in progress.
IsInspection	Bit		Flag to indicate if it is an inspection workorder.
InspectionStartDate	Date/Time		Inspection start date
InspectionEndDate	Date/Time		Inspection end date
InspectionTypeKey	Integer		Inspection Type identifier. Can be joined to SystemTableDataModel.InspectionType to get Inspection Type names.
UserDefinedWOStatusKey	Integer		User Defined WO Status identifier. Can be joined to SystemTableDataModel.UserDefinedWOStatus to get user defined WO status descriptions.
ShutdownKey	Integer		Shutdown identifier. Can be joined to SystemTableDataModel.Shutdown to get Shutdown details.
RegulatoryKey	Integer		Regulatory identifier. Can be joined to SystemTableDataModel.Regulatory to get additional Regulatory code and description.
RegulatoryCode	nvarchar		WO Regulatory code.

WorkorderOperations

Provides details for planning workorders at the operation (step) level.

Field	Data Type	Field Size	Description
WorkorderOperationKey	Integer		Workorder Operation identifier
WorkorderKey	Integer		Workorder identifier
ComponentCodeKey	Integer		Component Code identifier
ModifierCodeKey	Integer		Modifier Code identifier
JobCodeKey	Integer		Job Code identifier
CostBearerKey	Integer		Cost Bearer identifier
CostCentreKey	Integer		Cost Centre identifier
PartsCostExpenseKey	Integer		Parts Expense Element identifier
LabourCostExpenseKey	Integer		Labour Expense Element identifier
MiscCostExpenseKey	Integer		Miscellaneous Expense Element identifier
PartsEntryDistributionCodeKey	Integer		Parts Entry Distribution Code identifier
LabourEntryDistributionCodeKey	Integer		Labour Entry Distribution Code identifier
MiscEntryDistributionCodeKey	Integer		Miscellaneous Entry Distribution Code identifier
StrategyTaskJobKey	Integer		Strategy Task Job identifier

WorkGroupKey	Integer		Work Group identifier
HealthSafetyKey	Integer		Health & Safety identifier
LastModifiedByUserKey	Integer		Identifier of user that last modified the Workorder Operation
LastModifiedDate	Date/Time		Last Modified date of Workorder operation
CreatedByUserKey	Integer		Identifier of user that created the Workorder Operation
CreatedDate	Date/Time		Workorder Operation created date
UniqueKey	Varchar	50	Database generated unique key
OperationDescription	Varchar	200	Workorder Operation description
PlannedDuration	Float		Workorder Operation planned duration
ActualDuration	Float		Workorder Operation actual duration
OperationInstructions	Varchar	8000	Workorder Operation instructions
OperationOffset	Float		Workorder Operation offset
SortOrder	Integer		Workorder Operation sort order
Ignore_Operation	Bit		Flag to indicate if Workorder Operation is to be ignored
Completed	Bit		Flag to indicate if Workorder Operation is completed
PartsReturned	Bit		Flag to indicated if the Workorder parts are returned
Exported	Bit		Flag to indicate if Workorder Operation has been exported
OperationWorkStatusKey	Integer		WO Operation Work Status identifier
OperationWorkStatusCode	Varchar	20	WO Operation Work Status code
ResponsibleEmployeeKey	Integer		WO Operation Responsible Employee identifier. Can join to SystemTableDataModel.Employee to get additional employee details.
ResponsibleEmployee	Varchar	61	WO Operation Responsible Employee name

System Table Data Model

The System Table data model contains a set of system table views that can be used with many other AMT entities and data models to get system table item names, descriptions, and other details.

PriceGroup

Different groupings of part prices which may be in existence. For example, a particular customer may receive a 20% discount on the standard list price. In AMT, this arrangement would be represented as a specific parts pricing group.

Field	Data Type	Field Size	Description
PriceGroupKey	Integer		Parts Price Group identifier
OrganisationKey	Integer		Organisation identifier
CurrencyKey	Integer		Parts Price Group Currency identifier
PriceGroup	varchar	50	Parts Price Group name

PartType

Groupings of Parts such as Exchange, New, Reman, Fluid.

Field	Data Type	Field Size	Description
PartTypeKey	Integer		Part Type identifier
PartTypeCode	Varchar	10	Part Type code
PartTypeDescription	Varchar	50	Part Type Description

PartType	Varchar	63	Part Type name

PayType

Provides the Pay Type name from Pay Type identifier.

Field	Data Type	Field Size	Description
PayTypeKey			Pay Type identifier
PayType	Varchar	50	Pay Type name
DefaultRecord			Flag to indicate if this is the default Pay Type record

Priority

Provides Priority long and short descriptions. Can be used to link Priority identifiers from events and workorders.

Field	Data Type	Field Size	Description
PriorityKey	Integer	4	Priority identifier
PriorityDescription	Varchar	50	Priority description
PriorityShortDescription	Varchar	50	Priority short description

WorkLocation

Lists locations where maintenance can be performed.

Field	Data Type	Field Size	Description
WorkLocationKey	Integer		Work Location identifier
SiteName	Varchar	50	Work Location Site Name
WorkLocationDescription	Varchar	20	Work Location description

Shutdown

Provides Shutdown details, including name, description, planned and actual start and end dates, and category.

Field	Data Type	Field Size	Description
ShutdownKey	Integer		Shutdown identifier
ShutdownName	Varchar	50	Shutdown name
ShutdownDescription	Varchar	500	Shutdown description
ShutdownCompleted	Bit		Flag to indicate if the shutdown is completed
Site	Varchar	50	Site name
PlanStartDate	Date / Time		Shutdown planned start date
PlanEndDate	Date / Time		Shutdown planned end date
ActualStartDate	Date / Time		Shutdown actual start date
ActualEndDate	Date / Time		Shutdown actual end date
ShutdownCategory	Varchar	200	Shutdown category

GeolocationStatus

Provides Shutdown details, including name, description, planned and actual start and end dates, and category.

Field	Data Type	Field Size	Description
GeolocationStatusKey	Integer		Geolocation Status identifier
GeolocationStatus	Varchar	200	Geolocation Status

Responsibility

Provides Downtime Responsibility details and flags to indicate if Responsibility entries are either of maintenance or operations type.

Field	Data Type	Field Size	Description
ResponsibilityKey	Integer		Responsibility identifier
ResponsibilityDescription	Varchar	50	Responsibility description (e.g., Dealer, Customer)
ResponsibilityShortDescription	Varchar	50	Responsibility short description
Maintenance	Bit		Flag to indicate of this is a Maintenance responsibility
Operations	Bit		Flag to indicate of this is an Operations responsibility

ComponentCode

Provides Component Code details along with System and Sub System. Component Codes are used in areas of AMT such as Strategy Tasks, Workorders and Standard Jobs.

Field	Data Type	Field Size	Description
CostTypeKey	Integer		Cost Type identifier
CostType	Varchar	50	Cost Type name
SystemKey	Integer		System identifier
System	Varchar	50	System name
SubSystemKey	Integer		Sub System identifier
SubSystem	Varchar	50	Sub System name
ComponentCodeKey	Integer		Component Code identifier
ComponentCodeCode	Varchar	10	Component Code
ComponentCodeDescription	Varchar	65	Component Code description
ComponentCode	Varchar	78	Concatenation of Component Code and Description

LabourExpenseCode

Labour Expense Code information for timesheets and labour grouping.

Field	Data Type	Field Size	Description
LabourExpenseCodeKey	Integer		Labour Expense Code identifier
LabourExpenseCode	Varchar	50	Labour Expense Code
LabourGroupingKey	Integer		Labour Grouping identifier
LabourGrouping	Varchar	50	Labour Grouping name
DefaultRecord	Bit		Flag to indicate default Labour Expense Code record
DisplayVarchar	Varchar	200	Display Varchar
DefaultBeforeClockIn	Bit		Flag to indicate if this is the default code before clock-in
DefaultOnClockIn	Bit		Flag to indicate if this is the default code on clock-in

DefaultOnWorkorderCompletion	Bit		Flag to indicate if this is the default code on workorder completion
NotCosted	Bit		Flag to indicate if Labour Expense code is not costed

SystemSource

System Source details indicating where records originated from for certain entities (e.g. Standard Jobs).

Field	Data Type	Field Size	Description
SystemSourceKey	Integer		System Source identifier
SystemSourceCode	Varchar	20	System Source code
IsAmtSystemSource	Bit		Flag to indicate if it is an AMT System Source
IsUsedAsExternalStandardJobKey	Bit		Flag to indicate if System Source record is used as an external Standard Job key

AssetStatus

Asset Status details at equipment level.

Field	Data Type	Field Size	Description
AssetStatusKey	Integer		Asset Status identifier
AssetStatus	Varchar	100	Asset Status name

Source

Refers to the source of maintenance information when creating a downtime task - e.g.. Reported by the operator, daily inspection, oil sample analysis.

Field	Data Type	Field Size	Description
SourceKey	Integer		Source identifier
SourceDescription	Varchar	50	Source description
DefaultRecord	Integer		Flag to indicate if this is the default Source record
EMIActionTypeKey	Bit		Flag to indicate EMI action type
CustomerReportedIssue	Integer		Customer Reported issue number

AMTUser

Provides user identifier, organisation and login name for each AMT user login.

Field	Data Type	Field Size	Description
UserKey	Integer		AMT User identifier
OrganisationKey	Integer		Organisation identifier for AMT user
LoginName	Varchar	50	AMT user login name

Employee

Provides list and details of employees.

Field	Data Type	Field Size	Description
EmployeeKey	Integer		Employee identifier

EmployeeName	Varchar	61	Employee full name
Site	Varchar	50	Employee site
DefaultWorkGroupKey	Integer		Default employee work group identifier
DefaultWorkGroup	Varchar	50	Default employee work group name
DefaultLabourActivity	Varchar	50	Default employee labour activity
EmployeeWorkingStatus	Varchar	50	Employee working status
EmployeeNumber	Varchar	50	Employee number
ProductSupportSalesRep	Bit		Flag to indicate if employee is a Product Support sales representative
ProductSupportSalesGroup	Varchar	100	Employee product support sales group
AccountManager	Bit		Flag to indicate if employee is an account manager
AccountManagerGroup	Varchar	100	Account Manager group name
PrimeProductSalesPerson	Bit		Flag to indicate if employee is a prime product salesperson
PrimeProductSalesGroup	Varchar	100	Prime Product Sales Group name
IsTerminated	Bit		Flag to indicate if employee is terminated (deactivated)
TerminatedDate	Date / Time		Employee terminated date

TaskPlannedTime

When a Backlog Workorder is registered in AMT, the user can identify when the Backlog Workorder should be executed; typically, the items in the Task Planned Time list aligns to what people can select on their service sheets or work scopes in the field.

Field	Data Type	Field Size	Description
TaskPlannedTimeKey	Integer		Task Planned Time identifier
TaskPlannedTimeDescription	Varchar	50	Task Planned Time description
DefaultRecord	Bit		Flag to indicate default record
PlanDaysOffset	Integer		Planned offset in days

Symptom

The reason used to describe why work is being undertaken on a piece of equipment - e.g. Broken, leaking water / oil.

Field	Data Type	Field Size	Description
SymptomKey	Integer		Symptom identifier
SymptomDescription	Varchar	100	Symptom description
DefaultRecord	Bit		Indicates if record is default Symptom
StrategyDefault	Bit		Identifies default Symptom for strategy tasks

Cause

Used to describe why work is being undertaken on a piece of Equipment.

Field	Data Type	Field Size	Description
CauseKey	Integer		Cause identifier
CauseDescription	Varchar	150	Cause description
DefaultRecord	Bit		Indicates if record is default Cause
StrategyDefault	Bit		Identifies default Cause for strategy tasks
GlobalCauseCode	Varchar	50	Global Cause Code
GlobalCauseCodeDescription	Varchar	50	Global Cause Code Description

OccurrenceTypes

A code that represents "failure mode".

Field	Data Type	Field Size	Description
OccurrenceTypeKey	Integer		Occurrence Type identifier
OccurrenceType	Varchar	63	Occurrence Type name

ChangeoutCategory

Provides list of categories for component changeouts – e.g., End of Life, Swing In, Partial Remove.

Field	Data Type	Field Size	Description
ChangeoutCategoryKey	Integer		Changeout Category identifier
ChangeoutCategory	Varchar	63	Changeout Category name

JobReadyStatus

Provides Job Ready Status colours for planning workorders (yellow, green, blue, orange).

Field	Data Type	Field Size	Description
JobReadyStatusKey	Integer		Job Ready Status identifier
JobReadyStatus	Varchar	6	Job Ready Status name

TaskStatus

Provides list of workorder statuses – e.g., Outstanding, in progress, completed.

Field	Data Type	Field Size	Description
TaskStatusKey	Integer	4	Workorder Status identifier
TaskStatusDescription	Varchar	103	Workorder Status description

Parts

Provides list and details of parts used in AMT.

Field	Data Type	Field Size	Description
PartId	Integer		Part identifier
Part	Varchar	100	Part number
PartDescription	Varchar	50	Part description
PartType	Varchar	10	Part type
SourceOfSupply	Varchar	50	Source of Supply
PartSuperseded	Bit		Indicates if part is superseded
BudgetDeliveryTimeToWorkshop	float		Projected delivery time to workshop
BudgetTimeWaitingForRebuild	float		Projected waiting time for rebuild
BudgetRebuildDuration	float		Projected rebuild duration
BudgetDeliveryTimeToWarehouse	float		Projected delivery time to warehouse
BudgetTotalTurnTime	float		Projected total turnover time
DefaultExpenseElementKey	Integer		Default part expense element identifier

ReportTime

Provides a time conversion table from integer number to AM/PM format.

Field	Data Type	Field Size	Description
ReportTime	Varchar	5	Report time (e.g., 12 PM)
ReportTimeKey	Integer		Report time identifier

Workorder

Provides several planning workorder details not otherwise found in WorkorderDataModel.WorkorderDetails.

Field	Data Type	Field Size	Description
WorkorderKey	Integer		Workorder identifier
Description	Varchar	8000	Workorder description
WorkorderNumber	Varchar	150	Workorder number
CustomerRef	Varchar	100	Customer reference
SymptomComment	Varchar	1000	Symptom comments
RepairComment	Varchar	1000	Repair comments
CauseComment	Varchar	1000	Cause comments
FailedPartNo	Varchar	50	Failed part number
FailedPartNoDescription	Varchar	1000	Failed part description
FailedPartListPosition	Varchar	100	Failed Part List position
FailedPartListGroup	Varchar	100	Failed Part List group
FailedPartLifeAchieved	float		Life achieved of failed part
FailedGroupNo	Varchar	50	Failed group number
FailedGroupNoDescription	Varchar	1000	Failed group description
FailedGroupListPosition	Varchar	100	Failed group list position
FailedGroupPartsListGroup	Varchar	100	Failed group parts list
RebuildJobNumber	Varchar	50	Rebuild job number
EMIssueKey	Integer		EM Issue identifier
WorkorderCause	Varchar	150	Workorder Cause
WorkorderSite	Varchar	50	Workorder Site
SerialNumberOut	Varchar	100	Serial number out for component changeout
RebuildWorkorderLocation	Varchar	50	Rebuild workorder location
DurabilityIndex	Bit		Durability index
WorkInProgress	Bit		Work in Progress
IsStrategy	Bit		Indicates if this is a strategy workorder
IsDefect	Bit		Indicates if workorder is to correct a defect
IsInspection	Bit		Indicates if workorder is an inspection
InspectionStartDate	Date / Time		Inspection start date
InspectionEndDate	Date / Time		Inspection end date
InspectionTypeKey	Integer		Inspection Type identifier

CostCategory

Cost category codes and description (P/L/M – Parts/Labour/Miscellaneous).

Field	Data Type	Field Size	Description
CostCategoryKey	Integer		Cost Category identifier
CostCategoryCode	Varchar	10	Cost Category code

CostCategoryDescription	Varchar	50	Cost Category description

ParentWorkorderSettlement

Quick view to provide a pure and full WO number based on WO key.

Field	Data Type	Field Size	Description
ParentWorkorderSettlementKey	Integer		Parent Workorder Settlement identifier
PureWorkorderNumber	Varchar	150	Pure Workorder number
ParentWorkorderNumber	Varchar	150	Parent Workorder number

SourceOfSupply

Source of Supply details linked to parts used in AMT.

Field	Data Type	Field Size	Description
SourceOfSupplyKey	Integer		Source of Supply identifier
SourceOfSupplyCode	Varchar	50	Source of Supply code
SourceOfSupplyDescription	Varchar	50	Source of Supply description
SourceOfSupply	Varchar	103	Concatenation of Source of Supply name and description

ModifierCode

Code used to provide an additional identification to the Component Code, such as its position on the Equipment. Provides modifier codes and descriptions.

Field	Data Type	Field Size	Description
ModifierCodeKey	Integer		Modifier Code identifier
ModifierCodeCode	Varchar	50	Modifier Code
ModifierCodeDescription	Varchar	50	Modifier Code description
ModifierCode	Varchar	103	Concatenation of Modifier code and description
BudgetCode	Bit		Indicates if Modifier Code is a budget code (to be used in AMT forms)

TaskCounter

Task Counter is the fourth code used to identify a Strategy Task (the other three being Component Code, Modifier Code and Task Type). View provides task counter codes and descriptions.

Field	Data Type	Field Size	Description
TaskCounterKey	Integer		Task Counter identifier
TaskCounter	Varchar	203	Concatenation of Task Counter code and description
TaskCounterCode	Varchar	100	Task Counter code
BudgetCode	Bit		Indicates if Task Counter is a budget code (to be used in AMT forms)

ApplicationSeverity

Provides Application Severity codes at the equipment level. Used as part of the Product Support Marketing (PSM) module.

Field	Data Type	Field Size	Description
ApplicationSeverityKey	Integer		Application Severity identifier
ApplicationSeverityCode	varchar	100	Application Severity code

Region

System table allowing machines to be allocated to a specific region - e.g.: Australia, USA.

Field	Data Type	Field Size	Description
RegionKey	Integer		Region identifier
Region	Varchar	63	Concatenation of Region Code and Description
RegionCode	Varchar	10	Region Code
RegionDescription	Varchar	50	Region Description
Country	Varchar	200	Country
GlobalRegion	Varchar	50	Global Region

Division

System table relating to the area or division within a company structure - e.g.: Operations, Product Support, Heavy Construction.

Field	Data Type	Field Size	Description
DivisionKey	Integer		Division identifier
Division	varchar	63	Concatenation of Division Code and Description
DivisionCode	varchar	10	Division Code
DivisionDescription	varchar	50	Division Description

ReportDate

System table that allows to convert date keys (e.g., 20230110) into different date formats, convert into years, quarters, months, financial year, etc.

Field	Data Type	Field Size	Description
ReportDateKey	Integer		Report Date identifier. Formatted as YYYYMMDD.
DATE	Date/Time		Report Date. Formatted as 2020-01-01 00:00:00.000.
DateDescription	Varchar	200	Report Date description. Formatted as 01-Jan-2020.
CalPeriod	Integer		Calendar period. Formatted as YYYYMM.
CalPeriodDescription	Varchar	200	Calendar period description. Formatted as Jan 2020.
FinPeriod	Integer		Financial period (if different to the calendar period). Formatted as YYYYMM.
FinFeriodDescription	Varchar	8000	Financial period description (if different to the calendar period). Formatted as Jan 2020.
CalQuarter	Integer		Calendar quarter. Formatted as 20201, with 2020 being the year and 1 the first quarter.
CalQuarterDescription	Varchar	200	Calendar quarter description. Formatted as 2020-Q1.
FinQuarter	Varchar	16	Financial quarter (if different to the calendar quarter). Formatted as 20201.

FinQuarterDescription	Varchar	18	Financial period description (if different to the calendar period). Formatted as Jan 2020.
CalYear	Integer		Calendar year. Formatted as YYYY.
CalMonth	Integer		Calendar month. Formatted as M (e.g. 1 being January).
CalMonthDescription	Varchar	200	Calendar month description (e.g. January).
FinYear	Varchar	4	Financial year (if different to the calendar year). Formatted as YYYY.
FinMonth	Varchar	2	Financial month (if different to the calendar month) (e.g. 1 being July).
FinMonthDescription	Varchar	7	Financial month description (if different to the calendar month) (e.g. July).
Day	Integer		Day of the week formatted as number (e.g. 1 being Monday).
DayDescription	Varchar	200	Day of the week description (e.g. Monday).

ReportPeriod

System table that allows to convert report period keys (e.g., 202301) into different period formats, convert into years, quarters, months, financial period, etc.

Field	Data Type	Field Size	Description
ReportPeriodKey	Integer		Report Period identifier. Formatted as YYYYMM.
CalPeriodDescription	Varchar	200	Calendar Period description (e.g., Jun 2020).
FinPeriod	Integer		Financial Period (if different to calendar period). Formatted as YYYYMM.
FinFeriodDescription	Varchar	8000	Financial Period description (if different to the calendar period) (e.g., Jun 2020).
CalQuarter	Integer		Calendar quarter. Formatted as 20201, with 2020 being the year and 1 the first quarter.
CalQuarterDescription	Varchar	200	Calendar quarter description. Formatted as 2020-Q1.
FinQuarter	Varchar	16	Financial quarter (if different to the calendar quarter). Formatted as 20201.
FinQuarterDescription	Varchar	18	Financial period description (if different to the calendar period). Formatted as Jan 2020.
CalYear	Integer		Calendar year. Formatted as YYYY.
CalMonth	Integer		Calendar month. Formatted as M (e.g., 1 being January).
CalMonthDescription	Varchar	200	Calendar month description (e.g., January).
FinYear	Varchar	4	Financial year (if different to the calendar year). Formatted as YYYY.
FinMonth	Varchar	2	Financial month (if different to the calendar month) (e.g., 1 being July).
FinMonthDescription	Varchar	7	Financial month description (if different to the calendar month) (e.g., July).
IsCurrentFinYear	Integer		Flag to indicate if this is the current financial year.
IsCurrentFinPeriod	Integer		Flag to indicate if this is the current financial period.

EquipmentCriticality

Equipment Criticality can be used to classify equipment/assets into critical groups.

Field	Data Type	Field Size	Description
EquipmentCriticalityKey	Integer		Equipment Criticality identifier
EquipmentCriticality	Varchar	63	Concatenation of Equipment Criticality code and description
EquipmentCriticalityCode	Varchar	10	Equipment Criticality code
EquipmentCriticalityDescription	Varchar	50	Equipment Criticality description
EquipmentCriticalityRiskRating	Integer		Equipment Criticality Risk Rating
EquipmentCriticalityIsDefault	Bit		Flag to indicate if this is the Equipment Criticality default record

EquipmentCriticalityInactive	Bit		Flag to indicate if the Equipment Criticality record is inactive

EquipmentLocation

General location of equipment. Usually is not a replication of Branch/Site/Fleet but rather where on site the equipment is operating.

Field	Data Type	Field Size	Description
EquipmentLocationKey	Integer		Equipment Location identifier
EquipmentLocation	Varchar	63	Concatenation of Equipment Location code and description
EquipmentLocationCode	Varchar	10	Equipment Location code
EquipmentLocationDescription	Varchar	50	Equipment Location description

EquipmentCategory

This is a flexible system table that is used for financial reporting. It is set at the Equipment level.

Field	Data Type	Field Size	Description
EquipmentCategoryKey	Integer		Equipment Category identifier
EquipmentCategory	Varchar	103	Concatenation of Equipment Category code and description
EquipmentCategoryCode	Varchar	50	Equipment Category code
EquipmentCategoryDescription	Varchar	50	Equipment Category description

EquipmentClass

This is the system table which contains the highest grouping of equipment.

Field	Data Type	Field Size	Description
EquipmentClassKey	Integer		Equipment Class identifier
EquipmentClass	Varchar	103	Concatenation of Equipment Class code and description
EquipmentClassCode	Varchar	50	Equipment Class code
EquipmentClassDescription	Varchar	50	Equipment Class description

Manufacturer

List of Equipment Manufacturers.

Field	Data Type	Field Size	Description
ManufacturerKey	Integer		Manufacturer identifier
Manufacturer	Varchar	20	Concatenation of Manufacturer code and description
ManufacturerCode	Varchar	2	Manufacturer code
ManufacturerDescription	Varchar	50	Manufacturer description

Model

A specific type of equipment, with similar construction, features and operation, generally a Manufacturer Model.

Field	Data Type	Field Size	Description
ModelKey	Integer		Model identifier
Model	Varchar	20	Model name
ModelDescription	Varchar	8000	Model description
EquipmentGroupKey	Integer		Equipment Group identifier
EquipmentGroup	Varchar	103	Equipment Group name
ManufacturerKey	Integer		Manufacturer identifier
Manufacturer	Varchar	20	Manufacturer name
ManufacturerCode	Varchar	2	Manufacturer code
ManufacturerDescription	Varchar	50	Manufacturer description
AveragePrice	float		Model average price
AverageLocalContent	float		Model average local content
ModelGrouping1	Varchar	100	Optional free text field to specify Model Grouping
ModelGrouping2	Varchar	100	Optional free text field to specify Model Grouping

TaskHeader

List of task header which are the combination of Component Code, Modifier Code, Task Type and Task Counter. Applies to Strategy Tasks, Standard Jobs and Work Orders.

Field	Data Type	Field Size	Description
TaskHeaderKey	Integer		Task Header identifier
CostType	Varchar	50	Cost Type
System	Varchar	50	System
SubSystem	Varchar	50	Sub System
ComponentCode	Varchar	10	Component Code
ComponentCodeGroup	Varchar	30	Component Code Grouping - First digit of numeric component codes
ModifierCode	Varchar	50	Modifier Code
TaskType	Varchar	50	Task Type
TaskCounter	Varchar	100	Task Counter
Description	Varchar	200	Task Header description
PmPlanningTask	Bit		Indicates if Task Header is for a PM Planning task
ComponentChangeout	Bit		Indicates if Task Header is for a component changeout
PmTask	Bit		Indicates if Task Header is for a PM task
Rebuild	Bit		Indicates if Task Header is for a Rebuild task

UOM

Units of Measure (UOMs) are all the potential "usage types" that can be measured for an asset.

Field	Data Type	Field Size	Description
UOMKey	Integer		UOM identifier
UOM	Varchar	20	UOM short description

TaskType

An AMT specific code and description combination, which identifies the general activity to happen at an occurrence of a task.

Field	Data Type	Field Size	Description
TaskTypeKey	Integer		Task Type identifier
TaskTypeCode	Varchar	50	Task Type code
TaskType	Varchar	103	Concatenation of Task Type code and description
PmPlanningTask	Bit		Indicates if Task Type is for PM planning
ComponentChangeout	Bit		Indicates if Task Type is for a component changeout
PmTask	Bit		Indicates if Task Type is for a PM task
Rebuild	Bit		Indicates if Task Type is for a Rebuild task

CostCentre

A Cost Centre will typically refer to an organisational and/or departmental entity of a company and will exist in the company's accounting system. In AMT the Cost Centre can consist of 3 elements - CC Activity, CC Location and CC Responsibility.

Field	Data Type	Field Size	Description
CostCentreKey	Integer		Cost Centre identifier
CostCentre	Varchar	83	Concatenation of Cost Centre code and description
CostCentreCode	Varchar	30	Cost Centre code
CostCentreDescription	Varchar	50	Cost Centre description
CostCentreActivity	Varchar	10	Cost Centre Activity
CostCentreLocation	Varchar	10	Cost Centre Location
CostCentreResponsibility	Varchar	10	Cost Centre Responsibility

ExpenseElement

A system table used for grouping costs for financial reporting purposes. Usually, the Expense Elements will reflect the different category of costs and will exist in the Company's accounting system.

Field	Data Type	Field Size	Description
ExpenseElementKey	Integer		Expense Element identifier
ExpenseElement	Varchar	63	Concatenation of Expense Element code and description
ExpenseElementDescription	Varchar	50	Expense Element description
ExpenseElementCode	Varchar	10	Expense Element code
ExpenseElementDepreciation	Bit		Indicates if this is a depreciation Expense Element
ExpenseElementOwnership	Bit		Indicates if this is an ownership Expense Element
ExpenseElementCBD	Bit		Indicates if this is an CBD Expense Element
Inactive	Bit		Indicates if Expense Element is inactive
StandardJobPartsDefault	Bit		Indicates if this is the default Expense Element for Standard Job parts
StandardJobLabourDefault	Bit		Indicates if this is the default Expense Element for Standard Job labour
StandardJobMiscDefault	Bit		Indicates if this is the default Expense Element for Standard Job miscellaneous
GlobalExpenseElementCode	Varchar	10	Global Expense Element code
GlobalExpenseElementDescription	Varchar	50	Global Expense Element description
GlobalExpenseElement	Varchar	63	Concatenation of Global Expense Element code and description

CostBearer

A system table used for grouping costs to parties responsible for them.

Field	Data Type	Field Size	Description
CostBearerKey	Integer		Cost Bearer identifier
CostBearer	Varchar	63	Concatenation of Cost Bearer code and description
CostBearerDescription	Varchar	50	Cost Bearer description
DefaultValue	Bit		Indicates the default Cost Bearer
CostBearerCode	Varchar	10	Cost Bearer code

WorkGroup

Contains Work Groups (teams of Employees) that may be responsible for executing work orders on specific sites.

Field	Data Type	Field Size	Description
WorkGroupKey	Integer		Work Group identifier
SiteKey	Integer		Site identifier
Site	Varchar	50	Site name
WorkGroupCode	Varchar	50	Work Group code
WorkGroupDescription	Varchar	50	Work Group description
WorkGroup	Varchar	103	Concatenation of Work Group code and description

LabourActivity

A description of types of Labour.

Field	Data Type	Field Size	Description
LabourActivityKey	Integer		Labour Activity identifier
LabourActivityCode	Varchar	50	Labour Activity code
LabourActivityDescription	Varchar	50	Labour Activity description
LabourActivity	Varchar	103	Concatenation of Labour Activity code and description
DefaultExpenseElementKey	Integer		Indicates default Expense Element identifier for Labour Activity record

PartClassification

Parts classification is a system table that allows users to define the relevant approach for rebuilding rotable components. It is particularly important for the component capacity management functionality as you can define which rotable component cores are retained in the system vs those that leave the system. It also allows you to produce forecasts by supplier or specific rebuild centre.

Field	Data Type	Field Size	Description
PartClassificationKey	Integer		Part Classification identifier
PartClassification	Varchar	50	Part Classification name
CoreRetained	Bit		Indicates Core Retained

PartRating

Part Rating is designed to capture a comparison attribute of the component (e.g., if the component code is Pump, then Part Rating could be 250kw).

Field	Data Type	Field Size	Description
PartRatingKey	Integer		Part Rating identifier
PartRating	Varchar	50	Part Rating name

JobCodes

Lists the types of jobs that can be performed when a Workorder is executed.

Field	Data Type	Field Size	Description
JobCodesKey	Integer		Job Code identifier
JobCodesCode	Varchar	10	Job Code
JobCodesDescription	Varchar	50	Job Code description
JobCodes	Varchar	63	Concatenation of Job Code and Job Code description
BudgetCode	Bit		Indicates if this is a budget code to be available in AMT forms

MaintenanceType

A high-level maintenance code used for reporting purposes. Also known as Cost Activity.

Field	Data Type	Field Size	Description
CostActivityKey	Integer		Cost Activity identifier
CostActivityCode	Varchar	10	Cost Activity code
CostActivityDescription	Varchar	50	Cost Activity description
CostActivity	Varchar	63	Concatenation of Cost Activity code and description

CostResponsibility

A high-level system table that defines the responsibility for Equipment.

Field	Data Type	Field Size	Description
CostResponsibilityKey	Integer		Cost Responsibility identifier
CostResponsibility	Varchar	103	Concatenation of Cost Responsibility code and description
CostResponsibilityCode	Varchar	50	Cost Responsibility code
CostResponsibilityDescription	Varchar	50	Cost Responsibility description

CostActivity

A high-level system table that defines Cost Activities.

Field	Data Type	Field Size	Description
CostActivityKey	Integer		Cost Activity identifier
CostActivity	Varchar	63	Concatenation of Cost Activity code and description
CostActivityCode	Varchar	10	Cost Activity code
CostActivityDescription	Varchar	50	Cost Activity description

ReportCalendar

System table to define custom reporting calendars.

Field	Data Type	Field Size	Description
ReportCalendarKey	Integer		Report Calendar identifier
CalendarName	Varchar	500	Report Calendar name
CalendarFullName	Varchar	522	Concatenation of Report Calendar name and period
CalendarPeriod	Varchar	20	Report Calendar period
StartDate	Date/Time		Report Calendar period start date
EndDate	Date/Time		Report Calendar period end date

Branch

Branches are the centre responsible for the management of a group of sites. They are the top of the AMT equipment hierarchy.

Field	Data Type	Field Size	Description
BranchKey	Integer		Branch identifier
Branch	Varchar	100	Branch name
BranchCode	Varchar	50	Branch code
OrganisationKey	Integer		Organisation identifier
EnableAutoWOCreate	Bit		Flag to indicate branch is enabled for Auto Create workorder functionality
WorkorderSuffix	Varchar	50	Workorder number suffix to be added to workorders under this branch

Currency

Lists all the currencies that could be used by an organisation for transactions. These currencies are set up in AMT during installation and should only be changed in consultation with RPMGlobal.

Field	Data Type	Field Size	Description
CurrencyKey	Integer		Currency identifier
CurrencyCode	Varchar	3	Currency code
CurrencyDescription	Varchar	50	Currency description
Currency	Varchar	56	Concatenation of Currency code and description
PrimaryCurrency	Integer		Indicates if this is the primary currency

OperationWorkStatus

The Operation Work Status is used to identify different statuses for a work operation. Operation Work Status allow mobile users to redirect work order operations and alert supervisors and the next shift work group of a work order operation's progress.

Field	Data Type	Field Size	Description
OperationWorkStatusKey	Integer		Operation Work Status identifier (PK)
OperationWorkStatusCode	Nvarchar	20	Operation Work Status Code
OperationWorkStatusDescription	Nvarchar	126	Concatenation of Operation Work Status code and description
OrganisationKey	Integer		Organisation identifier

Usage Profile Data Model

The Usage Profile data model provides access to top level usage profile details, usage steps assigned to any profile as well as usage profile parent and child relationship details.

UsageProfile

List of Usage Profiles names and hierarchy levels.

Field	Data Type	Field Size	Description
UsageProfileKey	Integer		Usage Profile identifier (PK)
UsageProfileName	Varchar	100	Usage Profile name
HierarchyLevelKey	Integer		Usage Profile parent-child hierarchy level

UsageStep

List of Usage Profiles names and hierarchy levels.

Field	Data Type	Field Size	Description
UsageStepKey	Integer		Usage Step identifier (PK)
UsageStepDescription	Varchar	50	Usage Step description
UsageProfileKey	Integer		Usage Profile identifier. This field can be used to join to the UsageProfileDataModel.UsageProfile view to get the Usage Profile name.
UsageStepStartDate	Date/Time		Usage Profile Step start date
UsageStepEndDate	Date/Time		Usage Profile Step end date
UsageStepStatusKey	Integer		Usage Profile Step Status identifier

UsageProfileParentChildRelationship

Identifies the Usage Profile parent and child relationships and the usage amount per child.

Field	Data Type	Field Size	Description
UsageProfileRelationshipKey	Integer		Usage Profile Relationship identifier (PK)
UsageStepKey	Integer		Usage Step identifier
ParentQUOMKey	Integer		Parent UOM identifier. This field can be used to join to the SystemTableDataModel.UOM view to get additional UOM details for the parent UOM.
ChildQUOMKey	Integer		Child UOM identifier. This field can be used to join to the SystemTableDataModel.UOM view to get additional UOM details for the child UOM.
ChildUsagePerParent	Float		Child usage per parent UOM

UsageProfileStepAmounts

Details usage step amounts for usage profiles.

Field	Data Type	Field Size	Description
UsageProfileAmountKey	Integer		Usage Profile Step Amount identifier (PK)
UsageStepKey	Integer		Usage Profile Step identifier
UsageQUOMKey	Integer		Usage UOM identifier. This field can be used to join to the SystemTableDataModel.UOM view to get additional UOM details.
UsagePerCalendarYear	Float		Details usage amounts per calendar year

Universal Logging Data Model

The Universal Logging data model provides a way to report on or retrieve logged changes to several AMT entities, using Change Data Capture (CDC). Logs include work order, strategy task, equipment details, standard job changes among others. The Generic Logging system task must be enabled and running

AuditLogEvent

Header details for AMT logged changes. Provides the entity names, type of change, user, and time of change.

Field	Data Type	Field Size	Description
AuditLogEventKey	Integer		Audit Log Event identifier (PK)
AuditLogEntityTypeKey	Integer		Audit Log Entity Type identifier.
AuditLogUserKey	Integer		Audit Log user identifier. This identifies the AMT user who made the change.
AuditLogOrganisationKey	Integer		Audit Log Organisation identifier. Identifies the AMT organisation the user and changed entities are under.
AuditLogEntityKey	Integer		Audit Log entity identifier
User	Varchar	50	AMT user name of use who made the change
Organisation	Varchar	100	AMT organisation name
EntityName	Nvarchar	100	Entity name (e.g., Workorder or Strategy Task)
EntityDescription	Nvarchar	2112	Entity description. Provides further details for entity such as WO number or external identifiers.
Action	Varchar	13	Type of action taken, such as Update or Delete.
EventTime	Date/Time		Time when the change occurred
Source	Nvarchar	20	Source of logging (e.g., CDC)

AuditLogEventDetail

Provides details (i.e., old values and new values) of logged changes recorded in the AuditLogEvent view.

Field	Data Type	Field Size	Description
AuditLogEventKey	Integer		Audit Log Event identifier. This field can be used to join to the AuditLogEvent view to get the main details of logged changes.
AuditLogEventDetailKey	Integer		Audit Log Event Detail identifier (PK)
Attribute	Nvarchar	100	This specifies the field for which the change was logged (e.g., WO description)
NewValue	Nvarchar	1000	New value after change
OldValue	Nvarchar	1000	Old value before change