## 1 Anexos

## 1.1 Main

```
#include "max7219.h"
#include "utils.h"
#include "drawing.h"
\#include <msp430g2553.h>
#include <legacymsp430.h> // Para rodar interrupcoes
/*
                 MSP430G2553
             | VCC
                             GND
RIGHT\_BTN-->|P1.0|
                             XIN
             | P1.1
                            XOUT
             | P1.2
                             TST
      DIN < --|P1.3
                             RST
        CS < --|P1.4|
                            P1.7 < -STOP\_BTN
      CLK < --|P1.5|
                            P1.6 < -LEFT_BTN
             P2.0
                            P2.5
                            P2.4|
              P2.1
             P2.2
                            P2.3
*/
int main(){
  WDTCTL = WDIPW + WDTHOLD; // Desabilita WDT
                              // 1 Mhz DCO
  DCOCTL = CALDCO\_1MHZ;
  BCSCTL1 = CALBC1_1MHZ;
  initialise();
  setTestMode(0);
  setShutdown(0);
  setBrightness (0 xff);
  showDigits(8);
  configure_buttons();
  __enable_interrupt();
```

```
clear_screen();
  while (1) {
    ahead_arrow();
  return 0;
#pragma vector=PORT1_VECTOR
__interrupt void Port_1(void){
  if (P1IFG & RIGHT_BTN){
    while (!(P1IN \& RIGHT\_BTN)==0){
      right_arrow();
    P1IFG &= ~RIGHT_BTN;
  if (P1IFG & LEFT_BTN) {
    while (!( P1IN & LEFT_BTN)==0){
      left_arrow();
    P1IFG &= ~LEFT_BTN;
  if(P1IFG & STOP_BTN){
    while ((P1IN \& STOP\_BTN)==0){
      delay (20);
      stop();
    P1IFG &= ~STOP_BTN;
  return 0;
1.2
     MAX7219
#include "max7219.h"
#include "utils.h"
\#include <msp430g2553.h>
#define MAX7219_DIN BIT3
#define MAX7219_CS
```

```
static void MAX7219_SendByte (unsigned char dataout)
  char i;
  for (i=8; i>0; i--) {
    unsigned char mask = 1 \ll (i - 1);
    P1OUT &= ^{\sim} (MAX7219_CLK);
    if (dataout & mask)
      P1OUT \mid = MAX7219\_DIN;
    else
      P1OUT &= ^{\sim} (MAX7219_DIN);
    P1OUT \mid = MAX7219\_CLK;
  }
}
void initialise(){
 P1OUT \mid = MAX7219_{CS};
  P1DIR \mid = MAX7219\_DIN;
  P1DIR \mid = MAX7219_{CS};
  P1DIR \mid = MAX7219\_CLK;
  output (0x0b, 7);
  output (0x09, 0x00);
}
void output(char address, char data){
 P1OUT \mid = MAX7219_{CS};
  MAX7219_SendByte(address);
  MAX7219_SendByte(data);
 P1OUT &= ^{\sim} (MAX7219_CS);
 P1OUT \mid = MAX7219_{CS};
}
void setTestMode(int on){
  output (0x0f, on ? 0x01 : 0x00);
}
```

```
void setShutdown(int off){
  output (0x0c, off ? 0x00 : 0x01);
void showDigits(char numDigits){
  output (0x0b, numDigits -1);
void setBrightness(char brightness){
  output(0x0a, brightness);
void put_byte(char data) {
  char i = 8;
  char mask;
  \mathbf{while}(i > 0) {
    mask = 0x01 << (i - 1);
    P1OUT &= ^{\sim} (MAX7219_CLK);
    if (data & mask){
      P1OUT = MAX7219_DIN;
    }else{
      P1OUT &= (MAX7219_DIN);
    P1OUT \mid = MAX7219\_CLK;
    —i;
  }
}
void max_single(char reg, char col) {
  P1OUT &= ^{\sim} (MAX7219_CS);
  put_byte(reg);
  //asm("mov.w reg, R15");
  //asm("call \#putByte");
  //asm("pop R15");
  put_byte(col);
  P1OUT &= ^{\sim}(MAX7219_{CS});
  P1OUT \mid = (MAX7219\_CS);
}
```

void write8x8(char a, char b, char c, char d, char e, char f, char g,

```
\max_{single} (1, a);
  \max_{single} (2,b);
  \max_{single} (3, c);
  \max_{single} (4,d);
  \max_{single} (5, e);
  \max_{single} (6, f);
  \max_{single} (7, g);
  \max_{single} (8,h);
  delay (5000);
}
1.3
     Drawning
#include "drawing.h"
#include "utils.h"
#include "max7219.h"
void stop(){
  write8x8 (0x0, 0x42, 0x24, 0x18, 0x18, 0x24, 0x42, 0x0);
  delay (10000);
  write8x8(0xff,0xbd,0xdb,0xe7,0xe7,0xdb,0xbd,0xff);
  delay (10000);
}
void left_arrow(){
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x0);
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x18);
  write8x8 (0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x18,0x3c);
  write8x8(0x0,0x0,0x0,0x0,0x0,0x18,0x3c,0x7e);
  write8x8(0x0,0x0,0x0,0x0,0x18,0x3c,0x7e,0xff);
  write8x8(0x0,0x0,0x0,0x18,0x3c,0x7e,0xff,0x18);
  write8x8(0x0,0x0,0x18,0x3c,0x7e,0xff,0x18,0x18);
  write8x8(0x0,0x18,0x3c,0x7e,0xff,0x18,0x18,0x18);
  write8x8 (0x18,0x3c,0x7e,0xff,0x18,0x18,0x18,0x18);
  write8x8 (0x18,0x3c,0x7e,0xff,0x18,0x18,0x18,0x18);
  write8x8(0x3c,0x7e,0xff,0x18,0x18,0x18,0x18,0x0);
  write8x8 (0x7e, 0xff, 0x18, 0x18, 0x18, 0x18, 0x0, 0x0);
  write8x8(0xff,0x18,0x18,0x18,0x18,0x0,0x0,0x0);
  write8x8(0x18,0x18,0x18,0x18,0x18,0x0,0x0,0x0,0x0);
  write8x8(0x18,0x18,0x18,0x0,0x0,0x0,0x0,0x0);
  write8x8(0x18,0x18,0x0,0x0,0x0,0x0,0x0,0x0);
```

```
write8x8 (0x18, 0x0, 0x0, 0x0, 0x0, 0x0, 0x0, 0x0);
void right_arrow(){
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x0);
  write8x8(0x18,0x0,0x0,0x0,0x0,0x0,0x0,0x0);
  write8x8(0x3c,0x18,0x0,0x0,0x0,0x0,0x0,0x0);
  write8x8 (0 \times 7e, 0 \times 3c, 0 \times 18, 0 \times 0, 0 \times 0, 0 \times 0, 0 \times 0, 0 \times 0);
  write8x8 (0xff, 0x7e, 0x3c, 0x18, 0x0, 0x0, 0x0, 0x0);
  write8x8(0x18,0xff,0x7e,0x3c,0x18,0x0,0x0,0x0);
  write8x8(0x18,0x18,0xff,0x7e,0x3c,0x18,0x0,0x0);
  write8x8 (0x18,0x18,0x18,0xff,0x7e,0x3c,0x18,0x0);
  write8x8 (0x18,0x18,0x18,0x18,0x18,0xff,0x7e,0x3c,0x18);
  write8x8(0x18,0x18,0x18,0x18,0x18,0xff,0x7e,0x3c,0x18);
  write8x8 (0x0,0x18,0x18,0x18,0x18,0x18,0xff,0x7e,0x3c);
  write8x8 (0x0,0x0,0x18,0x18,0x18,0x18,0x18,0xff,0x7e);
  write8x8 (0x0,0x0,0x0,0x18,0x18,0x18,0x18,0xff);
  write8x8(0x0,0x0,0x0,0x0,0x18,0x18,0x18,0x18);
  write8x8(0x0,0x0,0x0,0x0,0x0,0x18,0x18,0x18);
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x18,0x18);
  write8x8 (0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x18);
}
void ahead_arrow(){
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x0);
  write8x8(0x0,0x0,0x0,0x80,0x80,0x0,0x0,0x0);
  write8x8 (0x0,0x0,0x80,0xc0,0xc0,0x80,0x0,0x0);
  write8x8(0x0,0x80,0xc0,0xe0,0xe0,0xc0,0x80,0x0);
  write8x8(0x80,0xc0,0xe0,0xf0,0xf0,0xe0,0xc0,0x80);
  write8x8(0x40,0x60,0x70,0xf8,0xf8,0x70,0x60,0x40);
  write8x8 (0x20, 0x30, 0x38, 0xfc, 0xfc, 0x38, 0x30, 0x20);
  write8x8 (0x10,0x18,0x1c,0xfe,0xfe,0xfc,0x1c,0x18,0x10);
  write8x8 (0x8, 0xc, 0xe, 0xff, 0xff, 0xe, 0xc, 0x8);
  write8x8(0x8,0xc,0xe,0xff,0xff,0xe,0xc,0x8);
  write8x8(0x4,0x6,0x7,0x7f,0x7f,0x7,0x6,0x4);
  write8x8(0x2,0x3,0x3,0x3f,0x3f,0x3f,0x3,0x3);
  write8x8(0x1,0x1,0x1,0x1f,0x1f,0x1f,0x1,0x1,0x1);
  write8x8(0x0,0x0,0x0,0xf,0xf,0xf,0x0,0x0,0x0);
  write8x8(0x0,0x0,0x0,0x7,0x7,0x7,0x0,0x0,0x0);
  write8x8(0x0,0x0,0x0,0x3,0x3,0x0,0x0,0x0);
  write8x8(0x0,0x0,0x0,0x1,0x1,0x0,0x0,0x0);
```

```
}
1.4
     Utils
#include "utils.h"
#include "max7219.h"
\#include <msp430g2553.h>
void delay(volatile unsigned int i){
  while ((i --)>0);
void clear_screen(){
  write8x8(0x0,0x0,0x0,0x0,0x0,0x0,0x0,0x0); // Cleaning screen
void configure_buttons(){
  P1DIR &= ~(RIGHT_BTN + LEFT_BTN + STOP_BTN); //Seta como entrada 0 =
  P1OUT &= ~(RIGHT_BTN + LEFT_BTN + STOP_BTN); // Desliga ambos os leds
  P1IE \mid = (RIGHT\_BTN + LEFT\_BTN + STOP\_BTN);
  P1IFG \&= (RIGHT_BTN + LEFT_BTN + STOP_BTN);
  P1REN = (RIGHT_BTN + LEFT_BTN + STOP_BTN);
  P1IES = (RIGHT_BTN + LEFT_BTN + STOP_BTN);
}
```