

ENAT RNP RWY 11 - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
010	IF	RIXIB	-	-	-12.0	-	-	-	A5000+	K230-	-	-	1.0
020	TF	OGDOL	-	-	-12.0	5.0	-	-	A5000+	K230-	-	-	1.0
010	IF	EKTOX	-	-	-12.0	-	-	-	A5000+	K230-	-	-	1.0
020	TF	OGDOL	-	-	-12.0	5.0	-	-	A5000+	K230-	-	-	1.0
010	IF	OGDOL	-	-	-12.0	-	-	-	A5000+	K230-	-	-	1.0
020	TF	AT420	-	-	-12.0	4.7	-	-	A4000+	-	-	-	1.0
030	TF	RW11	Y	-	-12.0	10.6	-	-	-	-	-3.5/50	-	0.3
040	TF	ATMOM	-	-	-12.0	10.4	-	-	-	K185-	-	-	1.0
050	HM	ATMOM	-	144 (156.2)	-12.0	1 MIN	-	R	A5000	-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.

Note: OGDOL holding not included in standard APCH transitions.