Module 2

"Data Binding Properties"





- Data Binding
- Data Conversion
- Validation
- Change Notification



The **Binding** Class

- ▶ Binding
 - ElementName, Source, RelativeSource
 - Path
 - XPath
 XML sources
 - Mode
 - Delay
 - NotifyOnSourceUpdated SourceUpdated event

 - FallbackValue + TargetNullValue
- Binding can be set
 - Declaratively in XAML
 - Full syntax or markup extension syntax "{}"
 - Programmatically in code
- Bindings can be cleared (in code) via BindingOperations.ClearBinding()



RelativeSource

- You can bind to another element in the visual tree relative to the element being bound
 - use the **RelativeSource** property

▶ RelativeSource

- Mode
 - FindAncestor
 - AncestorType
 - AncestorLevel
 - Self
 - PreviousData
 - TemplatedParent



Data Context

- It is possible to bind to CLR objects by
 - Referencing the namespace and assembly
 - Setting the **Binding.Source** property
- ▶ The can be shared among all child elements by setting the FrameworkElement.DataContext property
 - Can be set in XAML
 - Can be set in code
 - Bindings then implicitly refer to the data in **DataContext**
 - ElementName or Source can then be omitted



Binding Mode

- The binding mode specifies the direction of the binding
- Binding
 - Mode
 - Default determined by the target property
 - OneTime
 - OneWay
 - OneWayToSource
 - TwoWay
 - UpdateSourceTrigger
 - Default determined by the target property
 - Explicit when BindingExpression.UpdateSource()
 is called
 - IS Co
 - LostFocus
 - PropertyChanged



Small, Important Features... ©

- Bindings can be delayed
 - New feature in .NET 4.5

- Applies for updates from target to source in two-way bindings
 - The delay does not apply for both directions!
- Data binding can be set up "visually" through Visual Studio



- Data Binding
- Data Conversion
- Validation
- Change Notification



IValueConverter

- Value converters
 - Convert, format, localize, combine data
 - Conditionally or unconditionally
 - Usually applied with Data Binding
- ▶ IValueConverter
 - Convert()
 - ConvertBack()

Source -> Target Target -> Source

- Localization proceeds through the culture parameter
 - Defaults to xml:lang
- ▶ ValueConversionAttribute
 - Only conveys the intended meaning to tools
 - Has no semantic meaning!



IMultiValueConverter

- Multi-value converters
 - Performs similar conversion, but combines multiple values
- ▶ IMultiValueConverter
 - Convert()
 - Accepts object[] instead of just object
 - ConvertBack()
 - Returns object[] instead of just object
- Must use MultiBinding to apply multi-value converter!
- Side note:
 - There is also a PriorityBinding for use with asynchronous data binding. We will investigate that in Module 13



Data Binding Special Cases

- Converters can return special values when conversions are not possible (or not wanted)
- Binding.
 - FallbackValue
 - DoNothing

Ignore update

- DependencyProperty.
 - UnsetValue

"Errorneous" update



- Data Binding
- Data Conversion
- Validation
- Change Notification



Validation Rules

- Data bindings are subjected to a set of validation rules
 - Exceptions are by default not thrown
- ▶ ValidationRule
 - ExceptionValidationRule

built-in

- Setting Binding.ValidatesOnExceptions to true
 - is equivalent to adding ExceptionValidationRule
- Custom validation rules
 - Override ValidationRule.Validate()
 - ValidationResult signals success or failure



Handling Validation Errors

- Validation.
 - HasErrors
 - Errors

ValidationError collection

Error

event

- Raised if Binding.NotifyOnValidationError == true
- ValidationErrorEventArgs
 - Action
 - Added
 - Removed
 - Error
 - ErrorContent
 - Exception
 - RuleInError
 - BindingInError



Validation Error Templates

- Controls can set attachedValidation.ErrorTemplate property
- Note:
 - This is a ControlTemplate (not a DataTemplate)
 - AdornedElementPlaceholder refers back to control being validated!



IDataErrorInfo

IDataErrorInfo in System.ComponentModel

```
public interface IDataErrorInfo
{
   string Error { get; }
   string this[ string columnName ] { get; }
}
```

- DataErrorValidationRule
 - Checks for errors raised by classes implementing IDataErrorInfo
- Setting Binding.ValidatesOnDataErrors to true
 - is equivalent to adding **DataErrorValidationRule**
- ▶ WPF 4.5 adds INotifyDataErrorInfo for more advanced uses
 - There is a similar **Binding.ValidatesOnNotifyDataErrors**



- Data Binding
- Data Conversion
- Validation
- Change Notification



INotifyPropertyChanged

- Implement INotifyPropertyChanged to propagate modifications to a single element through data binding
 - PropertyChanged event
 - Raise event with CLR property name whenever it is changed



Caller Info Attributes

- ▶ C# 5.0 introduced three types of caller info attributes
 - [CallerMemberName]
 - [CallerFilePath]
 - [CallerLineNumber]

- Applicable to default parameters
 - Compiler replaces values at compilation time
 - In System.Runtime.CompilerServices
- ▶ Perfect for INotifyPropertyChanged...! ◎



Summary

- Data Binding
- Data Conversion
- Validation
- Change Notification



