

Module 8

"Inheritance and Polymorphism"




TEKNOLOGISK
INSTITUT

Agenda

- ▶ **Second Pillar of OOP: Inheritance**
- ▶ Third Pillar of OOP: Polymorphism
- ▶ Pattern Matching Types
- ▶ **System.Object**
- ▶ Lab 8
- ▶ Discussion and Review

What is Inheritance?

- ▶ Inheritance specifies an “is-a” relationship between classes




Generalization



Specialization

- ▶ New classes are said to *specialize* base classes
- ▶ Has all the characteristics + maybe more
- ▶ Single vs. Multiple inheritance

Class Hierarchies



Base Classes

- ▶ Create a derived class using ':' in class definition

```
class Car
{
    public readonly int maxSpeed;
    private int currentSpeed;

    public Car( int maxSpeed = 100 )
    {
        this.maxSpeed = maxSpeed;
    }
}
```

```
class MiniVan : Car
{
    public MiniVan()
    {
        ...
    }
}
```

```
MiniVan van = new MiniVan();
Console.WriteLine( van.maxSpeed ); ✓
Console.WriteLine( van.currentSpeed ); ✗
```

- ▶ Inherits all public members
- ▶ Can only derive from a single base class! But...




Sealed Classes

- ▶ Classes can explicitly prevent inheritance

```
sealed class MiniVan : Car
{
    public MiniVan()
    {
        ...
    }
}
```


```
class DeluxeMiniVan : MiniVan
{
    ...
}
```



- ▶ A lot of .NET Framework classes are sealed, e.g. **System.String**

Class Diagrams in Visual Studio

- ▶ Class diagrams can be easily visualized in Visual Studio
- ▶ "Add New Item" -> "Class Diagram", or
- ▶ Project node -> "View Class Diagram"



The **base** Keyword

- ▶ The **base** keyword is used to control base class creation

```
class Car
{
    public readonly int maxSpeed;
    private int currentSpeed;

    public Car( int maxSpeed = 110 )
    {
        this.maxSpeed = maxSpeed;
    }
}
```

```
class MiniVan : Car
{
    public MiniVan() :
        base( 90 )
    {
    }
}
```

```
MiniVan van = new MiniVan();
Console.WriteLine( van.maxSpeed ); // 90
```

- ▶ This is very similar to the **this** keyword, but for base classes



The protected Modifier



- ▶ Protected members are visible to derived classes also

```
class Car
{
    public readonly int maxSpeed;
    protected int currentSpeed;

    public Car( int maxSpeed = 110
    )
    {
        this.maxSpeed = maxSpeed;
    }
}
```

```
class MiniVan : Car
{
    public void CutSpeed()
    {
        currentSpeed /= 2;
    }
}
```

```
MiniVan van = new MiniVan();
van.CutSpeed();
Console.WriteLine( van.currentSpeed );
```



- ▶ But still not visible to the outside!




Agenda

- ▶ Second Pillar of OOP: Inheritance
- ▶ **Third Pillar of OOP: Polymorphism**
- ▶ Pattern Matching Types
- ▶ **System.Object**
- ▶ Lab 8
- ▶ Discussion and Review

What is Polymorphism?

- ▶ Polymorphism
 - The ability of objects belonging to related classes to respond to method calls of methods of the same name, each one according to an appropriate type-specific behavior



Virtual Methods

- ▶ Mark *virtual methods* with the **virtual** keyword

```
class Employee
{
    float _currentPay;

    public virtual void GiveBonus( float amount )
    {
        _currentPay += amount;
    }
}
```

- ▶ This allows behavior to be overridden in subclasses

Overriding Virtual Methods

- ▶ Override behavior using the **override** keyword

```
class Manager : Employee
{
    public int NumberOfOptions { get; protected set; }

    public override void GiveBonus( float amount )
    {
        base.GiveBonus( amount );

        Random r = new Random();
        NumberOfOptions += r.Next( 500 );
    }
}
```

- ▶ Use the **base** keyword to leverage parent implementation



Sealing Virtual Members

- ▶ Virtual methods can be sealed to prevent overriding

```
class SalesPerson : Employee
{
    public sealed override void GiveBonus( float amount )
    {
        int salesBonus = 0;
        ...
        base.GiveBonus( amount * salesBonus );
    }
}
```

```
class FreelanceSalesman : SalesPerson
{
    public int HoursWorked { get; protected set; }

    public override void GiveBonus( float amount )
    {
        base.GiveBonus( amount + HoursWorked * 2 );
    }
}
```



Abstract Classes

- ▶ Sometimes it does not make sense to instantiate certain classes
- ▶ Such classes are *abstract* classes

```
abstract class Employee
{
    public string Name { get; protected set; }
    private float _currentPay;

    public Employee( string name, float currentPay )
    {
        Name = name;
        _currentPay = currentPay;
    }
}
```




Abstract Methods

- ▶ An *abstract method* is a requirement to derived classes to implement it


```
abstract class Shape
{
    protected string _shapeName;

    public abstract void Draw( );
}
```

```
class Hexagon : Shape
{
    public override void Draw()
    {
        ...
    }
}
```



```
class Circle : Shape
{
    public Circle()
    {
    }
}
```



- ▶ An abstract method is a virtual method which must be overridden
- ▶ Abstract methods must occur only in abstract classes



Member Shadowing

- ▶ The inverse of overriding is *shadowing* members
- ▶ Use the new keyword to
 - Resolve name clashes in code
 - Hide methods with identical signature

```
class FrameworkClass
{
    public void Clear() { ... }
}
```

```
class MyClass : FrameworkClass
{
    public new void Clear()
    {
    }
}
```

- Can hide both virtual and non-virtual members
- ▶ Can be used to hide also data members



Parent/Child Conversions

- ▶ Conversion from child to parent class reference
 - Can be implicit or explicit
 - Never fails!
 - Can always be assigned to object
- ▶ Conversion from parent to child class reference
 - Has to be explicit
 - Runtime-checks the underlying type of object
 - Will throw an **InvalidCastException** if conversion is illegal

The `is` Operator

- ▶ The `is` operator checks whether a conversion can be made

```
Employee e = new Manager( ... );  
...  
if( e is Manager )  
{  
    Manager m = (Manager) e;  
  
    Console.WriteLine( m.NumberOfOptions );  
}
```



The as Operator

- ▶ The **as** operator performs conversion if it can be made
 - Otherwise null is returned
 - Exceptions are never thrown!


```
Employee e = new Manager( ... );  
...  
Manager m = e as Manager;  
if( m != null )  
{  
    Console.WriteLine( m.NumberOfOptions );  
}
```



Agenda

- ▶ Second Pillar of OOP: Inheritance
- ▶ Third Pillar of OOP: Polymorphism
- ▶ **Pattern Matching Types**
- ▶ **System.Object**
- ▶ Lab 8
- ▶ Discussion and Review

Example: Employee



Pattern Matching with `is`

- ▶ Three types of patterns for matching in C# 7
 - Constant patterns `c` e.g. `null`
 - Type patterns `T x` e.g. `int x`
 - Var patterns `var x`
- ▶ Matches and/or captures to identifiers to nearest surrounding scope

```
foreach (Employee e in all)
{
    if (e is SoftwareEngineer se)
    {
        Console.WriteLine($"{se.FullName} has produced" +
                           $"{se.CodeLinesProduced} lines of C#");
    }
}
```

- ▶ The `is` keyword is now compatible with patterns



Type Switch with Pattern Matching

- ▶ Can switch on any type
 - Case clauses can make use of patterns and new **when** conditions

```
Employee e = ...;
switch (e)
{
    case SoftwareArchitect sa:
        WriteLine($"{sa.FullName} plays with Visio");
        break;
    case SoftwareEngineer se when
        se.Level == SoftwareEngineerLevel.Lead:
        WriteLine($"{se.FullName} is a lead software engineer");
        break;
    case null:
    default:
        break;
}
```



Agenda

- ▶ Second Pillar of OOP: Inheritance
- ▶ Third Pillar of OOP: Polymorphism
- ▶ Pattern Matching Types
- ▶ **System.Object**
- ▶ Lab 8
- ▶ Discussion and Review

System.Object Members

- ▶ Every class ultimately derives from **System.Object**
- ▶ This master parent class is captured by the **object** keyword

Name	Characteristics
<code>ToString()</code>	Virtual
<code>Equals()</code>	Virtual
<code>GetHashCode()</code>	Virtual
<code>Finalize()</code>	Virtual
<code>GetType()</code>	Non-virtual
<code>MemberwiseClone()</code>	Non-virtual
<code>Equals()</code>	Static
<code>ReferenceEquals()</code>	Static

Overriding ToString()

- Override the **ToString()** method to provide a string representation for the object

```
abstract class Employee
{
    ...
    public override string ToString()
    {
        return string.Format( "Employee named \"{0}\"", Name );
    }
}
```

```
Manager manager = new Manager( "Angry Bob", ... );
Console.WriteLine( manager ); // ???
```



Overriding Equals()

- Override the **Equals()** method to provide custom equality

```
abstract class Employee
{
    ...
    public override bool Equals( object obj )
    {
        ...
        if (other.Name == this.Name )
        {
            return true;
        }
        ...
        return false;
    }
}
```

```
Manager m1 = new Manager(
    "Angry Bob", 900000, 1000 );
Manager m2 = new Manager(
    "Angry Bob", 900000, 1000 );


Console.WriteLine( m1.Equals( m2 ) );
Console.WriteLine( m1 == m2 );
```

- Does not influence the **==** operator!



Boxing and Unboxing

- ▶ Value types can be boxed as reference types
- ▶ This unified type system has many advantages, e.g. calling object methods on value types



- ▶ Downside is performance and safety
 - Can raise **InvalidCastException**



Quiz: Inheritance and Polymorphism – Right or Wrong?

```
abstract class Employee {  
    public string Name  
        { get; protected set; }  
    public abstract bool Work();  
}
```

```
class Developer : Employee {  
    public override bool Work()  
    {  
        Name = "Hard-worker!";  
        return true;  
    }  
}
```

```
class Manager : Employee  
{  
    public bool Work()  
    { return false; }  
}
```

```
Employee e = new Employee();
```

```
Employee e = new Developer();
```

```
Developer d = new Developer();
```

```
Developer d = new Employee();
```

```
Developer d = new Manager();
```

```
Developer d = new Developer();  
Console.WriteLine( d.Name );
```

```
Developer d = new Developer();  
d.Name = "Geek!";
```

```
Employee e1 = new Developer();  
Employee e2 = new Manager();  
Console.WriteLine(  
    e1.Work() == e2.Work()  
);
```

Lab 8: Using Inheritance and Polymorphism



Discussion and Review

- ▶ Second Pillar of OOP: Inheritance
- ▶ Third Pillar of OOP: Polymorphism
- ▶ **System.Object**



WINCUBATE

Jesper Gulmann Henriksen

PhD, MCT, MCSD, MCPD

Phone : +45 22 12 36 31

Email : jgh@wincubate.net

WWW : <http://www.wincubate.net>

Hasselvangel 243

8355 Solbjerg

Denmark