

Windbird primary battery

Type: ER34615

Open-voltage: 3.6V

Capacity: 19Ah

Size: D

Chemistry: LiSOCl₂

Structure: Spiral Bobbin

Connector : JST EHR-2



watch for polarity

Important information for testing the battery condition:

This type of battery behaves differently than alkaline batteries. You cannot know the condition of the battery by measuring its open-circuit voltage. If you test it with a voltmeter, the battery will always show a voltage of 3.6V, even if it is completely dead.

The only way to know the condition of the battery is to measure the voltage drop when you apply a resistive load of a few tens of ohms.



International size reference: D

ELECTRICAL CHARACTERISTICS

(typical values for cells stored for one year or less, at +30°C max.)

Nominal capacity 19Ah

(At 2 mA, +20°C, 2.0V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off voltage.)

Nominal voltage 3.6V

Maximum continuous current 100mA

(Higher currents possible, consult EVE.)

Maximum pulse capability: Typical up to 400mA

Storage (recommended) +30°C max
(for more severe condition consult EVE)

Operating temperature range -60°C / +85°C

(Operation at temperature different from ambient may lead to reduced capacity and lower voltage plateau readings.)

Typical weight 100g

ER34615

**Lithium-thionyl Chloride
(Li-SOCl₂) Battery**

For demanding and potentially explosive atmospheres

KEY FEATURES

- ✓ High and stable operating voltage
- ✓ High minimum voltage during pulsing
- ✓ Low self discharge rate (less than 1% after 1 year of storage at +25°C)
- ✓ Stainless steel container
- ✓ Hermetic glass-to-metal sealing
- ✓ Non-flammable electrolyte
- ✓ Restricted for transport(class 9)
- ✓ Compliant with IEC 60086-4 Safety standard and EN 60079-11 intrinsic safety standard (Class T4 assignment)
- UL Underwriters Laboratories (UL) Component Recognition (File Number MH28717)

MAIN APPLICATIONS



- ✓ Gas metering
- ✓ Utility metering
- ✓ Alarms and security devices
- ✓ Memory back-up
- ✓ Tracking systems
- ✓ Professional electronics ... etc.

⚠ WARNING:


Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 100°C, incinerate, or expose contents to water.
Do not solder directly to the cell, use tabbed cell instead.

ER34615

1. Typical discharge profile at +20°C (Median value)



2. Voltage plateau versus Current and Temperature (at mid-discharge)




AVAILABLE TERMINATIONS


Suffix-/S Standard
 Suffix-/T Solder Tabs
 Suffix-/W Flying Leads

[View available terminations](#)

3. Capacity versus Current and Temperature (2.0V cut off)



4. STORAGE CHARACTERISTICS



Attention:

Information in this document is subject to change without notice. Any representations in this document concerning performance are for informational purpose only. This document becomes contractual only after written confirmation by EVE.

EVE ENERGY CO., LTD.

Address: EVE Industrial Park, XiKeng Industrial zone, Huihuan Town, Huizhou, Guangdong, China

Operator: (86-752)260 6966 Fax: (86-752)260 6033

<http://www.evebattery.com> Email: sales@evebattery.com

Latest version can be downloaded from the EVE website