

This program calculates the total budget for a visit to Quituinan Ranch in Camalig, Albay. It processes group size to determine costs for entrance fees, ATV rentals, and photos while demonstrating currency using floor division.

```
In [ ]: # Program: Quituinan Ranch Trip Planner
# 1. DATA
entry = 70
atv = 200.0
photo = 20

x = float(entry)
y = float(atv)
z = float(photo)

# 2. QUESTIONS
# Getting information from the user
total_people = int(input('How many people are entering the ranch?'))
atv_people = int(input('How many people will ride the ATV?'))
photo_people = int(input('How many people want a souvenir photo?'))

# 3. CALCULATIONS

print('Number of Tourists:', total_people)
print('Number of People Availing ATV:', atv_people)
print('Number of People who Want to Take Pics:', photo_people)

x = float(entry)
y = float(atv)
z = float(photo)

print('Total cost for Entry only:', x * total_people, "PHP")
print('Total cost for ATV only:', y * atv_people, "PHP")
print('Total cost for Pics only:', z * photo_people, "PHP")

total_cost = (x * total_people) + (y * atv_people) + (z * photo_people)
print('The total cost for the group is:', (x * total_people) + (y * atv_people) + (z * photo_people), "PHP")
avg_per_person = total_cost / total_people
print('Average cost per person entering:', avg_per_person)

# Division using // rounds down to find bills
bills = total_cost // 500
print('Number of 500-peso bills:', bills)
# Finding the Leftover change
leftover = total_cost % 500
print('Loose change needed:', leftover)
```

Sample output of the program: Total Number of People = 15, People Taking ATV ride = 9, People Who Want to Take Photos = 6

```
In [4]: # 1. DATA
entry = 70
atv = 200.0
photo = 20

x = float(entry)
y = float(atv)
z = float(photo)

# 2. QUESTIONS
# Getting information from the user
total_people = int(input('How many people are entering the ranch?'))
atv_people = int(input('How many people will ride the ATV?'))
photo_people = int(input('How many people want a souvenir photo?'))
```

```
In [8]: # 3. CALCULATIONS

print('Number of Tourists:', total_people)
print('Number of People Availing ATV:', atv_people)
print('Number of People who Want to Take Pics:', photo_people)

x = float(entry)
y = float(atv)
z = float(photo)

print('Total cost for Entry only:', x * total_people, "PHP")
print('Total cost for ATV only:', y * atv_people, "PHP")
print('Total cost for Pics only:', z * photo_people, "PHP")

total_cost = (x * total_people) + (y * atv_people) + (z * photo_people)
print('The total cost for the group is:', (x * total_people) + (y * atv_people) + (z * photo_people), "PHP")
avg_per_person = total_cost / total_people
print('Average cost per person entering:', avg_per_person)

# Division using // rounds down to find bills
bills = total_cost // 500
print('Number of 500-peso bills:', bills)
# Finding the Leftover change
leftover = total_cost % 500
print('Loose change needed:', leftover)
```

Number of Tourists: 15
Number of People Availing ATV: 9
Number of People who Want to Take Pics: 6
Total cost for Entry only: 1050.0 PHP
Total cost for ATV only: 1800.0 PHP
Total cost for Pics only: 120.0 PHP
The total cost for the group is: 2970.0 PHP
Average cost per person entering: 198.0
Number of 500-peso bills: 5.0
Loose change needed: 470.0

How the Concepts are Used

```
In [ ]: # Type: Used int for whole numbers and float for decimals
# Reserved words: Keywords like 'int' or 'float' are used as functions
# Variables: Named 'total_cost' and 'visitors' as memory aids
# Operators: Used *, +, /, //, and % for math
# Precedence: Python calculates the multiplication before the addition
# Integer Division: Using / always creates a float result like 5.0
# Floor Division: Using // rounds down the total to count 500-peso bills
# Conversion: Changed user text input to a number using int()
```

User input: Used input() to pause and get info from the traveler
Comments: Used # to explain what every section of code does