

國立成功大學  
人工智慧科技碩士學位學程  
碩士論文

以聯合語義語音詞嵌入強化中日文  
神經機器翻譯

**Improving Chinese-Japanese Neural Machine  
Translation with Joint Semantic-Phonetic  
Word Embedding**

研究生：王士杰

Student : Shih-Chieh Wang

指導教授：賀保羅

Advisor : Paul Horton

Master Degree Program on Artificial Intelligence,  
National Cheng Kung University,  
Tainan, Taiwan, R.O.C.

Thesis for Master of Science Degree

July, 2021

中華民國一百一十年七月

# 以聯合語義語音詞嵌入強化中日文神經機器翻譯

王士杰<sup>\*</sup>

賀保羅<sup>†</sup>

國立成功大學人工智慧科技碩士學位學程

## 摘要

中文版簡介。手動換行會自動變成下一段文字區塊。

關鍵字：關鍵字1、關鍵字2、關鍵字3



---

<sup>\*</sup>學生

<sup>†</sup>指導教授

# Improving Chinese-Japanese Neural Machine Translation with Joint Semantic-Phonetic Word Embedding

Shih-Chieh Wang\*

Paul Horton†

Master Degree Program on Artificial Intelligence  
National Cheng Kung University

## Abstract

Add your abstract here.

**Keywords:** Keyword1, Keyword2, Keyword3



---

\*Student

† Advisor

# Acknowledgements

Add your acknowledgements here.

Shih-Chieh Wang



# CONTENTS

中文摘要	i
Abstract	ii
Acknowledgements	iii
Contents	iv
List of Tables	vi
List of Figures	vii
1 Introduction	1
1.1 Background	1
1.1.1 Progress of Neural Machine Translation	1
1.1.2 Chinese-Japanese Neural Machine Translation	2
1.1.3 Phonetic Information	3
1.2 Objective	3
1.3 Related Work	4
1.3.1 Chinese Word Embedding	4
1.3.2 Phonetic Word Embedding	7
2 Method	9
2.1 Tokenization	11
2.1.1 Tokenizers	11
2.1.2 SentencePiece	11
2.1.3 Jieba	11
2.1.4 Janome	11
2.2 Phonetic Data Extraction	11
2.2.1 dragonmapper	11
2.2.2 pykakasi	11
2.3 Embedding	11
2.3.1 Word2Vec	11
2.3.2 Phonetic Embedding	11
2.3.3 Joint Embedding	11
2.4 Corpus Filtering	11
2.5 NMT Model	11
2.5.1 Attention-based GRU encoder-decoder Model	11
2.5.2 Transformer	11
2.6 Embedding Analysis	11
2.6.1 Analogy Reasoning	11
2.6.2 Outlier Detection	11
2.6.3 Word Similarity	11

2.6.4	Homonym and Heteronym	11
3	Experiment and Result	12
3.1	Environment	12
3.1.1	PyTorch Lightning	12
3.1.2	wandb	12
3.2	Dataset	12
3.3	Parameter	12
3.4	Metric	12
3.5	Result	12
4	Discussion	13
4.1	Case Study	13
4.2	Embedding Analysis	13
5	Conclusion and Future Work	14
5.1	Conclusion	14
5.2	Future Work	14
	References	15



## LIST OF TABLES



# LIST OF FIGURES

1.1	An illustration of JWE model proposed in [Yu et al., 2017]	5
1.2	The Process of generating stroke n-grams shown in [Cao et al., 2018]	6
1.3	An illustration of cw2vec model proposed in [Cao et al., 2018]	6
1.4	Implementation of phonetic encoding proposed in [Khan and Xu, 2019]	7





# Chapter 1

## Introduction

Over the past few years, the field of neural machine translation (NMT) between Chinese and Japanese is still an unresolved problem. Recent studies in Chinese-Japanese NMT have used specific methods such as sub-character level features to improve the translation quality. This is due to the lack of parallel corpus and the difference between logogram (a character or symbol that represents a word) and alphabet (a set of letters used when writing in a language) writing systems. This research explores phonetic information as an additional feature for improving the quality of Chinese-Japanese NMT systems.

### 1.1 Background

NMT is a popular area of natural language processing (NLP), has been proposed by using an end-to-end model which transforms a source sentence into a latent space and decodes it directly into a target sentence [Sutskever et al., 2014, Cho et al., 2014]. The model is called the encoder-decoder model or sequence-to-sequence model, and they are widely used by large technology companies such as Google, Facebook, Microsoft, and DeepL.

#### 1.1.1 Progress of Neural Machine Translation

The progress of NMT and NLP are inseparable. The development of models, tokenization methods, embeddings, and the solutions to less or no parallel data, all involved in the progress of NMT.

Recurrent neural networks (RNNs), attention mechanisms, and transformers have been proposed sequentially throughout the progress of encoder-decoder models. RNN that recursively passes states in its networks was first applied in the encoder-decoder model. Attention-mechanism had addressed the problem of insufficient information in the latent space between encoder and decoder based on RNN. Transformers had replaced the RNN structure with full attention-mechanism (i.e., self-attention) to achieve better results and used widely in NMT tasks.

Tokenization is one of the most important parts of any NLP task. It determines how a sentence will be tokenized, and it will generate different meanings to a sentence with different algorithms. Besides word-level

and character-level tokenization, several subword-level tokenization algorithms had become the mainstream. For example: Byte-Pair Encoding (BPE) [Sennrich et al., 2016b], Unigram Language Model [Kudo, 2018], WordPiece [Schuster and Nakajima, 2012], and SentencePiece [Kudo and Richardson, 2018]. This paper will utilize BPE, SentencePiece [Sennrich et al., 2016b, Kudo and Richardson, 2018] and two word-level tokenizer (*Jieba*<sup>1</sup> and *Janome*<sup>2</sup>) as tokenization methods.

The concept of embeddings, also known as distributed representations, was first proposed by [Hinton et al., 1986, Bengio et al., 2003], but was difficult to implement due to hardware limitations. With the development of parallel computing and GPU, many embedding implementations have been proposed, such as Word2Vec [Mikolov et al., 2013], GloVe [Pennington et al., 2014], and fastText [Bojanowski et al., 2017]. The contextualized word embedding is another concept that obtains context-dependent word embedding from the whole sentence, meaning that the same word with a different position can obtain different embedding through the model. The representative ones are ELMo [Peters et al., 2018] and BERT [Devlin et al., 2019]. This paper will select Word2Vec [Mikolov et al., 2013] as the tool for creating word embeddings because of its simplicity, rapidity, and convenience of analysis.

Several fields have been studied to solve the problems like low-resources and noisy parallel data in NMT tasks. Back-translation [Sennrich et al., 2016a] is a data augmentation method that uses monolingual data of the target language to generate source data and offset the imbalance between encoder and decoder. Parallel corpus filtering was examined for a large number of NMT tasks [Koehn et al., 2018], using pre-filtering rules and scoring functions to retain good sentence pairs can effectively reduce the corpus size and obtained better translation results. This paper will practice corpus filtering to retain quality training data and reduce corpus size to increase experimental efficiency.

### 1.1.2 Chinese-Japanese Neural Machine Translation

NMT system has gained a lot of improvement in translating between English and other languages by utilizing the techniques described in section 1.1.1. However, the improvement in translating between Chinese and Japanese is limited. The main reasons are the inadequacy of the corpus and the differences in the writing systems of Chinese, Japanese, and Western languages.

Many studies have focused on improving the Chinese-Japanese (zh-ja) NMT system. In addition to us-

---

<sup>1</sup><https://github.com/fxsjy/jieba>

<sup>2</sup><https://mocobeta.github.io/janome>

ing the methods [Imamura et al., 2018, Chu et al., 2017, Zhang et al., 2020] described in section 1.1.1, many feature engineering techniques have been proposed to utilize the features in Chinese Characters (*Hanzi*) and Japanese *Kanji*. For example, a character-level zh-ja NMT system had been improved by using radicals as character feature information [Zhang and Matsumoto, 2017]. Furthermore, the use of decomposed sub-character level information such as ideographs and strokes of Chinese characters, also improved the results [Zhang and Komachi, 2018].

### 1.1.3 Phonetic Information

Phonetic information is another feature that had been applied to NMT systems. [Khan and Xu, 2019] had suggested that a phonetic representation usually corresponds to semantically distinct characters or words. [Liu et al., 2019] had pointed out that phonetic information can effectively resist the homophone noises generated by typographical mistakes in Chinese sentences. Both papers had improved the performance of the NMT system between Chinese and other Western languages.

This paper attempts to use *Bopomofo* and *Hiragana* as Chinese and Japanese phonetic information to improve the performance of the zh-ja NMT system. Bopomofo also named *Zhuyin* (注音), is located in the Unicode block in the range U+3100–U+312F. It consists of 37 characters and 4 tone marks to transcribe all possible Chinese characters. Although it is the main component of Mandarin Chinese, it usually does not appear in Chinese sentences. That is, the machine loses some of the phonetic information when reading Chinese sentences. Hiragana (平仮名, ひらがな) is a component of Japanese, along with *Katakana* and *Kanji*. It consists of 46 base characters and is located in the Unicode block in the range U+3040–U+309F. Compared to Bopomofo, Hiragana is often found in Japanese sentences with *Katakana* and *Kanji*, forming mixed writing of *Kanji* and *Kana* (仮名交じり文). However, Hiragana disappears after forming *Kanji*, just like Bopomofo forms *Hanzi*. Therefore, the machine cannot obtain the phonetic information directly from Japanese sentences.

## 1.2 Objective

This paper aims to determine whether the use of phonetic information can help improve the performance of the zh-ja NMT system. We will use embedding, which is commonly used to represent semantics, to represent the features of phonetic information. The *gensim* library<sup>3</sup> will be utilized to implement Word2Vec [Mikolov et al.,

---

<sup>3</sup><https://radimrehurek.com/gensim/index.html>

2013] to extract both semantic and phonetic embedding. The embeddings will be trained on a small corpus (less than 1 million lines of sentences) to see if they are useful for the subsequent NMT task.

Combining the findings from other studies [Liu et al., 2019, Khan and Xu, 2019] described in section 1.1.3, we hypothesize that embeddings with the combination of semantics and phonetics (joint embedding) can improve the performance of the zh-ja NMT system more effectively than embeddings with only semantics or phonetics.

We will perform a series of experiments to test the hypothesis. First, we examine whether the joint embedding can improve the results of the zh-ja NMT system with different tokenization methods. Second, we conduct NMT tasks under four conditions: without any pre-trained embedding, with pre-trained semantic embedding, with pre-trained phonetic embedding, and with joint semantic-phonetic embedding. Third, we analyze the changes that occur when phonetic information is added to the general semantic embedding. The analyses include analogy reasoning, outlier detection, word similarity, and the influence on both homonyms and heteronyms.

## 1.3 Related Work

The core technique in this paper is to enhance the ability of word embeddings by utilizing feature engineering on phonetic information. Therefore, we are going to review some studies that use additional features to improve word embeddings. The review will be carried out from two perspectives, one is to improve embedding with the features of Chinese characters such as radicals and strokes, and the other is to improve embedding with the features of phonetics. The concept of Word2Vec [Mikolov et al., 2013] is commonly used in reviews, and we will mention it in section 2.3.1 of Chapter 2.

### 1.3.1 Chinese Word Embedding

We will review some studies which suggested that the rich, decomposed information of Chinese characters can be exploited to train the word embeddings with words or characters jointly. Some of the most popular studies in this field are: *CWE* [Chen et al., 2015], *MGE* [Yin et al., 2016], *JWE* [Yu et al., 2017], and *cw2vec* [Cao et al., 2018]. The following sections review the approaches from JWE and cw2vec because their concepts are relatively new and their performance is better.

## Joint Learning Word Embedding Model (JWE)

The authors of JWE [Yu et al., 2017] proposed a model that combines word, character, and sub-character components to learn embeddings. They implemented the model (Figure 1.1) based on the Continuous Bag of Words (CBOW) proposed in Word2Vec [Mikolov et al., 2013], and changed the default input words in CBOW by further adding the characters and sub-character components of input words.




Figure 1.1: An illustration of JWE model proposed in [Yu et al., 2017]

As shown in the Figure 1.1 above, The JWE model is trained to predicts the present word from the context words in the same way as CBOW. The symbol  $w$  represents words,  $w_i$  is the current word,  $w_{i-1}$  and  $w_{i+1}$  are the context words. The symbol  $c$  represents the characters of context words,  $c_{i-1}$  is the characters of  $w_{i-1}$ , and  $c_{i+1}$  is the characters of  $w_{i+1}$ . The symbol  $s$  represents the sub-characters of context words.  $s_i$  is the sub-character components of  $w_i$ , and  $s_{i-1}$ ,  $s_{i+1}$  are the components of  $w_{i-1}$  and  $w_{i+1}$ . For example, a word 智能 (intelligence) has two characters 智 (wisdom) and 能 (able), and each has sub-character components: 知, 日 and 亠, 月, 匕, 匕. The JWE model aims to maximize the sum of log-likelihoods of 3 conditional probabilities that come from the context words ( $h_{i1}$ ), characters ( $h_{i2}$ ), and sub-characters ( $h_{i3}$ ).

$$L(w_i) = \sum_{k=1}^3 \log P(w_i | h_{ik}) \quad (1.1)$$

## cw2vec Model

Inspired by fastText [Bojanowski et al., 2017], the authors of cw2vec [Cao et al., 2018] proposed an n-gram feature based on the strokes of Chinese characters. They first split and transformed the text into stroke information, and mapped the strokes into 5 corresponding stroke ids, then merge the ids and generate n-gram features from these stroke ids. The diagram in the paper (Figure 1.2) shows the complete process.




Figure 1.2: The Process of generating stroke n-grams shown in [Cao et al., 2018]

The authors used Skip-Gram, a second method other than CBOW proposed by Word2Vec [Mikolov et al., 2013], as the base model, and replaced word inputs with stroke n-grams (Figure 1.3). It is mentioned in the paper that the final embeddings come from the contextual word vectors.




Figure 1.3: An illustration of cw2vec model proposed in [Cao et al., 2018]

These word embeddings designed for Chinese all utilized the radicals or strokes in Chinese characters. No research in Chinese word embeddings has so far used phonetic information extracted from Chinese or Japanese as features.

### 1.3.2 Phonetic Word Embedding

We will review studies that use phonetic information to construct word embeddings. These studies are closely related to our research, and we will learn from their practical differences and use them as the cornerstone for our experiments.

#### Phonetic Encoding

The study [Khan and Xu, 2019] extracted sentences from Chinese or Western languages into phonetic encodings<sup>4</sup>, which used *Soundex*, *NYSIIS*, *Metaphone*, and *Hanyu Pinyin* as the extraction algorithm. After that, they applied BPE [Sennrich et al., 2016b] to tokenize the sentences and encodings, and trained separate embeddings from the sentences and each encoding (empty boxes in Figure 1.4). Lastly, they concatenated the embeddings and fed them into the NMT system.




Figure 1.4: Implementation of phonetic encoding proposed in [Khan and Xu, 2019]

This paper did not explain the implementation of phonetic information in detail, but they had presented a hypothesis and verified it. That is, phonetics is a function that groups semantically distinct words. The words with the same pronunciation and spelling are usually distinguished by the different contexts.

<sup>4</sup>The logogram encoding is also used as a feature but is not explained here. Random clustering is used for comparison purposes.

## Joint Textual and Phonetic Embedding

This paper [Liu et al., 2019] focused on using phonetic embedding to adjust the homophone noise problem, which is a frequent problem in a parallel corpus. For instance, when a single word in the source sentence is misplanted as a corresponding homophone (e.g., 有 (yǒu, to have) is wrongly replaced with 友 (yǒu, friend)), the model will read the wrong embedding and training in a wrong direction. The phonetic embedding can be seen as a feature to offset the errors that occur in semantic embeddings with homophone noise.

The paper trained the text (denoted by  $a$ ) as semantic embedding (denoted by  $\pi(a)$ ) and phonetic embedding (denoted by  $\psi(a)$ ), and combined two embeddings with a configurable parameter (denoted by  $\beta$ ) as follows:

$$\pi([a, \psi(a)]) = (1 - \beta) \times \pi(a) + \beta \times \pi(\psi(a)) \quad (1.2)$$

This study did not give the details of constructing embeddings, but they had mentioned that the best result occurs when the  $\beta$  is 0.95. That is, when they used 5% of semantic embedding and 95% of phonetic embedding, they obtained the best performance in their NMT system.

To summarize the findings in these related works. The phonetic encodings can emphasize the difference between semantically diverse sentences. The joint semantic-phonetic embedding also shows the robustness to noise in parallel corpora. All of these features can help improve the performance of the NMT system. However, the methods of using phonetic information as embeddings had been explored mainly in Chinese and Western languages. They also used *Pinyin* instead of Bopomofo as the component to decompose Chinese characters. According to our study, no research has been proposed to apply and analyze phonetic information as an additional feature in Chinese and Japanese NMT systems.



## Chapter 2

### Method

method.





## **2.1 Tokenization**

### **2.1.1 Tokenizers**

### **2.1.2 SentencePiece**

### **2.1.3 Jieba**

### **2.1.4 Janome**

## **2.2 Phonetic Data Extraction**

### **2.2.1 dragonmapper**

### **2.2.2 pykakasi**

## **2.3 Embedding**

### **2.3.1 Word2Vec**

### **2.3.2 Phonetic Embedding**

### **2.3.3 Joint Embedding**



## **2.4 Corpus Filtering**

## **2.5 NMT Model**

### **2.5.1 Attention-based GRU encoder-decoder Model**

### **2.5.2 Transformer**

## **2.6 Embedding Analysis**

### **2.6.1 Analogy Reasoning**

### **2.6.2 Outlier Detection**

### **2.6.3 Word Similarity**

### **2.6.4 Homonym and Heteronym**

# Chapter 3

## Experiment and Result

experiment and result.

### 3.1 Environment

#### 3.1.1 PyTorch Lightning

#### 3.1.2 wandb

### 3.2 Dataset

### 3.3 Parameter

### 3.4 Metric

### 3.5 Result



## Chapter 4

### Discussion

discussion.

#### 4.1 Case Study

#### 4.2 Embedding Analysis



## Chapter 5

### Conclusion and Future Work

conclusion.

#### 5.1 Conclusion

#### 5.2 Future Work



# REFERENCES

- [Bengio et al., 2003] Bengio, Y., Ducharme, R., Vincent, P., and Janvin, C. (2003). A neural probabilistic language model. *The journal of machine learning research*, 3:1137–1155.
- [Bojanowski et al., 2017] Bojanowski, P., Grave, E., Joulin, A., and Mikolov, T. (2017). Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- [Cao et al., 2018] Cao, S., Lu, W., Zhou, J., and Li, X. (2018). cw2vec: Learning chinese word embeddings with stroke n-gram information. In *Proceedings of the AAAI Conference on Artificial Intelligence*, number 1.
- [Chen et al., 2015] Chen, X., Xu, L., Liu, Z., Sun, M., and Luan, H. (2015). Joint learning of character and word embeddings. In *Twenty-Fourth International Joint Conference on Artificial Intelligence*.
- [Cho et al., 2014] Cho, K., van Merriënboer, B., Gulcehre, C., Bougares, F., Schwenk, H., and Bengio, Y. (2014). Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*.
- [Chu et al., 2017] Chu, C., Dabre, R., and Kurohashi, S. (2017). An empirical comparison of domain adaptation methods for neural machine translation. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 385–391.
- [Devlin et al., 2019] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- [Hinton et al., 1986] Hinton, G. E. et al. (1986). Learning distributed representations of concepts. In *Proceedings of the eighth annual conference of the cognitive science society*, volume 1, page 12. Amherst, MA.
- [Imamura et al., 2018] Imamura, K., Fujita, A., and Sumita, E. (2018). Enhancement of encoder and attention using target monolingual corpora in neural machine translation. In *Proceedings of the 2nd Workshop on Neural Machine Translation and Generation*, pages 55–63.

- [Khan and Xu, 2019] Khan, A. R. and Xu, J. (2019). Diversity by phonetics and its application in neural machine translation. *arXiv preprint arXiv:1911.04292*.
- [Koehn et al., 2018] Koehn, P., Khayrallah, H., Heafield, K., and Forcada, M. L. (2018). Findings of the wmt 2018 shared task on parallel corpus filtering. In *Proceedings of the Third Conference on Machine Translation: Shared Task Papers*, pages 726–739.
- [Kudo, 2018] Kudo, T. (2018). Subword regularization: Improving neural network translation models with multiple subword candidates. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 66–75, Melbourne, Australia. Association for Computational Linguistics.
- [Kudo and Richardson, 2018] Kudo, T. and Richardson, J. (2018). SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 66–71, Brussels, Belgium. Association for Computational Linguistics.
- [Liu et al., 2019] Liu, H., Ma, M., Huang, L., Xiong, H., and He, Z. (2019). Robust neural machine translation with joint textual and phonetic embedding. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3044–3049, Florence, Italy. Association for Computational Linguistics.
- [Mikolov et al., 2013] Mikolov, T., Sutskever, I., Chen, K., Corrado, G., and Dean, J. (2013). Distributed representations of words and phrases and their compositionality. *arXiv preprint arXiv:1310.4546*.
- [Pennington et al., 2014] Pennington, J., Socher, R., and Manning, C. D. (2014). Glove: Global vectors for word representation. In *Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543.
- [Peters et al., 2018] Peters, M. E., Neumann, M., Iyyer, M., Gardner, M., Clark, C., Lee, K., and Zettlemoyer, L. (2018). Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 2227–2237, New Orleans, Louisiana. Association for Computational Linguistics.



- [Schuster and Nakajima, 2012] Schuster, M. and Nakajima, K. (2012). Japanese and korean voice search. In *2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5149–5152.
- [Sennrich et al., 2016a] Sennrich, R., Haddow, B., and Birch, A. (2016a). Improving neural machine translation models with monolingual data. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 86–96, Berlin, Germany. Association for Computational Linguistics.
- [Sennrich et al., 2016b] Sennrich, R., Haddow, B., and Birch, A. (2016b). Neural Machine Translation of Rare Words with Subword Units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.
- [Sutskever et al., 2014] Sutskever, I., Vinyals, O., and Le, Q. V. (2014). Sequence to sequence learning with neural networks. In *Advances in Neural Information Processing Systems*, pages 3104–3112.
- [Yin et al., 2016] Yin, R., Wang, Q., Li, P., Li, R., and Wang, B. (2016). Multi-granularity chinese word embedding. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pages 981–986.
- [Yu et al., 2017] Yu, J., Jian, X., Xin, H., and Song, Y. (2017). Joint embeddings of chinese words, characters, and fine-grained subcharacter components. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 286–291.
- [Zhang et al., 2020] Zhang, B., Nagesh, A., and Knight, K. (2020). Parallel corpus filtering via pre-trained language models. *arXiv preprint arXiv:2005.06166*.
- [Zhang and Matsumoto, 2017] Zhang, J. and Matsumoto, T. (2017). Improving character-level japanese-chinese neural machine translation with radicals as an additional input feature. In *2017 International Conference on Asian Language Processing (IALP)*, pages 172–175.
- [Zhang and Komachi, 2018] Zhang, L. and Komachi, M. (2018). Neural machine translation of logographic language using sub-character level information. In *Proceedings of the Third Conference on Machine Translation: Research Papers*, pages 17–25, Brussels, Belgium. Association for Computational Linguistics.