## INFORMATION

"Information is that which allows you to make a correct prediction with accuracy better than chance."

Adami, Christoph. "What Is Information?" Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences, vol. 374, no. 2063, Mar. 2016, p. 20150230, https://doi.org/10.1098/rsta.2015.0230.

"Information is that which allows you to make a correct <u>prediction</u> with accuracy better than <u>chance</u>."

Adami, Christoph. "What Is Information?" Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences, vol. 374, no. 2063, Mar. 2016, p. 20150230, https://doi.org/10.1098/rsta.2015.0230.


# defining and measuring information

guess the number am I thinking of!

what is the most efficient approach?



is it > 8?



is it > 8? ×




is it > 8? × is it > 4?



is it > 8? × is it > 4? ✓





is it > 8? × is it > 4? ✓ is it > 6? ✓

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

is it > 8? 
$$\times$$
is it > 4?  $\checkmark$ 
is it > 6?  $\checkmark$ 
is it > 7?

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16


- is it > 8? × is it > 4? ✓ is it > 6? ✓ is it > 7? ×
- 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16




with 4 questions from 16 to 1




with 4 questions from 16 to 1




$$N = 16$$





$$\frac{N = 16}{N = 8}$$



$$\frac{N = 16}{N = 8}$$
$$N = 4$$









## information = reduced uncertainty uncertainty is measured with the logarithm of N

$$H=log_2(N)$$




## or: how often can we cut the remaining possibilities in half?


$$H = log_2(N)$$




$$H_0 = log_2(16) = 4$$




$$H_1 = log_2(8) = 3$$




$$I=H_0-H_1$$



$$I=log_2(16)-log_2(8)$$



$$I=4-3=1$$



uncertainty and information are

measured in **bits** 

## how many yes/no questions to reduce

 $H=0=log_2(1)$ 


## how many yes/no questions to reduce uncertainty to zero?

$$H=0=log_2(1)$$


 $H=log_2(N)$ 

poker

#### which card am I holding?





52 card poker deck







7 🔷 **A** 3 🔷 5 🔷 6 4 🔷 8 K 🔷 9 🔷 Q 🔷 10








is it hearts?




is it hearts?




is it hearts?

is it 8 or above?



is it hearts?


is it 8 or above?
yes



is it hearts?

is it 8 or above?
yes

is it jack or above?




is it hearts?

is it 8 or above?
yes

is it jack or above?

yes



is it hearts?


yes

is it 8 or above?

is it jack or above?


yes

is it queen or above?




is the card black? no is it hearts? yes is it 8 or above? yes is it jack or above? yes Q 10 is it queen or above? yes 3 5

is the card black? no Q is it hearts? yes is it 8 or above? 10 yes is it jack or above? yes Q 10 is it queen or above? yes 3 5 is it king? Q






### uncertainty with N = 52 possibilities?



$$H=log_2(52)pprox 5.7$$

### uncertainty with N = 52 possibilities?



one bit of information with each answer...


$$log_2(52) - log_2(26) = 1$$

one bit of information with each answer...

$$log_2(52) - log_2(26) = 1$$


...that cuts the remaining options in half

is it a spades card? Q 6 is it a spades card?



is it a spades card?

how much information?



is it a spades card? no

how much information?

$$H_0 = log_2(52) pprox 5.7$$

$$H_1 = log_2(39) pprox 5.29$$



























































Q

























is it a spades card? no

#### how much information?

$$H_0 = log_2(52) pprox 5.7$$

$$H_1 = log_2(39) pprox 5.29$$

$$H_0-H_1pprox 0.41$$



































































































Q












next\_move()


**→** E2 → E4


# how much information is one move?























## $c2 \rightarrow c4$

how many possibilities?

### 64 fields x 64 fields

how many possibilities?

#### $64 \times 64 = 4096$

possible moves\*

#### $64 \times 64 = 4096$

$$H = log_2(4096) = 12$$

#### $64 \times 64 = 4096$

$$H = log_2(4096) = 12$$

one chess move is 12 bits of information

# an alternative way to calculate # bits

### <u>c</u> <u>2</u> <u>c</u> <u>4</u>

4 digits

### <u>c</u> 2 <u>c</u> 4

4 digits 8 possible symbols per digit

#### c 2 c 4

4 digits
8 possible symbols per digit
how many bits per digit?

#### <u>c</u> 2 <u>c</u> 4

4 digits
8 possible symbols per digit
how many bits per digit?

$$H_{digit} = log_2(8) = 3$$

#### <u>c</u> <u>2</u> <u>c</u> <u>4</u>

4 digits
8 possible symbols per digit
how many bits per digit?

$$H_{digit} = log_2(8) = 3$$
  $H_{move} = log_2(8) imes 4 = 12$ 


### $H_{avg} = log_2(S) imes n$

S: number of possible symbols n: number of digits in our message

## $H_{max} = \lceil log_2(S) \rceil imes n$

when calculating bits for storage, we must always consider the worst case


drawing balls from an urn




$$p( ) = 2/3$$

#### Example adapted from:

Pinkard, Henry, and Laura Waller. A Visual Introduction to Information Theory. arXiv:2206.07867, arXiv, 16 June 2022, <a href="https://doi.org/10.48550/arXiv.2206.07867">https://doi.org/10.48550/arXiv.2206.07867</a>.



Pinkard, Henry, and Laura Waller. A Visual Introduction to Information Theory. arXiv:2206.07867, arXiv, 16 June 2022, <a href="https://doi.org/10.48550/arXiv.2206.07867">https://doi.org/10.48550/arXiv.2206.07867</a>.



Pinkard, Henry, and Laura Waller. A Visual Introduction to Information Theory. arXiv:2206.07867, arXiv, 16 June 2022, https://doi.org/10.48550/arXiv.2206.07867.



# # digits and # symbols

# **{A}**

**{A}** 

AA

AA, AB, BA, BB

# {A, B, C}

## {A, B, C}

AA, AB, BA, BB, AC, BC, CA, CB, CC

# {A, B, C, D}

## {A, B, C, D}

AA, AB, BA, BB, AC, BC, CA, CB, CC, AD, DA, BD, DB, CD, DC, DD

# {A, B, C, D, E}


## {A, B, C, D, E}

AA, AB, BA, BB, AC, BC, CA, CB, CC, AD, DA, BD, DB, CD, DC, DD, AE, EA, BE, EB, CE, EC, DE, ED, EE

#### with # digits n = 2

# symbols	# messages
1	1
2	4
3	9
4	16
5	25

#### with length n = 2



# and more digits?


AAA, AAB, ABA, ABB, BBB, BBA, BAA, BAB

AAAA, AAAB, AABA, AABB, ABAA, ABAB, ABBA, ABBB, BAAA, BAAB, BABA, BABB, BBAA, BBAB, BBBA, BBB


#### with # symbols S = 2

# digits	# messages
1	2
2	4
3	8
4	16
5	32

#### with # symbols S = 2



#### with # symbols S = 2



# possible messages with *n* digits and S symbols

$$N = S^n$$

mastermind



### eight colors



### five slots



A B C D E



### # possible permutations

 $N=5^8=390625$ 

# # maximum entropy in bits

 $H_{max}=log_2\ 5^8=18.575$ 

hints reduce uncertainty (entropy)



### first guess

opponent's hints



## opponent's hints first guess correct A B

## opponent's hints first guess wrong position correct B

### how much information did we get?



B C D E





# new possible permutations?

$$N=4^8=65536$$

# reduced entropy in bits?

$$H=log_2\ 4^8=16$$